

PTZ-4518X-IS2

5MP IR NETWORK PTZ Camera



Key Features

- 1/2.8" IMX335 CMOS
- 2592 x 1944@30fps
- H.265+, H.265, H.264
- F1.6-3.8 18x lens
- Built-in Mic & Speaker
- IR Light Range: up to 100 m
- BLC/3D DNR/HLC/WDR/HDR
- Water and dust resistant(IP65)
- Color: 0.01 lux @(F1.6), 0 lux with light

Specifications

Camera	
Image Sensor	1/2.8" IMX335 CMOS
Min. Illumination	Color: 0.01lux @(F1.6), 0 lux with IR light
Shutter Speed	1/10 s to 1/10,000 s
Slow Shutter	Yes
Day & Night	IR cut Filter
Digital Noise Reduction	3D DNR 2D DNR
WDR	120dB
Lens	
Focal Length	4.7mm to 84.6mm 18x Optical zoom
Aperture	F1.6-3.8
Lens Type	Varifocal lens,motorized lens,4.7 to 84.6mm
FOV	horizontal FOV: 55° to 2.4°, vertical FOV: 33 to 1.4°, diagonal FOV: 61.5° to 2.8°
Lens Mount	M14
PTZ	
Movement Range(Pan)	360°
Movement Range(Tilt)	0° to 90°
Pan Speed	Configurable, from 0.5°/s to 60°/s. Preset speed:60°/s
Tilt speed	Configurable, from 0.5°/s to 60°/s. Preset speed:60°/s
Patrol Scan	8 patrols,up to 32 presets for each patrol
Power-off Memory	Yes
Auto Tracking	Human Tracking
Illuminator	
IR Light Range	IR Up to 100m
Smart Supplement Light	Yes
Compression Standard	
Video Compression	Main stream: H.265+/H.265/H.264 Sub-stream: H.265+/H.265/H.264
H.264 Type	High Profile/Main Profile/Base Profile
H.265 Type	High Profile/Main Profile/Base Profile
H.265+	High Profile/Main Profile/Base Profile
Smart Feature-set	
Smart Event	Human detection, Vehicle detection
Basic Event	Motion detection
Image	
Max. Resolution	2592 × 1944
Main Stream	50Hz: 30 @FPS(2592 × 1944),30@FPS(2560 × 1440),25FPS@(2304 × 1296),30FPS@ (1944 × 1944),30FPS@(1200 × 1200),60@FPS(1920 × 1080,1280 × 720); 60Hz: 30@FPS(2592 × 1944),30@FPS(2560 × 1440),30FPS@(2304 × 1296),30FPS@(1944 × 1944),30FPS@(1200 × 1200),60@FPS(1920 × 1080,1280 × 720);
Sub-Stream	50Hz: 30 fps (720 x 480,640 × 480, 640 × 360, 480 × 480,480 × 360,CIF) 60Hz: 30 fps (720 x 480,640 × 480, 640 × 360, 480 × 480,480 × 360,CIF)

Image Enhancement	WDR/HDR/3D DNR/2D DNR/HLC/BLC
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness, and white balance adjustable by client software or web browser
SVC	H.264 and H.265 and H.265+ encoding support
Day/Night Switch	Day/Night/Auto/Schedule
Network	
Network Storage	Support local storage and NAS (NFS, SMB/CIFS)
Protocols	HTTP, RTSP, DHCP, FTP, NTP, ONVIF, P2P, DHCP, SMTP, RTMP
Client	AjDevTool, LMS, Videolink
Interface	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
Built-in Microphone	YES
Built-in Speaker	Power: 3W.MAX. Sound pressure lever:10cm: 100dB.
Reset Key	YES
On-Board Storage	Built-in memory card slot, support microSD card, up to 512GB
General	
Operating Conditions	-30 °C to +85 °C, humidity 95% or less (non-condensing)
Web Client Language	14 languages: English, Russian, German, Italian, Turkish, Korean, Japanese, Traditional Chinese, Simple Chinese, Ukrainian, Portuguese, Croatian, Polish, Farsi
Power Supply	DC 12V 2A , Φ 5.5 *2.1mm coaxial plug power PoE(802.3at) Max.20W
Protection Level	IP65
Material	Front cover:metal, body:metal & plastic, bracket:metal
Dimensions	Camera: 136x 222mm (5.35" × 8.74") Package: 170× 170 × 275 mm (6.69" × 6.69" × 10.8")
Weight	Apporx.1.35kg(2.98 lb)
With Package Weight	Apporx.2.0kg(4.63lb)



Available Model

PTZ-4518X-IS(4.7-84.6mm)

Dimension

