

The Bubble Pro Series aerators feature diffuser modules that sit at the bottom of the pond, connected by weighted tubing, which is in turn connected to an air compressor on shore. The compressor pumps air through the weighted air line to the diffusers at the pond bottom. This ensures adequate oxygen levels during hot summer months. When the air reaches the diffuser, several thousand small air bubbles are created. These bubbles rise to the surface and produce an upward current. Water at the pond bottom is lifted to the surface where oxygen is replenished by the atmosphere.



Bubble Pro Mini

The Bubble Pro Mini comes complete with one diffuser; one length of 100-foot by 3/8-inch Quick Sink weighted tubing; a 1/4-hp, rocking piston compressor; an air outlet with pressure relief valve; and all fittings and clamps required. Designed for easy installation, the Bubble Pro Mini comes with a two-year warranty. Also available for 230-volt power.

Coverage Area:

1/4 acre at 5 to 8 feet in pond depth 1/2 acre at 9 to 12 feet in pond depth 1 acre at 13 to 16 feet in pond depth



Bubble Pro

The Bubble Pro comes complete with two diffusers; two lengths of 100-foot by 3/8-inch Quick Sink weighted tubing; a 1/4-hp, rocking-piston compressor; a valved air outlet assembly with individual controls for each hose and a pressure relief valve; and all required fittings and clamps. Designed for easy installation, the Bubble Pro comes with a two-year warranty. Also available for 230-volt power.

Coverage Area:

1/2 acre at 5 to 8 feet in pond depth 1 acre at 9 to 12 feet in pond depth 2 acres at 13 to 16 feet in pond depth



The Bubble Pro Max comes complete with three diffusers; three lengths of 100-foot by 3/8" Quick Sink weighted tubing; a 1/2-hp, rocking-piston compressor; a valved air outlet assembly with individual controls for each hose and a pressure relief valve; and all required fittings and clamps. Designed for easy installation, the Bubble Pro comes with a two-year warranty. Also available for 230-volt power.

Coverage Area:

3/4 acre at 5 to 8-foot pond depth 1-1/2 acres at 9 to 12-foot pond depth 3 acres at 13 to 16-foot pond depth



Bubble Pro Max XL

The Bubble Pro Max XL comes complete with four diffusers; four lengths of 100-foot by 3/8" Quick Sink weighted tubing; a 3/4-hp, rocking-piston compressor; a valved air outlet assembly with individual controls for each hose and a pressure relief valve; and all required fittings and clamps. Designed for easy installation, the Bubble Pro Max XL comes with a two-year warranty. Also available for 230-volt power.

Coverage Area:

1 acre at 5 to 8-foot pond depth 2 acres at 9 to 12-foot pond depth 4 acres at 13 to 16-foot pond depth



