

# SUPERFLEX PU









SMOOTH BORE POLYURETHANE SUPER FLEXIBLE DUCTING



## Product Information

|              |   |
|--------------|---|
| Order Ref:   | SPU-SIZE MM   |
| Tube:        | STRONG, VERY FLEXIBLE AND SMOOTH TRANSPARENT POLYURETHANE WITH SHOCK RESISTANT HARDENED PVC SPIRAL            |
| Application: | FOR INDUSTRIAL VENTILATION AND AIRFLOW SYSTEMS; SUCTION OF DUST, AIR, GASES, POWDERS AND LIQUIDS. FOOD GRADE. |

2

|       |  ID |  OD | WALL THICKNESS |  VACUUM |  BR |  W/A |  COIL |
|-------|--|--|----------------|--|---|---|--|
| Inch  | mm   | mm   | mm             | m.H <sup>2</sup> O   | mm  | gr/m  | m  |
| 1     | 25   | 31   | 0.6            | 6  | 65  | 300   | 20   |
| 1 1/4 | 32   | 39   | 0.7            | 6  | 70  | 400   | 20   |
| 1 1/2 | 38   | 46   | 0.9            | 6  | 78  | 470   | 20   |
| 2     | 51   | 59   | 0.9            | 6  | 100   | 615   | 20   |
| 2 1/2 | 63   | 72   | 0.9            | 5  | 120   | 750   | 20   |

|       |     |     |     |     |     |      |    |
|-------|-----|-----|-----|-----|-----|------|----|
| 3     | 76  | 85  | 0.9 | 4   | 145 | 920  | 20 |
| 3 1/2 | 90  | 100 | 0.9 | 3.5 | 180 | 1080 | 20 |
| 4     | 102 | 114 | 1.1 | 3   | 200 | 1250 | 20 |
| 5     | 127 | 138 | 1.1 | 2.5 | 250 | 1560 | 20 |
| 6     | 152 | 165 | 1.1 | 2   | 350 | 1850 | 20 |
| 8     | 203 | 216 | 1.1 | 1.5 | 410 | 2500 | 10 |



-20°C to +80°C

Branding: SUPERFLEX PU-SIZE-MM

Colour : CLEAR/GREY HELIX

We use cookies to give you the best experience on our site. By using our site you accept our [Privacy Policy](#) [Accept & Close](#)