

FURUTECH

Furutech High Performance 4 Pin XLR Connector



FP-706F (R) / FP-705M (R)

Furutech makes a wide variety of OEM parts known the world over for their quality construction and superb sound. Our engineers examine every part of the signal and power path no matter how small and optimize each and every connection.

Take 4 Pin XLR connectors:

Furutech's beautifully finished, beautiful sounding FP-705M / FP-706F connectors feature α (Alpha) copper alloy conductors set in a special PBT / fiberglass resin insulation for minimal impedance and for high soldering temperatures. The FP-705M / FP-706F are finished in black painted housings.

Features and Materials

- Main conductor: Rhodium-plated α (Alpha) Copper alloy conductor
- Insulation with PBT and fiberglass Resin
- Housing: Nonmagnetic Zinc/Al alloy and Copper alloy (End shell)
- Connections: Soldered
- Specified for cable diameters up to 9mm
- Dimensions:
 - o FP-705M: 18.8mm \pm 0.1mm diameter x 63.2mm \pm 0.1mm overall length
 - o FP-706F: 19.5mm \pm 0.1mm diameter x 64.2mm \pm 0.1mm overall length

All metallic parts are treated with the

**FURUTECH α (Alpha) Process (Super Cryogenic & Demagnetizing Treatment.)*