## PARTS CONNE

## Fidelity Components TubeCap

The **TubeCap®** is made of polyprophylene film with special features. This is particularly thin and the self-healing properties are markedly pronounced due to a special coating. This leads to a very high electrical strength in the capacitor with compact dimensions.

The **TubeCap**® combines a high degree of dielectric strength and low residual inductivity with a very compact form of construction. It has been developed as a high-quality technical alternative to high-voltage electrolytic capacitors and is thus ideally suited to use in tube amplifiers.

## The advantages vis-à-vis electrolytic capacitors are:

- Lower ESR and lower residual inductivity
- No drying out; therefore longer service life
- Excellent Self-healing properties
- More compact form of construction
- There is no series connection necessary for increasing the dielectric strength.







Technical specifications: Dielectric: Polypeopylen

Dielectric: Polypropylen
Dielectric strengh: 550-1 000 VDC
Loss factor: tan < 0.005 bei 1 kHz
Sealing compound: PU UL 94-V0
Useful Life: 100 000 h @ hot spot 60°


Failure rate: 1 fit Cover: 0.5 x U ; 40°



Specifications casing 1: Bucket: Plastic bucket UL 94-V0 Terminals: copper wire, tin-plated Ø1.4 mm Weight: approx. 70g



Specifications casing 2: Bucket: aluminum bucket, unshrunken UL 94-V0 Terminals: copper wire, tin-plated Ø1,4 mm Weight: approx. 105g



Specifications casing 3: Bucket: aluminum bucket, unshrunken UL 94-V0 Terminals: internal screw thread M6 x 10 Weight: approx. 215g

Specifications casing 4: Bucket: aluminum bucket, unshrunken UL 94-V0 Terminals: internal screw thread M6 x 10 Weight: approx. 345g

tcap
MKP-capacitors for tubes applications

				ESR@10	ESL
	Capacity	VDC	Casing	Hz (typ.)	@500kHz
	$[\mu F] \pm 5\%$	[Volt]		[mOhm]	[nH]
MUNDORF-018-70406	10	1000	1	13	17.0
MUNDORF-019-70407	20	750	1	10	17.0
MUNDORF-020-70408	30	600	1	9	17.0
MUNDORF-021-70409	47	600	2	7	24.5
MUNDORF-022-72480	100	550	3	9	88,6
MUNDORF-023-72481	200	550	4	9	92.5

Toll Free: 1-866-681-9602 • Local: 905-681-9602 • Fax: 905-631-5777 Website: www.partsconnexion.com • Email: info@partsconnexion.com