

XLO•PRO™

For over twenty five years XLO has presided over the manufacturing of their products for 100% quality control backed with a limited lifetime warranty. We have the design and engineering expertise to form all of our cable's components right down to our precision machined connectors. Using special metals, premium dielectrics, XLO's proprietary winding geometries results in deeper, fuller and more detailed sound that immerses you in the performance.

XLO•PRO™ Cable Design

- Integrated Field-Balanced[™] winding geometry
- OCC (Ohno Continous Cast) Time-Aligned™ copper conductors
- Low-capacitance PTFE (Polytetrafluroethylene) dielectrics
- Precision-machined connectors with 24K mil-spec gold-plated contacts

XP-1A Single-Ended Audio Interconnect



XP-2A Balanced Audio Interconnect



XP-3A Shielded Phono Cable



Also available in DIN to RCA for Tone Arm cables

XP-4A 75 Ohm Coaxial Digital Cable



XP-4B AES/EBU Balanced Digital Cable



XP-5.2 Speaker Cable



Available with Banana plugs, 6.0 mm or 8.0 mm Spades

XP-5.4BW Bi-Wire Speaker Cable



Available with Banana plugs, 6.0 mm or 8.0 mm Spades

XP-1SW Single-Ended Subwoofer Cable

XP-2SW Balanced Subwoofer Cable





XP-10 AC Power Cable



Available with NEMA, Schuko, UK or Swiss plugs and 15A or 20A IEC