



Product Specification Guide

Product Name:

COLOR ATELIER BONDING PRIMER

PRODUCT DESCRIPTION: Mineral based, high solid, interior & exterior bonding primer. It adds tooth to the surface, is designed to mineralize synthetic, or unstable substrates prior to plaster applications, including Color Atelier Limestone Plaster, and Tadelakt. It is a premium quality essential primer contains marble dust and other minerals, designed for use with plasters to achieve a more consistent appearance and uniform absorption.

PROPERTIES:

- Matte finish
- Thicker consistency, easy application with roller
- Odorless
- Zero VOC
- Water thinned
- Fast drying
- Can be used on wood

READ ALL INSTRUCTIONS THOROUGHLY BEFORE USE

APPLICATION: Stir, shake thoroughly prior to use. Apply one or two coats with a roller. Allow minimum of 6 hours of dry time in between coats.

COVERAGE: Product is sold by weight.

14 lbs covers approximately 200 sq. ft.

50 lbs covers approximately 700 sq. ft.

Dry mil thickness: 1.4 mils/

COLOR: The natural state of the primer is white, may be tinted with universal liquid pigments if required.

PACKAGING: Color Bonding Primer for Plaster is available in 1-Gallon and 3.5-Gallon size.

SURFACE PREPARATION: For best results, all surfaces must be cleaned thoroughly, cured, firm and dry. Also free from dust, dirt and oil. Newly completed walls should be left to cure before the application of Bonding Primer.

NOTE: Do not apply if air or surface temperature is below 50 °F or is likely to fall below 50 °F within 2 hours of application.

DRYING TIME: 2 hours to dry. At 77 °F and 50% Relative humidity.

CLEAN UP & THINNING: Use Water. Clean brushes, rollers, pads etc. with warm, soapy water immediately after completion of painting.

Dry empty containers may be recycled in a can recycling program. Local disposal requirements vary; see your local dealer and consult your sanitation department or state-designated environmental agency on disposal options in your area.

CAUTION: Do not take internally. Close container after each use. **MAY IRRITATE EYES.** Do not get into eyes. If in eyes, rinse well with water. If swallowed, call Poison Control Centre or doctor immediately.

STORAGE: Keep tightly sealed. Store at room temperature. Do not store outside. Protect from freezing. Rotate stock every 90 days.

OPENING: Cut through slots on lid. Pry lid up at slots. To close, snap lid down firmly. Mix with a drill before decanting or use.

KEEP OUT OF REACH OF CHILDREN

NOTICE: We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within 30 days from that date it was, or reasonably should have been discovered.



VOC: 0 g/l