

Product Specification Guide

Product Name:

LIMESTONE PLASTER – FINE-TEXTURED

PRODUCT DESCRIPTION: Color Atelier Limestone Plaster is a natural mineral-based, medium to fine-textured finish, with a matte or slightly polished look, depending on technique.

- Achieve smooth, or fine-textured natural stone effect on interior surfaces with timeless, natural plaster.
- Finish creates a multi-toned stone look in matte-to-low sheen finish, with medium size grain forming a thicker body, comparable to coarser marmorino or sandstone.
- The natural blend of limestone, and marble dust gives this unique, tintable paste product a distinct look with an easy application and ability to create authentic textures and various natural stone looks.
- Product comes in ready to use paste, and is available in a curated palette of colors. Natural (untinted) version can be tinted to any desired color.
- Applied using a trowel in successive thin coats, Finish creates a timeless multitoned stone look with subtle variations and nuanced elegance.
- Manufactured in USA with highest quality natural ingredients, and non toxic formula. Durable and breathable finish. Naturally prevents mold and mildew growth. Hypo allergenic, produces a healthy indoor living environment.

READ ALL INSTRUCTIONS THROUGHLY BEFORE USE

COVERAGE: 1-Gallon will cover 50 to 70 sqft for two coats; depending on surface and texture.

APPLICATION: Apply Limestone Plaster on level 3+ finished drywall primed with Color Atelier Bonding Primer. The surface should be clean and cohesive; repair dents, holes, and imperfections. Mix the product thoroughly before use to ensure consistency. Apply the first coat of Limestone Plaster with a trowel, as evenly as possible avoiding trowel lines and ridges. Spread the material evenly maintaining the same thickness across the wall. Apply the second coat after the first coat is completely dry, this coat is where you can create some kind of a troweled texture, if desired, or close-in evenly. Apply the second coat using slight pressure while applying product with trowel. You may polish the limestone plaster finish to a low satin like sheen, if desired, or leave it matte.

Clear Wax and Sealer are optional topcoats.

Matte finish: On the last coat, as the plaster dries, do not burnish the plaster.

Polished finish: On the last coat, as the plaster dries, burnish plaster with edge of trowel obtaining a smooth surface and a low satin like sheen. Wax can be applied for an even higher polish.

Top coats: If desired, Lime Plaster can be finished with Sealer, or Wax, after allowing a minimum of 48 hours to dry.

Limewash: Limewash Paint can be applied in a thin manner on top of Limestone Plaster for subtle or dramatic decorative color finishes.

NOTE: Do not apply when surface or ambient temperature is below 41 degrees Fahrenheit or above 93 degrees Fahrenheit.

DRYING TIME: Allow to dry 24 hours between coats.

CLEAN UP: Immediately after use with hot, soapy water.

PACKAGING: Color Atelier Limestone Plaster is available in 1-Gallon & 3.5-Gallon sizes.

STORAGE: Keep tightly sealed. Store at the room temperature. Do not store outside. Protect from freezing. Rotate stock every 90 days.

OPENING: Cut through slots on lid. Pry lid up at slots. To close, snap lid down firmly. Mix with a drill before decanting or use.

CAUTION: Do not take internally. Close container after each use. MAY IRRITATE EYES. Do not get into eyes. If in eyes, rinse well with water. If swallowed, call Poison Control Centre or doctor immediately.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information at 1-800-424-LEAD or log onto www.epa.gov/lead

NOTICE: We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within 30 days from the date it was or reasonably should have been discovered.

KEEP OUT OF REACH OF CHILDREN

