

Product Specification Guide

Product Name:

LIME PLASTER - SMOOTH

PRODUCT DESCRIPTION: Color Atelier Lime Plaster is a natural mineral-based, fine grade, smooth finish, for low-to-high sheen, depending on technique.

- Achieve smooth stone and marble-like effects on interior surfaces with timeless, natural plaster.
- Finish shows tonal variations and is smooth to touch, comparable to traditional Italian Venetian plasters but with a more subtle, organic appeal.
- The natural blend of limestone and marble dust and gives this unique, tintable paste product a distinct look with an easy application and polishing ability.
 Without polishing finish will appear low sheen.
- Product comes in ready to use, smooth paste, and is available in a curated palette of colors. Natural (untinted) version can be tinted to any desired color.
- Applied using a trowel, coating knife, or spatula in successive thin coats to create
 a luminous, silky finish, making it a perfect fit in both traditional and contemporary
 settings.
- Manufactured in USA with highest quality natural ingredients, and non toxic formula. Durable and breathable finish. Naturally prevent mold and mildew growth. Hypo allergenic, produces a healthy indoor living environment.

READ ALL INSTRUCTIONS THROUGHLY BEFORE USE

COVERAGE: 1-Gallon will cover 80 to 120 sqft for two coats; depending on surface and texture.

APPLICATION: Apply Lime Plaster on level 4+ finished drywall primed with Color Atelier Mineral Primer (smooth) or Color Atelier Bonding Primer (slightly textured). The surface should be clean and cohesive; repair dents, holes, and imperfections. Mix the product thoroughly before use to ensure consistency. Apply Lime Plaster in two or more coats, in successive thin layers, with a trowel, coating knife or spatula, as evenly as possible avoiding lines and ridges. Spread the material evenly maintaining the same thickness across the wall. It may be necessary to scrape or sand any high points in order to smoothen the first coat. Apply the second coat after the first coat is completely dry. As the finish coat begins to dry up slightly, come back to it with a clean trowel to begin polishing lightly, increase the pressure each time by doing several passes. Third coat is optional for an extra smoothness or polish. The color variations of the finish is more pronounced with increased burnishing and in darker colors.

Clear Wax and Sealer are optional topcoats.

Matte finish: On the last coat, as the plaster dries, do not burnish the plaster.

Polished finish: On the last coat, as the plaster dries, burnish plaster with edge of trowel obtaining a smooth surface and satin-like finish. Wax can be applied for an even higher polish.

Top coats: If desired, Lime Plaster can be finished with Sealer, or Wax, after allowing a minimum of 48 hours to dry.

Limewash: Limewash Paint can be applied in a thin manner on top of Lime Plaster for subtle or dramatic decorative color finishes.

NOTE: Do not apply when surface or ambient temperature is below 41 degrees Fahrenheit or above 93 degrees Fahrenheit.

DRYING TIME: Allow to dry 24 hours between coats.

CLEAN UP: Immediately after use with hot, soapy water.

PACKAGING: Color Atelier Lime Plaster is available in 1-Gallon & 3.5-Gallon sizes.

STORAGE: Keep tightly sealed. Store at the room temperature. Do not store outside. Protect from freezing. Rotate stock every 90 days.

OPENING: Cut through slots on lid. Pry lid up at slots. To close, snap lid down firmly. Mix with a drill before decanting or use.

CAUTION: Do not take internally. Close container after each use. MAY IRRITATE EYES. Do not get into eyes. If in eyes, rinse well with water. If swallowed, call Poison Control Centre or doctor immediately.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information at 1-800-424-LEAD or log onto www.epa.gov/lead

NOTICE: We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within 30 days from the date it was or reasonably should have been discovered.

KEEP OUT OF REACH OF CHILDREN

