



## Product Specification Guide

**Product Name:**

**COLOR ATELIER WAX-SEALER**

---

**PRODUCT DESCRIPTION:** Wax-based liquid sealer, 2-in-1, versatile, and durable for Tadelakt wet area use, as well as lime paints and plasters. Color Atelier Wax-Sealer is a liquid beeswax sealer that is a versatile, durable, clear, protective topcoat. It provides the ultimate protection, giving the surfaces a silky feel. Wax-Sealer is designed to protect the plaster walls by increasing stain resistance and wipeability, without affecting the color, and maintaining the unchanged troweled effect. It gives a very low sheen naturally, and can be polished to a higher sheen, if desired.

### **ADVANTAGES:**

- Durable on wet areas
- Versatile wax-based sealer
- Clear Finish
- Fast Drying
- Easy Application
- Can be diluted according to use

### **READ ALL INSTRUCTIONS THOROUGHLY BEFORE USE**

**COVERAGE:** Per Gallon the coverage will be approximately 400 square feet in one coat, undiluted. Can be diluted according to use.

**APPLICATION:** After all plastering, burnishing is completed, you may seal the walls. Allow the final coat tadelakt, lime plaster or lime paint surfaces to dry/ cure at least for 2-3 days before applying the wax-sealer on top. Stir it thoroughly prior to use. Simply apply it with a flat tip brush in a random or multi-directional method in thin layers, and brush it on section by section, back wipe any excess and rub in softly using a circular motion with a lint free cloth. One or two

coats of sealer are recommended depending on the area, and the application. Wet areas require at least two coats of wax-sealer. Allow the sealer to dry completely in between coats. The process is simple and quick, do not overwork it, and make sure to apply it thin, avoid thick coats. You can dilute the product with water if needed.

**SURFACE PREPARATION:** All surfaces must be firm, dry, and cleaned free of dust, dirt.

**MAINTENANCE:** Remove surface dust to clean. To renew protection, apply the product every two to three years.

**NOTE:** Storage temperature: from 41 °F to 86 °F. Do not apply when surface or ambient temperature is below 50 °F or above 86 °F.

**DRYING TIME:** Allow to dry about two hours between coats.

**CLEAN UP:** Immediately after use with hot, soapy water, or solvents.

**PACKAGING:** Color Atelier Wax-Sealer is available in Quart and 1-Gallon sizes.

**TECHNICAL FEATURES:**

**Color:** Appears milky white in can, dries clear. Always perform a test sample before use as a slight color variation may occur.

**Odor:** Light, slight petroleum odor.

**Flash point:** 174 °F (> 79°C)

**STORAGE:** To close, snap lid down firmly. Keep tightly closed. Store at the room temperature. Do not store outside. Rotate stock every 90 days.

**OPENING:** Cut through slots on lid. Pry lid up at slots.

**CAUTION:** Keep out of reach of children. Do not take internally. If in eyes, rinse well with water. If swallowed, call Poison Control Centre or doctor immediately. Wash hands after use. When spraying or sanding use a NIOSH approved respirator. Provide adequate ventilation.

**NOTICE:** We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within 30 days from the date it was or reasonably should have been discovered.

**KEEP OUT OF REACH OF CHILDREN.**

