

Blazemaster MK VI



EN 659

Stockcode	Description	s	Size				
	Blazemaster ® Pro-Fit MK V	T-1					
2610000059	FF/WCW/RP/HP/CKL/KKW	6SF	XXS				
2610000060	FF/WCW/RP/HP/CKL/KKW	6	XXS				
2610000069	FF/WCW/RP/HP/CKL/KKW	7SF	XS				
2610000070	FF/WCW/RP/HP/CKL/KKW	7	XS				
2610000080	FF/WCW/RP/HP/CKL/KKW	8	S				
2610000090	FF/WCW/RP/HP/CKL/KKW	9	M				
2610000100	FF/WCW/RP/HP/CKL/KKW	10	L				
2610000110	FF/WCW/RP/HP/CKL/KKW	11	XL				
2610000120	FF/WCW/RP/HP/CKL/KKW	12	XXL				
2610000130	FF/WCW/RP/HP/CKL/KKW	13	XXXL				
Blazemaster ® Pro-Fit MK VI-3							
2630000059	FF/WCW/FRP/HP/CKL/KKW	6SF	XXS				
2630000060	FF/WCW/FRP/HP/CKL/KKW	6	XXS				
2630000069	FF/WCW/FRP/HP/CKL/KKW	7SF	XS				
2630000070	FF/WCW/FRP/HP/CKL/KKW	7	XS				

C€ 0598

2630000080 FF/WCW/FRP/HP/CKL/KKW

2630000090 FF/WCW/FRP/HP/CKL/KKW

2630000100 FF/WCW/FRP/HP/CKL/KKW

2630000110 FF/WCW/FRP/HP/CKL/KKW

2630000120 FF/WCW/FRP/HP/CKL/KKW

2630000130 FF/WCW/FRP/HP/CKL/KKW

Gloves are made to the following (EN 659) sizes: 6.7. 8. 9,10,11,12,13

MARKING

Each packet shall be labelled/ contain information concerning size, type, quantity, manufacturer, the UKCA & CE mark and/or the European Standard for Firefighters gloves reference No: EN 659:2003 + A1:2008. This information is provided in each packet

Tacte (EN 650-2002+A1-2008) Parformance Levels

16313 (FIN 033.2003TAT.200			uo) renonnance Lev	CIO
Abrasion Resista	ance	3	Blade Cut Resistance	4
Tear Resistance		3	Puncture Resistance	3
Burning Behavio	ur	4	Contact Heat Wet & Dry	/ Pass
Contact Heat		3*	Convective Heat	4
Radiant Heat (40) Kw)	Pass	Heat Shrinkage	Pass
Lining	Pass		Seam Strength	Pass
Chemical Tests	Pass		Donning Test	Pass
Immersion	Pass		-	

BS ENISO 21420:2020

Chromium(VI) Max 2 ppm Azo Dyes Min 3.5 Max 9.5

Water Resistance Dexterity Pass ISO 811 Water Resistance >20kPa Viral Penetration No Leaks

WARNINGS:

Test results apply to the gloves in the as received condition but do not extend to any leather cuff .Result may differ if cleaned. Do not use near moving machinery due to entanglement hazard. Overall classification may not reflect the performance of only the outermost layer. These gloves may not be suitable for protection against sharply pointed objects such as hypodermic needles.

Note overall classification does not necessarily reflect the performance of the outer layer. Gloves should not be used when there is a risk of entanglement in moving

PACKING AND STORAGE

S

М

XL

XXL

XXXL

10

11

12

13

Gloves are usually wrapped and bundled in polymeric packaging. Can be used under normal climatic conditions. New gloves can be used up to five years after date of supply if stored correctly. The gloves are packed in bundles, along with this leaflet. Gloves should be stored away from direct sunlight to maintain the optimum properties of the glove. Labels or information shall contain the user instructions for the minimum resale quantity. This bundle is suitable for transportation and storage.

OBSOLESCENCE: Stored correctly, the gloves' physical properties will not change for up to five years.

Care Instructions: Both new and used gloves should be thoroughly inspected before and after use, especially after cleaning treatment, and before being worn to ensure no damage is present. Damaged gloves should not be worn and should be disposed of. Wet or contaminated gloves should not be used. Dirty gloves may not provide the same level of protection as that shown. Gloves should not be left in a contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible, provided no serious hazards exist, before removal from the hands. Excess contaminant should first be removed, e.g. loose dirt can be brushed off with a soft brush. Rinse the gloves in clean water. Soiled gloves should be cleaned with a damp cloth. Strong cleaning agents e.g. bleach should not be used; strong detergents may impair the water resistance. Remove the gloves and thoroughly rinse in several changes of clear lukewarm water. It is essential that the gloves are rinsed in water

after cleaning to remove all traces of mild detergent if used. The gloves may be de-contaminated with mild detergent solution, then rinsed with clean water and allowed to dry naturally, ideally with some air movement. Squeeze out the surplus water from the fingertips downwards. Never wring the gloves. Pull the gloves gently into shape. They can then be hung up to dry in a current of air but away from a direct heat source or sunlight. Do not dry on a hot surface. When nearly dry, ease them carefully onto the hands so that the softness, shape and size can be restored.

When the contaminant is not removable or presents a potential hazard, it is advisable to ease left and right hand gloves off alternatively using the gloved hand so that the gloves are removed without the contaminant contacting the bare hands. Washing is not recommended. Do not wring. Do not tumble dry. Do not use bleach. Reshape whilst still damp.

Warning:

 \Box

婡

 \Rightarrow

Further copies of this information and information on other products are available from :Bennett Safetywear Ltd [] +44 (0)151 924 3996, Blazemaster® is registered trademark of Bennett Safetywear Ltd.

COMPLEX SAFETY CATERGORY

Gloves are designed to protect hands in the working environment in accordance with, BS EN ISO 21420:2020 & EN407:2020. EN 659:2003+A1:2008. When selecting a glove based on risk analysis it should be understood that the protection is limited to the risk level and standards mentioned above. The type examination was carried out ITS Testing Services.

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.

GENERAL. The quality systems used to manufacture and supply the gloves are in compliance with ISO 9001:2015.

PLEASE NOTE

The information contained here is intended to assist the wearer in the selection of personal protective equipment. The result of the laboratory tests should help with correct glove selection; however, it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the glove suitabile for the intended use.

Council Regulations (EU) 2016/425 on personal prtotective equipment and as amended to appply in GB. and with the national standard transposing harmonised standard No :BS EN 659:2003:A1:2009. BS EN 407:2020. BS EN 388:2016 & A1:2018. BS EN ISO 21420:2020, and is identical to the PPE which is subject of UKCA certificate LECFI00383091 issued by:ITS TESTING SERVICES. CENTRE COURT. MERIDAN BUSINESS PARK, LEICESTER, U.K., LE19 1 WD. Approved Body Number: AB0362 who performed the type-examination and is subject to the procedure set out in the Regulations (EU) 2016/425 on personal prtotective equipment and as amended to appply in GB Module D under the supervision of the approved body SGS United Kingdom, Rossmore Business Park, Ellesmere Port, South Wirral, Cheshire, CH65 3EN, United Kingdom. Their approved body number is 0120 and is also the subject of the EU certificate. No: LECFI00379801 issued by: ITS Testing Services, Centre Court, Meridian Business Park, Leicester, LE19 1WD, UK., notified body number is 0362: who performed the type-examination. The notified body Intertek Italia S.p.A. Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio -Milano (MI) Italy NB 2575, now owns this document, and it is valid under this notified body., and is subject to the procedures under the supervision of the notified body SGS Fimko Ov. Takomotie 8. Helsinki. 00380. Finland. Their notified body number is 0598.

Bennett Safetywear Ltd declares that the new PPE as

described in the TD 1003 technical specification for

Blazemaster Gloves are in conformity with European

Done at: Bennett Safetywear Ltd, 7-11 MERSEY ROAD, CROSBY, LIVERPOOL, UK

Signature:

Mr E. Baker

.Quality Manager

This series satisfies the basic requirements of the PPE Regulation (EU) 2016/425 on personal protective equipment and as amended to apply in GB being innocuous/free from nuisance factors, ergonomic and breathable. Conditions of use are not simulated by the test results and as such service life cannot be specified. Further copies of this information and declarations of conformity are available on request from:

> Bennett Safetywear Ltd **2** +44 (0)151 924 3996

Web: http://bennettsafetywear.co.uk.

DECLARATION