

# AJAX™ Guardian

2519600060	TRD/PSU/WR/HP/CKL/30/VS	6
2519600070	TRD/PSU/WR/HP/CKL/30/VS	7
2519600080	TRD/PSU/WR/HP/CKL/30/VS	8
2519600090	TRD/PSU/WR/HP/CKL/30/VS	9
2519600100	TRD/PSU/WR/HP/CKL/30/VS	10
2519600110	TRD/PSU/WR/HP/CKL/30/VS	11
2519600120	TRD/PSU/WR/HP/CKL/30/VS	12
2519600130	TRD/PSU/WR/HP/CKL/30/VS	13
2519801060	TRD/PSU/WR/HP/CKL/30	6
2519810070	TRD/PSU/WR/HP/CKL/30	7
2519810080	TRD/PSU/WR/HP/CKL/30	8
2519810090	TRD/PSU/WR/HP/CKL/30	9
2519810100	TRD/PSU/WR/HP/CKL/30	10
2519810110	TRD/PSU/WR/HP/CKL/30	11
2519810120	TRD/PSU/WR/HP/CKL/30	12
2519810130	TRD/PSU/WR/HP/CKL/30	13
2519620090	TRD/PSU/WR/HP/CKL/30/VS/1EP	9
2519630090	TRD/PSU/WR/HP/CKL/30/VS/2EP	9
2519640090	TRD/PSU/WR/HP/CKL/30/VS/3EP	9
2519650090	TRD/PSU/WR/HP/CKL/30/1EP	9
2519660090	TRD/PSU/WR/HP/CKL/30/2EP	9
2519670090	TRD/PSU/WR/HP/CKL/30/3EP	9
2519700060	TRD/PSU/WR/HP/CKL/34/VS	6
2519700070	TRD/PSU/WR/HP/CKL/34/VS	7
2519700080	TRD/PSU/WR/HP/CKL/34/VS	8
2519700090	TRD/PSU/WR/HP/CKL/34/VS	9
2519700100	TRD/PSU/WR/HP/CKL/34/VS	10
2519700110	TRD/PSU/WR/HP/CKL/34/VS	11
2519700120	TRD/PSU/WR/HP/CKL/34/VS	12
2519700130	TRD/PSU/WR/HP/CKL/34/VS	13
2519710060	TRD/PSU/WR/HP/CKL/34	6
2519710070	TRD/PSU/WR/HP/CKL/34	7
2519710080	TRD/PSU/WR/HP/CKL/34	8
2519710090	TRD/PSU/WR/HP/CKL/34	9
2519710100	TRD/PSU/WR/HP/CKL/34	10
2519710110	TRD/PSU/WR/HP/CKL/34	11
2519710120	TRD/PSU/WR/HP/CKL/34	12
2519710130	TRD/PSU/WR/HP/CKL/34	13
2519720090	TRD/PSU/WR/HP/CKL/34/VS/1EP	9
2519730090	TRD/PSU/WR/HP/CKL/34/VS/2EP	9
2519740090	TRD/PSU/WR/HP/CKL/34/VS/3EP	9
2519750090	TRD/PSU/WR/HP/CKL/34/1EP	9
2519760090	TRD/PSU/WR/HP/CKL/34/2EP	9

2519770090	TRD/PSU/WR/HP/CKL/34/3EP	9
2519800060	TRD/PSU/WR/HP/CKL/34/3EP	6
2519800070	TRD/PSU/WR/HP/CKL/34/3EP	7
2519800080	TRD/PSU/WR/HP/CKL/34/3EP	8
2519800090	TRD/PSU/WR/HP/CKL/34/3EP	9
2519800100	TRD/PSU/WR/HP/CKL/34/3EP	10
2519800110	TRD/PSU/WR/HP/CKL/34/3EP	11
2519800120	TRD/PSU/WR/HP/CKL/34/3EP	12
2519610060	TRD/PSU/WR/HP/CKL/36/3EP	6
2519610070	TRD/PSU/WR/HP/CKL/36/3EP	7
2519610080	TRD/PSU/WR/HP/CKL/36/3EP	8
2519610090	TRD/PSU/WR/HP/CKL/36/3EP	9
2519610100	TRD/PSU/WR/HP/CKL/36/3EP	10
2519610110	TRD/PSU/WR/HP/CKL/36/3EP	11
2519610120	TRD/PSU/WR/HP/CKL/36/3EP	12
2519610130	TRD/PSU/WR/HP/CKL/36/3EP	13
2519820060	TRD/PSU/WR/HP/CKL/36/VS/3EP	6
2519820070	TRD/PSU/WR/HP/CKL/36/VS/3EP	7
2519820080	TRD/PSU/WR/HP/CKL/36/VS/3EP	8
2519820090	TRD/PSU/WR/HP/CKL/36/VS/3EP	9
2519820100	TRD/PSU/WR/HP/CKL/36/VS/3EP	10
2519820110	TRD/PSU/WR/HP/CKL/36/VS/3EP	11
2519820120	TRD/PSU/WR/HP/CKL/36/VS/3EP	12
2519820130	TRD/PSU/WR/HP/CKL/36/VS/3EP	13

This series satisfies the basic requirements of the PPE Regulations in being innocuous/free from nuisance factors, ergonomic . Conditions of use are not simulated by the test results and as such service life cannot be specified. Results should be used for guidance in initial selection.

**PACKING AND STORAGE**

New gloves can be used up to five years after the date of manufacture if stored correctly. Store in original packaging. This is suitable for transportation and storage.

The gloves shall be bundled along with this leaflet in polymeric bags in carboard cartons and each bag will be labelled with the appropriate marking with regards to amount, type, size, manufacturer and performance level, CE & UKCA mark. Each garment will contain labels containing similar details. Store the gloves in a cool dry place and out of direct sunlight. Ideally stored between 5 and 25C in a dry well ventilated area in original packaging.

**OBSOLESCENCE**

Stored correctly, the gloves' physical properties will not change for up to five years.

**GENERAL**

The quality systems used to manufacture and supply the gloves are in compliance with ISO 9001:2015.

Packaging/Labels:

**Informative:**

**SELECTION OF PUBLIC ORDER GLOVES**

Selecting the correct size glove. It is important to select the correct fitting glove. To determine your hand size measures the circumference of your hand about 2.5 cm below the knuckle not including your thumb. See Bennett Safetywear Glove Sizes Guide

Your hand size is the circumference measured in inches. Once you have measured your hand size you can select the correct size glove. If your hand circumference measures 9 inches your EN 420 hand size is size 9.If your hand circumference is bigger than 9" but less than 10 " choose the size 10 glove. e.g.. If you have a 9½" hand circumference choose a size 10 glove and so on.

**DONNING OF PUBLIC ORDER GLOVES**

Now that the correct glove has been selected the glove should be placed on the hand. Note all rings should be removed before wearing gloves. Occasionally during transportation the glove linings may become slightly bunched inside glove. To re-align the glove lining, don the glove correctly, locate your digits into the fingers of the gloves and pull on the finger tips and glove cuff. This stretches out the glove and allows the glove to go on more easily.

**DOFFING OF GLOVES.**

When you need to doff your glove: Gloves should be visually inspected before wearing for signs of damage which may impair the performance of the item. Damaged gloves will not provide the protection stated in the user information sheet and should not be used

**DISPOSAL OF GLOVES**

Gloves should be disposed of responsibly. Currently gloves are not recyclable.

**ADVICE:**

These gloves are not intended to protect against slash injuries from edged weapons and glass. These gloves are intended to enable operatives to use all the other protective clothing and equipment designed for use in violent situations and in training (e.g. personal defence shields) without removing their gloves. The provision of such dexterity necessitates limitation



EN 407

**CE 0598**



EN 388

Performance Level	Type	Std
Abrasion Resistance: 3	Blade Cut Resistance Coup: X	EN 388:2016+A1:2018
Tear Resistance: 4	Puncture Resistance: 4	EN 388:2016+A1:2018
Blade Cut Resistance TDM: F	Impact Protection: X	EN 388:2016+A1:2018
Burning Behaviour: 4	Contact Heat: 2	EN 407:2020
Convective Heat: 4	Radiant Heat: 3	EN 407:2020
Small Drop Molten Metal: X	Large Drops Molten Metal: X	EN 407:2020
Lining: Pass		EN 659:2003
Impact test: Pass		BS7971-6:2016
Chemical: Pass		BS7971-6:2016
Ergonomics: Pass		BS7971-6:2016
Chromium(VI): Pass	pH:Pass	EN ISO 21420:2020
Dexterity: 5		EN ISO 21420:2020

\* Gloves should not be expected to provide protection against prolonged contact with hot surfaces.

\*\*Gloves should not be expected to provide protection against all chemicals

\*\*\*Gloves should have a full ergonomics assessment by specifiers /users to ensure compatibility with other items of PPE.

\*\*\*\* Gloves should not be expected to provide protection against Electrical or Biological hazards.

Web site : <http://www.bennettsafetywear.co.uk> Email : [sales@bennettsafetywear.co.uk](mailto:sales@bennettsafetywear.co.uk)

of the stiffness and thickness of the gloves and thus limits the protection that can be provided.

Note gloves with trigger fingers do not offer the same level of protection in the region of the trigger finger. Results listed do not necessarily reflect the performance classification of the outermost layer of the product. Gloves should not be worn when there is a risk of entanglement by moving parts of machines.


Users should ensure that the gloves are compatible with their chosen personal defence equipment such as batons, incapacitant sprays and handcuffs.

The gloves might not fully protect against cuts and perforations in direct blows from, for example, sharp knives, spikes, needles, machetes, felling axes, chain saws, samurai swords and skimmed glass.

The gloves might not fully protect against direct blows by, for example, bricks, bottles, bars, slates or hand held weapons such as metal or wooden bars, bats or poles. The gloves might not protect against burns if the operative enters a burning building, vehicle etc. The gloves cannot be expected to protect against injury from immersion in all chemicals.

#### UK & EU DECLARATION

Bennett Safetywear Ltd declares that the new PPE as described in the technical specification for TD 1014 for Ajax Guardian gloves are in conformity with the Regulation 2016/425 on PERSONAL PROTECTIVE EQUIPMENT, and as amended to apply in GB and with the national transposing harmonised standard No BS EN 388:2016, BS EN ISO 21420:2020, BS EN 407:2020 & And is also the subject of the EU certificate which complies with and provisions of European Council Regulations (EU) 2016/425, . No: OZO296-CPT001/22 issued by: Mirta KONTROL d.o.o. Gradiška 3, 10040 Zagreb, Dubrava, Hrvatska (Croatia) Their notified body number is 2474, and is subject to the procedures under the Module D supervision of the notified body SGS Fimko Oy, P.O. Box 30 (Särkiniementie 3), 00211 HELSINKI, Finland 0598. Their notified body number is 0598.

Done at : Bennett Safetywear Ltd, 7-11 MERSEY ROAD, CROSBY, LIVERPOOL, UK  
Signature:  Mr E. Baker .Quality Manager

**Further copies of this information and declarations of conformity are available on request from:**

**Bennett Safetywear Ltd**

**+44 (0)151 924 3996**


**Web : <http://www.bennettsafetywear.co.uk>**

#### CARE / MAINTENANCE

Cleaning and disinfection is not intended for these gloves.

Both new and used gloves should be thoroughly inspected before use, especially after cleaning treatment, and before being worn to ensure no damage is present. Gloves should not be left in a contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible, provided no serious hazards exists, before removal from the hands. Excess contaminant should first be removed and the gloves may be de-contaminated with mild detergent solution, then rinsed with clean water and dried ideally with some air movement. When the contaminant is not removable or presents a potential hazard it is advisable to ease left and right hand gloves off alternatively using the gloved hand so that the gloves are removed without the contaminant contacting the bare hands.

Do not wring. Do not tumble dry. Do not use bleach. Contaminated gloves should not be used.


Warning: 

**Performance of the gloves is stated as new and maybe affected after use/ cleaning be inspected before use and before and after and cleaning.**

#### General Care Instructions:

##### LEATHER gloves

Using sufficient mild detergent washing up liquid in lukewarm water create a good lather. Wet the gloves completely and slip them on. They can now be washed as one would wash ones hands. Any badly soiled parts should be treated by rubbing with a pad of cotton wool which has been dipped in to lather. Remove the gloves and thoroughly rinse in several changes of clear lukewarm water. Gloves may release a little dye into the water and should therefore be washed on their own.

It is essential that the gloves are rinsed in water after washing to remove all traces of the detergent. Warning: 

##### Drying of Leather Gloves

Squeeze out the surplus water from the finger tips downwards. Never wring the gloves. Pull the gloves gently into shape and blow into them to separate the surfaces. They can then be hung up to dry in a current of air but away from a direct heat source or sunlight.

When nearly dry ease them carefully onto the hands so that the softness, shape and size can be restored and when quite dry polish with a soft cloth

**Do not dry on a hot surface.**