

# The following Method of Entry Mitts are manufactured by Bennett Safetywear Ltd. (BSL)

Stockcode 1231500021	Dev No 1371	Description1 Trade Black leather moe mitts		Size 9
1199990012		Black leather moe mitt		9
1231000011	1409A	Enforcer Mitt	7007D	9 10
1231000011	1409A 1409A	Enforcer Mitt	1409A	9
1231000031	1409A	Black leather	1 finger mitt 18	9
1231100021	1509	Black leather MOE	mitts	9
1231200031	1560	Black leather mitts	aramid lined 22	9
1231600021	1560/EW/VS	Black leather mitts	search and seizure	e 9
1971200090	1756	Protective sleeve 1756		

Gloves are made to EN ISO21420:2020 Annex B sizes



#### Areas of Protection

GLOVE STYLE	PALM AREA PROTECTED	BACK OF HAND AREA PROTECTED	FRONT CUFF AREA PROTECTED	BACK CUFF AREA PROTECTED
1409	YES	YES	YES	YES
1409 A	YES	YES	YES	YES
1409 B	YES	YES	YES	YES
1560	YES	YES	YES	YES
1371	NO	YES	YES	YES
1509	NO	YES	YES	YES

4

Additional Test BS EN 420:2003-A1:2009 : Clause 4.2 Water Penetration

# BENNETT SAFETYWEAR LTD 7-11 MERSEY ROAD, CROSBY, LIVERPOOL, UK **TD NO: 1029**

#### **GLOVE DESCRIPTION**

Chrome leather/Aramid sandwiched mitts. Gloves offer excellent cut and puncture resistanc when used for gaining entry.

### MARKING

Each packet shall be labelled / contain the appropriate marking with regards to the amount, type , size, manufacturer , performance levels and UKCA & CE mark. Labels on the gloves will contain similar information. This information will be provided in the minimum resale quantity.

#### INTERMEDIATE SAFETY CATERGORY

Gloves are designed to protect hands in the working environment in accordance with EN 388:2016+A1 :2018, EN21420:2020. When selecting a glove based on risk analysis it should be understood that the protection is limited to the risk level and standards mentioned above.

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.


#### WARNINGS:

Test results apply to the gloves in the as received condition. Result may differ if cleaned. Do not use near moving machinery due to entanglement hazard. Overall classification may not reflect the performance of only the outermost layer. These gloves may not be suitable for protection against sharply pointed objects such as hypodermic needles.

# **CARE / MAINTENANCE**

Cleaning and disinfection is not intended for these gloves.

Both new and used gloves should be thoroughly inspected before and after use, especially after cleaning treatment, and before being worn to ensure no damage is present. Damaged gloves should not be worn and should be disposed of. Wet or contaminated gloves should not be used. Dirty gloves may not provide the same level of protection as that shown. Gloves should not be left in a contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible, provided no serious hazards exist, before removal from the hands. Excess contaminant should first be removed, e.g. loose dirt can be brushed off with a soft brush. The gloves may be de-contaminated with mild detergent solution, then rinsed with clean water and allowed to dry naturally, ideally with some air movement. When the contaminant is not removable or presents a potential hazard it is advisable to ease left and right hand gloves off alternatively using the gloved hand so that the gloves are removed without the contaminant contacting the bare hands. Washing is not recommended. Do not wring. Do not tumble dry. Do not use bleach. Reshape whilst still damp.



ISSUE 8

PACKING AND STORAGE

Gloves can be used up to five years after date of supply if stored correctly.

The gloves are packed in bundles, along with this leaflet. This bundle is suitable for transportation and storage.

#### OBSOLESCENCE

Stored correctly, the gloves' physical properties will not change for up to five years.

#### GENERAL

The quality systems used to manufacture and supply the gloves are in compliance with ISO 9001:2015.

# PLEASE NOTE

The information contained here is intended to assist the wearer in the selection of personal protective equipment. The result of the laboratory tests should help with correct glove selection; however, it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the glove suitabile for the intended use.

#### DECLARATION

Bennett Safetywear Ltd declares that the new PPE as described in the TD 1029 technical specification for M.o.E. Mitts, and is identical to the PPE which is subject of UKCA certificate ??? issued by: ITS TESTING SERVICES, CENTRE COURT, MERIDAN BUSINESS PARK, LEICESTER, U.K., LE19 1 WD, Approved Body Number: AB0362 who performed the type-examination and is subject to the procedure set out in the Council Regulations (EU) 2016/425 and as amended to apply in GB and with the national standard transposing harmonised standard No : BS EN 388:2016+A1 :2018, BS ENISO 21420:2020, and is also the subject of the EU certificate. No: LECFI00373359, issued by: ITS Testing Services, Centre Court, Meridian Business Park, Leicester, LE19 1WD, UK., notified body number is 0362: who performed the type-examination . The notified body Intertek Italia S.p.A. Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy NB 2575, now owns this document, and it is valid under this notified body Done at : Bennett Safetywear Ltd, 7-11 MERSEY ROAD, CROSBY, LIVERPOOL, UK Signature:

Mr E. Baker .Quality Manager

Further copies of this information and declarations of conformity are available on request from:

> Bennett Safetvwear Ltd **\*** +44 (0)151 924 3996 Web : http://bennettsafetywear.co.uk

**EC/TECH DIGEST**