

TEL: 00 44 151 924 3996, FAX 00 44 151 924 6548, EMAIL: sales@bennettsafetywear.co.uk, Web:// www.bennettsafetywear.co.uk

Information for customer

Stockcode	Dev No	Description	Stockcode	Dev No	Description
1960000021 199990011 1961300021 1960400031	03P/2077 1609 1609G 1100	B1/NMX/1E B2/NMX/OF B2/NMX/OF/G B42/NMX/1E	1999900011 1999900011 1961200021 1961310021	1262EW 1609E 1760 1115	B2/NMX/NGEW B2/NMX/OFE/G B1NMX/OF/VF B42/NMX/PNC
1960500011 4499990031 1961000031 1961160021 1999990011 1999990011	1363 V0712 1504B 1504D 1727 1729	B42/NMX/NP/SS B1/NMX/1E//CWL B1/NMX/B/2E B1/NMXB/1E/BT B42/NMXB/NP/SS B1/NMXB/1E B2/NMXB/OF/G	1961170031 1961150011 1961190031 1999990011 1999990011 1961320011	1504 1504C 1504E 1728 1651	B1/NMXB/1E B1/NMXB/2EM B1/NMXB/2EM/BT B4/NMXB/1E B1/NMXB/1E/G B11/NMXB/1E/G

DESCRIPTION

Meta-aramid knitted fabric hoods and balaclavas with excellent thermal insulation and inherently flame retardant. Hoods must be worn with clothing manufactured to the same standard EN11612:2015, and EN ISO 13688:2013.

Shape Image: Legister of the property of the pro	dard EN11612:2015 and EN ISO 13688:2013								
No: 1363 1100 1115 1262 Ecru No	Shape						Colour		
No 4 4 4 4 2 1 Front Layers 2 2 2 2 1 Back Shape Image: Control of the property o	Dev	1727	1728	1730	1731	1504	Black		
Layers 2 2 2 2 1 Back	No:	1363	1100	1115	1262		Ecru		
Shape Image: Control of the control of th	No	4	4	4	2	1	Front		
Dev 1504A 1504B 1504C 1504D 1729 Black No: 07P/2262 07P/2077 Ecru No 1 1 1 1 1 Front Layers	Layers	2	2	2	2	1 _	Back		
No: 07P/2262 07P/2077 Ecru No 1 1 1 1 1 Front Layers	Shape	0.		ि	四	四			
No 1 1 1 1 1 1 Front Layers	Dev	1504A	1504B	1504C	1504D	1729	Black		
Layers	No:	07P/2262				07P/2077	Ecru		
1 1 1 1 Back		1	1	1	1	1	Front		
		1	1	1	1	1	Back		

Hoods and balaclavas are made to one size. Note test data relates to 1 layer of fabric after 15 dry clean cycles.

Test Data	
EN ISO 11612: 2015	Level
Limited flame spread – Face ignition	A1
Limited flame spread – Seams	A1
Dimensional change due to cleaning	<5%
Burst strength	700kF
Burst strength (seam)	450kF



Convective heat C1 Radiant heat

MARKING

Each packet shall be labelled / contain the appropriate marking with regards to the amount, type, size, manufacturer, performance levels, UKCA & C€ mark. Labels on the Hoods will contain similar information. This information will be provided in the minimum resale quantity.

INTERMEDIATE SAFETY CATERGORY

Hoods are designed to protect heads in the working environment in accordance with EN ISO 11612: 2015 & ISO 13688:2013 and both UK & EU regulations. When selecting a hood based on risk analysis it should be understood that the protection is limited to the risk level and standards mentioned above.

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.

WARNINGS: Test results apply to the Hoods after dry cleaning cycles. Do not use near moving machinery due to entanglement hazard.

CARE / MAINTENANCE

Both new and used Hoods should be thoroughly inspected before and after use, especially after cleaning treatment, and before being worn to ensure no damage is present. Damaged Hoods should not be worn and should be disposed of. Wet or contaminated Hoods should not be used. Dirty Hoods may not provide the same level of protection as that shown. Hoods should not be left in a contaminated condition if re-use is intended, in which case Hoods should be cleaned as far as possible. If contaminated during use with a splash of chemical or flammable liquid, the user should withdraw immediately and carefully remove the garment so that it does not come into contact with any part of the skin. These items do not offer protection against molten metal.

Do not wring. Do not tumble dry. Do not use bleach. Hoods may be dry cleaned.



PACKING AND STORAGE

Can be used under normal climatic conditions. Hoods shall be wrapped in polymeric packaging.

Hoods can be used up to five years after date of supply if stored correctly. Store in original packaging. Hoods should be ideally stored in a cool dry place away from direct sunlight at ambient temperatures (between 5°C and 25°C) in a dry well ventilated area in original packaging to maintain the optimum properties of the hood. The Hoods are packed in bundles, along with this leaflet. This bundle is suitable for transportation and storage.

OBSOLESCENCE

Stored correctly, the Hoods' physical properties will not change for up to five vears.

GENERAL

The quality systems used to manufacture and supply the Hoods are in compliance with ISO 9001:2015.

PLEASE NOTE

The information contained here is intended to assist the wearer in the selection of personal protective equipment. The result of the laboratory tests should help with correct garment selection; however, it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the garment suitable for the intended use.

DECLARATION

Bennett Safetywear Ltd declares that the new PPE as described in the TD 1044 technical specification for Benex hoods and balaclavas are in conformity with provisions of Council Regulations (EU) 2016/425 on personal protective equipment and as amended to apply in GB and with the national standard transposing harmonised standard No :BS EN ISO 11612: 2015 & ISO 13688:2013 and identical to the PPE which is the subject of the UKCA certificate LECFI00383475 issued by: ITS TESTING SERVICES, CENTRE COURT, MERIDAN BUSINESS PARK, LEICESTER, U.K., LE19 1 WD, Approved Body Number: AB0362 who performed the type-examination and is subject to the procedure set out in the Regulations (EU) 2016/425 on personal protective equipment and also identical to the PPE which is the subject of the EU certificate. No: LECFI00374298, issued by: ITS Testing Services, Centre Court, Meridian Business Park, Leicester, LE19 1WD, UK., notified body number is 0362: who performed the type-examination. The notified body Intertek Italia S.p.A. Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy NB 2575, now owns this document, and it is valid under this notified body

Done at : Bennet.t Safetywear Ltd, 7-11 MERSEY ROAD, CROSBY, LIVERPOOL . UK

Mr E. Baker .Quality Manager

Further copies of this information and declarations of conformity are available on request from:

> Bennett Safetywear Ltd **2** +44 (0)151 924 3996 Web: http://bennettsafetywear.co.uk

TD1044 Issue 5 07/03/2022