

All the following



gloves are manufactured by
Bennett Safetywear Ltd, (BSL)



STOCKCODE	DESCRIPTION	SIZE	TYPE
1400600031	W9/G2/HR/WT/AP5/18BL/LC5	9	A
1400600100	W9/G2/HR/WT/AP5/18BL/LC5	10	A
1400600110	W9/G2/HR/WT/AP5/18BL/LC5	11	A
1400600120	W9/G2/HR/WT/AP5/18BL/LC5	12	A
1400700090	W9/G2/HR/18BL	9	B
1400700100	W9/G2/HR/18BL	10	B
1400700110	W9/G2/HR/18BL	11	B
1400700120	W9/G2/HR/18BL	12	B

GLOVE DESCRIPTION

Chrome leather gloves with a knitted aramid composite liner and some with an additional aramid composite palm reinforcement

COMPLEX SAFETY CATERGORY

Gloves are designed to protect hands in the working environment in accordance with EN 388:2016 +A1:2018, ENISO21420:2020 & EN407:2020. When selecting a glove based on risk analysis it should be understood that the protection is limited to the risk level and standards mentioned above. None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.

CE 0598 UK CA 0120

MARKING Each packet shall be labelled / contain the appropriate marking with regards to the amount, type, size, manufacturer, performance levels UKCA & CE mark. Labels on the gloves will contain similar information. This information will be provided in the minimum resale quantity. Store in original packaging.

PACKING AND STORAGE

Gloves shall be wrapped and bundled in polymeric packaging. Can be used under normal climatic conditions. Gloves shall be wrapped in polymeric packaging. Gloves can be used up to five years after date of supply if stored

7-11 MERSEY ROAD, CROSBY, LIVERPOOL, UK

correctly. The gloves are packed in bundles, along with this leaflet. Gloves should be stored away from direct sunlight to maintain the optimum properties of the glove. Labels or information shall contain the user instructions for the minimum resale quantity. This bundle is suitable for transportation and storage. Gloves are made to ENISO 21420:2020 sizes.

Performance Levels

	A	B	GLOVE TYPE
Abrasion Resistance	4	4	EN 388:2016 +A1:2018
Blade Cut Resistance (COUP)	X	X	EN 388:2016 +A1:2018
Tear Resistance	4	4	EN 388:2016 +A1:2018
Puncture Resistance	4	4	EN 388:2016 +A1:2018
Blade Cut Resistance (TDM)	F	D	EN 388:2016 +A1:2018
Burning Behaviour	4	4	EN 407: 2020
Contact Heat	X	X	EN 407 :2020
Convective Heat	X	X	EN 407 :2020
Radiant Heat	X	X	EN 407 :2020
Small Drops of Molten Metal***	4	4	EN 407 :2020
Large Drops of Molten Metal***	4	4	EN 407: 2020
Doffing	Pass	Pass	EN 407:2020
pH	Min = (3.5) Max= (9.5)		EN ISO 21420:2020
Chromium(VI)	Less than 2ppm		EN ISO 21420:2020
Water Penetration	4	4	EN 420:2003+A1:2009

EN 388



EN 407

The levels of performance are for the hand areas.
*** Molten Metal = Iron at 1400°C ± 20° C Results should be used for guidance in initial selection.

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.

WARNINGS:

Test results apply to the gloves in the as received condition but do not extend to any leather cuff. Result may differ if cleaned. Do not use near moving machinery due to entanglement hazard. Overall classification may not reflect the performance of only the outermost layer. These gloves may not be suitable for protection against sharply pointed objects such as hypodermic needles.

CARE / MAINTENANCE

Cleaning and disinfection is not intended for these gloves.

Both new and used gloves should be thoroughly inspected before and after use, especially after cleaning treatment, and before being worn to ensure no damage is present. Damaged gloves should not be worn and should be disposed of. Wet or contaminated gloves should not be used. Dirty gloves may not provide the same level of protection as that shown. Gloves should not be left in a contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible, provided no serious hazards exist, before removal from the hands. Excess contaminant should first be removed, e.g. loose dirt can be brushed off with a soft brush. The gloves may be de-contaminated with mild detergent solution, then rinsed with clean water and allowed to dry naturally, ideally with some air movement. When the contaminant is not removable or presents a potential hazard it is advisable to ease left and right hand gloves off alternatively using the gloved hand so that the gloves are removed without the contaminant

TECHNICAL DIGEST No:1051

contacting the bare hands. Washing is not recommended. Do not wring. Do not tumble dry. Do not use bleach. Reshape whilst still damp.

Warning:

OBSOLESCENCE .Stored correctly, the gloves' physical properties will not change for up to five years.

GENERAL. The quality systems used to manufacture and supply the gloves are in compliance with ISO 9001:2015.

PLEASE NOTE

The information contained here is intended to assist the wearer in the selection of personal protective equipment. The result of the laboratory tests should help with correct glove selection; however it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the glove suitable for the intended use.

DECLARATION

Bennett Safetywear Ltd declares that the new PPE as described in the TD 1051 technical specification for Welding Gloves are in conformity with with regulation (EU) 2016/425 and as amended to apply in GB and with the national standard transposing harmonised standard No : BS EN 407:2020, BS EN 388:2016 +A1:2018, BS ENISO 21420:2020 , and is identical to the PPE which is subject of UKCA certificate LEICFI00384277 issued by:ITS TESTING SERVICES, CENTRE COURT, MERIDAN BUSINESS PARK, LEICESTER, U.K., LE19 1 WD, Approved Body Number: AB0362 who performed the type-examination and is subject to the procedure set out in the legislation (EU) 2016/425 and as amended to apply in GB Module D under the supervision of the approved body SGS United Kingdom, Rossmore Business Park, Ellesmere Port, South Wirral, Cheshire, CH65 3EN,United Kingdom.Their approved body number is 0120 and is also the subject of the EU certificate. No: LECFI00374852 issued by: by ITS Testing Services, Centre Court, Meridian Business Park, Leicester, LE19 1WD, UK., notified body number is 0362: who performed the type-examination . The notified body Intertek Italia S.p.A. Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy NB 2575, now owns this document, and it is valid under this notified body., and is subject to the procedures under the supervision of the notified body SGS Fimko Oy, P.O. Box 30 (Särkiniementie 3), 00211 HELSINKI, Finland 0598. Their notified body number is 0598.

Done at : Bennett Safetywear Ltd, 7-11 MERSEY ROAD, CROSBY, LIVERPOOL , UK

Signature:



Mr E. Baker .Quality Manager

This series satisfies the basic requirements of the PPE regulation (EU) 2016/425 and as amended to apply in in being innocuous/free from nuisance factors, ergonomic and breathable. Conditions of use are not simulated by the test results and as such service life cannot be specified. Further information is available at the below address: Further information is available at the below address:

Further copies of this information and declarations of conformity are available on request from:

Bennett Safetywear Ltd
☎ +44 (0)151 924 3996
Web :<http://bennettsafetywear.co.uk>