

**EXTRICATOR® Plus +(TS)**

Technical rescue glove, not suitable for use with naked flame.

2512010050*	Extricator® PLUS RTC / RESCUE Glove	5-XXXX
2512010060*	Extricator® PLUS RTC / RESCUE Glove	6-XXS
2512010070*	Extricator® PLUS RTC / RESCUE Glove	7-XS
2512010080*	Extricator® PLUS RTC / RESCUE Glove	8-S
2512010090*	Extricator® PLUS RTC / RESCUE Glove	9-M
2512010100*	Extricator® PLUS RTC / RESCUE Glove	10-L
2512010110*	Extricator® PLUS RTC / RESCUE Glove	11-XL
2512010120*	Extricator® PLUS RTC / RESCUE Glove	12-XXL
2512010130*	Extricator® PLUS RTC / RESCUE Glove	13-XXXL
2512030050**	Extricator® PLUS/TS RTC/ RESCUE Glove	5-XXXX
2512030060**	Extricator® PLUS/TS RTC / RESCUE Glove	6-XXS
2512030070**	Extricator® PLUS/TS RTC / RESCUE Glove	7-XS
2512030080**	Extricator® PLUS/TS RTC / RESCUE Glove	8-S
2512030090**	Extricator® PLUS/TS RTC / RESCUE Glove	9-M
2512030100**	Extricator® PLUS/TS RTC / RESCUE Glove	10-L
2512030110**	Extricator® PLUS/TS RTC / RESCUE Glove	11-XL
2512030120**	Extricator® PLUS/TS RTC / RESCUE Glove	12-XXL
2512030130**	Extricator® PLUS/TS RTC / RESCUE Glove	13-XXXL



All styles and sizes available with touch screen finger tips with improved dexterity. Can be used under normal climatic conditions.

Gloves should be replaced when they have become damaged. Store in original packaging. Can be used up to 5 years after date of manufacture if stored correctly. Gloves should be stored away from direct sunlight to maintain the optimum properties of the glove. Gloves shall be wrapped and bundled in polymeric packaging. Each packet shall be labelled/contain information concerning size, type, quantity, distributor, the CE mark. This information is provided in each packet. Gloves are made to the following (EN 420) sizes: 6,7,8,9,10,11,12,13

TEST	Level	Reinforced Palm	Palm	EN388
Abrasion Resistance:		4	4	EN 388:2016
Blade Cut Resistance:		5	X	EN 388:2016
Tear Resistance:		4	3	EN 388:2016
Puncture Resistance:		4	2	EN 388:2016
Blade cut Resistance TDM		F	D	EN 388:2016
Burning Behaviour			X	EN 407:2004
Contact Heat			1	EN 407:2004
Convective Heat			X	EN 407:2004
Radiant Heat			X	EN 407:2004
Small Drops of Molten Metal			X	EN 407:2004
Large Quantities of Molten Metal			X	EN 407:2004
Chromium(VI):		<2ppm		EN 420:2003+A1
pH:		3>9		EN 420:2003+A1
Dexterity:**		5		EN 420:2003+A1



Protection levels are not uniform all over the glove. Protection levels stated apply to the palm and do not necessarily reflect the performance of the outermost layer.

This glove series satisfies the basic requirements of the PPE Regulations in being innocuous/free from nuisance factors, ergonomic, breathable. Conditions of use are not simulated by the test results and as such service life cannot be specified. Results should be used for guidance in initial selection.

**Informative:**  
**WARNINGS:**  
 Gloves should not be worn when there is a risk of entanglement by moving parts of machines. Inspect regularly for obvious signs of damage. Do not use if palm/fingers shows signs of cut, perforations or other serious mechanical damage.

**EC/TECH DIGEST**

Gloves should be replaced if the outer layers of the glove have become so damaged that the liners/membrane becomes visible. Do not use near naked flame.

**General Care Instructions**

Both new and used gloves should be thoroughly inspected before and after use, especially after cleaning treatment, and before being worn to ensure no damage is present. Damaged gloves should not be worn and should be disposed of. Wet or contaminated gloves should not be used. Dirty gloves may not provide the same level of protection as that shown. Gloves should not be left in a contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible, provided no serious hazards exist, before removal from the hands. Excess contaminant should first be removed, e.g. loose dirt can be brushed off with a soft brush. The gloves may be de-contaminated with mild detergent solution, then rinsed with clean water and allowed to dry naturally, ideally with some air movement. When the contaminant is not removable or presents a potential hazard it is advisable to ease left and right hand gloves off alternatively using the gloved hand so that the gloves are removed without the contaminant contacting the bare hands. Washing is not recommended.

Do not wring. Do not tumble dry. Do not use bleach. Gloves may be rinsed in water and allowed to drip dry in ambient temperatures. Reshape whilst still damp. Drying of Gloves  
 Squeeze out the surplus water from the finger tips downwards. Never wring the gloves. Pull the gloves gently into shape and blow into them to separate the surfaces. They can then be hung up to dry in a current of air but away from a direct heat source or sunlight.

When nearly dry ease them carefully onto the hands so that the softness, shape and size can be restored and when quite dry polish with a soft lint free cloth

**MARKING**

Each packet shall be labelled / contain the appropriate marking with regards to the amount, type, size, manufacturer, performance levels and CE mark. Labels on the gloves will contain similar information. This information will be provided in the minimum resale quantity.

**INTERMEDIATE SAFETY CATERGORY**

Gloves are designed to protect hands in the working environment in accordance with EN388:2016, EN420:2003+A1:2009 & EN407:2004. When selecting a glove based on risk analysis it should be understood that the protection is limited to the risk level and standards mentioned above. The EU type examination was carried out ITS Testing Services, Centre Court, Meridian Business Park, Leicester, LE19 1WD, UK., notified body number is 0362: performed the type-examination .The notified body Intertek Italia S.p.A. Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy NB 2575, now owns this document, and it is valid under this notified body. None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.

**WARNINGS:**

Test results apply to the gloves in the as received condition but do not extend to any leather cuff .Result may differ if cleaned. Do not use near moving machinery due to entanglement hazard. Overall classification may not reflect the performance of only the outermost layer. These gloves may not be suitable for protection against sharply pointed objects such as hypodermic needles.

**ISSUE 5**

**PACKING AND STORAGE**

Can be used under normal climatic conditions. Gloves shall be wrapped in polymeric packaging. Gloves can be used up to five years after date of supply if stored correctly. Store in original packaging. Gloves should be ideally stored in a cool dry place away from direct sunlight at ambient temperatures( between 5°C and 25°C) in a dry well ventilated area in original packaging to maintain the optimum properties of the glove. The gloves are packed in bundles, along with this leaflet. This bundle is suitable for transportation and storage.

**OBSOLESCENCE**

Stored correctly, the gloves' physical properties will not change for up to five years.

**GENERAL**

The quality systems used to manufacture and supply the gloves are in compliance with ISO 9001:2015.

**PLEASE NOTE**

The information contained here is intended to assist the wearer in the selection of personal protective equipment. The result of the laboratory tests should help with correct glove selection; however, it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the glove suitable for the intended use.

This glove series satisfies the basic requirements of the PPE Regulation (EU) 2016/425 in being innocuous/free from nuisance factors, ergonomic and breathable. Conditions of use are not simulated by the test results and as such service life cannot be specified.

**EU DECLARATION**

Bennett Safetywear Ltd declares that the new PPE as described in the TD 1056 technical specification for Extricator gloves are in conformity with provisions of Council Regulations (EU) 2016/425 and with the national standard transposing harmonised standard No :BS EN 388:2016,BS EN 407:2004, BS EN 420:2003, identical to the PPE which is the subject of the EU certificate. No: LECFI00378418, issued by: ITS Testing Services, Centre Court, Meridian Business Park, Leicester, LE19 1WD, UK., notified body number is 0362: who performed the type-examination . The notified body Intertek Italia S.p.A. Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy NB 2575, now owns this document, and it is valid under this notified body, and is subject to the quality procedures under the supervision of the notified body SGS Fimko Oy, P.O. Box 30 (Särkiniementie 3), 00211 HELSINKI, Finland. Their notified body number is 0598.

Done at : Bennett Safetywear Ltd, 7-11 MERSEY ROAD, CROSBY, LIVERPOOL , UK

Signature:

Mr E. Baker .Quality Manager

Further information is available at the below address:

**Bennett Safetywear Ltd, ☎ +44 151 924 3996**

**Web: <http://www.bennettsafetywear.co.uk>**

01/01/2021