

EXTRICATOR® PLUS -TS(G)/TPR
 Technical rescue glove, not suitable for use with naked flame.

2512040130	RTC RESCUE GLOVE	13	XXXL
2512040120	RTC RESCUE GLOVE	12	XXL
2512040110	RTC RESCUE GLOVE	11	XL
2512040100	RTC RESCUE GLOVE	10	L
2512040090	RTC RESCUE GLOVE	9	M
2512040080	RTC RESCUE GLOVE	8	S
2512040070	RTC RESCUE GLOVE	7	XS
2512040060	RTC RESCUE GLOVE	6	XXS



Gloves are made to the following (BS EN ISO 21420:2020) sizes: 6,7,8,9,10,11,12,13
 All styles and sizes available with touch screen finger tips with improved dexterity.



WARNINGS:

Overall classification may not reflect the performance of only the outermost layer. Gloves should not be worn when there is a risk of entanglement by moving parts of machines. Inspect regularly for obvious signs of damage. Do not use if palm/fingers shows signs of cut, perforations or other serious mechanical damage. Gloves should be replaced if the outer layers of the glove have become so damaged that the liners becomes visible. Do not use near naked flame. These gloves may not be suitable for protection against sharply pointed objects such as hypodermic needles.

MARKING

Each packet shall be labelled / contain the appropriate marking with regards to the amount, type, size, manufacturer, performance levels, CE and UKCA mark. Labels on the gloves will contain similar information. This information will be provided in the minimum resale quantity.

TEST	Level	Reinforced Palm	Palm	EN388
Abrasion Resistance:		4	2	EN 388:2016
Blade Cut Resistance:		5	5	EN 388:2016
Tear Resistance:		4	4	EN 388:2016
Puncture Resistance:		4	2	EN 388:2016
Blade cut Resistance TDM		F	F	EN 388:2016
Burning Behaviour		X	X	EN 407:2020
Contact Heat		1	1	EN 407:2020
Convective Heat		X	X	EN 407:2020
Radiant Heat		X	X	EN 407:2020
Small Drops of Molten Metal		X	X	EN 407:2020
Large Quantities of Molten Metal		X	X	EN 407:2020
Chromium(VI):	<2ppm			BS EN ISO 21420:2020
pH:	3><9			BS EN ISO 21420:2020



Protection levels are not uniform all over the glove.

Protection levels stated apply to the palm and do not necessarily reflect the performance of the outermost layer.

This glove series satisfies the basic requirements of the UK 2019 S1696 Schedule 35 Regulation 38 & (EU) 2016/425 in being innocuous/free from nuisance factors, ergonomic, breathable. Conditions of use are not simulated by the test results and as such service life cannot be specified. Results should be used for guidance in initial selection. Informative:

General Care Instructions

Both new and used gloves should be thoroughly inspected before and after use, especially after cleaning treatment, and before being worn to ensure no damage is present. Damaged gloves should not be worn and should be disposed of. Wet or contaminated gloves should not be used. Dirty gloves may not provide the same level of protection as that shown. Gloves should not be left in a contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible, provided no serious hazards exist, before removal from the hands. Excess contaminant should first be removed, e.g. loose dirt can be brushed off with a soft brush.



Do not wring. Do not tumble dry. Do not use bleach. Gloves should be allowed to drip dry in ambient temperatures. Reshape whilst still damp.

Drying of Gloves

Squeeze out the surplus water from the finger tips downwards. Never wring the gloves. Pull the gloves gently into shape and blow into them to separate the surfaces. They can then be hung up to dry in a current of air but away from a direct heat source or sunlight.

When nearly dry ease them carefully onto the hands so that the softness, shape and size can be restored and when quite dry polish with a soft lint free cloth

INTERMEDIATE SAFETY CATERGORY

Gloves are designed to protect hands in the working environment in accordance with BS EN 388:2016, BS EN ISO 21420:2020 & BSEN 407:2020. When selecting a glove based on risk analysis it should be understood that the protection is limited to the risk level and standards mentioned above.

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.

The type examination was carried out by ITS Testing Services, Centre Court, Meridian Business Park, Leicester, LE19 1WD, UK. Their test house number is AB0362

PACKING AND STORAGE

Can be used under normal climatic conditions.

Gloves shall be wrapped in polymeric packaging.

Gloves should be replaced when they have become damaged.

Gloves can be used up to five years after date of supply if stored correctly. Store in original packaging. Gloves should be ideally stored in a cool dry place away from direct sunlight at ambient temperatures between 5°C and 25°C) in a dry well ventilated area in original packaging to maintain the optimum properties of the glove.

The gloves are packed in bundles, along with this leaflet. This bundle is suitable for transportation and storage.

Each packet shall be labelled/contain information concerning size, type, quantity, distributor, the UKCA & CE mark. This information is provided in each packet.

OBSOLESCENCE

Stored correctly, the gloves' physical properties will not change for up to five years.

GENERAL

The quality systems used to manufacture and supply the gloves are in compliance with ISO 9001:2015.


PLEASE NOTE

The information contained here is intended to assist the wearer in the selection of personal protective equipment. The result of the laboratory tests should help with correct glove selection; however, it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the glove suitable for the intended use.

This series satisfies the basic requirements of the (EU) 2016/425, and as amended to apply in GB, in being innocuous/free from nuisance factors, ergonomic and breathable. Conditions of use are not simulated by the test results and as such service life cannot be specified.

DECLARATION

Bennett Safetywear Ltd declares that the new PPE as described in the TD 1076 technical specification for EXTRICATOR® PLUS -TS(G)/TPR are in conformity with the legislation PPE Regulation 2016/425 on personal protective equipment, and as amended to apply in GB, Module D and with the national standard transposing harmonised standard No : BS EN 407:2020, BS EN 388:2016, BS EN ISO 21420:2020, and is identical to the PPE which is subject of UKCA certificate LECF00383099 issued by:ITS TESTING SERVICES, CENTRE COURT, MERIDAN BUSINESS PARK, LEICESTER, U.K., LE19 1 WD, Approved Body Number: AB0362 who performed the type-examination and is subject to the procedure set out in the legislation PPE Regulation 2016/425 on personal protective equipment, and as amended to apply in GB Module D and also the subject of the EU certificate. OZO296-CPT002/22, issued by: Mirta KONTROL d.o.o. Gradiška 3, 10040 Zagreb, Dubrava, Hrvatska (Croatia) Their notified body number is 2474

Done at : Bennett Safetywear Ltd, 7-11 MERSEY ROAD, CROSBY, LIVERPOOL , UK
 Signature:  Mr E. Baker .Quality Manager

Further copies of this information and declarations of conformity are available on request from:

Bennett Safetywear Ltd
+44 (0)151 924 3996
 Web : <http://bennettsafetywear.co.uk>