Model S1341

Combination Station, Stainless Steel Bowl Eye/Face Wash Plastic Showerhead, Auxiliary Hand-Held Drench Hose



SPECIFICATIONS:

Model S1341 is a pedestal mounted combination station with an eye/face wash, with a stainless steel bowl, ABS plastic eye/face wash spray heads, an inline strainer and a stay-open 1/2" ball valve with a push handle and a shower with a plastic showerhead and a 1" stay-open ball valve with a pull rod and an auxiliary hand held drench hose with a self-closing valve.

STANDARD EQUIPMENT:

Showerhead: Yellow, ABS plastic 7-3/8" diameter showerhead with a 20 gpm flow regulator. An anti-microbial agent is molded into the ABS material, providing integrated protection.

Shower Valve: 1" NPT rough chrome plated brass stay-open ball valve. Unit is provided with a stainless steel actuator arm and a 29" stainless steel null rod

Eye/Face Wash Bowl: Stainless steel, 11-3/4" diameter bowl.

Spray Head Assembly: ABS yellow plastic Eye/Face Wash heads supplied by a combined integral 3.7 GPM (14 LPM) Flow Control, with integral flip Dust Covers, internal Flow Controls and Filters to remove debris from the water. An anti-microbial agent is molded into the ABS material, providing integrated protection.

Eye/Face Wash Valve: 1/2" NPT chrome plated brass stay-open ball valve with a stainless steel push handle and a 50 mesh inline strainer.

Drench Hose: Auxiliary eye/face and body drench hose with an ABS plastic eye/face wash spray head, self-closing squeeze lever valve, an eight foot reinforced PVC hose and pipe hook. An anti-microbial agent is molded into the ABS material, providing integrated protection.

Water Supply: 1-1/4" NPT female threaded side or top inlet.

Waste: 1-1/4" NPT female outlet.

Piping & Mounting: Schedule 40 galvanized steel piping and a 9-1/8" diameter cast iron floor flange with a yellow powder coated finish.

Universal Sign: ANSI compliant, vertical identification sign.

Weekly Test Tag: A water prooftest card to record the date and inspector's name for weekly functional testing of the unit.



OPTIONAL ACCESSORIES:

Additional costs may be incurred

☐ -AL2 Electric alarm with flashing light and horn

□ -BF Barrier free, handicap accessible

-CS1 Stainless steel "clam shell" cover

☐ -ET71-2-BVS-OTG Thermostatic mixing valve is ASSE Listed per

the ASSE 1071 standard. The tepid output water complies with ANSI Z358.1 standard. Valve includes Ball Valve Shut-offs and Outlet

Temperature Gauge

☐ -FLW1 Flow switch, single pole

☐ -FPV Freeze protection valve (eye/face wash only)

☐ -HFC Hand foot control

-MC1 Modesty curtain for horizontal showers

-MS1 MAP (magnetically actuated proximity) switch,

for one (1) actuator

☐ -MS2 MAP (magnetically actuated proximity) switches,

for two (2) actuators

□ -SDC Stainless steel dust covers

□ -SPV Scald protection valve (eye/face wash only)

☐ -SV1 Stainless steel 1" ball valve

-SV2 Stainless steel 1/2" ball valve





Acorn Safety assumes no responsibility for use of void or superseded data. © Copyright Acorn Safety*, City of Industry, CA, Division of Acorn Engineering Company*, Member of Morris Group International™. Please visit www.acorneng.com for most current specifications.

Submittal # **\$1341** [CMB] Date: 01/08/20

Product carries the following certifications:






ACORN SAFETY

P.O. Box 3527 City of Industry, CA 91744 U.S.A. Phone 800-591-9372 626-855-4804

www.acorneng.com

TECHNICAL DIMENSIONS

All dimensions are subject to manufacturer's tolerance of plus or minus 1/2" nominal and subject to change without notice. Acorn Safety® assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. © Acorn Safety®, A Division of Acorn Engineering Company®, Member of Morris Group International™. Please visit www.acorneng.com for most current specifications.



GENERAL NOTES:

1. ALL DIMENSIONS ARE IN INCHES [MM].

▲ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

\$1341 Date: 01/08/20

Acorn Safety warrants that its products are free from defects in material or workmanship under normal use and service for a period of one year from date of shipment. Acorn's liability under this warranty shall be discharged solely by replacement or repair of defective material, provided Acorn is notified in writing within one year from date of shipment, F.O.B. Industry, California.

SUMMARY VAL FOR STURING	Model Number & Options	_Quantity	ACORO SAFETY
LECTION SI & APPROVA MANUFACTI	ContactSignature (Approval for	Title	800-591-9372 or 626-855-4804
SELI R.	(Approval for Manufacturing)	Date	www.acorneng.com