

## BLUVAC+ PROFESSIONAL

The BluVac + Pro is Bluetooth Smart® wireless Vacuum gauge: having additional display units (PSI and inHg), an Evacuation Progress Indicator, Saturation Temperature Display, and a Leak Rate Indicator in either units/second or units/minute. The BluVac + Pro can be operated stand alone or in conjunction with an iOS or Android compatible app.

The BluVac + Pro's unique Rise Time Analyzer can consistently ensure proper evacuation, providing a PASS or FAIL indication in as little as 15 seconds. This eliminates the need to wait for the completion of a manual rise-time test.

### BENEFITS

- 0 to 25,000 Micron Range with 0.1 Micron Resolution less than 10,000 Microns
- Measures Vacuum in Microns, Pascals, Millibar, Millitorr, mmHg, Calibration Self Test — Can be field calibrated with no special equipment
- Sensor withstands overpressure up to 500 PSI
- Mobile Device and App Compatibility**



## HVAC SUPER PRO

Bonds Copper, Aluminum and Brass in any Combination. Starts to set up in 20 seconds and forms a solid bond in 3 minutes. In 12 minutes the bond will withstand 850 PSI of refrigerant pressure. Bonding time in 1 minute for Aluminum and is set in 4 minutes



- Approx. 2 Hours is fully cured and will withstand 1200 psi of refrigerant pressure
- Compatible with all refrigerants and oils
- Use with standard copper or brass fittings
- One Bottle Makes 200 or more Bonds on 1/2" Tubing



## REFRIGERANT GAS LEAK DETECTOR

EL 520 is used to quickly and accurately isolate leaks in all commercial, residential, industrial and automotive air conditioning and refrigeration systems. It detects all HFC, CFC and HCFC refrigerants including R134A, R12, R22, R32 as well as blends such as R404A, R407C, R 410A, R508B, and others.

- Microprocessor Controlled Technology
- Fully Automatic
- Sturdy Blow Moulded Carrying Case
- Spare Sensor
- Batteries (2 AA Alkaline)

<b>Calibration</b>	<b>Automatic</b>
<b>Response Time</b>	<b>Instantaneous</b>
<b>Reset Time</b>	<b>Instantaneous</b>
<b>Sensitivity</b>	<b>&lt; 3 gram/yr</b>
<b>Probe Length</b>	<b>12"</b>



**EL-320 FOR FLAMMABLE GASES**

**EL-720 FOR CARBON DIOXIDE**

Dealer Details:

# Trying to Identify Refrigerant Leaks?



**EXTERNAL LEAK STOP**

[www.bprefcool.com](http://www.bprefcool.com)



## EXTREME ULTRA

EXTREME ULTRA is an ultimate Refrigerant Gas Leak sealant that solves all the problems related to small refrigerant gas leakages in AC/R systems. After more than 4 years of R&D efforts and thousand of tests, 6ml dose leak stop that can work with all types of refrigerant gases included R22, R32, R134a, R410a & R1234yf, EXTREME ULTRA 6ml new formula treats A/C and Refrigeration systems up to 21KW (6 tons). EXTREME ULTRA locates the refrigerant gas leaks and permanently seals them, without reacting to moisture and oxygen.

### BENEFITS

1. Only 6ml can treat A/C & Refrigeration Systems up to 21 KW (6 tons)
2. Permanently seals refrigerant Gas leaks both in metal and rubber components of A/C and Refrigeration systems
3. Safe to AC/R system components
4. Non reactive to humidity and air
5. Polymer-free
6. Visible to any UV lamp
7. Not flammable, Not irritant, Safe for the operator
8. Significantly reduces compressor noise
9. Ideal for preventative maintenance
10. Repairs leaks up to **0.3 mm**



**Intertek**  
LABORATORY TESTED

**EXTREME WHITE**  
FOR HYDROCARBONS

**6 ml DOSAGE**  
FOR ANY CAR

**Made in ITALY**

## LEAK LOCATOR

1. HIGH VISIBILITY
2. TIME SAVING
3. NON-FLAMMABLE
4. NON-TOXIC
5. NON-CORROSIVE

### DIRECTIONS TO USE

1. Shake before use
2. Spray from a distance of 25-30 cm onto the area to be tested
3. Bubbles in the applied film indicate the location of a leak
4. Test compatibility with the painted or coated surfaces, plastic prior to application

**IDEAL FOR ALL GAS LEAK DETECTION**



## INSTANT - HVAC/R PATCH

1. Two part - Bonding Fluid and Micro Cells
2. Point of Purchase - Bubble Pac Package
3. For permanently sealing holes in all metals and rigid plastics
4. Forms a high strength bond in seconds
5. Full cure in 20 minutes - put equipment back in service
6. Rated at 350 PSI contained air or refrigeration pressure
7. Handles 200°F (93.3°C) continuous temperature
8. Tested to 1800 PSI.



**MADE IN THE USA**

## BRILLIANT HVAC&R

UV LEAK DETECTOR DYE FOR AIR CONDITIONING AND REFRIGERATION SYSTEMS  
Locate refrigerant gas leaks with BRILLIANT HVAC&R: the leak detection dye visible with UV light. Universally suitable for every conditioning and refrigeration system.

### BENEFITS

1. Tracks Gas leaks in the system
2. Visible when exposed to every UV light
3. No solvents!
4. Advice stickers included



**Made in ITALY**



## SEALUP

SEALUP is the professional choice to eliminate any leakage between the threads, the gaskets and the joints of the A/C systems.

### BENEFITS

1. Perfect sealant efficacy
2. It stays flexible
3. Resists to every Vibrations
4. Effective on metals, plastics and rubber
5. Allows the joints to be reopened
6. Easy to remove



### TECHNICAL CHARACTERISTICS

1. Temperature: from -90°C to +200°C
2. Pressure: from vacuum -1 Bar up to 500 Bar

**LEAK SEALANT**

[www.bprefcool.com](http://www.bprefcool.com)