



SL30

Network Column Speaker

ZYCOO SL30 is a high-performance SIP-enabled column speaker used for SIP paging, notification/tone broadcasting, and streamed high-definition music playback. SL30 has high sensitivity and capacity, giving clear and rich saturation, whether SIP-based propaganda broadcasting or background music playing. SL30 also supports dry contact signal digital input and various sensors integration. Meanwhile, PoE is supported too.

Applicable Scenarios



Schools



Health Care



Shopping Centers

Train/Bus
StationsGovernment
OfficesIndoor
Carparks

Residential



Retail Shops



Airports

Office
Buildings

Warehouses



Hotels

Features

- SL30 is a triune-speaker driver units design, two low-frequency woofer driver unit, and one high-frequency tweeter driver unit. It provides premium sound quality, enhances the audience experience.
- Standard PoE (IEEE 802.3at) support, simple and easy installation with a single network cable. External power supply can be used if required.
- With the 3.5mm audio input jack, SL30 can collect external audio sources from devices such as mobile phones, computers, mp3, etc. and playback through its own speakers.
- Various sensors can be integrated, like smoke sensors, infrared sensors.
- With IP65 protection rating and well thermal durability. SL30 is suitable for outdoor installation and operations, even in extreme outdoor environments.
- ZYCOO IP Audio Center auto-provisioning support, large-scale installations (local or remote) will be straightforward and time-saving.
- Standard SIP protocol supported can be integrated with ZYCOO IP Audio Center or other third-party SIP servers. SIP paging using wideband G.722 codec, which provides crystal clear HD voice.
- Music playback through ZYCOO IP Audio Center using streaming media. HD MP3 audio files supported for superior quality o background music.
- Support Multicast and Peer-to-Peer (P2P) to share data between devices without a central server while the devices use under the same local network.
- Build-in Class-D amplifier with local and server controlled volume output level, SL30 guarantees the full and consistent coverage and audio comfort and the flab.
- SL30 supports three lines SIP accounts, in which users may register the endpoint in more than one system for achieving different functionality purposes

Specifications

Speaker	
Speaker Component	Two 3.25" woofer units + one 1" tweeter unit
Sensitivity	87dB/1m/1W
Max sound pressure level	102dB
Amplifier	Build-in Class D Amplifier
Coverage pattern	58°~90°, maximum effective distance 65m
Rate power	4Ω 30W
Frequency range	100Hz – 20KHz
Material	Aluminum film
Acoustics	Mono
Audio	
Audio codecs	G.722, G.711 A-law, G.711 U-law, Opus
Audio streaming	Mp3 sampling rate 8-48KHz, bit rate 64-320kbps, mono or stereo
Network	
Interface	10/100Mbps, Support PoE IEEE 802.3at
Network protocol	SIP(RFC3261), HTTP, TCP/IP, SSL, DNS, SNTP, NTP, RTSP, RTP, RTCP, TCP, UDP, MQTT, ICMP, DHCP, ARP, SSH
Administration	
Configuration	Web interface or auto provisioning server
Provisioning method	MQTT IoT Protocol
Mechanical Properties	
Memory	128MB RAM, 256MB Flash
Power Input	PoE IEEE 802.3at or DC 24V-2A
Casing	Aluminum, white-color rust preventive coating
IP Rating	Ip65
Weight	2.5Kg
Dimension	100*100*235mm
Mounting Method	Wall/pole mounted
Environmental	
Installation environment	Indoor/Outdoor
Operating temperature	-20°C - 50°C (-4°F - 122°F)
Storage temperature	-40°C- 70°C (-40°F - 158°F)
Humidity	10%-95% RH Non-condensing
Approvals	
Approvals	EN 55032:2015, EN 55035:2017, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 62368-1:2014+A11:2017, FCC Part 15B Class A



We Focus · We Deliver

No. 1602, 16th Floor, Building No. 599, Century City South Road, High-tech Zone, Chengdu, Sichuan Province, China

+86 28 85337096

zycoo@zycoo.com