VBX FLASH®

VIRUCIDAL DISINFECTION BY UVC



















VBX FLASH® IS NEW VIRUCIDAL AUTOMATED 3 MINUTES DISINFECTION CABINET, CERTIFIED ACCORDING TO NF T72-281 STANDARD, IPX4 SPLASH PROOF AND IN SUPERIOR 304 STAINLESS STEEL

PRODUCT PRESENTATION

VBX FLASH® is a range of virucide cabinet offering 2 capacities: VBX25 and VBX50.

> VBX FLASH® disinfects all types of accessories in 3 minutes (verified by an independent laboratory).

VBX FLASH® is guaranteed 2 years (except Virokill lamps), made in France and worldwide IECEE certified (except North America).

PRODUCT OPERATION

- Virucidal disinfection time 3 minutes (factory setting).
 For better disinfection, do not place the objects to be sterilized on top of each other.
- Internal reflective surface for better circulation of UVC rays.
- **Red Indicator light** during operation; green when the disinfection cycle is complete.
- Total user safety guaranteed by a safety switch that cuts off all power when the door is open
- Activation of disinfection as soon as the door is closed.
- The end user should always control the long-term shelf life of the raw material of the item to be disinfected
- Interior shelf to best position the baskets and facilitate their insertion / extraction.

PRODUCT PERFORMANCE

- Test carried out its COFRAC certified virology laboratory.
- According to virucidal efficacy test:
 NF T 72-281.
- Results

| VIRUS TESTED | REDUCTION VIRUCID | EFFICIENCY VIRUCID |
|------------------------|-----------------------|-----------------------|
| Adénovirus Type 5 | 5,06 log reduction | 99,99999% |
| Norovirus murin S99 | 4,32 log reduction | 99,9999% |

- EN 62471 Photobiological Safety lab. LCIE
- EMC certification
- IECEE international electrical safety
- CSR Design & Manufacturing (in accordance with sustainable development methods)

TECHNICAL DESCRIPTION

| | VBX25 | VBX50 |
|--|--------------------------|--------------------------|
| Dimensions | 496 mm x 404 mm x 220 mm | 939 mm x 404 mm x 220 mm |
| Weight | 6,5 kg | 11,5 kg |
| Power | 1 x 25 W | 2 x 25 W |
| Number of VBX FLASH [®] devices minimum for customization | 36 | 18 |

CHARACTERISTICS

| Power supply | 210-240VAC 50/60Hz |
|-------------------|---|
| Preset cycle life | 3 min |
| Useful life | 6000 h |
| Lamp | Virokill Lamp VKL25WE27U puissance de 25W |





BRC S.A.S.

21, Rue des Coteaux de Grand-Lieu 44830 BOUAYE - FRANCE Tél. +33 (0)2 40 34 57 24 - +33 (0)6 86 15 34 02

dircom@brcsa.com

