















CATERING

AGRICULTURE

INDUSTRY

MEDICAL/SOCIAL

SHOPS, OFFICES

PRESENTATION

VBX is a new generation of virucidal sterilisation cabinet, with a choice of two different devices: the VBX15 and the VBX30. VBX is automatic, innovative, patented and and fitted with either 5 or 10 stands (customisable).

VBX disinfects goggles, glasses, masks, gloves, tweezers, scissors and other accessories.

VBX has a 2 year warranty*, made in France and IECEE certified worldwide (except North America).

* Excluding lamp.

OPERATION

Virucidal sterilisation time

30 minutes (factory setting). For improved sterilisation performance, do not place items to be sterilised on top of each other.

- Internal reflective surface for improved distribution of UVC light.
- Internal shelf at an optimum distance from the lamps for the best possible virucidal action of UVC light.
- Indicator light red during operation; green when the sterilisation cycle is complete.
- Total user safety guaranteed by a safety switch that cuts all power when the door is open.
- Auto-start mechanism activates sterilisation as soon as the door is
- activates sterilisation as soon as the door is closed.
- Customisable shelf on request, adjusted to the items to be sterilised.
- The end user should always check the long-term service life of the raw material in the item to be disinfected.



PERFORMANCE

- Test conducted in COFRAC certified virology laboratory.
- Standard used for virucidal efficacy test: NF T 72-281.
- Results

VIRUS Tested	VIRUCIDAL Reducation	VIRUCIDAL Efficacy
Adenovirus Type 5	5.24 log reduction	99.99999%
Murine noro- virus S99	4.27 log reduction	99.999%





SPECIFICATIONS

	VBX15A	VBX30A
Number of items	5	10
Door(s)	One door protected against UVC rays	Double door protected against UVC rays
Dimensions	496 mm x 404 mm x 220 mm	939 mm x 404 mm x 220 mm
Weight	6.5 kg	11.5 kg
Stand	PPE (Masks and gloves)	PPE (Masks and gloves)
Material	304 stainless steel	304 stainless steel
Protection index	IPX4	IPX4
Output	1 x 15 W	2 x 15 W
Closing mechanism	Magnetic closing	Magnetic closing
Warranty	2 years	2 years
Logo	No logo (standard) // Customisable logo	No logo (standard) // Customisable logo
Minimum number of VBX devices for customisation*	36	18
Additional number of VBX devices for further customisation	18	9
EAN code	3430020004431	3430020004134

^{*} The minimum orders to qualify for customisation are 36 VBX15 or 18 VBX30.

UVC SOURCE

	VBX 15 / VBX 30	
Lamp	Lamp UVC E27	
Brand	Virokil Lamp	
Protection	No protection	

SHIPPING

By sea:

- **VBX15:** individual cardboard package, 18 devices per pallet (1200 mm x 800 mm x 1500 mm), 140 kg.
- **VBX30:** individual cardboard package, 9 devices per pallet (1200 mm x 800 mm x 1500 mm), 115 kg.

CHARACTERISTICS

Power supply	210-240VAC 50/60Hz
UVC exposure	14,000 J/m ²
Pre-set cycle time	30 min
Service life	6,000 h

BRC S.A.S.

21, Rue des Coteaux de Grand-Lieu 44830 BOUAYE - FRANCE Tel. +33 (0)2 40 34 57 24 - Fax +33 (0)2 40 34 74 76 dircom@brcsa.com

