


How to use the tamper mat and distributor?

Some customers may be confused about how to use the tamper mat and distributor. Please follow the instruction below.




How to use the tamper mat?

01. Gently put the tamper mat on the edge of table or countertop.



02. Align the table edge with the right triangle of the map, then the map will fit well with the table.



03. It is feasible to place the tamper and distributor on the mat.



04. Put the portafilter on the mat while tamping coffee ground.



05. It can also use to knock the espresso puck out of the portafilter.



Why use the distributor ?

During espresso brewing, it's common for an individual to tamp the loaded portafilter by pressing it on the countertop's edge with an espresso tamper. The biggest problem with brewing espresso is the human error of irregular compression, which causes channeling.

Channeling may be described as uneven compression distributed throughout the filter. Water finds the path of least resistance rather than evenly flowing through the entire bed. This channeling leads to improperly saturated grounds, and poorly brewed espresso, resulting in an unpalatable, bitter flavor.

How to use the distributor?

01. Put the distributor on to the portafilter.



02. Then rotate the distributor to even the surface of coffee grounds.



03. The surface of the coffee grounds is evenly now, but the inside is not tight.



04. Tamp the coffee grounds down with the tamper to make it tightly.



Now, the tamping process is finished, let's brew a cup of perfect espresso!