



QDD03

Electric Tractor 0.3t

Tiny frame makes flexible driving;
Best choice for light and small parts handling;
Back up function ensure convenient travelling.

EP EQUIPMENT CO.,LTD
www.ep-ep.com



Electric Tractor 0.3t QDD03

Distinguishing mark				
1.1	Manufacturer			EP
1.2	Model designation			Tricycle
1.3	Drive unit			Electric
1.4	rated capacity	Q	kg	250
1.5	Wheelbase	y	mm	1140
Weight				
2.1	Service weight (include battery)		kg	135
2.2	Axle loading, laden driving side/loading side		kg	315/70
2.3	Axle loading, unladen driving side/loading side		kg	95/40
Types,Chassis				
3.1	Tyre type Driving wheels/Loading wheels			pneumatic
3.2	Tyre size, driving wheels (diameter×width)		mm	Φ250×85
3.3	Tyre size, loading wheels (diameter×width)		mm	Φ355×65
3.4	Wheels, number driving, caster/loading (x=drive wheels)		mm	2x +1
Dimensions				
4.1	Height drawbar in driving position min./max.	h ₁₄	mm	950/1050
4.2	Overall length	l ₁	mm	1660
4.3	Length to face of forks	h ₁₃	mm	300
4.4	Overall width	b ₁	mm	800
4.5	Fork dimensions	s/ e/ l	mm	610×800
4.6	Ground clearance, center of wheelbase	m ₂	mm	65
4.7	Turning radius	Wa	mm	1550
Performance data				
5.1	Travel speed, laden/ unladen		km/ h	8.5/ 9
5.2	Max. gradeability, laden/unladen		%	8/16
5.3	Service brake type			Electromagnetic
Electric-engine				
6.1	Drive motor rating S2 60 min		kW	0.8
6.2	The maximum allowed size battery		mm	130x165x150
6.3	Battery voltage/nominal capacity K5		V/ Ah	4x12/20
6.4	Battery weight		kg	4x7
Addition data				
8.1	Type of drive unit			DC
10.1	Steering type			Machanical Steering
10.2	Sound pressure level at the driver's ear		dB (A)	74

1.The parameters in the table are of the standard model. For more information, please contact us.
2.The parameters are subject to change without notice.

