

N-B200/N-B230

200W/230W Moving head Beam Light

200W/230W摇头光束灯

Technical Parameters:

power supply : AC 100-240 V 50/60Hz

Lamp : 200W (Philips MSD Platinum 5R , Color temperature : 8000K)
230W (OSRAM SIRIUS HRI 230W , Color temperature : 8500K)

Average Lifespan: 2000H

Color : 14 color + blank color wheel

Gobo : 17 fixed gobo + blank gobo

Prism : rotation 8-face prism, Bilateral rotation

Lens : high precision optical lens

Focus : linear adjustment

Dimmer : 0-100% linear adjustment

Pan/Tilt : X axis 540° Y axis 270° , 16 bit precision scan

Beam angle : parallel beam angel 0-3.8°

Strobe : Double lens strobe (0.5-9 times/ second)

Control mode : Standard DMX512, Automatic and Master/ slave mode

Channel : 16 /20 CHS

packing dimensions (L x W x H) : 415x343x487mm

G.W : 15G

技术参数:

电源供应: AC100V~240V/50~60Hz,

功率: 200W/230W

光源: 200W (Philips MSD Platinum 5R , 色温可达8000K)

230W (OSRAM SIRIUS HRI 230W , 色温可达8500K)

光源寿命: 2000小时

颜色: 1个色盘 带有14种颜色+空白

图案: 1个图案盘带有17个固定图案片+空白

棱镜: 旋转八面棱镜,可双向旋转

镜头: 高精度复合光学镜头

调焦: 线性调焦

调光: 0-100%线性调节

投射光范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit

光束角度: 平行光束角: 0-3.8°

频闪: 双片式频闪(0.5-9次/秒)

控制模式: DMX512/自走/声控

通道数量: 16通道/20通道

两种通道模式

包装尺寸: 415x343x487mm

毛重: 15KG



用心、决心打造放心品质



N-B132

132W Moving head Beam Light

132W摇头光束灯

Technical Parameters:

power supply : AC 100-240 V 50/60Hz

Lamp : 132W (Philips 2R or OSRAM 2R or JSCN 2R)

Average Lifespan: 2000H

Color : 14 color + blank color wheel

Gobo : 17 fixed gobo + blank gobo

Prism : rotation 8-face prism, Bilateral rotation

Dimmer : 0-100% linear adjustment

Control mode : Standard DMX512, Automatic and

Master/ slave mode

Channel : 16 /20 HS

Features : Remote control lamp's switch function, display light

and lamp's using time, Automatically adjust cooling-fan's speed,

50% energy saving when strobe lens shu

技术参数:

电源供应: AC100V~240V/50~60Hz,

功率: 200W

光源: 132W (Philips 2R or OSRAM 2R or 森莱浦 2R)

光源寿命: 2000小时

颜色: 1个色盘 带有14种颜色+空白

图案: 1个图案盘带有17个固定图案片+空白

棱镜: 旋转八面棱镜,可双向旋转

调光: 0-100%线性调节

控制模式: DMX512/自走/声控

通道数量: 16通道/20通道 两种通道模式选择

其它功能: 远程控制灯泡开关功能, 显示灯具、灯泡使

用时间, 风机自动调速功能, 机械闭光时自动降低50%

光源功率, 采用光电复位系统, 当偶然发生误动后, 可

自动检索复位

N-BL012

LED infinite Beam light LED无极光束灯

Technical Parameters

Voltage: AC100-240V 50-60Hz

Power: 145w

Souce: 12pcs 10w CREE 4-in-1 LEDs

Control Mode: DMX-512, music control, automatic, master & slave

Strobe: 1-25Hz

Dimming: 1-100% linear dimming

Gobo: 25 different gobos

Pan/Tilt : X axis 540° Y axis 200° , 16 bit precision scan

Function: 1. New seven color beam with flower effect and many

amazing effect.

2. Three lamps as a section controllable.

3. The Lens inside can rotate without limitation.

packing size (L x W x H) : 330*260*460 mm

G.W : 6.5 G

技术参数:

工作电压: AC100-240V 50-60Hz

耗电功率: 145w

光源: 12颗CREE 4合一、RGBW

控制模式: DMX512/自走/声控

调光: 线性调光

投射范围: 水平540°, 解析度16Bit, 垂直200°, 解析度16Bit


功能: 全新的无极光束、开花, 多种梦幻宏效果功能, 无信号

时灯具会慢自走

包装尺寸: 330*260*460mm (1台装)

毛重: 6.5KG





2010年上海展



2011年广州展



2011年上海展



2012年北京展




2013年北京展



2012年广州展



2013年广州展



2014年广州展



工程案例
Project case

2009年上海五月天演唱会

2010年成都中国会所

2012年增城,你好!新年晚会

2012年邵武元宵焰火晚会

2012年台北灯会

工程案例
Project case



2013年杭州麦霸KTV

2013年恩平88BAR




2013年西塘潘多拉酒吧



2014年西塘地心引力酒吧



2013年西塘水调歌头酒吧



N-Y004/Y004A

7/12pcs 4 in 1 MINI Moving head LED Beam Light
7/12颗4合1迷你LED摇头光束灯

Technical Parameters:
技术参数:

Power supply: AC100~240V,50/60Hz
Power Consumption: 150W
Light Source: 7/12 pcs 10W (USA cree RGBW 4 in 1) LED
Control mode: DMX-512, music control, automatic, master & slave
Level Scanning: 540° (16 bit precision scan)
Vertical Scan: 270° (16 bit precision scan)
Beam angle: 13.5
Product Size: 33X24.5X38.5cm
Gross Weight: 5kg

电源供应: AC100~240V,50/60Hz
额定功率: 150W
光源: 7/12颗10W (美国科瑞 RGBW 4 in 1) LED, 专用光学透镜, 高强度聚光
控制模式: 512信号控制, 自走, 声控模式, 主从, 水平扫描: 540° (16 bit精度扫描)
垂直扫描: 270° (16 bit精度扫描)
频闪: 高速电子调节频闪可达1-25次/秒或随机频闪
光束角度: 13.5
产品尺寸: 33X24.5X38.5cm
净重: 5KG

N-Y003

36pcs 3W MINI Moving head LED Beam Light
36颗3W迷你LED摇头光束灯

Technical Parameters:
技术参数:

Power supply: AC100~240V,50/60Hz
Power Consumption: 150W
Light Source: 36 pcs 3W LED
Control mode: DMX-512, music control, automatic, master & slave
Level Scanning: 540° (16 bit precision scan)
Vertical Scan: 270° (16 bit precision scan)
Beam angle: 13.5
Product Size: 33X24.5X38.5cm
Gross Weight: 5kg

电源供应: AC100~240V,50/60Hz
额定功率: 150W
光源: 36颗3W LED, 专用光学透镜, 高强度聚光
控制模式: 512信号控制, 自走, 声控模式, 主从, 水平扫描: 540° (16 bit精度扫描)
垂直扫描: 270° (16 bit精度扫描)
频闪: 高速电子调节频闪可达1-25次/秒或随机频闪
光束角度: 13.5
产品尺寸: 33X24.5X38.5cm
净重: 5KG



N-Y001

108 pcs LED Moving Head Light
108颗LED摇头灯

Technical Parameters:
技术参数:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 400W
Light Source: High power 3W LED, 108 pcs of leds: 30Red, 30 Green, 30 Blue, 18 White
Beam angle: 15°, 25°, 45°(optional)
Color: 16.7 million for RGBW
Control mode: DMX-512, music control, automatic, master & slave
Channel: 16/12 channels
Level Scanning 630° (16 bit precision scan)
Vertical Scan: 270° (16 bit precision scan)
电源供应: AC90~240V, 50HZ~60HZ
功率: 400W
光源: 108颗3W大功率LED (红色30颗, 绿色30颗, 蓝色30颗, 白色18颗)
发光角度: 15°, 25°, 45°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制, 声控, 自走, 主从
控制通道: 16/12通道
水平扫描: 630度
垂直扫描: 270度

N-Y002

36pcs 10W LED Zoom Moving head Light
36颗10W全彩4合1 LED调焦摇头灯

Technical Parameters:
技术参数:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 400W
Light Source: 36 pcs 10W RGBW 4 in 1 LED
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave
Channel: 16/12 channels
Lamp life: 50,000hours lifetime
Pan: 630degree
Tilt: 270 degree
Zoom: 15~60
Outer cover material: Aluminum body
电源供应: AC90~240V, 50HZ~60HZ
功率: 400W
光源: 36颗10W全彩4合1灯珠
颜色: 1670万颜色变化
控制方式: DMX-512信号控制, 声控, 自走, 主从
控制通道: 16/12通道
水平扫描: 630度
垂直扫描: 270度
调焦角度: 15~60度





N-Y019

19*12W Beam moving head
19颗12W调焦光束摇头灯

Technical Parameters:
Power supply: AC100~240V,50/60Hz
Power Consumption: 260w
Light Source: 19 pcs 12W RGBW LED
Channel: 16channels
Level Scanning: 540° (16 bit precision scan)
Vertical Scan: 270° (16 bit precision scan)
color: RGBW full color
Control mode: DMX-512, automatic, master & slave
Fuction: small, fast, with the function of ZOOM.
Size: 325X188X396 mm
Weight: 9.2 Kg
Focusing Angle: 5-60

技术参数:
电源供应: AC100~240V,50/60Hz
额定功率: 260W
光源: 19颗12W RGBW 四合一 LED
控制通道: 16
水平扫描: 540° (16 bit精度扫描)
垂直扫描: 270° (16 bit精度扫描)
颜色: RGBW 全彩色
控制模式: 512信号控制, 自走模式, 主从, 功能: 超小, 速度快, 功能强大的LED摇头光束, 带调焦功能
产品尺寸: 25X188X396 mm
净重: 9.2KG
调焦角度: 5-60度

N-Y018

Two movement heads 8 eyes LED Beam Light
双排八眼LED 摇头光束灯

Technical Parameters:
Power supply: AC100~240V,50/60Hz
Power Consumption: 120W
Light Source: 8 pcs 10W (cree RGBW 4 in 1 or White) LED
Control mode: DMX-512, music control, automatic, master & slave
Vertical Scan: 270°
Color: RGBW 7 color or white

技术参数:
电源供应: AC100~240V,50/60Hz
额定功率: 120W
光源: 8颗10W (美国科瑞 RGBW 4 in 1 或白色) LED, 专用光学透镜, 高强度聚光。
控制模式: 512信号控制, 主从, 声控模式
垂直扫描: 270°
颜色: RGBW 七彩色 或白色



N-Y016

4head RGBW/White LED Moving Beam Light
4头RGBW七彩 /白光LED 摇头光束

Technical Parameters:
Power supply: AC100~240V,50/60Hz
Power Consumption: 80 w
Light Source: 4 pcs 10W (cree RGBW 4 in 1 or white) LED
Channel: 9 or 39channels/White 9 or 28 channels
Stroboscopic: 1-25 times per second
Level Scanning: 540° (16 bit precision scan)
Vertical Scan: 270° (16 bit precision scan)
color: RGBW 7 color or White
Control mode: DMX-512, music control, automatic, master & slave

技术参数:
输入电压: AC100-240V,50Hz-60Hz
最大功率: 80W
光源: 4颗10W高亮度白光/科瑞四合一全彩
通道: 9通道或39通道/白色9通道或28通道
频闪: 1-25次/秒
水平扫描: 540°+微调
垂直扫描: 270°+微调
颜色: 七彩色或白色
控制: 自走、声控、主从机、DMX512

N-Y017

1 head RGBW/White LED Moving Beam Light
单头RGBW七彩 /白光LED 摇头光束

Technical Parameters:
Power supply: AC100~240V,50/60Hz
Power Consumption: 30 w
Light Source: 1 pcs 10W (cree RGBW 4 in 1 or white) LED
Channel: 13 or 11 channels/White 9/7 channels
Level Scanning: 540° (16 bit precision scan)
Vertical Scan: 270° (16 bit precision scan)
color: RGBW 7 color or White
Control mode: DMX-512, music control, automatic, master & slave

技术参数:
输入电压: AC100-240V,50Hz-60Hz
最大功率: 30W
光源: 1颗10W高亮度白光/科瑞四合一全彩
通道: 13或11通道/白色9或7通道
水平扫描: 540°+微调
垂直扫描: 270°+微调
颜色: 七彩色或白色
控制: 自走、声控、主从机、DMX512



N-Y018

4 head RGBW LED Scanning Beam Light
4头RGBW七彩LED 扫描光束灯

Technical Parameters:
Power supply: AC100~240V,50/60Hz
Power Consumption: 80 w
Light Source: 4 pcs 10W (cree RGBW 4 in 1) LED
Level Scanning: 120°
Vertical Scan: 120°
color: RGBW 7 color
Control mode: DMX-512, music control, automatic, master & slave

技术参数:
输入电压: AC100-240V,50Hz-60Hz
最大功率: 80W
光源: 4颗科瑞 四合一全彩
水平扫描: 120°
垂直扫描: 120°
颜色: 七彩色
控制: 自走、声控、主从机、DMX512



N-Y006

8 head RGBW LED Moving Beam Light
8头RGBW LED 摇头光束

Technical Parameters:

技术参数:

Power supply: AC100-240V,50/60Hz
Power Consumption: 120W
Light Source: 8 pcs 10W (USA cree RGBW 4 in 1) LED

Control mode: DMX-512, music control, automatic, master & slave

Vertical Scan: 270°
Color: RGBW 4 color
Control Channel: 10 or 38
packing size(L x W x H): 1150x160x 250mm /PCS
Gross Weight: 8 kg
电源供应: AC100-240V,50/60Hz
额定功率: 120W

光源: 8颗10W (美国科瑞 RGBW 4 in 1) LED. 专用光学透镜, 高强度聚光


控制模式: 512信号控制, 自走, 声控模式, 主从垂直扫描: 270°

颜色: 红绿蓝白四色

控制通道: 10或38通道控制模式

包装尺寸: 1150x160x250mm

毛重: 8KG



N-Y005

8 head White LED Moving Beam Light
8头白光 LED 摇头光束

Technical Parameters:

技术参数:

Power supply: AC100-240V,50/60Hz
Power Consumption: 120W
Light Source: 8 pcs 10W white LED
Control mode: DMX-512, music control, automatic, master & slave

Vertical Scan: 270°

Color: white

Control Channel: 5/14

packing size(L x W x H): 1150x160x 250mm /PCS

Gross Weight: 8 kg

电源供应: AC100-240V,50/60Hz

额定功率: 120W

光源: 8颗10W 白光 LED. 专用光学透镜, 高强度聚光.

控制模式: 512信号控制, 主从, 声控模式

垂直扫描: 270°

颜色: 白色

控制通道: 5或14, 两种通道控制模式

产品尺寸: 1150x160x 250mm /支

净重: 8KG



N-Y015/N-Y007

150W/120W LED Pattern Moving head Light

Technical Parameters:

power supply: AC 100-240 V 50/60Hz
Power Consumption: 240W

Light Source: German BUTTERFLY 1 * 150 w white LED 120W (USA Luminus) LED

Color: 7 colors + white color +rainbow effect

Rotating Gobo:7 Gobo (interchangeable),Gobo-flow effect, Gobo shake

Static gobo: 9 Gobo, Gobo-flow effect, Gobo shake

Prism: rotation 3-face prism, Bilateral rotation

Focus: linear adjustment

Dimmer: 0-100% linear adjustment

Pan/Tilt: X axis 540° Y axis 270°, 16 bit precision scan

Strobe: 0-20HZ

Control mode: Standard DMX512, Automatic and Master/ slave mode

Channel: 16/17 CHS

packing size (L x W x H):490x370x375mm

G.W: 15KG

150W/120W LED 摇头图案灯

技术参数:

电源供应: AC100V-240V/50-60Hz,
功率: 240W

光源: 150W(德国BUTTERFLY)
120W(美国莱明纳斯) LED

颜色: 7种颜色+白光+彩虹效果

旋转图案盘: 7个图案, 图案流水效果, 抖动效果

静态图案盘: 9个图案, 图案流水效果, 抖动效果

棱镜: 旋转三棱镜, 可双向旋转

调焦: 线性调焦

调光: 0-100%线性调节

投射光范围: 水平540°, 解析度168bit, 垂直270°, 解析度10Bit

频闪: 0-20HZ

控制模式: DMX512/自走/主从

通道数量: 16/17通道

包装尺寸: 490x370x375mm

毛重: 15KG



N-Y010

90W LED pattern Moving head Light

Technical Parameters:

power supply: AC 100-240 V 50/60Hz

Power Consumption: 150W

Light Source:90W LED

Color: 7 colors + white color +rainbow effect

Rotating Gobo: rotation pattern 2 glass + 5 metal pattern

Static gobo: 9 Gobo, Gobo-flow effect, Gobo shake

Prism: rotation 3-face prism, Bilateral rotation

Digital zoom 15°, 28°

Dimmer: 0-100% linear adjustment

Pan/Tilt: X axis 540° Y axis 270°, 16 bit precision scan

Strobe: 0-20HZ

Control mode: Standard DMX512, Automatic and Master/ slave mode

Channel: 11 /14 CHS

packing size(L x W x H) :295 x 290 x 515 mm

G.W: 14. 8KG

90W LED 摇头图案灯

技术参数:

电源供应: AC100V-240V/50-60Hz,

功率: 150W

光源: 90W LED

颜色: 7种颜色+白光+彩虹效果

旋转图案盘: 2个玻璃图案+5个金属图案(可互换)

静态图案盘: 9个图案, 图案流水效果, 抖动效果

棱镜: 旋转三棱镜, 可双向旋转

电子变焦: 15°, 28°

调光: 0-100%线性调节

投射范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit

频闪: 0-20HZ

控制模式: DMX512/自走/声控

通道数量: 11通道/14通道 两种通道模式选择

尺寸: 295 x 290 x 515mm

毛重: 14.8KG



N-Y008

60W LED pattern Moving head Light

Technical Parameters:

power supply: AC 100-240 V 50/60Hz

Power Consumption: 150W

Light Source:60W (USA Luminus) LED

Color: 7 colors + white color +rainbow effect

Rotating Gobo:7 Gobo (interchangeable),

Gobo-flow effect, Gobo shake

Static gobo: 9 Gobo, Gobo-flow effect, Gobo shake

Prism: rotation 3-face prism, Bilateral rotation

Focus: linear adjustment

Dimmer: 0-100% linear adjustment

Pan/Tilt: X axis 540° Y axis 270°, 16 bit precision scan

Strobe: 0-20HZ

Control mode: Standard DMX512, Automatic and Master/ slave mode

Channel: 11 /14 CHS

packing dimensions(L x W x H):520x380x350mm

G.W: 16KG

60W LED 摇头图案灯

技术参数:

电源供应: AC100V-240V/50-60Hz,

功率: 150W

光源: 60W(美国莱明纳斯) LED

颜色: 7种颜色+白光+彩虹效果

旋转图案盘: 7个图案, 图案流水效果, 抖动效果

静态图案盘: 9个图案, 图案流水效果, 抖动效果

棱镜: 旋转三棱镜, 可双向旋转

调焦: 线性调焦

调光: 0-100%线性调节

投射光范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit

频闪: 0-20HZ

控制模式: DMX512/自走/主从

通道数量: 11通道/14通道 两种通道模式选择

包装尺寸: 520x380x350mm

毛重: 16KG





N-Y011/N-Y009

60W/30W LED pattern Moving head Light


Technical Parameters:

power supply: AC 100-240 V 50/60Hz
Power Consumption: 80W
Light Source: 60W/30W LED
Color: 7 colors + white color
Rotating Gobo: 7 Gobo (interchangeable),
Focus: Manual focusing
Dimmer: 0-100% linear adjustment
Pan/Tilt: X axis 540°, Y axis 270°, 16bit precision scan
Strobe: 0-20HZ
Control mode: DMX512, Automatic and Master/ slave mode
Channel: 10CHS
packing dimensions(L x W x H): 350×350×440mm
G.W: 11KG

60W/30W LED 摇头图案灯

技术参数:

电源供应: AC100V~240V/50~60Hz,
功率: 80W
光源: 60W/30W LED
颜色: 7种颜色+白光
旋转图案盘: 7个图案, 图案轮可双向旋转
调焦: 手动调焦
调光: 0-100%线性调节
投射范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit
频闪: 0-20HZ
控制模式: DMX512/自走/主从
通道数量: 10通道
包装尺寸: 350×350×440mm
毛重: 11KG



N-Y012

30W LED MINI Patten Moving head Light

Technical Parameters:

power supply: AC 100-240 V 50/60Hz
Power Consumption: 60W
Light Source: 30W LED
Color: 9 colors + white color
Rotating Gobo: 7 kinds of replacing rotating design + white light
Focus: Manual focusing
Dimmer: 0-100% linear adjustment
Pan/Tilt: X axis 540°, Y axis 270°, 16 bit precision scan
Strobe: 0-20HZ
Prism: prism function
Control mode: DMX512, Automatic and Master/ slave mode
Channel: 11/12CHS
packing size(L x W x H): 420×340×280mm
G.W: 7.5 KG

30W LED MINI摇头图案灯

技术参数:

电源供应: AC100V~240V/50~60Hz,
功率: 60W
光源: 30W LED
颜色: 9种颜色+白光
旋转图案盘: 7种可更换旋转图案片+白光, 图案轮可双向旋转
调焦: 手动调焦
调光: 0-100%线性调节
投射范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit
频闪: 0-20HZ
棱镜: 3棱镜
控制模式: DMX512/自走/声控
通道数量: 11/12通道
包装尺寸: 420×340×280mm
毛重: 7.5KG



N-Y013

15W LED Mini Pattern Moving head Light

Technical Parameters:

power supply: AC 100-240 V 50/60Hz
Power Consumption: 30W
Light Source: 15W LED
Color: 7 colors + white color
Gobo: 9 design + white + rainbow effect
Focus: Manual focusing
Dimmer: 0-100% linear adjustment
Pan/Tilt: X axis 540°, Y axis 270°, 16 bit precision scan
Control mode: DMX512, Automatic and Master/ slave mode
Channel: 13CHS
Special features: built-in a variety of lighting applications, but acoustic synchronous running out of control

15W LED 迷你摇头图案灯

技术参数:

电源供应: AC100V~240V/50~60Hz,
功率: 30W
光源: 15W LED
颜色: 7种颜色+白光
图案: 9个图案 + 白光 + 彩虹效果
调焦: 手动调焦
调光: 0-100%线性调节
投射范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit
控制模式: DMX512/自走/声控
通道数量: 13通道
功能: 内置多种灯光效果程序, 可脱离控台声控同步运行



FY-7005/7010/7020/7025/7050

RGB Moving head animation laser

摇头全彩动画激光

Technical Parameters:

Power Supply: AC110V / AC230V, 50HZ~60HZ
Power Consumption: 150W max
Laser Power: RGB 500mw~5000mw
Laser Color: RGB
Scan System: 20-40kpps vibratory mirror system,
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control(optional)
Control Channel: 18 or 23
Flight case Size: 560×440×840mm
Total weight: <45KG
Operating Environment: 10~35°indoor



技术参数:

电源供应: AC110V / AC230V, 50Hz~60Hz
额定功率: <150W
激光功率: RGB 500mw~5000mw
激光颜色: 全彩
扫描系统: 20-40kpps 振镜扫描,
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控, 自走, 主从, SD卡控制(可选)
控制通道: 18个或23个
航空箱尺寸: 560×440×840mm
总重: <45KG
工作环境: 室内(10~35°)



FY-1605/1610/1620/1650/FY-1320

Single Color Moving head animation laser

摇头单色动画激光


Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ
Power Consumption: 100W max
Laser Power: G 500mw~5000mw, B 2000mw
Laser Color: Green (532nm), Blue(450nm)
Scan System: 20-40kpps vibratory mirror system,
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control(optional)
Control Channel: 16 or 21
Flight case Size: 560×440×840mm
Total weight: <43KG
Operating Environment: 10~35°indoor



技术参数:

电源供应: AC110V / AC230V, 50Hz~60Hz
额定功率: <100W
激光功率: 绿 500mw~5000mw, 蓝2000mw
激光颜色: 绿色(532nm)或蓝色(450nm)
扫描系统: 20-40kpps 振镜扫描,
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控, 自走, 主从, SD卡控制(可选)
控制通道: 16个或21个
航空箱尺寸: 560×440×840mm
总重: <43KG
工作环境: 室内(10~35°)



F5000-908/910/915/920/930

RGB Animation laser 8W-30W
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 350W max
Laser Power: RGB 8W-30W
Wavelength: Green:532nm/Red:635nm or 640nm/
Blue: 450nm or 457nm
Laser Modulation: analog modulation
Laser Color: RGB full colors
Scan System: high speed scanner 30-80kpps,
Control Mode: ILDA, DMX-512, music control,
automatic, master & slave, SD
Card control(optional)
Cool System: fan
Operating Environment: 10-35°indoor

全彩动画激光灯8W-30W
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <350W
激光功率: 8W-30W
激光波长: 绿光: 532nm、红光: 635nm或
640nm、蓝光: 450nm或457nm
调制信号: 模拟调制
激光颜色: 全彩色
扫描系统: 30-80kpps高速振镜扫描系统,
控制方式: ILDA, DMX-512, 声控、自走、
主从、SD卡控制(可选)
冷却系统: 风机强制冷却系统
工作环境: 室内(10-35°)



F2000-901/9015/902/903/904/905/906/908

RGB Animation laser 1W-8W
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 200W max
Laser Power: RGB 1W-8W
Wavelength: Green 532nm, Red 655nm/635nm/
638nm/640nm, Blue450nm
Laser Modulation: analog modulation or TTL
Laser Color: RGB
Scan System: high speed scanner30-60kpps,
Control Mode: ILDA, DMX-512, music control,
autom-atic, master & slave, SD
Card control(optional)
Cool System: fan
Operating Environment: 10-35°indoor

全彩动画激光灯1W-8W
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <200W
激光功率: 1W-8W
激光波长: 绿光: 532nm、红光: 655nm或
635nm或638nm或640nm、
蓝光: 450nm
激光调制信号: 模拟调制或TTL调制
激光颜色: 全彩
扫描系统: 30-60kpps高速振镜扫描系统,
控制方式: ILDA, DMX-512, 声控、自走、
主从、SD卡控制(可选)
冷却系统: 风机强制冷却系统
工作环境: 室内(10-35°)



F4-RGB901/RGB9015/RGB902/RGB903/RGB904

RGB Animation laser 1W-4W
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 100W max
Laser Power: RGB 1W-4W
Wavelength: Green 532nm, Red 650nm/635nm
or 638nm, Blue450nm
Laser Modulation: analog modulation or TTL
Laser Color: RGB
Scan System: 15-30kpps vibratory mirror system,
Laser Patterns:128pcs
Control Mode: ILDA, DMX-512, music control,
automatic, master & slave, SD
Card control(optional)
Cool System: fan
Operating Environment: 10-35°indoor
Packing Size: 530×390×280mm
Gross Weight:16KG max

全彩动画激光灯1W-4W
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <100W
激光功率: 1W-4W
激光波长: 绿光: 532nm、红光: 650nm或
635nm或638nm、蓝光: 450nm
激光调制信号: 模拟调制或TTL调制
激光颜色: 全彩色
扫描系统: 15-30kpps振镜扫描,
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控、自走、
主从、SD卡控制(可选)
冷却系统: 风机强制冷却系统
工作环境: 室内(10-35°)
纸箱包装尺寸: 530×390×280mm
毛重: <16KG



F1000-818/820/901/9015/902/903

RGB Animation laser 1W-3W
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 100W max
Laser Power: RGB 1-3W
Wavelength: Green 532nm, Red 655nm/638nm,
Blue450nm
Laser Modulation: analog modulation or TTL
Laser Color: RGB seven colors
Scan System: 15-25kpps vibratory mirror system,
scan angle: ±20degrees
Laser Patterns:128pcs
Control Mode: ILDA, DMX-512, music control,
automatic, master & slave
Control Channel: 12
Cool System: fan
Operating Environment: 10-35°indoor

全彩动画激光灯1W-3W
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <100W
激光功率: RGB 1-3W
激光波长: 绿光: 532nm、红光: 655nm或
638nm、蓝光: 450nm
激光调制信号: 模拟调制或TTL调制
激光颜色: 全彩色
扫描系统: 15-25kpps振镜扫描,
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控、自走、
主从、
控制通道: 12
冷却系统: 风机强制冷却系统
工作环境: 室内(10-35°)



NF-815/-820/-828

RGB Animation laser 830mw-2.3W
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 100W max
Laser Power: RGB 830mw-2.3W
Wavelength: Green 532nm, Red 650nm/638nm,
Blue450nm
Laser Modulation: analog modulation or TTL
Laser Color: RGB
Scan System: 30kpps vibratory mirror system,
Control Mode: ILDA, DMX-512, music control,
automatic, master & slave
Control Channel: 12
Cool System: fan
Operating Environment: 10-35°indoor
Flightcase Size: 415×335×340mm
Gross Weight: 15KG max

全彩动画激光灯830mw-2.3W
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <100W
激光功率: RGB830mw-2.3W
激光波长: 绿光: 532nm、蓝光: 450nm、
红光: 650nm或638nm
激光调制信号: 模拟调制或TTL调制
激光颜色: 全彩
扫描系统: 30kpps振镜扫描,
控制方式: ILDA, DMX-512, 声控、自走、
主从
控制通道: 12
冷却系统: 风机强制冷却系统
工作环境: 室内(10-35°)
航空箱包装尺寸: 415×335×340mm
毛重: <15KG



F600-705/-710/-718/-720

RGB Animation laser 500mw-2.3W
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 100W max
Laser Power: RGB 500mw-2.3W
Wavelength: Green 532nm, Red 650nm/638nm,
Blue450nm
Laser Modulation: analog modulation or TTL
Laser Color: RGB
Scan System: 15-25kpps vibratory mirror system,
Laser Patterns:128pcs
Control Mode: ILDA, DMX-512, music control,
automatic, master & slave, SD
Card control(optional)
Control Channel: 17or 22
Cool System: fan
Operating Environment: 10-35°indoor
Packing Size: 410×310×190mm
Gross Weight: 8KG max

全彩动画激光灯500mw-2.3W
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <100W
激光功率: RGB 500mw-2.3W
激光波长: 绿光: 532nm、红光: 650nm或
638nm、蓝光: 450nm
激光调制信号: 模拟调制或TTL调制
激光颜色: 全彩
扫描系统: 15-25kpps振镜扫描,
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控、自走、
主从、SD卡控制(可选)
控制通道: 17或22
冷却系统: 风机强制冷却系统
工作环境: 室内(10-35°)
纸箱包装尺寸: 410×310×190mm
毛重: <8KG





F1003-750/F1003-723/F1101-750

RGB Animation laser 230mw-500mw
Technical Parameters:

Power Supply: AC90-240V, 50HZ~60HZ
Power Consumption: 60W max
Laser Power: RGB 500mw/230mw
Wavelength: Green 532nm, Red 650nm, Blue: 450nm or 405nm
Laser Color: RGB seven colors
Scan System: 15-25kpps vibratory mirror system
Scan Angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave SD Card control (optional)
Control Channel: 22 or 12
Operating Environment: 10-35°indoor
Inner Packing Size: 345×290×165mm, Gross Weight: 3KG max
Packing Size: 910×370×320mm (5 pcs), Total weight: 17KG max

全彩动画激光灯230mw-500mw
技术参数:

电源供应: AC90-240V, 50Hz~60Hz
额定功率: <60W
激光功率: 500mw/230mw
激光波长: 绿光: 532nm, 红光: 650nm, 蓝光: 450nm/紫光405nm
激光颜色: 全彩色
扫描系统: 15-25kpps振镜扫描,
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控、自走、主从、SD卡控制(可选)
控制通道: 22/12个
工作环境: 室内(10-35°)
内包尺寸: 345×290×165mm
毛重: <3KG
外包尺寸: 910×370×320mm (5支/箱), 总重量: <17KG



F3-503/F3-506/F3-513/F600-503

Three Color Animation Laser 250mw-1300mw
Technical Parameters:

Power Supply: AC90-240V, 50HZ~60HZ
Power Consumption: 80W max
Laser Power: RGY/RBM 500mw~1300mw
Wavelength: Green:532nm, Red:650nm or 638nm Blue:450nm
Laser Modulation: TTL
Laser Color: RGY or RBM three color
Scan System: 15-25kpps vibratory mirror system,
Scan Angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave, ILDA(optional)
Control Channel: 12 or 22
Cool System: fan
Operating Environment: 10-35°indoor

三色动画激光250mw-1300mw
技术参数:

电源供应: AC90-240V, 50Hz~60Hz
额定功率: <80W
激光功率: RGY/RBM500mw-1300mw
激光波长: 绿光: 532nm, 红光: 650nm/638nm 蓝光: 450nm
激光调制信号: TTL
激光颜色: 红、绿、黄三色或红、蓝、粉三色
扫描系统: 15-25kpps振镜扫描,
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控、自走、主从、ILDA(可选)
控制通道: 12或22个
冷却系统: 风机强制冷却系统
工作环境: 室内(10-35°)

F3-520/F3-501

Three Color Animation Laser 200mw-480mw
Technical Parameters:

Power Supply: AC90-240V, 50HZ~60HZ
Power Consumption: 30W max
Laser Power: RGY 200mw-480mw
Wavelength: green:532nm, red: 650nm, blue:450nm
Laser Color: RGY or RBM three color
Scan System: 15kpps vibratory mirror system,
Scan Angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave, ILDA(optional)
Control Channel: 12
Cool System: fan
Operating Environment: 10-35°indoor

三色动画激光200mw-480mw
技术参数:

电源供应: AC90-240V, 50Hz~60Hz
额定功率: <30W
激光功率: RGY 200mw-480mw
激光波长: 绿光: 532nm, 红光: 650nm 蓝光: 450nm
激光颜色: 红、绿、黄或红、蓝、粉红三色
扫描系统: 15kpps振镜扫描,
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控、自走、主从、ILDA(可选)
控制通道: 12
冷却系统: 风机强制冷却系统
工作环境: 室内(10-35°)



F5000-681/682/685/690/695/698/699

Green Animation Laser 1W-30W
Technical Parameters:

Power Supply: AC90-240V, 50HZ~60HZ
Power Consumption: 1000W max
Laser Power: 1W-30W
Laser Source: solid semiconductor laser generator
Wavelength: Green:532nm
Laser Modulation: analogue modulation or 0-20K TTL modulation
Scan System: 20KPPS scanning(Large lens)or 40kpps high speed scanner
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control(optional)
Cool System: fan
Operating Environment: 10-35°indoor

单绿动画激光1W-30W
技术参数:

电源供应: AC90-240V, 50Hz~60Hz
额定功率: <1000W
激光功率: 1W-30W
激光光源: 半导体激光发生器
激光波长: 绿光: 532nm
激光调制信号: 模拟调制或TTL调制0~20K
扫描系统: 20K大镜片振镜片或者40kpps高速振镜扫描系统,
控制方式: ILDA, DMX-512, 声控、自走、主从、SD卡控制(可选)
冷却系统: 风机强制冷却系统
工作环境: 室内(10-35°)


F4-675/681/682/683/685

Green Animation Laser 500mw-5W
Technical Parameters:

Power Supply: AC90-240V, 50HZ~60HZ
Power Consumption: 200W max
Laser Power: 500mw-5W
Wavelength: 532nm
Laser Color: Green
Scan System: 15-40kpps vibratory mirror system,
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control(optional)
Control Channel: 10 or 17
Cool System: fan
Operating Environment: 10-35°indoor
Packing Size: 530×390×280mm
Gross Weight: <13KG

单绿动画激光500mw-5W
技术参数:

电源供应: AC90-240V, 50Hz~60Hz
额定功率: <200W
激光功率: 500mw-5W
激光波长: 绿光: 532nm
激光颜色: 翠绿色
扫描系统: 15-40kpps振镜扫描,
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控、自走、主从、SD卡控制(可选)
控制通道: 10或17个
冷却系统: 风机强制冷却系统
工作环境: 室内(10-35°)
包装尺寸: 530×390×280mm
毛重: <13KG



NF-653/655/660/662/665

Green Animation Laser 300mw-5W
Technical Parameters:

Power Supply: AC90-240V, 50HZ~60HZ
Power Consumption: 200W max
Laser Power: 300mw-5W
Laser Color: Green(532nm)
Scan System: 30kpps vibratory mirror system,
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave
Control Channel: 10 or 23
Operating Environment: 10-35°indoor
Flight case Size: 415×335×340mm
Gross Weight: 16KG max

单绿动画激光300mw-5W
技术参数:

电源供应: AC90-240V, 50Hz~60Hz
额定功率: <200W
激光功率: 300mw-5W
激光颜色: 翠绿色(532nm)
扫描系统: 30kpps振镜扫描
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控、自走、主从
控制通道: 10或23个
工作环境: 室内(10-35°)
航空箱尺寸: 415×335×340mm
毛重: <16KG





F1000-653/655/681/682/683/685

Green Animation laser 200mw-5W
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 100W max
Laser Power: 200~5000mw
Laser Color: Green(532nm)
Scan System: 15-30kpps vibratory mirror system,
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control,
automatic, master & slave
Control Channel: 10
Operating Environment: 10~35°indoor

绿色动画激光灯200mw-5W
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <100W
激光功率: 200~5000mw
激光颜色: 翠绿色(532nm)
扫描系统: 15-30kpps振镜扫描
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控, 自走,
主从
控制通道: 10个
工作环境: 室内(10~35°)



F1101-650/651/652/653

Green Animation Laser 100~300mw
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 60W max
Laser Power: 100mw/150mw/200mw/300mw
Laser Color: Green(532nm)
Scan System: 15kpps vibratory mirror system,
Scan Angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control,
automatic, master & slave
Control Channel: 10 or 22
Operating Environment: 10~35°indoor
Inner Packing Size: 345×290×165mm
Gross Weight: 2.6~3.2KG
Packing Size: 910×370×320mm(5 pcs)
Total weight: 15~18KG

单绿动画激光100mw~300mw
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <60W
激光功率: 100mw/150mw/200mw/300mw
激光颜色: 翠绿色(532nm)
扫描系统: 15kpps振镜扫描
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控,
自走、主从
控制通道: 10或22个
工作环境: 室内(10~35°)
内包尺寸: 345×290×165
毛重: 2.6~3.2KG
外包尺寸: 910×370×320mm(5支/箱)
总重量: 15~18KG



F6-606/610/615/ F6-302/305/310 / F6-13

Single Color Animation SD card Laser
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 60W max
Laser Power: Green:60-150mw
Blue:200-1000mw Red:300mw
Laser Color: Green or Blue or Red
Scan System: 20kpps vibratory mirror system,
scan angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control,
automatic, master & slave, SD
Card control(optional)
Operating Environment: 10~35°indoor

单色动画SD卡激光

技术参数:
电源供应: AC90~240V, 50Hz~60Hz
额定功率: <60W
激光功率: 绿:60-150mw,
蓝:200-1000mw,红:300mw
激光颜色: 绿或蓝或红
扫描系统: 20kpps振镜扫描
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控,
自走、主从、SD卡控制(可选)
工作环境: 室内(10~35°)



F1101-305/310/510

Blue/Pink Animation Laser 500~1000mw
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 60W max
Laser Power: 500mw~1000mw
Laser Color: Blue(450nm)/Pink
Scan System: 15-30kpps vibratory mirror system,
Scan Angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: DMX-512, music control,
automatic, master & slave,
ILDA(optional)
Control Channel: 10 or 22
Operating Environment: 10~35°indoor
Inner Packing Size: 345×290×165mm
Gross Weight: 2.2~3KG
Packing Size: 910×370×320mm(5pcs)
Total weight: 12~16KG

单蓝/粉色动画激光500~1000mw
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <60W
激光功率: 500mw~1000mw
激光颜色: 蓝色(450nm)/粉红色
扫描系统: 15-30kpps振镜扫描
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控,
自走、主从、ILDA(可选)
控制通道: 10或22个
工作环境: 室内(10~35°)
内包尺寸: 345×290×165
毛重: 2.2~3KG
外包尺寸: 910×370×320mm(5支/箱)
总重量: 12~16KG



F1002-302/303/305/308/310

Blue Animation Laser 200~1000mw
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 50W max
Laser Power: 200mw~1000mw
Laser Color: Blue(450nm)
Scan System: 15kpps vibratory mirror system,
Scan Angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic,
master & slave, ILDA(optional)
Control Channel: 10
Operating Environment: 10~35°indoor
Inner Packing Size: 270×230×165mm
Gross Weight: 2~2.2KG
Packing Size: 905×300×260mm(5pcs)
Total weight: 11~12.5KG

单蓝动画激光200~1000mw
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <50W
激光功率: 200mw~1000mw
激光颜色: 蓝色(450nm)
扫描系统: 15kpps振镜扫描
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控, 自走,
主从、ILDA(可选)
控制通道: 10个
工作环境: 室内(10~35°)
内包尺寸: 270×230×165mm
毛重: 2~2.2KG
外包尺寸: 905×300×260mm(5支/箱)
总重量: 11~12.5KG



F1002-606/610/615

Green Animation Laser 60mw~150mw
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 50W max
Laser Power: 60mw/100mw/150mw
Laser Color: Green(532nm)
Scan System: 15kpps vibratory mirror system,
Scan Angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic,
master & slave, ILDA(optional)
Control Channel: 10
Operating Environment: 10~35°indoor
Inner Packing Size: 270×230×165mm
Gross Weight: 2~2.4KG
Packing Size: 905×300×260mm(5 pcs)
Total weight: 12~14KG

单绿动画激光60mw~150mw
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <50W
激光功率: 60mw/100mw/150mw
激光颜色: 翠绿色(532nm)
扫描系统: 15kpps振镜扫描,
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控, 自走,
主从、ILDA(可选)
控制通道: 10个DMX-512信号通道
工作环境: 室内(10~35°)
内包尺寸: 270×230×165
毛重: 2~2.4KG
外包尺寸: 905×300×260mm(5支/箱)
总重量: 12~14KG





F1668 / F1688

RGB Dazzling laser RGB 步步炫 激光灯

Technical Parameters:
Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 30W
Laser Power: Green(532nm) 60/100mw,
Red (650nm) 150mw/(638nm)
300mw, Blue200/1000mw (450nm)

Laser Color: RGB seven color
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs, Including 3D, grating
and other 13 group effect
Control Mode: DMX-512, music control,
automatic, master & slave

Control Channel : 23

Operating Environment: 10~35°indoor

技术参数:

电源供应: AC90~240V, 50Hz~60Hz

额定功率: 30W

激光功率: 532nm绿光60/100mw, 650nm

红光150mw或638nm 红光300mw,

450nm蓝光200/1000mw

激光颜色: RGB七彩

扫描系统: 15kpps振镜扫描

激光图案: 128幅, 包括3D,光栅等15组效果

控制方式: DMX-512、声控、自走、主从

控制通道: 23

工作环境: 室内(10~35°)



F6228 / F6268

RG Dazzling laser RG 步步炫 激光灯

Technical Parameters:
Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 30W

Laser Power: Green(532nm) 60/100mw,
Red (650nm) 150mw/
(638nm)300mw

Laser color: RGY 3 color
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs, Including 3D, grating
and other 13 group effect

Control Mode: DMX-512, music control,
automatic, master & slave

Control Channel : 23

Operating Environment: 10~35°indoor

技术参数:

电源供应: AC90~240V, 50Hz~60Hz

额定功率: 30W

激光功率: 532nm绿光60/100mw, 650nm

红光150mw或638nm 红光300mw

激光颜色: 红绿黄三色

扫描系统: 15kpps振镜扫描

激光图案: 128幅, 包括3D,光栅等15组效果

控制方式: DMX-512、声控、自走、主从

控制通道: 23

工作环境: 室内(10~35°)



F1643A / F1643

RGB 5D Twin Effects RGB

Technical Parameters:
Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 30W
Laser Power: Green(532nm)60mw / Red(650nm)
150mw / Blue200~300mw(450nm)

Laser Color: RGB seven color

Scan System: 15kpps vibratory mirror system

Laser Patterns: 128pcs, Including 3D, grating
and other 5 group effect

Control Mode: DMX-512, music control, automatic,
master & slave, Wireless remote(Optional)

Control Channel: 23

Operating Environment: 10~35°indoor

RGB五维流花台

技术参数:

电源供应: AC90~240V, 50Hz~60Hz

额定功率: 30W

激光功率: 532nm绿光60mw, 650nm红光

150mw, 450nm蓝光200~300mw

激光颜色: RGB七彩

扫描系统: 15kpps振镜扫描

激光图案: 128幅, 包括3D,光栅等5组效果

控制方式: DMX-512、声控、自走、主从、

遥控(可选)

控制通道: 23

工作环境: 室内(10~35°)



F6295A/F6223A / F6295/F6223

RB/RG 5D Twin Effects RB/RG

Technical Parameters:
Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 30W
Laser Power: Green(532nm)60mw / Red(650nm)
150mw / Blue200~300mw(450nm)

Laser Color: RBM /RGY three color

Scan System: 15kpps vibratory mirror system

Laser Patterns: 128pcs, Including 3D, grating
and other 5 group effect

Control Mode: DMX-512, music control, automatic,
master & slave, Wireless remote(Optional)

Control Channel: 23

Operating Environment: 10~35°indoor

RB/RG五维流花台

技术参数:

电源供应: AC90~240V, 50Hz~60Hz

额定功率: 30W

激光功率: 532nm绿光60mw, 650nm红光

150mw, 450nm蓝光200~300mw

激光颜色: 红蓝粉/红绿黄三色

扫描系统: 15kpps振镜扫描


激光图案: 128幅, 包括3D,光栅等5组效果

控制方式: DMX-512、声控、自走、主从、

遥控(可选)

控制通道: 23

工作环境: 室内(10~35°)



F1508 / F1508A

RGB rotating Twin Effects RGB

Technical Parameters:
Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 30W
Laser Power: Green(532nm) 60mw / Red (650nm)
150mw / Blue200~300mw(450nm)

Laser Color: red & green & blue

Scan System: 15kpps vibratory mirror system

Laser Patterns: 128pcs

Control Mode: DMX-512, music control, automatic,
master & slave, Wireless remote(Optional)

Control Channel: 23

Operating Environment: 10~35°indoor

RGB旋转流花台

技术参数:

电源供应: AC90~240V, 50Hz~60Hz

额定功率: 30W

激光功率: 532nm绿光60mw, 650nm红光

150mw, 450nm蓝光200~300mw

激光颜色: 红色、绿色、蓝色

扫描系统: 15kpps振镜扫描

激光图案: 128幅,


控制方式: DMX-512、声控、自走、主从、

遥控(可选)

控制通道: 23

工作环境: 室内(10~35°)





F1045A/F5830A/F1045/F5830

RB/RG rotating Twin Effects Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 30W
Laser Power: Green(532nm)60mw / Red(650nm) 150mw / Blue200~300mw(450nm)
Laser Color: red & blue or red & green
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave, Wireless remote (Optional)
Control Channel: 23
Operating Environment: 10~35° indoor

RB/RG 旋转流花台 技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: 30W
激光功率: 532nm绿光60mw, 650nm红光 150mw, 450nm蓝光200~300mw
激光颜色: 红色、蓝色或、红色、绿色
扫描系统: 15kpps振镜扫描
激光图案: 128幅
控制方式: DMX-512、声控、自走、主从、遥控(可选)
控制通道: 23
工作环境: 室内(10~35°)

F1003-250/F1101-250

RGB Twin Effects Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 30W
Laser Power: Green(532nm)60mw
Red(650nm)150mw
Blue200~300mw(450nm)
Laser Color: red & green & blue
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave
Control Channel: 22
Operating Environment: 10~35° indoor
Inner Packing Size: 345×290×165mm
Gross Weight: 2.4KG
Packing Size: 910×370×320mm(5 pcs)
Total weight: 13.5KG

RGB 流花台 技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: 30W
激光功率: 532nm绿光60mw
650nm红光150mw
450nm蓝光200~300mw
激光颜色: 红色、绿色、蓝色
扫描系统: 15kpps振镜扫描
激光图案: 128幅激光效果图案
控制方式: DMX-512、声控、自走、主从
控制通道: 22
工作环境: 室内(10~35°)
内包尺寸: 345×290×165mm
毛重: 2.4KG
外包装尺寸: 910×370×320mm(5支/箱)
总重量: 13.5KG


F1003-220 /245/F1101-220/245

RB/RG Twin Effects Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 20W
Laser Power: Green (532nm) 60mw
Red (650nm) 150mw
Blue (450nm) 200~300mw
Laser Color: red&Blue or green & red
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave
Control Channel: 22
Operating Environment: 10~35° indoor
Inner Packing Size: 345×290×165mm
Gross weight: 2.2KG
Packing Size: 910×370×320mm(5 pcs)
Gross weight: 12KG

RB/RG 流花台 技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: 20W
激光功率: 532nm绿光60mw
650nm红光150mw
450nm蓝光200~300mw
激光颜色: 红蓝或红绿
扫描系统: 15kpps振镜扫描
激光图案: 128幅激光效果图案
控制方式: DMX-512、声控、自走、主从
控制通道: 22个
工作环境: 室内(10~35°)
内包尺寸: 345×290×165mm
毛重: 2.2KG
外包装尺寸: 910×370×320mm(5支/箱)
总重量: 12KG



F1002-210/ 230

RG/RB Twin Effects Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 20W
Laser Power: Green (532nm) 50mw
Red (650nm) 100mw
Blue(450nm)200~300mw
Laser Color: red & green or red & blue
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave
Control Channel: 22
Operating Environment: 10~35° indoor
Inner Packing Size: 260×290×185mm
Gross weight: 2.1KG
Packing Size: 905×300×260mm(5 pcs)
Total weight: 11KG

RG/RB流花台 技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: 20W
激光功率: 532nm绿光50mw
650nm红光100mw
450nm蓝光200~300mw
激光颜色: 红绿或红蓝
扫描系统: 15kpps振镜扫描
激光图案: 128幅激光效果图案
控制方式: DMX-512、声控、自走、主从
控制通道: 22个
工作环境: 室内(10~35°)
内包尺寸: 260×290×185mm
毛重: 2.1KG
外包装尺寸: 905×300×260mm(5支/箱)
总重量: 11KG

F1001/F1001A/F1001B

RG/RB Cat eye Technical Parameters:

Power Supply: AC90~240V
Power Consumption: 20W
Laser Power: Green (532nm) 50mw
Red (650nm) 100mw
Blue(450nm)200~1000mw
Laser Color: green & red or red & blue
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs, There are 8 festival patterns, New Year's Day, Easter, Valentine's Day, Christmas Day, Wedding and Birthday.
Control Mode: music control, automatic Wireless remote(optional)
Operating Environment: 10~35° indoor

红绿/红蓝节日猫眼 技术参数:

电压供应: AC90~240V
额定功率: 20W
激光功率: 绿光50mw/532nm
红光100mw/650nm
蓝光 200~1000mw/450nm
激光颜色: 红色、绿色或红色和蓝色
扫描系统: 15kpps振镜扫描
激光图案: 128幅图案, 内置新年、元宵节、情人节、万圣节、圣诞节、婚礼、生日以及平日等八套节目
控制方式: 声控、自走、遥控(可选)
工作环境: 室内(10~35°)




F092A/F092B/F092C

4 in 1 grating laser Technical Parameters:

Power Supply: AC110V /AC230V, 50HZ~60HZ
Power Consumption: 20W
Laser Power: Green(532nm)50mw
Red (650nm)100mw
Blue(450nm)200~300mw
Laser Color: green & red or blue & red or green & blue
Control Mode: music control, automatic
Operating Environment: 10~35° indoor
Inner Packing Size: 265×180×100mm
Gross Weight: 1.25 KG
Packing Size: 530×280×390mm(10 pcs)
Total weight: 13 KG

四合一光栅激光灯 技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz
额定功率: 20W
激光功率: 532nm绿光 50mw
650nm红光100mw
450nm蓝光200~300mw
激光颜色: 红色、绿色、红色、蓝色、绿色、蓝色
控制方式: 声控、自走
工作环境: 室内(10~35°)
内包尺寸: 265×180×100mm
毛重: 1.25KG
外包装尺寸: 530×280×390mm(10个/箱)
总重量: 13KG





F1340/F1340B

RG/RB 40 in 1 grating laser
Technical Parameters:

Power Supply: AC110V /AC230V, 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Green(532nm)50mw

Blue(450nm) 200~1000mw

Laser Color: red & green or red & blue

Laser Patterns: 40pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红绿/红蓝40合一
技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,

532nm绿色50mw,450nm


蓝色200~1000mw

激光颜色: 红色和绿色 或 红色和蓝色

激光图案: 40个

控制方式: 声控、自走

工作环境: 室内(10~35°)



F1332/F1332B

RG/RB 32 in 1 grating laser
Technical Parameters:

Power Supply: AC110V /AC230V, 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Green(532nm)50mw

Blue(450nm) 200~1000mw

Laser Color: red & green or red & blue

Laser Patterns: 32pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红绿/红蓝32合一
技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,

532nm绿色50mw,450nm

蓝色200~1000mw

激光颜色: 红色和绿色 或 红色和蓝色

激光图案: 32个

控制方式: 声控、自走

工作环境: 室内(10~35°)



F1320/F1320B/F1320W

RG/RB/RGB 20 in 1 grating laser
Technical Parameters:

Power Supply: AC110V /AC230V, 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Green(532nm)50mw

Blue(450nm) 200~1000mw

Laser Color: red & green or red & blue or RGB

Laser Patterns: 20pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红绿/红蓝/红绿蓝20合一
技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,

532nm绿色50mw,450nm

蓝色200~1000mw

激光颜色: 红和绿 或 红和蓝 或 红绿蓝

激光图案: 20个

控制方式: 声控、自走

工作环境: 室内(10~35°)



F1312/F1312B

RG/RB 12 in 1 grating laser
Technical Parameters:

Power Supply: AC110V /AC230V, 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Green(532nm)50mw

Blue(450nm) 200~1000mw

Laser Color: red & green or red & blue

Laser Patterns: 12pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红绿/红蓝12合一
技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,

532nm绿色50mw,450nm


蓝色200~1000mw

激光颜色: 红色和绿色 或 红色和蓝色

激光图案: 12个

控制方式: 声控、自走

工作环境: 室内(10~35°)



FX312/FX312B

RG/RB 12 in 1 grating Ceiling laser
Technical Parameters:

Power Supply: AC110V /AC230V, 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Green(532nm)50mw

Blue(450nm) 200~1000mw

Laser Color: red & green or red & blue

Laser Patterns: 12pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红绿/红蓝吸顶12合一
技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,

532nm绿色50mw,450nm

蓝色200~1000mw

激光颜色: 红色和绿色 或 红色和蓝色

激光图案: 12个

控制方式: 声控、自走

工作环境: 室内(10~35°)



F1208/F1208A

RB 12 in 1/8 in 1 grating laser
Technical Parameters:

Power Supply: AC110V /AC230V, 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Blue(450nm) 200~1000mw

Laser Color: red & blue

Laser Patterns: 12/8pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红蓝12合一/8合一
技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,

450nm 蓝色200~1000mw

激光颜色: 红色和蓝色

激光图案: 12/8个

控制方式: 声控、自走

工作环境: 室内(10~35°)





F1209/F1209A

RG 12 in 1 / 8 in 1 grating laser
Technical Parameters:

Power Supply: AC110V /AC230V , 50HZ~60HZ
Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw / Green (532nm)50mw

Laser Color: red & green

Laser Patterns: 12 /8pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红 绿12/8合一
技术参数:

电源供应: AC110V /AC230V. 50Hz~60Hz
额定功率: 20W


激光功率: 650nm红光100~150mw. 532nm
绿光50mw

激光颜色: 红色和绿色

激光图案: 12/8个

控制方式: 声控、自走

工作环境: 室内(10~35°)



F088/F088B

F088/ F088B RG/RB Firefly
Technical Parameters:

Power Supply: AC110V /AC230V , 50HZ~60HZ
Power Consumption: 20W

Laser Power: Green (532nm) 50mw, Red (650nm) 100mw, Blue(450nm)300mw

Laser Color: red & green or red & blue

Control Mode: DMX-512, music control, automatic
Control Channel: 5

Inner Packing Size: 270*245*105mm

Gross Weight: 2.35 KG

Packing Size: 565*295*275mm(5 pcs)

Total weight: 12.8 KG

红绿/红蓝萤火虫
技术参数:

电源供应: AC110V /AC230V. 50Hz~60Hz
额定功率: 20W

激光功率: 532nm绿光 50mw. 650nm红光
100mw. 450nm蓝光300mw

激光颜色: 红绿或红蓝

控制方式: DMX-512, 自走, 声控


控制通道: 5个

内包尺寸: 270*245*105mm

毛重: 2.35KG

外包尺寸: 565*295*275mm (5个/箱)

总重量: 12.8 KG



F099

MINI RG laser
Technical Parameters:

Power Supply: AC110V /AC230V , 50HZ~60HZ
Power Consumption: 20W

Laser Power: Green (532nm) 50mw
Red (650nm) 100mw

Laser Color: green & red

Control Mode: music control, automatic

迷你红绿激光
技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz
额定功率: 20W

激光功率: 532nm 绿光 50mw
650nm 红光 100mw

激光颜色: 红色、绿色

控制方式: 自走、声控

F099A/F099B/F099C/F099D/F099E/F099F/F099G

MINI RG Firefly 2 in 1/4 in 1/6 in 1/8 in 1/12 in 1/20 in 1/ grating laser
Technical Parameters:

Power Supply: AC110V /AC230V , 50HZ~60HZ
Power Consumption: 10W

Laser Power: Red (650nm) 80~100mw,
Green(532nm) 15~30mw

Laser Color: red & green

Laser Patterns: 1pcs /2 pcs/4 pcs/6 pcs/8 pcs/
12 pcs/20 pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红绿萤火虫/4合一/6合一/8合一/12合一/20合一 迷你激光
技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz
额定功率: 20W


激光功率: 650nm红光80~100mw, 532nm
绿光 15~30mw

激光颜色: 红色和绿色

激光图案: 1/2/4/6/8/12/20个

控制方式: 声控、自走

工作环境: 室内(10~35°)



F0970-83/86/33

Green /Blue Animation Motor Laser
Technical Parameters:

Power Supply: AC110V /AC230V, 50HZ~60HZ
Power Consumption: 30W max

Laser Power: G:60mw/100mw, B:200-1000mw

Laser Color: green(532nm) ,Blue(450nm)

Scan System: Micro-step motor scanner,
big angle scanning

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

Inner Packing Size:260*215*100mm

Gross Weight:1.45KG

Packing Size:535*270*450mm(10pcs)

Total weight:15.5KG

单绿/单蓝电机动画激光灯
技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz
额定功率: <30W

激光功率: 绿60mw/100mw. 蓝200~1000mw

激光颜色: 绿色 (532nm), 蓝色 (450nm)

扫描系统: 高精度步进电机扫描系统,
大角度扫描

控制方式: 自走、声控


工作环境: 室内(10~35°)

内包尺寸: 260*215*100mm

毛重: 1.45KG

外包尺寸: 535*270*450mm(10支/箱)

总重量: 15.5KG



F0971B-66/71

Green Rain Curtain
Technical Parameters:

Power Supply: AC110V /AC230V, 50HZ~60HZ
Power Consumption: 50W max

Laser Power: 60mw/100mw

Laser Color: green (532nm)

Scan System: Micro-step motor scanner,
big angle scanning

Control Mode: DMX-512, music control, automatic

Control Channel: 8

Operating Environment: 10~35°indoor

Inner Packing Size: 360*290*185mm

Gross Weight:2.25KG

Packing Size: 905*300*260mm (5 pcs)

Total weight: 12.5KG

单绿扫描激光雨
技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz
额定功率: <50W

激光功率: 60mw, 100mw

激光颜色: 翠绿色 (532nm)

扫描系统: 高精度步进电机扫描系统,
大角度扫描

控制方式: DMX-512, 自走、声控

控制通道: 8个DMX-512信号通道

工作环境: 室内(10~35°)

内包尺寸: 360*290*185mm

毛重: 2.25KG

外包尺寸: 905*300*260mm (5个/箱)

总重量: 12.5KG

F0971B-33/ 35/38/F0971B-12

Blue/Red Rain Curtain
Technical Parameters:

Power Supply: AC110V /AC230V, 50HZ~60HZ
Power Consumption: 60W max

Laser Power: Blue (450nm) 300mw / 500mw/800mw,
Red (638nm) 200mw

Laser Color: Blue or Red

Scan System: Micro-step motor scanner,
big angle scanning

Control Mode: DMX-512, music control, automatic

Control Channel: 8

Operating Environment: 10~35°indoor

Inner Packing Size: 360*290*185mm

Gross Weight:2.25KG

Packing Size: 905*300*260mm (5 pcs)

Total weight: 12.5KG

蓝色/红色 扫描激光雨
技术参数:

电源供应: AC110V /AC230V, 50Hz~60Hz
额定功率: <60W

激光功率: 450nm蓝: 300mw/500mw/800mw,
638nm红: 200mw

激光颜色: 蓝色或红色

扫描系统: 高精度步进电机扫描系统,
大角度扫描

控制方式: DMX-512, 自走、声控

控制通道: 8个DMX-512信号通道


工作环境: 室内(10~35°)


内包尺寸: 360*290*185

毛重: 2.25KG

外包尺寸: 905*300*260mm (5个/箱)

总重量: 12.5KG





F1010-06/03/12

Green /Blue/ Red Laser Curtain

Technical Parameters:
Power Supply: AC110V/AC230V, 50HZ~60HZ
Power Consumption: 10W max
Laser Power: G:60mw/B: 300-1000mw/R: 300mw
Laser Color: green (532nm), Blue (450nm),
R (638nm)
Control Mode: TTL modulation
Operating Environment: 10-35°indoor

单绿/单蓝/单红激光雨帘
技术参数:
电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: <10W
激光功率: 绿60mw, 蓝300-1000mw,
红300mw
激光颜色: 绿色(532nm), 蓝(450nm),
红(638nm)
控制方式: TTL调制
工作环境: 室内(10-35°)



F0971-53/56/58/59

Green/Red/Blue Laser

Technical Parameters:
Power Supply: AC110V/AC230V, 50HZ~60HZ
Power Consumption: 50W max
Laser Power: Green(532nm)60mw/100mw,
Red(650nm)100mw,
Blue(450nm)200-1000mw
Laser Color: Green or Red or Blue
Scan System: Micro-step motor scanner,
big angle scanning
Control Mode: DMX-512, music control, automatic
Control Channel: 8
Operating Environment: 10-35°indoor
Inner Packing Size: 320*230*110mm
Gross Weight: 2.6KG max
Packing Size: 655*340*265mm (5 pcs/箱)
Total weight: 14KG max

绿色/红色/蓝色激光灯
技术参数:
电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: <50W
激光功率: 532nm绿: 60mw/100mw,
650nm红: 100mw,
450nm蓝: 200-1000mw
激光颜色: 绿色或红色或蓝色
扫描系统: 高精度步进电机扫描系统,
大角度扫描
控制方式: DMX-512、自走、声控
控制通道: 8个DMX-512信号通道
工作环境: 室内(10-35°)
内包尺寸: 320*230*110mm
毛量: <2.6KG
外包尺寸: 655*340*265mm (5个/箱)
总重量: <14KG




F0973

RGY Tri Colour Laser

Technical Parameters:
Power Supply: AC110V /AC230V, 50HZ~60HZ±10%
Power Consumption: 30W
Laser Power: Green (532nm) 40mw
Red (650nm) 150mw
Laser Color: green & red & yellow
Scan System: Micro-step motor scanner,
big angle scanning
Control Mode: DMX-512, music control, automatic
Control Channel: 5
Operating Environment: 10-35°indoor
Inner Packing Size: 320*230*110mm
Gross Weight: 2.9KG
Packing Size: 655*340*265mm (5 pcs)
Total weight: 15.8KG

红绿黄三色激光
技术参数:
电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: 30W
激光功率: 绿光 (532nm) 40mw
红光 (650nm) 150mw
激光颜色: 绿色、红色、黄色
扫描系统: 高精度步进电机扫描系统,
大角度扫描
控制方式: DMX-512、自走、声控
控制通道: 5个
工作环境: 室内(10-35°)
内包尺寸: 320*230*110mm
毛量: 2.9KG
外包尺寸: 655*340*265mm (5个/箱)
总重量: 15.8KG




F1066

Red & Green Four Head Laser Light

Technical Parameters:
Power Supply: AC110V/AC230V, 50HZ~60HZ
Power Consumption: 30W
Laser Power: Green(532nm)60mw
Red(650nm) 100mw*2
Laser Color: green & red
Scan System: Micro-step motor scanner,
Control Mode: DMX-512, music control, automatic
Control Channel: 5
Operating Environment: 10-35°indoor
Inner Packing Size: 700*250*180mm
Gross Weight: 4.7KG
Packing Size: 720*530*410mm (4 pcs)
Total weight: 20.5KG

红绿四头激光
技术参数:
电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: 30W
激光功率: 532nm绿60mw,
650nm红100mw*2
激光颜色: 绿色、红色
扫描系统: 高精度步进电机扫描系统,
控制方式: DMX-512, 自走、声控
控制通道: 5个
工作环境: 室内(10-35°)
内包尺寸: 700*250*180mm,
内包毛量: 4.7KG
外包尺寸: 720*530*410mm (4个/箱)
外包毛重: 20.5KG



F1066B/F1066C

5/4 Color Four Head Laser Light

Technical Parameters:
Laser Power: Green(532nm)60mw, Red(650nm)
150mw*1+100mw*2, Purple(405nm)
100mw, Green(532nm)60mw, Red(650nm)
100mw*2, Blue(450nm)200-300mw
Laser Color: green & red & purple & yellow & fuchsine
green & red & blue & yellow
Scan System: Micro-step motor scanner,
Control Mode: DMX-512, music control, automatic
Control Channel: 5
Operating Environment: 10-35°indoor
Inner Packing Size: 700*250*180mm
Gross Weight: 5.3KG
Packing Size: 720*530*410mm (4 pcs)
Total weight: 23.5KG

五彩/四色缤纷激光灯
技术参数:
激光功率: 532nm绿60mw, 650nm红光
(150mw*1+100mw*2),
405nm紫光100mw,
532nm绿60mw, 650nm红光
100mw*2, 450nm蓝光200-300mw
激光颜色: 绿色、红色、紫色、黄、品红
或者绿色、红色、蓝色、黄色
扫描系统: 高精度步进电机扫描系统,
控制方式: DMX-512, 自走、声控
控制通道: 5个
工作环境: 室内(10-35°)
内包尺寸: 700*250*180mm,
内包毛量: 5.3KG
外包尺寸: 720*530*410mm (4个/箱)
外包毛重: 23.5KG

F1022/F1022G/F1022B/F1022Y/F1022M/F1022D

Double Head Laser Light

Technical Parameters:
Power Consumption: 60W max
Laser Power: F1022: Green(532nm)40mw & Red
(650nm) 100mw,
F1022G: Green(532nm) 60mw
F1022B: Blue(450nm)500-1000mw
F1022Y: Green(532nm)60mw & Red
(650nm) 150mw
F1022M: Blue(450nm)500mw & Red
(650nm) 150mw
F1022D: Green(532nm)40mw & Blue
(450nm)300mw
Laser Color: F1022: Green & Red, F1022G: Green
F1022B: Blue, F1022Y: Green & Red
& Yellow, F1022M: Blue & Red & fuchsine
F1022D: Green & Blue
Inner Packing Size: 345*290*165mm
Gross Weight: 3.3KG
Packing Size: 910*370*320mm (5 pcs)
Total weight: 18.5KG

双头激光
技术参数:
额定功率: <60W
激光功率: F1022: 绿(532nm)40mw、红
(650nm) 100mw,
F1022G: 绿(532nm) 60mw
F1022B: 蓝(450nm)500-1000mw,
F1022Y: 绿(532nm)60mw和
红(650nm) 150mw
F1022M: 蓝(450nm)500mw、
红(650nm) 150mw
F1022D: 绿(532nm)40mw、
蓝(450nm)300mw
激光颜色: F1022: 绿和红, F1022G: 绿
F1022B: 蓝, F1022Y:
绿、红、黄, F1022M:
蓝、红、品红
F1022D: 绿、蓝
内包尺寸: 345*290*165mm,
内包毛重: 3.3KG
外包尺寸: 910*370*320mm, (5个/箱)
外包毛量: 18.5KG



2014/2014A

MINI LED Super Rocket
Technical Parameters:
 Power Supply: AC100~240V, 50HZ~60HZ
 Power consumption: 25W
 Light Source: 4 pcs 3W or 6 pcs 1W led
 Color : 4 or 6 color
 Control mode : DMX-512, music control, automatic
 Channel : 8 channels
 Operating Environment : indoor

LED 迷你无极剑
技术参数:
 额定电压: AC100~240V, 50Hz~60Hz
 功率: 25W
 光源: 4颗3W或6颗1W灯珠
 颜色: 四色或六色
 控制方式: DMX-512、声控、自走
 控制通道: 8通道
 工作环境: 室内



N-X013A

Mini LED Butterfly
Technical Parameters:
 Power Supply: AC100~240V, 50HZ~60HZ
 Power consumption: 30W
 Light Source: 2 pcs 10W (USA cree RGBW 4in1) LED
 Color : seven color
 Control mode : DMX-512, music control, automatic
 Channel : 8 channels
 Lens: 8*2 PCS
 Operating Environment : indoor

迷你LED蝴蝶灯
技术参数:
 额定电压: AC100~240V, 50Hz~60Hz
 功率: 30W
 光源: 2颗10W (美国科瑞RGBW四合一) 灯珠
 颜色: 七彩色
 控制方式: DMX-512、声控、自走
 控制通道: 8通道
 镜片: 8*2片
 工作环境: 室内



N-X015/X015A

MINI LED Butterfly
Technical Parameters:
 Power Supply: AC100~240V, 50HZ~60HZ
 Power consumption: 25W
 Light Source: 2 pcs 10W(USA cree RGBW 4in1)
 Color : seven color
 Control mode : DMX-512, music control, automatic
 Channel : 8 channels
 Lens: 6*2 PCS or 5*2pcs
 Operating Environment: indoor

迷你LED蝴蝶灯
技术参数:
 额定电压: AC100~240V, 60Hz~60Hz
 功率: 25W
 光源: 2颗10W (美国科瑞RGBW四合一) 灯珠
 颜色: 七彩色
 控制方式: DMX-512、声控、自走
 控制通道: 8通道
 镜片: 6*2片或5*2片
 工作环境: 室内



N-X016

Mini LED Super Rocket
Technical Parameters:
 Power Supply: AC100~240V, 50HZ~60HZ
 Power consumption: 25W
 Light Source: 4 pcs 3W (USA CREE)
 Color : Red and Green and Blue and White
 Control mode : DMX-512, music control, automatic
 Channel : 8 channels
 Operating Environment: indoor

LED 光剑箭
技术参数:
 额定电压: AC100~240V, 50Hz~60Hz
 功率: 25W
 光源: 4颗3W(美国科瑞) LED灯珠
 颜色: 红绿蓝白
 控制方式: DMX-512、声控、自走
 控制通道: 8通道
 工作环境: 室内



N-X013

LED Butterfly
Technical Parameters:
 Power Supply: AC100~240V, 50HZ~60HZ
 Power consumption: 40W
 Light Source: 2 pcs 10W(USA cree RGBW 4in1)
 Color : seven color
 Control mode : DMX-512, music control, automatic
 Channel : 8 channels
 Operating Environment : indoor


LED蝴蝶灯
技术参数:
 额定电压: AC100~240V, 50Hz~60Hz
 功率: 40W
 光源: 2颗10W (美国科瑞RGBW四合一) 灯珠
 颜色: 七彩色
 控制方式: DMX-512、声控、自走
 控制通道: 8通道
 工作环境: 室内



N-X013B

Mini LED Super Rocket
Technical Parameters:
 Power Supply: AC100~240V, 50HZ~60HZ
 Power consumption: 25W
 Light Source: 4 pcs 3W
 Color : Red and Green and Blue and White
 Control mode : DMX-512, music control, automatic
 Channel : 8 channels
 Lens: 8*8 PCS
 Operating Environment : indoor

Mini LED无极箭
技术参数:
 额定电压: AC100~240V, 50Hz~60Hz
 功率: 25W
 光源: 4颗3W LED灯珠
 颜色: 红绿蓝白
 控制方式: DMX-512、声控、自走
 控制通道: 8通道
 镜片: 8*8片
 工作环境: 室内



N-X024/N-X024A

LED ZOOM Magic Crystal Ball
Technical Parameters:
 Power Supply: AC110V/AC230V, 50HZ~60HZ
 Power consumption : 20W
 Light Source : 4 pcs 3W (CREE) /2 pcs 10W(USA CREE) RGBW 4in1
 Color : RGB or RGBW
 Control mode : DMX-512, music, automatic
 Channel : 6 channels
 Operating Environment : indoor

LED调焦水晶魔球
技术参数:
 额定电压: AC110V/AC230V, 50Hz~60Hz
 功率: 20W
 光源: 4颗3W (科瑞) 或2颗10W 四合一 (科瑞)
 颜色: 红、绿、蓝或红、绿、蓝、白
 控制方式: DMX-512信号控制、声控、自走
 控制通道: 6通道
 工作环境: 室内



N-X014

LED Magic Crystal Ball
Technical Parameters:
 Power Supply: AC100~240V, 50HZ~60HZ
 Power consumption : 25W
 Light Source : 6 pcs 3W LED
 Color : Red and Green and Blue
 Control mode : DMX-512, music, automatic
 Channel : 6 channels
 Operating Environment : indoor


LED水晶魔球
技术参数:
 额定电压: AC110V/AC230V, 50Hz~60Hz
 功率: 25W
 光源: 6颗3W LED
 颜色: 红、绿、蓝
 控制方式: DMX-512信号控制、声控、自走
 控制通道: 6通道
 工作环境: 室内



N-X014A/N-X014B

LED Magic Crystal Ball
LED MP3 Magic Crystal Ball
Technical Parameters:
 Power Supply: AC110V/AC230V, 50HZ~60HZ
 Power consumption : 20W
 Light Source : 6 pcs 1W or 3 pcs 1W
 Color : 6 color: Red and Green and Blue and white and yellow and pink
 Or 3 color: Red and Green and Blue
 Control mode : automatic automatic, Music control, remote control
 Operating Environment : indoor

LED 水晶魔球
LED MP3水晶魔球
技术参数:
 额定电压: AC110V/AC230V, 50Hz~60Hz
 功率: 20W
 光源: 6 颗1W 或3颗1W 灯珠
 颜色: 6色: 红、绿、蓝、白、黄、粉
 或 3色: 红绿蓝
 控制方式: 仅自走 或 自走、声控、遥控
 工作环境: 室内



F1238

RGB 8 Head Laser Light 红绿蓝8头激光灯

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ
Power Consumption: 80W
Laser Power: Green(532nm)60mw×3, Red(650nm)
150mw×3, Blue(450nm)200mw×2
Laser Color: green & red & blue
Scan System: Micro-step motor scanner, big angle scanning
Control Mode: DMX-512, music control, automatic
Control Channel: 26
Operating Environment: 10~35°indoor

技术参数:

电源供应: AC110V/AC230V, 50HZ~60HZ
额定功率: 80W
激光功率: 532nm绿60mw×3, 650nm红光150mw×3,
450nm蓝光200mw×2
激光颜色: 绿色、红色、蓝色
扫描系统: 高精度步进电机扫描系统, 大角度扫描
控制方式: DMX-512, 自走、声控
控制通道: 26个
工作环境: 室内(10~35°)

F1237

7 color 7 Head Laser Light 七头七色激光灯

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ
Power Consumption: 80W
Laser Power: Green(532nm)60mw×3, Red(650nm)
100mw×1+150mw×3, Blue(450nm)200mw×2
Laser Color: RGB 7 color
Scan System: Micro-step motor scanner, big angle scanning
Control Mode: DMX-512, music control, automatic
Control Channel: 12
Operating Environment: 10~35°indoor

技术参数:

电源供应: AC110V/AC230V, 50HZ~60HZ
额定功率: 80W
激光功率: 532nm绿60mw×3, 650nm红光100mw×1,
650nm红光150mw×3, 450nm蓝光200mw×2
激光颜色: 红、绿、蓝、白、黄、粉红、青
扫描系统: 高精度步进电机扫描系统, 大角度扫描
控制方式: DMX-512, 自走、声控
控制通道: 12个
工作环境: 室内(10~35°)

High power green laser landmark can be installed in the top buildings, such as tourist attractions and other outdoor place, is a laser application technology, computer image processing technology and speed scanner control of high-tech products. This products used high power green laser, can deduce dynamic short line, surface, rotating and geometric patterns, also can play text editor. Laser patterns can scan 360-degree, can enjoy its unique laser effects in a far place, wonderful effects, robust, shock, is the city landmark, the famous scenic, can become a shining landmark in the city and the unique urban landscape, urban lighting project a symbol of high quality.

高功率绿激光地标可安装在城市高层大厦顶端, 旅游景点等户外场所, 是集激光应用技术、计算机图像处理技术和超高速振镜控制技术于一体的高科技产品。该产品使用高功率的绿激光, 可在空中演绎出各种动态的线、面、旋转体等几何图案, 也可演绎编辑的各种图形文字。纯粹绚丽的激光图案可360度全方位扫描, 方圆数公里均能观赏到其独特的激光夜景, 视觉效果强劲、震撼, 具有王者风范, 是都市标志性建筑、著名景区的点睛之“笔”, 能使该建筑物活景区成为城市中耀眼的地标及独特的城市夜景, 是城市亮化工程中高品位的象征。

HW-910/920/930/940



Laser Landmarks 10W-40W

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power Consumption: 1500W max
Laser Power: 10W-40W
Laser Color: Green(532nm)
Scan System: high speed scanner
≥20kpps vibratory mirror system
Single line range: 1KM-10KM
Range Scanning: 1KM-5KM
Pan: 360 degree
Control Software: Pangolin or Phoneix
Cool System: fan

10W~40W 风冷地标激光灯

技术参数:

电源供应: AC100~240V, 50HZ~60HZ
额定功率: <1500W
激光功率: 10W-40W
激光颜色: 翠绿色(532nm)
扫描系统: 高速震镜扫描 ≥20Kkpps, 具有完善的过小、过压、过载、过热等监控和保护功能
单线射程距离: 1KM-10KM
扫描距离: 1KM-5KM
旋转角度: 水平360度
控制软件: 美国Pangolin(穿山甲)、德国Phoenix(火凤凰)
冷却方式: 风冷

Laser man is the laser programming, creative dance, music to combine a new laser performers, along with the rhythm of the music, laser dancer seems to have been given life, form time to time with the shadow moving. The beam of light is the best, gorgeous and surprise. applicable for Disco, Clubs, KTV station, pub, bar where the special dancing effect required.

激光人是融合了激光编程、舞蹈创意、音乐制作三位一体的全新激光舞蹈表演形式, 伴随着动感的音乐节奏, 舞者就像光影界的魔术师, 激光仿佛被赋予了生命的灵性, 时而光随影动, 时而人舞交融。每一束光线都是最好的道具, 或绚烂或惊奇。

激光人表演系统一般由激光器、控制软件及表演程序、激光扫描组件、舞台、激光笔等组成。适用于Disco, 演艺吧、夜总会、电视台、歌剧院等要求较高的场所使用。



F5000-820/830/850/950

Laser Man

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power Consumption: 200W max
Laser Power: Green2W/3W/5W or RGB 5W
Laser Color: Green(532nm) or RGB
Scan System: high speed scanner 40kpps vibratory mirror system
Control Mode: ILDA
Control Software: Pangolin or Phoneix
Operating Environment: 10~35°indoor

激光人

技术参数:

电源供应: AC100~240V, 50HZ~60HZ
额定功率: <200W
激光功率: 绿2W/3W/5W或RGB 5W
激光颜色: 翠绿色(532nm)或RGB
扫描系统: 40kpps振镜扫描
控制方式: ILDA
控制软件: 美国Pangolin(穿山甲)、德国Phoenix(火凤凰)
工作环境: 室内(10~35°)



N-J025

LED Matrix Light

Technical Parameters:

Power Supply: AC90-240V, 50/60Hz

Power Consumption: 750W

Light Source: 25pcs RGB 30W (3 in 1 or white) Led

Control mode: DMX-512, music control,
automatic, master & slave

Channel: 8CH/20CH/80CH

Beam Angle: 45°, 25°, 15°(optional)

Operating Environment: indoor

25头LED 矩阵灯

技术参数:

输入电压: AC90-240V, 50/60Hz

额定功率: 750W

灯珠数量: 25颗30W 3-in-1 LED 或者单
色白光LED

控制模式: DMX512模式、主从机模式、
自走模式、声控模式

通道模式: (8CH/20CH/80CH)

3种DMX模式

光束角度: 45度/25度/15度选择

颜色范围: 1670万种颜色(0~100%饱和度可调)

工作环境: 室内使用

N-P026

100w RGB (3 in 1) COB LED PAR Light

Technical Parameters:

Power Supply: AC90-240V, 50HZ-60HZ

Power Consumption: 120W

Light Source: 1 pcs 100W RGB (3 in 1) COB LED

Beam angle: 40°

Color: 16.7 million for RGB

Control mode: DMX-512, music control,
automatic, master & slave

Strobe: 0-20Hz

Outer cover material: Aluminum body

100w RGB 3合1 COB LED PAR灯

技术参数:

电源供应: AC90-240V, 50Hz~60Hz

功率: 120W

光源: 1颗100w RGB (3合1) COB LED

发光角度: 40°

颜色: 1670万颜色变化

控制方式: DMX-512信号控制、声控、
自走、主从

频闪: 0-20Hz

机壳材料: 铸铝

N-P027

100w 2 in 1 COB LED PAR Light

Technical Parameters:

Power Supply: AC90-240V, 50HZ-60HZ

Power Consumption: 120W

Light Source: 1 pcs 100W White and Yellow 2 in 1

Function: Each color can be controlled alone,
8CTs inside (2800, 3200, 500, 4200,
4900, 5600, 5900, 6500K) Also you
can choose the CT in the DMX channels

Beam angle: 40°

Control mode: DMX-512, music control,
automatic, master & slave

Strobe: 0-20Hz

Outer cover material: Aluminum body

100w 2合1 COB LED PAR灯

技术参数:

电源供应: AC90-240V, 50Hz~60Hz

功率: 120W

光源: 1颗100w 正白和黄色(2合1)COB LED

功能: 每种颜色可单独控制, 内置了8种

色温可选 (2800、3200、3500、

4200、4900、5600、5900、6500K),

也可以通过控台来混色。

发光角度: 40°

控制方式: DMX-512信号控制、声控、
自走、主从

频闪: 0-20Hz

机壳材料: 铸铝



N-P022

18 pcs RGBWA 5 in 1 LED Waterproof PAR Light

Technical Parameters:

Power Supply: AC90-240V, 50HZ-60HZ

Power Consumption: 300W

Light Source: 18 pcs 12W RGBWA 5 in 1 LED

Beam angle: 25°, 40°(optional)

Color: 16.7 million for RGB

grade of waterproof: IP65

Control mode: DMX-512, music control,
automatic, master & slave

Outer cover material: Aluminum body

18颗RGBWA 5合1防水PAR灯

技术参数:

电源供应: AC90-240V, 50Hz~60Hz

功率: 300W

光源: 18颗12W RGBWA 5合1 LED

灯珠发光角度: 25°, 40°可选

颜色: 1670万颜色变化

防水等级: IP65

控制方式: DMX-512信号控制、声控、
自走、主从

机壳材料: 铸铝

N-P015

24 pcs RGBW 4 in 1 LED Waterproof PAR Light

Technical Parameters:

Power Supply: AC90-240V, 50HZ-60HZ

Power Consumption: 300W

Light Source: 24 pcs 10W RGBW 4 in 1 LED

Beam angle: 25°, 40°(optional)

Color: 16.7 million for RGB

grade of waterproof: IP65

Control mode: DMX-512, music control,
automatic, master & slave

Outer cover material: Aluminum body

24颗 RGBW 4合1 LED 防水 PAR灯

技术参数:

电源供应: AC90-240V, 50Hz~60Hz

功率: 300W

光源: 24颗10W RGBW 4合1 LED灯珠

发光角度: 25°, 40°可选

颜色: 1670万颜色变化

防水等级: IP65

控制方式: DMX-512信号控制、声控、
自走、主从

机壳材料: 铸铝

N-P016

18 pcs RGBW 4 in 1 LED Waterproof PAR Light

Technical Parameters:

Power Supply: AC90-240V, 50HZ-60HZ

Power Consumption: 200W

Light Source: 18 pcs 10W RGBW 4 in 1 LED

Beam angle: 25°, 40°(optional)

Color: 16.7 million for RGB

grade of waterproof: IP65

Control mode: DMX-512, music control,
automatic, master & slave

Outer cover material: Aluminum body

18颗 RGBW 4合1 LED 防水 PAR灯

技术参数:

电源供应: AC90-240V, 50Hz~60Hz

功率: 200W

光源: 18颗10W RGBW 4合1 LED灯珠


发光角度: 25°, 40°可选

颜色: 1670万颜色变化

防水等级: IP65

控制方式: DMX-512信号控制、声控、
自走、主从

机壳材料: 铸铝




N-P017

12 pcs RGBW 4 in 1 LED Waterproof PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 150W
Light Source: 12 pcs 10W RGBW 4 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
grade of waterproof: IP65
Control mode: DMX-512, music control,
automatic, master & slave
Outer cover material: Aluminum body

12颗 RGBW 4合1 LED 防水 PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 150W
光源: 12颗10W RGBW 4合1 LED灯珠
发光角度: 25°, 40°可选
颜色: 1670万颜色变化
防水等级: IP65
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P007/ N-P008

36 pcs LED Waterproof PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 120W
Light Source: High power 1W or 3W LED,
36 pcs of leds: 12 Red, 12 Green, 12 Blue
Beam angle: 15°, 25°, 45°(optional)
Color: 16.7 million for RGB
grade of waterproof: IP65
Control mode: DMX-512, music control,
automatic, master & slave
Outer cover material: Aluminum body

36颗 LED 防水 PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 120W
光源: 36颗1W/3W高功率LED(红色12颗,
绿色12颗, 蓝色12颗)
发光角度: 15°, 25°, 45°可选
颜色: 1670万颜色变化
防水等级: IP65
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P009/ N-P010

54 pcs LED Waterproof PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 120W/200W
Light Source: High power 1W or 3W LED,
54 pcs of leds: 12Red, 18Green, 18Blue,
6White
Beam angle: 15°, 25°, 45°(optional)
Color: 16.7 million for RGB
grade of waterproof: IP65
Control mode: DMX-512, music control,
automatic, master & slave
Outer cover material: Aluminum body

54颗LED防水 PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 120W/200W
光源: 54颗1W/3W高功率LED(红色12颗,
绿色18颗, 蓝色18颗, 白光6颗)
发光角度: 15°, 25°, 45°可选
颜色: 1670万颜色变化
防水等级: IP65
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P021

18 pcs RGBWA 5 in 1 LED PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 300W
Light Source: 18 pcs 12W RGBWA 5 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control,
automatic, master & slave
Outer cover material: Aluminum body

18颗RGBWA 5合1 PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 300W
光源: 18颗12W RGBWA 5合1 LED
灯珠发光角度: 25°, 40°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P018

24 pcs RGBW 4 in 1 LED PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 300W
Light Source: 24 pcs 10W RGBW 4 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic,
master & slave
Outer cover material: Aluminum body

24颗 RGBW 4合1 LED PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 300W
光源: 24颗10W RGBW 4合1 LED灯珠
发光角度: 25°, 40°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P019

18 pcs RGBW 4 in 1 LED PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 200W
Light Source: 18 pcs 10W RGBW 4 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic,
master & slave
Outer cover material: Aluminum body

18颗 RGBW 4合1 LED PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 200W
光源: 18颗10W RGBW 4合1 LED灯珠
发光角度: 25°, 40°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P020

12 pcs RGBW 4 in 1 LED PAR Light
12颗 RGBW 4合1 LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 200W
Light Source: 12 pcs 10W RGBW 4 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave
Outer cover material: Aluminum body

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 200W
光源: 12颗10W RGBW 4合1 LED灯珠
发光角度: 25°, 40°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制, 声控, 自走, 主从
机壳材料: 铸铝



N-P012

54 pcs RGB 3 in 1 LED PAR Light
54颗RGB 3合1 LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 200W
Light Source: 54 pcs 3W RGB 3 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave
Outer cover material: Aluminum body

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 200W
光源: 54颗3W RGB 3合1 LED
发光角度: 25°, 40°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制, 声控, 自走, 主从
机壳材料: 铸铝



N-P001

18 pcs 1W LED PAR Light
18颗1W LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 20W
Light Source: 18 pcs 1W LED
Beam angle: 15°, 25°, 45°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 20W
光源: 18颗1W LED
发光角度: 15°, 25°, 45°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制, 声控, 自走, 主从



N-P0023 / N-P0024

7 pcs RGBW 4in1 LED PAR Light 7颗RGBW 4合1 LED PAR灯
6 pcs RGB 3in1 LED PAR Light 6颗RGB 3合1 LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 20W
Light Source: 7 pcs RGBW 4 IN 1 4w LED / 6 pcs RGB 3 IN 1 3w LED
Beam angle: 25°, 45°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 20W
光源: 7颗RGBW 四合一 4W LED / 6颗RGB 三合一 3W LED
发光角度: 15°, 25°, 45°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制, 声控, 自走, 主从



N-P003 / N-P004

36 pcs LED PAR Light 36颗 LED PAR灯

Technical Parameters:

Power Supply: AC90~240V 50HZ~60HZ
Power Consumption: 120W max
Light Source: High power 1W or 3W LED, 36 pcs of leds: 12 Red, 12 Green, 12Blue
Beam angle: 15°, 25°, 45°, optional
Color: RGB color mixing
Function: Color Changing, Strobe, Speed Luminance adjustable, etc.
Control mode: DMX-512, music control, automatic, master & slave
Channel: 6 channels
Outer cover material: Aluminium, black and white
Operating Environment: indoor

技术参数:

额定电压: AC90~240V 50Hz~60Hz
功率: <120W
光源: 36颗1W/3W高功率LED (红色12颗, 绿色12颗, 蓝色12颗)
发光角度: 15°, 25°, 45°可选
颜色: RGB混色
功能: 颜色变化, 频闪, 渐变, 速度/亮度调节
控制方式: DMX-512, 声控, 自走, 主从
机壳材料: 铝, 有黑色和白色
工作环境: 室内



N-P005 / N-P006

36 pcs LED PAR Light 36颗 LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 60W/120W
Light Source: High power 1W or 3W LED, 36 pcs of leds: 12 Red, 12 Green, 12Blue
Beam angle: 15°, 25°, 45° optional
Color: RGB color mixing
Function: Color Changing, Strobe, Speed / Luminance adjustable, etc.
Control mode: DMX-512, music control, automatic, master & slave
Channel: 6channels
Outer cover material: Aluminium
Operating Environment: indoor

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 60W/120W
光源: 36颗1W/3W高功率LED (红色12颗, 绿色12颗, 蓝色12颗)
发光角度: 15°, 25°, 45°可选
颜色: RGB混色
功能: 颜色变化, 频闪, 渐变, 速度/亮度调节
控制方式: DMX-512, 声控, 自走, 主从
控制通道: 6通道
机壳材料: 铸铝
工作环境: 室内



N-P013 / N-P014

54 pcs LED PAR Light 54颗LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 120W/200W
Light Source: High power 1W or 3W LED, 54 pcs of leds: 12Red, 14Green, 14Blue, 14White
Beam angle: 15°, 25°, 45°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave
Outer cover material: Aluminum body, black

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 120W/200W
光源: 54颗1W/3W高功率LED (红色12颗, 绿色14颗, 蓝色14颗, 白光14颗)
发光角度: 15°, 25°, 45°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制, 声控, 自走, 主从
机壳材料: 铸铝



N-P025

54 3W Warm white LED PAR Light 54颗3W 暖白LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 200W
Light Source: High power 3W Warm white LED
Beam angle: 15°, 25°, 45°(optional)
Color Temperature: 2800K~3200K
Control mode: DMX-512, music control, automatic, master & slave
Channel: 4/8 channels
Outer cover material: Aluminum body, black

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 200W
光源: 54颗3W高功率暖白LED
发光角度: 15°, 25°, 45°可选
色温: 2800~3200K
控制方式: DMX-512信号控制, 声控, 自走, 主从
控制通道: 4/8通道 (可选)
机壳材料: 铸铝, 颜色为: 黑色



N-X023

KTV MINI Matrix Light Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ
Power consumption: 30W
Light Source: 64 pcsΦ5 LEDs
Color: Red and Green and Blue and white
Control mode: music control, automatic
Outer cover material: Iron
Operating Environment: indoor

KTV 迷你小矩阵灯 技术参数:

额定电压: AC110V/AC230V, 50Hz~60Hz
功率: 30W
光源: 64 颗高亮度Φ5 LED
颜色: 红、绿、蓝、白
控制方式: 声控、自走
机壳材料: 铁
工作环境: 室内



N-X001

LED Seven Heads Magic Light Technical Parameters:

Power Supply: AC110V/AC230V 50HZ~60HZ
Power consumption: 60W max
Light Source: 469 pcs Φ5 LEDs
Color: Red and Green and Blue
Function: 7 gobo teams dynamic change, Zoom out or Zoom in for each team is available. gobo speed change adjustable, gobo with flash function, etc.
Control mode: DMX-512, music control, automatic, master & slave
Channel: 9 or 11 channels
Outer cover material: Iron and Aluminium,
Operating Environment: indoor

LED七头魔幻灯 技术参数:

额定电压: AC110V/AC230V 50Hz~60Hz
功率: <60W
光源: 469颗高亮度Φ5 LED
颜色: 红、绿、蓝
功能: 7组图案动感变换, 每组图案均可放大缩小, 图案变换速度可调节, 并具有频闪功能
控制方式: DMX-512, 声控, 自走, 主从控制通道: 9通道/11通道
机壳材料: 铁和铝
工作环境: 室内



N-X017

LED Crystal Mushroom Technical Parameters:

Power Supply: AC100-240V, 50HZ~60HZ
Power consumption: 35W
Light Source: 1pcs 9W LED
Color: Red and Green and Blue
Control mode: DMX-512, music, automatic
Operating Environment: indoor

LED蘑菇灯 技术参数:

额定电压: AC110V/AC230V, 50Hz~60Hz
功率: 35W
光源: 1颗9W LED
颜色: 红、绿、蓝
控制方式: DMX-512信号控制, 声控, 自走
工作环境: 室内



N-X003

LED Four Head Laser Light Technical Parameters:

Power Supply: AC110V/AC230V 50HZ~60HZ
Power consumption: 20W
Light Source: 256 pcs Φ5 LEDs
Color: Red and Green and Blue
Function: 85 Gobos Dynamic change, simulate the laser beam effect, the gobos can move by level and vertical, rotate, enlarge and narrow changeable, flashes frequency, and the brightness is adjustable.
Control mode: DMX-512, music control, automatic, master & slave
Channel: 10 channels
Outer cover material: Iron
Operating Environment: indoor

LED四头线条灯 技术参数:

额定电压: AC110V/AC230V 50Hz~60Hz
功率: 20W
光源: 256颗高亮度Φ5 LED
颜色: 红、绿、蓝
功能: 85种图案动感变换, 图案可移动翻转, 放大缩小, 变换速度可调节, 并具有渐隐、频闪、亮度调节等功能
控制方式: DMX-512, 声控、自走、主从控制通道: 10通道
机壳材料: 铁
工作环境: 室内




N-X005

LED Monnflower Light Technical Parameters:

Power Supply: AC230V 50HZ~60HZ
Power consumption: 20W
Light Source: 61 pcs Φ5 LEDs
Color: Red and Green and Blue
Function: chang color, flowing water/flashes frequency the pace is adjustable. etc.
Control mode: music control, automatic
Outer cover material: Aluminium
Operating Environment: indoor

LED六角月光灯 技术参数:

额定电压: AC230V 50Hz~60Hz
功率: 20W
光源: 61颗高亮度Φ5 LED
颜色: 红、绿、蓝
功能: 换色、流水/频闪效果, 速度可调
控制方式: 声控、自走
机壳材料: 铝
工作环境: 室内



N-X007

LED small airship Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 20W
Light Source: 64 pcsΦ10 LEDs
Color: Red and Green and Blue and white
Control mode: music control, automatic
Operating Environment: indoor

LED小飞艇 技术参数:

额定电压: AC100~240V, 50Hz~60Hz
功率: 20W
光源: 64颗高亮度Φ10 LED
颜色: 红、绿、蓝、白
控制方式: 声控、自走
工作环境: 室内



N-X023

LED PYRAMID LIGHT Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 60W
Light Source: 4 pcs 10W (USA cree RGBW 4 in 1)
Color: RGBW
Control mode: DMX-512, music control, automatic
Channel: 8 channels
Operating Environment: indoor

LED魅力四射 技术参数:

额定电压: AC100~240V, 50Hz~60Hz
功率: 60W
光源: 4颗10W(美国科瑞RGBW四合一)灯珠
颜色: 红绿蓝白
控制方式: DMX-512, 声控、自走
控制通道: 8通道
工作环境: 室内



N-X012

LED Magic Crystal Ball Technical Parameters:

Power Supply: AC110V/AC230V 50HZ~60HZ
Power consumption: 20W
Light Source: 9W LED diodes
Color: Red and Green and Blue
Control mode: DMX-512, music, automatic, master & slave
Channel: 7 channels
Outer cover material: Iron
Operating Environment: indoor

LED水晶魔球 技术参数:

额定电压: AC110V/AC230V 50Hz~60Hz
功率: 20W
光源: LED 大功率 9W
颜色: 红、绿、蓝
控制方式: DMX-512信号控制、声控、自走、主从
控制通道: 7通道
机壳材料: 铁
工作环境: 室内



N-X021

LED new small sun light
Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 10W
Light Source: 48 pcs Φ10 LEDs
Color: Red and Green and Blue
Control mode: automatic
Operating Environment: indoor

LED 小太阳灯
技术参数:

额定电压: AC100~240V, 50HZ~60HZ
功率: 10W
光源: 48颗高亮度 Φ10 LED
颜色: 红、绿、蓝
控制方式: 自走
工作环境: 室内



N-X020

LED 6 EYES FLOWER
Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 25W
Light Source: 1 pcs 15W RGB LED
Color: RGB
Control mode: DMX-512, music control, automatic, master & slave
Operating Environment: indoor

LED六眼泡泡灯
技术参数:

额定电压: AC100~240V, 50HZ~60HZ
功率: 20W
光源: 1颗15W RGB LED
颜色: 红、绿、蓝
控制方式: DMX512, 自走、声控、主从
工作环境: 室内



N-X025

LED CRYSTAL MAGIC & SUNFLOWER LIGHT
Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ
Power consumption: 20W
Light Source: 3 pcs 1W + 48 pcs 5mm led
Color: RGB
Control mode: automatic, music control
rotary effect + Sunshine effect
Operating Environment: indoor

LED水晶魔球太阳灯
技术参数:

额定电压: AC110V/AC230V, 50HZ~60HZ
功率: 20W
光源: 3颗1W+ 48颗5mm高亮度灯珠
(16颗红色, 16颗蓝色, 16颗绿色)
颜色: 红、绿、蓝
控制方式: 自走、声控
效果: 水晶魔球效果+太阳灯效果
工作环境: 室内



N-X026

Ceiling LED EFFECT LIGHT
Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 20W
Light Source: 1 or 2 pcs RGBW 4 in 1 led
Color: RGBW
Control mode: automatic, music control
Operating Environment: indoor

吸顶LED碎花灯
技术参数:

额定电压: AC100~240V, 50HZ~60HZ
功率: 20W
光源: 1颗/2颗RGBW 四合一灯珠
颜色: 红、绿、蓝、白
控制方式: 自走、声控
工作环境: 室内



N-X019

LED white spotlight
Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ
Power consumption: 10W
Light Source: 1 pcs 3W/5W (USA CREE) LED
Color: White
Control mode: automatic
Operating Environment: indoor

LED白色射灯
技术参数:

额定电压: AC110V/AC230V, 50HZ~60HZ
功率: 10W
光源: 1颗3W/5W (美国科瑞) LED
颜色: 白色
控制方式: 自走
工作环境: 室内



N-X018

LED 7 colors spotlight
Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 15W
Light Source: 1 pcs 10W (RGBW 4 IN 1) LEDs
Color: 7 colors
Control mode: DMX-512, music control, automatic
Channel: 6 channels
Operating Environment: indoor

LED七彩射灯
技术参数:

额定电压: AC100~240V, 50HZ~60HZ
功率: 15W
光源: 1颗10w (RGBW 4 in 1) LED
颜色: 七彩
控制方式: DMX512, 自走、声控
控制通道: 6通道
工作环境: 室内



N-X027

LED 7 colors spotlight
Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 15W
Light Source: 1 pcs 10W (RGBW 4 IN 1) LEDs
Color: 7 colors
Control mode: music control, automatic
Operating Environment: indoor

LED自走七彩射灯
技术参数:

额定电压: AC100~240V, 50HZ~60HZ
功率: 15W
光源: 1颗10w (RGBW 4 in 1) LED
颜色: 七彩
控制方式: 自走、声控
工作环境: 室内



N-X028/N-X029

ED 7 colors/White Ceiling spotlight
Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 15W
Light Source: 1 pcs 10W (RGBW 4 IN 1)/1pcs 3-10W White LED
Color: 7 colors or white
Control mode: music control, automatic, Induction control (optional)
Operating Environment: indoor

LED吸顶七彩/白光射灯
技术参数:

额定电压: AC100~240V, 50HZ~60HZ
功率: 15W
光源: 1颗10w (RGBW 4 in 1) 或 1颗3-10W 白色LED
颜色: 七彩或白色
控制方式: 自走、声控、感应控制 (可选)
工作环境: 室内



N-X030

LED 7 colors Ceiling washing light
Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 20W

Light Source: 1 pcs 15W (RGB 3 IN 1) LED

Color: RGB mixing color

Control mode: music control, automatic,

DMX512 control (optional),

Induction control (optional)

Operating Environment: indoor

吸顶LED七彩染色灯
技术参数:

额定电压: AC100~240V, 50HZ~60HZ

功率: 20W

光源: 1颗15w (RGB 3 in 1) LED

颜色: RGB混色

控制方式: 自走、声控、DMX512(可选)、

感应控制(可选)

工作环境: 室内



N-X031

LED 7 colors Ceiling washing light

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 20W

Light Source: 2 pcs 15W (RGB 3 IN 1) LED

Color: RGB mixing color

Control mode: music control, automatic,

DMX512 control (optional),

Induction control (optional)

Operating Environment: indoor

吸顶LED七彩染色灯
技术参数:

额定电压: AC100~240V, 50HZ~60HZ

功率: 20W

光源: 2颗15w (RGB 3 in 1) LED

颜色: RGB混色

控制方式: 自走、声控、DMX512(可选)、

感应控制(可选)

工作环境: 室内

N-X032

LED 7 colors Ceiling washing light

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 40W

Light Source: 3 pcs 10W (RGB 3 IN 1) LED

Color: RGB mixing color

Control mode: music control, automatic,

DMX512 control (optional),

Induction control (optional)

Operating Environment: indoor

吸顶LED七彩染色灯
技术参数:

额定电压: AC100~240V, 50HZ~60HZ

功率: 20W

光源: 1颗15w (RGB 3 in 1) LED

颜色: RGB混色

控制方式: 自走、声控、DMX512(可选)、

感应控制(可选)

工作环境: 室内



N-S006

MINI Strobe
Technical Parameters:

Power Supply: AC100~230V, 50HZ~60HZ

Power consumption: 10W

Light Source: 36 pcs 5050 LED

Function: flash pace adjustable

Control mode: automatic, music control

Operating Environment: indoor

迷你36颗贴片频闪
技术参数:

额定电压: AC100~230V, 50HZ~60HZ

功率: 10W

光源: 36颗5050 LED

功能: 频闪速度可调

控制模式: 自走、声控

工作环境: 室内



N-S007

LED White Strobe

Technical Parameters:

Power Supply: AC100~230V, 50HZ~60HZ

Power consumption: 20W

Light Source: 216pcs 5050 LED

Function: flash pace adjustable

Control mode: automatic, music control

Operating Environment: indoor

贴片频闪

技术参数:

额定电压: AC100~230V, 50HZ~60HZ

功率: 20W

光源: 216颗5050 LED

功能: 频闪速度可调

控制模式: 自走、声控

工作环境: 室内



N-S010/S011/S012

LED White Strobe

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 60W

Light Source: 1 pcs 20W/30W/50W white LED

Function: flash pace adjustable

Control mode: music control, automatic

Outer cover material: Iron

Operating Environment: indoor

LED白光频闪

技术参数:

电源供应: AC100~240V, 50HZ~60HZ

功率: 60W max

光源: 1颗20W/30W/50W 高功率白色LED

功能: 频闪速度可调

控制模式: 自走、声控

机壳材料: 铁

工作环境: 室内



N-S013/S014/S015

20w/30w/50w ceiling LED strobe light

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 60W

Light Source: 1 pcs 20W/30W/50W white LED

Function: flash pace adjustable

Control mode: music control, automatic

Outer cover material: Iron

Operating Environment: indoor

20w/30w/50w 吸顶LED频闪

技术参数:

电源供应: AC100~240V, 50HZ~60HZ

功率: 60W max

光源: 1颗20W/30W/50W 高功率白色LED

功能: 频闪速度可调

控制模式: 自走、声控

机壳材料: 铁

工作环境: 室内

N-S017

1000W Strobe

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ

Power consumption: 1200W

Lamp type : 1000W pulse tube

Function: flash pace adjustable

Control mode: automatic, controller control

Outer cover material: Iron

Operating Environment : indoor



1000W频闪

技术参数:

电源供应: AC110V/AC230V, 50HZ~60HZ

功率: 1200W

光源: 1000W脉冲管

功能: 频闪速度可调

控制模式: 自走、控制器控制

机壳材料: 铁

工作环境: 室内

N-S018

1500W Strobe

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ

Power consumption: 1800W

Lamp type : 1500W pulse tube

Function: flash pace/luminance adjustable

Control mode: automatic, controller control

Outer cover material: Iron

Operating Environment : indoor



1500W频闪

技术参数:

电源供应: AC110V/AC230V, 50HZ~60HZ

功率: 1800W

光源: 1500W脉冲管

功能: 频闪速度/亮度可调

控制模式: 自走、控制器控制

机壳材料: 铁

工作环境: 室内

N-S019

3000W DMX Strobe

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ

Power consumption: 3500W

Lamp type : 3000W pulse tube

Function: 0-25 times / sec can be adjusted

continuously dazzling effects, and

special effects can be edited. Intelligent

thermal control, reducing the time

required for cooling, with fan cooling.

lash pace/luminance adjustable

Control mode: automatic, DMX512

Control Channel : 1/3/4

Outer cover material: Iron

Operating Environment : indoor



3000W 炫目超强化 DMX频闪

技术参数:

电源供应: AC110V/AC230V, 50HZ~60HZ

功率: 3500W

光源: 使用长效氙气灯管

功能: 频闪频率: 0-25次/秒可调节,

连续的眩目效果, 及可编辑的特殊

效果。智能化热能控制, 减低冷却

所需时间, 有风扇冷却功能。

控制模式: 自走、DMX512

控制通道: 1CH/3CH/4CH可选, 最大控制

通道4CH

机壳材料: 铁

工作环境: 室内

N-C1308

Controller 1308

Technical Parameters:

Power input: DC 9-12V 1000ma min

Dimensions: 250mmX150mmX100mm

Net Weight: 1.5kg

Also it have following functions except the

parameter of downloaded program-mes can not be changed:

Choose 1 among the 7 different programmes

Change the speed of the sequence of the

programme

Run the programme normally or automatically

Stop the programme

Storage up to a maximum of 7 different pro-

grammes up to a maximum of 127 cues for

each programme

It accepts up to a maximum of 512 DMX

channels

The programmes are stored in a flash

memory 4Mb

The advantage of Easy control is not only price but

also convenient use method -- it is really very easy

to operate even you not know anything about DMX

512 console before.



控制台1308

技术参数:

电源输入: DC9V 1000mA

外形尺寸: 250mmX150mmX100mm

重量: 1.5 kg

易控台除了不能直接更改下载的程序外还有如

下的功能:

- * 备有7个可录制编程空间
 - * 场景转换速度可调
 - * 可由手动或自动驱动场景转换
 - * 暂停场景转换功能
 - * 最多可以存储7个不同的程序, 每个程序可以有127个不同的步
 - * 它最多可以控制512个通道
 - * 程序是储存在一个4MB的闪存里
- 易控台的优点不仅在于价格而且操作方法非常方便 -- 是真正的易于操控的, 哪怕你从来没有用过DMX512控台。

N-C1323

Controller 1323

Technical Parameters:

* 3Pin female DMX connector

* Dimension: 482X133X75 mm

* Net weight: about 2.2KG.

* Controls up to 12 intelligent lights of up

to 16 channels each

* 23 banks of 8 scenes, 184 scenes max

* 192 DMX channels of control

* 6 sets of chases containing 240 scenes

* Sequential linking of chases

* Grab any fixture on the fly

* 3 space 19" rack mount

* MIDI compatible

* Beat activation, tap-sync and auto run



控制台1323

技术参数:

- * 3芯母 DMX 输入座
- * 尺寸: 482X133X75 mm
- * 净重: 约 2.2KG.
- * 可控每台有16通道的灯12台
- * 可编程23个记忆储存 (bank) , 每个可储存8个场景 (scene) 共计192通道
- * 6个可编程步序 (chase) , 每个步序可编184步 (即23个bank8个 scene)
- * 步序 (chase) 可循环运行
- * 可随意提灯操作
- * 可控声, 同步或是自动运行
- * 标准19"机柜安装长度
- * MIDI输入
- * 断电、重启自动播放功能

N-C1312

Controller 1312

Technical Parameters:

* Frequency: 2.45GHz

* Transmit distance: 300m (Visible distance)

* Limitless receivers

* DMX channel: 512 CHL (each receiver)

* Antenna: Helical SMA antenna

* Electric: AC100-240V, 50/60HZ

* Dimension: 153 x 147 x 41mm

* Net Weight: 0.5kg (with AC power supply)

Specification:

* Maximum 16 transmitters at same place without any disturb.

Each transmitter has 512 channels and total 8192 channels.

* Professional and un-replaceable W-LAN product for

convenient use to control as much as maximum lighting

units you need especially for architectural building.

* Easy learn and operate

* One transmitter to one receiver, One transmitter to multiple

receiver or Multiple transmitter to multiple receiver.

* Free set frequency and transmit password with transmitter

and receiver via buttons on operation panel



控制台1312

技术参数:

- * 频率: 2.45GHz
- * 接收器数量不受限制
- * 最远距离: 250米 (无障碍情况下)
- * 尺寸: 153X147X41
- * 电源: 100-240V, 50/60HZ
- * 重量: 0.5KG (含电源)
- * DMX通道数: 512通道 (每一个接收器特征)
- * 同一个地点最多安装16个发送器, 准确快速互不干扰, 每一个发送器都有512通道, 最多可控制8192通道
- * 此产品非常专业, 是不可替代的简单实用的产品, 多台同时使用时可以最大限度的实现你想要控制的灯特别是在建筑上
- * 简单易学, 操作方便
- * 可以一发送一接收, 可以一发送多个接收, 也可以多个发送多个接收
- * 发送器和接收器可以通过按键切换频率和通讯密码可以自己设定



N-C512A

Controller 512A 控制台 512A

Technical Parameters:

Power supply: DC9V 1000mA
DMX512/1990 Standard, 512 channels
Up to 32 scanners may be connected with a maximum of 16 channels each assignable joystick for easy of movement, four keys fine adjustment
8 chases and 32 scenes can be run at the same time
32 chases (at most 120 steps for each chase)
3840 chase steps
The music trigger source can be selected between audio line input or in-build microphone
The Data auto-saves
DMX signal output connector: XLR-D3F X4
Size: 482mmX300mmX100mm
Net Weight: 6Kg

技术参数:

电源输入: DC9V 1000mA
DMX512/1990信号输出, 512个控制通道
512个控制通道
可同时控制32台16通道电脑灯
16个通道的控制推子
一个可设置的摇杆装置
可同时运行8个走灯程序和32个场景
32个走灯程序, 每个程序最大120步
共3840个电脑灯走灯程序步
走灯音乐同步, 线路电平-10dB--+10dB
自适应/机内话筒
关机数据保存
DMX信号输出连接器: XLR-D3F X4
外形尺寸: 482mm×365mm×110mm
重量: 6.0KG

N-CS512

Controller S512 控制台 S512

Technical Parameters:

Power input: DC9V 1000mA
DMX512/1990 standard, 512 DMX control channels.
4 output with optical isolated, withstand 2000Vrms.
Up to 32 scanners may be connected with a maximum of 16 channels each.
A large backlight LCD to display operation parameters.
16 sliders for channel, 1 slider for speed control.
1600 chase steps, 48 chases, up to 100 steps each.
Each step contains its speed and cross time, can be set respectively. Trigger mode selectable: Music synchronously and manual speed.
Cooperating with the chase speed slider, the time of the program step can be changed from 0.03s to 180s.
48 scanner scenes can be used directly.
8 chases, 48 scenes operated at the same time.
At most 32 scanners can be selected
15 environment programs to output the combination, which are composed of different scenes, chases and manual output quickly.
Dimension: 498 x 420 x 115mm
Net Weight: 6.5kg

技术参数:

电源输入: DC9V 1000mA
DMX512/1990标准, 512个DMX控制通道。
2路带光隔离的独立输出驱动端口, 具有抗2000VDC电气冲击能力。
可控制32台16通道电脑灯。
带背光的大屏幕LCD显示各种运行参数。
16个通道推杆, 1个速度控制推杆。
1600个走灯程序步容量, 48个走灯程序, 每程序最多100步, 每步速度, 渐变参数独立设置, 可选音乐同步或手动速度控制。
在走灯速率推杆的配合下, 程序步的时间范围可从0.03S-180S。
48个可直接调用的电脑灯场景。
可同时运行8个走灯程序, 48个场景, 并可同时对32台电脑灯进行手动运行(提灯)。
15个环境键, 快速调用不同的场景、走灯、手动运行组合。
尺寸: 498mm×420mm×115mm
重量: 6.5KG



N-C200

Controller 200 控制台 200

Technical Parameters:

Power input: DC 9-12V 1000ma min
DMX512/1990 Standard
Total of 192 output channels
30 banks have 8 programmable scenes each
16 slider for manual control of channels
Midi control over banks, chases and Blackout
Record up to 6 programmable chases with fade time and speeds
LED function and program display
Built in microphone for music triggering
Auto mode program controlled by fade time sliders
Dimensions: 520mm×183mm×73mm
Net Weight: 3.0kg

技术参数:

电源输入: DC9V 1000mA
DMX512/1990信号输出, 192控制通道
有30个BANKS, 每个BANKS有8个可编程的SCENES
有16个可调位器调节输出大小, 内置MIC头, 提供声音触发, 在自动触发状态, 通过TAPSYNC键或SPEED电位器确定自动触发时间在MIDI接口, 可随时间MIDI信号控制, 4位数码显示屏, BLACK OUT功能可用于手动或MIDI做程控制, CHASES编程和CHASES运动功能, 可用手动或MIDI做程控制输出延时功能, 用FADE TIME电位器调节延时时间
外形尺寸: 520mm×183mm×73mm
重量: 3.0KG



N-C2024

Controller 2024 控制台 2024

Technical Parameters:

Power supply: DC9V 10 00mA
DMX512/1990 Standard, 504 channels
Up to 20 scanners may be connected with a maximum of 24 channels each
24 channels for dimmers
8 slider for manual control of channels assignable joystick for ease of movement
24 chases (at most 40 steps for each chase)
960 chase steps
Each chase speed and cross time can be saved automatic
128 K high capacity memory card
The Data auto-saves
DMX signal output connector: XLR-D3F
Size: 485mm×250mm×91mm
Net Weight: 5Kg

技术参数:

电源输入: DC9V 10 00mA
DMX512/1990信号输出, 504个控制通道
可同时控制20台24通道电脑灯+24调光通道
8个通道的控制推子
一个可设置的摇杆装置
24个走灯程序, 每个程序最大40步
共960个电脑灯走灯程序步
各程序速度, 渐变自动记忆
128K 大容量记忆
关机数据保存
DMX信号输出连接器: XLR-D3F
外形尺寸: 485mm×250mm×91mm
重量: 5kg

N-C1216

Controller 1216 控制台 1216

Technical Parameters:

Power supply: DC9V 10 00mA
DMX512/1990 Standard, 240 channels
Up to 12 scanners may be connected with a maximum of 16 channels each
24 channels for dimmers, 24 channels for switch of lamp
8 slider for manual control of channels assignable joystick for ease of movement
12 chases (at most 40 steps for each chase)
480 chase steps
Each chase speed and cross time can be saved automatic
128 K high capacity memory card
The Data auto-saves
DMX signal output connector: XLR-D3F
Size: 485mm×250mm×91mm
Net Weight: 5Kg

技术参数:

电源输入: DC9V 10 00mA
DMX512/1990信号输出, 408个控制通道
可同时控制12台16通道电脑灯+24调光通道+24开关通道
8个通道的控制推子
一个可设置的摇杆装置
12个走灯程序, 每个程序最大40步
共480个电脑灯走灯程序步
各程序速度, 渐变自动记忆
128K 大容量记忆
关机数据保存
DMX信号输出连接器: XLR-D3F
外形尺寸: 485mm×250mm×91mm
重量: 5kg



N-C240A

Controller 240A 控制台 240A

Technical Parameters:


Power input: DC 9-12V 300ma min
12 scanners of 16 channels each
30 banks have 6 programmable scenes each
6 programmable chase have 240 scenes each
8 slider for manual control of channels
2 assignable wheels for ease of movement
auto mode program controlled by speed and fade time sliders
fade time/assign fade time
reversible DMX channels fixture to react in opposition to others in a chase
8 channel or 16 channel mode
fine adjustment for Wheel pan and tilt
blackout master button
manual override button allow you to grab any fixture on the fly
built in microphone for music triggering
midi control over banks, chases and blackout
power failure memory
Dimensions(mm): 482 x 190 x 90
Net Weight: 3.0kg

技术参数:

电源输入: DC9-12V 300mA
最多可控制12台电脑灯, 每台电脑灯最多16个通道
可编程30个记忆储存(BANK), 每个可存储8个场景(SCENCE)
6个可编程程序(CHASE), 每个程序可编240步(即30个BANK SCENE)
8个通道控制推子
两个手控轮
在自动运行模式中, FADE可选择全部具有ALL或X/Y, 具有FADE, 都具有SPEED调节, 8通道或16通道工作模式
数码轮装置可对灯具的水平/垂直运动进行微调
具Blackout输出
内置麦克风 MIDI控制
掉电记忆保护
尺寸: 482mm×190mm×90mm
重量: 3.0KG



N-CS362



三基色 36°2
Three colors light lamp 36°2
Voltage: 220 v / 50 Hz
Light source: sarkl tube 36 w x 2
Color temperature: 3200 k
Power: 72 w
Weight: 3 kg
技术参数:
三色色光灯以重质佳, 寿命长, 功耗低, 和准色温, 光线柔和等优点, 广泛应用于各演播室, 会议室, 灯具采用进口铝质铝件反光材料, 光利用率高, 显色指数Ra≥95, 具有较好的色还原性, 能完全满足电视摄像对光源的技术要求, 可选用国产或进口可调光/可调光电子镇流器。
电压: 220v/50Hz
光源: 三基色 36w x 2
色温: 3200K
功率: 72w
重量: 3kg

N-CS554



三基色 55°4
Three colors light lamp 55°4
Technical parameters:
Power: 220 w
Power supply: 220 v / 50 Hz
Color temperature: 3200 K
Weight: 5.2 kg
Specification: 63.5 cmx29cmx11cm
技术参数:
功率: 220 w
电压: 220v/50Hz
色温: 3200K
重量: 5.2kg
规格: 63.5cmx29cmx11cm

N-CY04



四眼灯 4眼
Four eyes audience light
技术参数:
采用灯筒组合设计, 重量轻, 体积小, 造型美观大方, 光斑面积大, 光场均匀, 作为大面积之照明灯具, 广泛应用于歌厅, 舞台, 电视演播厅和大型演唱会等场所。
电压: 220v/50Hz
光源: par35 dwe 120v/650w石英卤钨密封泡
色温: 3200K
功率: 260W
重量: 6kg

N-CZ2500



2500W电子追光灯
2500W Electronic follow spot
Technical parameters:
Working voltage: AC220V/240 50/60 Hz
Power: 2500 w
Light source: HMI2500W
Beam Angle: 15 degrees
The projection distance: 80 m
Size: 1260x470x320mm
27 kg weight
Power supply: 24 kg
技术参数:
工作电压: AC220V/240 50/60Hz
功率: 2800W
光源: HMI2500W
光束角度: 15度
投射距离: 80m
尺寸: 1260x470x320mm
重量: 27kg
电源: 24KG

N-TJ50



50W单轴旋转, 旋转灯
50W Rotation LOGO light
Technical parameters:
Working voltage: AC100-240v 50/60 Hz
Light source: 50W
CT: 3000K
Projection distance: within 8m
Bulb life: 4000 h
Size: 290 x200x100mm
weight: 1.4 kg
技术参数:
工作电压: AC100-240v 50/60 Hz
光源: 50W
色温: 3000K
投射距离: 8m
尺寸: 290 x200x100mm
重量: 1.4kg

N-CS364



三基色 36°4
Three colors light lamp 36°4
Power: 144 w
Power supply: 220 v / 50 Hz
Color temperature: 3200 k
Weight: 4.5 kg
Specification: 62.5 cmx29cmx11cm
技术参数:
功率: 144 w
电压: 220v/50Hz
色温: 3200K
重量: 4.5kg
规格: 62.5cmx29cmx11cm

N-CS364C/ N-CS554C



嵌入式可调角度三基色柔光灯
Embedded tricolor lambyncy lamp adjustable Angle
SP-Q36°4 white box, hole size, 630°295 mm
SP-Q55°4 white box, hole size, 630°295 mm
技术参数:
SP-Q36°4 白色铝框, 开孔尺寸, 500°295mm
SP-Q55°4 白色铝框, 开孔尺寸, 630°295mm

N-CZ1200



1200W机械追光灯
1200W Mechanical follow spot
Technical parameters:
Working voltage: AC220V/240 50/60 Hz
Power: 1500 w
Light source: HMI1200W
Beam Angle: 15 degrees
The projection distance: 80 m
Size: 1400 x440x260mm
Weight: 35 kg
技术参数:
工作电压: AC220V/240 50/60Hz
功率: 1500W
光源: HMI1200W
光束角度: 15度
投射距离: 80m
尺寸: 1400x440x260mm
重量: 35kg
适用场所: 大型舞台, 体育馆, 演唱会, 多功能宴会厅及迪斯可等场所

N-CZ575



575迷你追光灯
Mini follow spot
Technical parameters:
Voltage: 220 v / 50 Hz
Light source: 575 w
Design: wedding day, the little angel, good in one hundred, to choose from, can be customized according to customer's demand
Projection distance: 5-20 meters, 10 meters best effect.
Function: four figure control, adjustable aperture, stroboscopic.
Outsourcing size: 61 cmx30cmx20cm
技术参数:
电压: 220V/50HZ
光源: 575W
造型: 新娘快闪, 小天使, 百年好合等可选, 也可以根据客户的要求定制
投射距离: 5-20米, 10米效果最佳
功能: 四图五色, 光圈可调, 频闪
外包装尺寸: 61cmx30cmx20cm

N-TL10/N-TL30



10W/30W LED LOGO投影机
10W/30W LED LOGO light
Technical parameters:
Working voltage: AC100-240 50/60 Hz
Light source: 10W (CREE)/30W white LED
CT: 6000K
Projection distance: within 5m/10m
Bulb life: 30000 h
Size: 250 x150x140mm
weight: 2 kg
技术参数:
工作电压: AC100-240v 50/60 Hz
光源: 10W(CREE)/30W 白光
色温: 6000K
投射距离: 5m/10M
尺寸: 250 x150x140mm
重量: 2kg

N-CY20



影视冷光源灯
Film and television cold light back into the light
Technical parameters:
Rated voltage: AC220V
Quartz halogen tungsten lamp bulb: 2000 w
Total weight: 7.0 kg
Lens: MENISCUS - 330
The lamp socket: G16
Color of pieces: 356°356
Material: aluminum
技术参数:
额定电压: AC220V
灯管: 2000W石英卤钨灯泡
总重量: 7.0kg
镜片: MENISCUS-330
灯插座: G16
色片夹: 356°356
材质: 铝材

N-CY22



影视聚光灯
The film and television spotlights
Technical parameters:
Rated voltage: AC220V
Light source: 2000 w quartz halogen tungsten lamp
Lamp holder: G16
The highest surface temperature: < 200 ° C
The highest temperature: < 40 ° C
Minimum distance: 0.4 m
Minimum distance: 1.5 m
Net weight: 3.2 kg
Gross weight: 4.2 kg
Size: with 28°28° 37 cm
Packing size: 25.5°25.5°41 cm
技术参数:
色片夹提供多种规格镜片和两种灯座, 灯筒片款式以满足不同的需求, 适用于灯光师, 影棚, 再这款光学镜头使更多的光线汇聚于灯筒射光, 该系列镜头灯设计独特, 操作方便, 维护更方便, 额定电压: AC220V
光源: 1000W/2000W石英卤钨灯泡
灯座: G16
最高表面温度: <200°C
最高温度: <40°C
最小间距: 0.4米
最小间距: 1.5米
净重: 3.2kg
毛重: 4.2kg
内尺寸: 28°28°37cm
外包装尺寸: 25.5°25.5°41cm

N-CY24



高效成像灯
Efficient imaging light
Technical parameters:
Voltage: 220 v / 50 Hz
Light source: 220 v HPL750w G9.5
Color temperature: 3200 k
Beam is adjusted for: 19°
Weight: 5.9 kg
技术参数:
电压: 220v/50Hz
光源: 220v HPL750w G9.5
色温: 3200K
光束调整为: 19°
重量: 5.9kg
该灯亮度均匀, 打出成光柱效果, 小舞台可作追光灯用, 可用于走秀, 酒吧等打光局部区域的效果; 也可会议厅面光用。

N-CD2000



2000W地排灯 2KW On line
Voltage: 220 v / 50 Hz
Double side quartz tungsten halogen light source: 2000 w tube
Color temperature: 3200 k
Power: 2000 w
Weight: 6.5 kg
Double fan cooling
技术参数:
电压: 220v/50Hz
光源: 2000w双端石英卤钨管
色温: 3200K
功率: 2000w
重量: 6.5kg
双风扇散热

N-CY21



影视面光灯
The film back to the light
Technical parameters:
Rated voltage: AC220V
Quartz halogen tungsten lamp bulb: 2000 w
Total weight: 7.0 kg
Lens: MENISCUS - 330
The lamp socket: G16
Color of pieces: 356°356
Material: aluminum
技术参数:
额定电压: AC220V
灯管: 2000W石英卤钨灯泡
总重量: 7.0kg
镜片: MENISCUS-330
灯插座: G16
色片夹: 356°356
材质: 铝材

N-CY23



影视聚光灯 The film and television soft light
Rated voltage: AC220V
Light source: 1000 w / 2000 w quartz halogen tungsten lamp
Lamp holder: G16
The highest surface temperature: < 210 ° C
The highest temperature: < 40 ° C
Minimum distance: 0.4 m
Minimum distance: 1.5 m
Net weight: 3.2 kg
Gross weight: 4.2 kg
Size: with 28°28° 37 cm
Packing size: 25.5°25.5°41 cm
技术参数:
色片夹提供多种规格镜片和两种灯座, 灯筒片款式以满足不同的需求, 适用于灯光师, 影棚, 再这款光学镜头使更多的光线汇聚于灯筒射光, 该系列镜头灯设计独特, 操作方便, 维护更方便, 额定电压: AC220V
光源: 1000W石英卤钨灯泡
灯座: G16
最高表面温度: <210°C
最高温度: <40°C
最小间距: 0.4米
最小间距: 1.5米
净重: 3.2kg
毛重: 4.2kg
内尺寸: 28°28°37cm
外包装尺寸: 25.5°25.5°41cm

N-CY25



变焦成像灯
Zoom imaging light 25 degrees to 50 degrees
Technical parameters:
Rated voltage: AC220V
Light source: HPL575 / HPL750
Lamp holder: G9.5
The highest surface temperature: < 200 ° C
The highest temperature: < 40 ° C
Minimum distance: 0.4 m
Minimum distance: 1.5 m
Net weight: 8.5 kg gross weight: 10 kg
Size: 78°24°24 cm
Packing size: 86°30.5°28 cm
Focusing range: 25 to 50 degrees
技术参数:
额定电压: AC220V
光源: HPL575/HPL750
灯座: G9.5
最高表面温度: <200°C
最高温度: <40°C
最小间距: 0.4米
最小间距: 1.5米
净重: 8.5kg 毛重: 10kg
内尺寸: 78°24°24cm
包装尺寸: 86°30.5°28cm
调焦范围: 25-50度

N-CT2000



2000W天排灯 2kW Day discharge lamp
Voltage: 220 v / 50 Hz
Double side quartz tungsten halogen light source: 2000 w tube
Color temperature: 3200 k
Power: 2000 w
Weight: 6.5 kg
Double fan cooling
技术参数:
电压: 220v/50Hz
光源: 2000w双端石英卤钨管
色温: 3200K
功率: 2000w
重量: 6.5kg
双风扇散热

AB-1500



Power: 1500W
Voltage: AC110V,220-250V 50/60Hz
Heat-up Time: 12 minutes
Tank capacity: 2L
Approx. Fog Projection: 12 M
Output: 20000cu.ft/min
Control mode: Circuitry Control,
Remote Control
Weight: 7.4KG
Size: 46.5*22.5*19.5(cm)
功率: 1500W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 12分钟
油桶容量: 2L
喷油距离: 12米
喷油量: 20000cu.ft/min
控制模式: 线控、遥控
重量: 7.44KG
尺寸: 46.5*22.5*19.5(cm)

F-3000R



Power: 3000W
Voltage: AC110V,220-250V 50-60Hz
Heat-up Time: 12 minutes
Tank capacity: 10L
Output: 43000cu.ft/min
Control mode: DMX512,Manual
Controler,
Remote Control
Weight: 20KG
Size: 72*31*18(cm)
功率: 3000W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 12分钟
油桶容量: 10L
喷油量: 43000cu.ft/min
控制模式: DMX512, 线控、遥控
重量: 20KG
尺寸: 72*31*18(cm)

S-1200



Power: 1200W
Voltage: AC110V,220-250V 50/60Hz
Tank capacity: 5L
Output: 60 Cubic Meters
Control mode: DMX512,Circuitry Control,
Remote Control
Weight: 11KG
Size: 51.5*31*23(cm)
功率: 1200W
工作电压: AC110V,220-250V 50/60Hz
油桶容量: 5L
喷油量: 60 Cubic Meters
控制模式: DMX512, 线控、遥控
重量: 11KG
尺寸: 51.5*31*23(cm)

Z-800



Power: 900W
Voltage: AC110V,220-250V 50/60Hz
Heat-up Time: 7 minutes
Tank capacity: 1L
Output: 5000cu.ft/min
Control mode: Circuitry Control
Weight: 4KG
Size: 33*17*14(cm)
功率: 900W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 7分钟
油桶容量: 1L
喷油量: 5000cu.ft/min
控制模式: 线控
重量: 4KG
尺寸: 33*17*14(cm)

AB-1200



Power: 1200W
Voltage: AC110V, 220-250V 50/60Hz
Heat-up Time: 8 minutes
Tank capacity: 2L
Approx. Fog Projection: 10 M
Output: 18000cu.ft/min
Control mode: Circuitry Control,
Remote Control
Weight: 6.8KG
Size: 49.5*23*14(cm)
功率: 1200W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 8分钟
油桶容量: 2L
喷油距离: 10米
喷油量: 18000cu.ft/min
控制模式: 线控、遥控
重量: 6.8KG
尺寸: 49.5*23*14(cm)

AB-900



Power: 900W
Voltage: AC110V,220-250V 50/60Hz
Heat-up Time: 8 minutes
Tank capacity: 1L
Approx. Fog Projection: 8 M
Output: 5000cu.ft/min
Control mode: Circuitry Control,
Remote Control
Weight: 4.6KG
Size: 33.5*19*14(cm)
功率: 900W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 8分钟
油桶容量: 1L
喷油距离: 8米
喷油量: 5000cu.ft/min
控制模式: 线控、遥控
重量: 4.6KG
尺寸: 33.5*19*14(cm)

T-400



Power: 400W
Voltage: AC110V,220-250V 50/60Hz
Heat up Time: 8 minutes
Tank capacity: 0.3L
Output: 2000cu.ft/min
Control mode: Circuitry Control
Weight: 2.5 KG
Size: 23*11*11(cm)
功率: 400W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 8分钟
油桶容量: 0.3L
喷油距离: 8米
喷油量: 2000cu.ft/min
控制模式: 线控
重量: 2.5KG
尺寸: 23*11*11(cm)

B-300



Power: 300W
Voltage: AC110V,220-250V 50/60Hz
Bubble Oil Container: 2.5L
Blowing Height: 10 M
Output: 600 cubic meters
Control mode: Remote Control
Weight: 14KG
Size: 45*39*41(cm)
功率: 300W
工作电压: AC110V,220-250V 50/60Hz
油桶容量: 2.5L
喷油距离: 10米
喷油量: 600 cubic meters
控制模式: 线控
重量: 14KG
尺寸: 45*39*41(cm)

新感觉灯光

—— 酒吧、KTV全线灯光供应商



广州新感觉灯光音响设备有限公司是一家集科研、生产、销售、工程服务为一体的科技型专业灯光民营企业。本公司聚集了一批光电科技研发精英和经验丰富、技术精湛的专业生产施工人员，精雕细琢后推出了品种繁多、质量上乘的智能化舞台灯光系列产品。目前主要产品包括了摇头灯系列，激光灯系列、LED PAR灯系列、LED效果灯系列、频闪灯系列等等，涵盖了酒吧、KTV使用的全线灯光产品。

卓越的品质和优良的服务为我们赢得了广阔的市场空间，也使我们的产品倍受国内外用户的青睐；目前我们已经和欧亚、南北美洲等多个国家和地区建立了代理、经销等多种形式的合作关系，而在国内各地的舞台灯光工程、市政工程、地标建筑、主题公园、舞厅、俱乐部、电视台、歌剧院及大型演出等场所，我们的产品也得到了广泛的应用。

以精品缔造行业传奇，以品质树立诚信品牌，以服务感动所有客户，新感觉愿与您携手并进，共同打造灯光世界的绚丽辉煌！

Guangzhou New Feel Lighting & Audio Equipment CO. LTD is a researching, producing, selling and professional privately-owned manufacturer. We gathered a group of experienced photoelectric R & D elites and skilled producing technicians. We are professional supplier specializing in all range of lighting for bars and KTV, now our main products including moving head series, laser series, LED PAR light series, LED effect series and strobe light etc.

With superior quality and excellent service has made us owned a board marketing space and enabled our products highly appreciated both at home and abroad. At present we established agents, distributions and many other kinds of cooperating relationship with Europe and Asia, North and South Americas and so on. Our products have widely used in our own country, such as stage lighting engineering, municipal works, land mark building, theme park, dance hall, club, opera house, big show and other entertainment venues.

Well-made goods make industrial legend, quality entrusted brand, superior service inspire customer. In order to be remarkable in lighting field, New Feel is looking forward to working with you.



封二

配件系列 Accessories Series

保险绳 / Safety rope



灯架 / Stand



灯钩 / Lighthook



玻璃球 / Glass Ball Light

色片 / Color Filter (1x40m)



航空箱 / Fly Box



光源

Lamp With Different Measurement



封三



酒吧、KTV全线灯光供应商
Professional supplier specializing in
all range of lighting for bars and KTV

新感觉实业发展有限公司
NEW FEEL INDUSTRIAL DEVELOPMENT LIMITED

广州新感觉灯光音响设备有限公司
GUANGZHOU NEW FEEL LIGHTING AND AUDIO EQUIPMENTS CO.,LTD.

地址：广州白云区石井镇榕溪榕茵路35号榕茵工业园B栋2楼

Add: 2/F, Rongxi Industry Zone, No.35, Rongyin Road, Shijing Town,
Baiyun District, Guangzhou, China.

Tel: +86 20-36393166 36396409

Http://www.newfeellight.com

E-mail: info@newfeellight.com



酒吧、KTV全线灯光供应商
Professional supplier specializing in
all range of lighting for bars and KTV



2014-2015 Catalogue

封底

封面