



N-B280

280W Moving head Beam Light

Technical Parameters:

power supply: AC 100-240 V 50/60Hz
Power Consumption: 400W
Lamp: 280W
Color temperature: 7500K
Average Lifespan: 2000H
Color: 13 color + blank color wheel
Gobo: 14 fixed gobo + blank gobo + 9
Rotation gobo + blank gobo
Prism: 6-facet linear prism + 8-facet
circular prism, Bilateral rotation
Lens: high precision optical lens
Focus: linear adjustment
Dimmer: 0-100% linear adjustment
Pan/Tilt: X axis 540° Y axis 270°, 16 bit precision scan
Strobe: Double lens strobe (0.5-9 times/second)
Control mode: Standard DMX512, Automatic and
Master/ slave mode
Channel: 16/24 CH

三合一摇头光束灯 280W

技术参数:

输入电压: AC100-240V, 50/60Hz
额定功率: 400W 光源: 280W灯泡
色温: 7500K
光源使用寿命: 2,000 小时
色盘: 13个颜色+空白
图案盘: 1个固定图案盘 (14个图案+白光)
1个旋转图案盘 (9个图案+空白)
棱镜: 1个可旋转八棱镜 1个可旋转一字
六棱镜
光学部分: 高精度光学组合
染色效果: 可调整染色效果
调光: 0-100%线性调光
X轴/Y轴: X轴 540° Y轴 270°, 16bit精调
频闪: 双透镜频闪 (0.5-9次每秒)
控制模式: DMX512国际标准信号,
自走模式, 主从模式
通道数量: 16和24个通道可选

N-B200/N-B230

200W/230W Moving head Beam Light

200W/230W摇头光束灯

Technical Parameters:

power supply: AC 100-240 V 50/60Hz
Lamp: 200W/230W
Average Lifespan: 2000H
Color: 14 color + blank color wheel
Gobo: 17 fixed gobo + blank gobo
Prism: rotation 8-face prism, Bilateral rotation
Lens: high precision optical lens
Focus: linear adjustment
Dimmer: 0-100% linear adjustment
Pan/Tilt: X axis 540° Y axis 270°,
16 bit precision scan
Beam angle: parallel beam angle 0-3.8°
Strobe: Double lens strobe (0.5-9 times/second)
Control mode: Standard DMX512, Automatic
and Master/ slave mode
Channel: 16/20 CHS

技术参数:

电源供应: AC100V-240V/50-60Hz,
功率: 200W/230W
光源: 200W/230W
光源寿命: 2000小时
颜色: 14个色盘带有14种颜色+空白
图案: 1个图案盘带有17个固定图案
棱镜: 旋转八面棱镜, 可双向旋转
镜头: 高精度混合光学镜头
调焦: 线性调焦
调光: 0-100%线性调光
投射光范围: 水平540°, 解析度16Bit,
垂直270°, 解析度16Bit
光束角度: 平行光束角: 0-3.8°
频闪: 双片式频闪 (0.5-9次/秒)
控制模式: DMX512/自走/声控
通道数量: 16通道/20通道两种通道模式



N-B132

132W Moving head Beam Light

Technical Parameters:

power supply: AC 100-240 V 50/60Hz
Lamp: 132W (Philips 2R or OSRAM 2R or JSCN 2R)
Average Lifespan: 2000H
Color: 14 color + blank color wheel
Gobo: 17 fixed gobo + blank gobo
Prism: rotation 8-face prism, Bilateral rotation
Dimmer: 0-100% linear adjustment
Control mode: Standard DMX512, Automatic and
Master/ slave mode
Channel: 16/20 CH
Features: Remote control lamp's switch function, display light
and lamp's using time, Automatically adjust cooling-fan's speed,
50% energy saving when strobe lens shu
技术参数:
电源供应: AC100V-240V/50-60Hz,
功率: 200W
光源: 132W (Philips 2R or OSRAM 2R or 森莱浦 2R)
光源寿命: 2000小时
颜色: 14个色盘带有14种颜色+空白
图案: 1个图案盘带有17个固定图案+空白
棱镜: 旋转八面棱镜, 可双向旋转
调光: 0-100%线性调光
控制模式: DMX512/自走/声控
通道数量: 16通道/20通道 两种通道模式选择
其它功能: 远程控制灯泡开关功能, 显示灯具, 灯泡使
用时间, 风机自动调速功能, 机械闪光灯时自动降低50%
光源功率, 采用光电复位系统, 当偶然发生误动后, 可
自动检索复位

N-BL130

130W beam pattern laser 3 in 1 scanner spot light 酒吧王子 (三合一光束扫描灯)


Technical Parameters:

power supply: AC 100-240V, 50/60Hz
Power: 300W
Lamp: 130W (2R)
Average Lifespan: 2000H
Color: 14 color + blank color wheel
Gobo: 17 fixed gobo + blank gobo
Prism: rotation 3-face prism, Bilateral rotation
Lens: high precision optical lens
Dimmer: 0-100% linear adjustment
Pan/Tilt: X axis 120° Y axis 90°
Control mode: Standard DMX512, Automatic and
Master/ slave mode
Channel: 17/21 CH

技术参数:

电源供应: AC100-240V/50-60Hz
功率: 300W
光源: 130W(2R)
光源寿命: 2000小时
颜色: 14个色盘带有14种颜色+空白
图案: 1个图案盘带有17个固定图案+空白
棱镜: 旋转三棱镜, 可双向旋转
镜头: 高精度混合光学镜头
调光: 0-100%线性调光
投射光范围: 水平120°, 垂直90°
控制模式: DMX512/自走/声控/主从
通道数量: 17通道/21通道 两种通道模式选择
功能特点: 本产品集光束, 图案, 激光三种效果于一身, 体积小,
功能强大, 质量稳定, 必将成为酒吧今年最热门的产品。





N-Y004/Y004A

7/12pcs 4 in 1 MINI Moving head LED Beam Light
7/12颗4合一迷你LED摇头光束灯

Technical Parameters: 技术参数:

Power supply: AC100~240V, 50/60Hz
Power Consumption: 150W
Light Source: 7/12 pcs 10W (USA Cree RGBW 4 in 1) LED
Control mode: DMX-512, music control, automatic, master & slave
Level Scanning: 540° (16 bit precision scan)
Vertical Scan: 270° (16 bit precision scan)
Beam angle: 13.5°
Product Size: 33X24.5X38.5cm
Gross Weight: 5kg

电源供应: AC100~240V, 50/60Hz
额定功率: 150W
光源: 7/12颗10W (美国科锐 RGBW 4 in 1) LED, 专用光学透镜, 高强度聚光
控制模式: 512信号控制, 自走, 声控模式, 主从, 水平扫描: 540° (16 bit精度扫描)
垂直扫描: 270° (16 bit精度扫描)
频闪: 高速电子调节频闪可达1-25次/秒或随机频闪
光束角度: 13.5°
产品尺寸: 33X24.5X38.5cm
净重: 5KG

N-Y003

36pcs 3W MINI Moving head LED Beam Light
36颗3W迷你LED摇头光束灯

Technical Parameters: 技术参数:

Power supply: AC100~240V, 50/60Hz
Power Consumption: 150W
Light Source: 36 pcs 3W LED
Control mode: DMX-512, music control, automatic, master & slave
Level Scanning: 540° (16 bit precision scan)
Vertical Scan: 270° (16 bit precision scan)
Beam angle: 13.5°
Product Size: 33X24.5X38.5cm
Gross Weight: 5kg

电源供应: AC100~240V, 50/60Hz
额定功率: 150W
光源: 36颗3W LED, 专用光学透镜, 高强度聚光
控制模式: 512信号控制, 自走, 声控模式, 主从, 水平扫描: 540° (16 bit精度扫描)
垂直扫描: 270° (16 bit精度扫描)
频闪: 高速电子调节频闪可达1-25次/秒或随机频闪
光束角度: 13.5°
产品尺寸: 33X24.5X38.5cm
净重: 5KG



N-Y001

108 pcs LED Moving Head Light
108颗LED摇头灯

Technical Parameters: 技术参数:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 400W
Light Source: High power 3W LED, 108 pcs of leds: 30Red, 30 Green, 30 Blue, 18 White
Beam angle: 15°, 25°, 45° (optional)
Color: 16.7 million for RGBW
Control mode: DMX-512, music control, automatic, master & slave
Channel: 16/12 channels
Level Scanning: 630° (16 bit precision scan)
Vertical Scan: 270° (16 bit precision scan)
电源供应: AC90~240V, 50Hz~60Hz
功率: 400W
光源: 108颗3W高功率LED (红色30颗, 绿色30颗, 蓝色30颗, 白色18颗)
发光角度: 15°, 25°, 45°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制, 声控, 自走, 主从
控制通道: 16/12通道
水平扫描: 630度
垂直扫描: 270度



N-Y002

36pcs 10W LED Zoom Moving head Light
36颗10W全彩4合1 LED调焦摇头灯

Technical Parameters: 技术参数:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 400W
Light Source: 36 pcs 10W RGBW 4 in 1 LED
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave
Channel: 16/12 channels
Lamp life: 50,000 hours lifetime
Pan: 630 degree
Tilt: 270 degree
Zoom: 15~60
Outer cover material: Aluminum body
电源供应: AC90~240V, 50Hz~60Hz
功率: 400W
光源: 36颗10W全彩4合1灯珠
颜色: 1670万颜色变化
控制方式: DMX-512信号控制, 声控, 自走, 主从
控制通道: 16/12通道
水平扫描: 630度
垂直扫描: 270度
调焦角度: 15~60度





N-Y019

19*12W Beam moving head

19颗12W调焦光束摇头灯

Technical Parameters:

Power supply: AC100~240V,50/60Hz

Power Consumption: 260 w

Light Source: 19 pcs 12W RGBW LED

Channel: 16channels

Level Scanning: 540° (16 bit precision scan)

Vertical Scan: 270° (16 bit precision scan)

color: RGBW full color

Control mode: DMX-512, automatic, master & slave

Fuction: small, fast, with the function of ZOOM.

Size: 325X188X396 mm

Weight: 9.2 Kg

Focusing Angle: 5-60

技术参数:

电源供应: AC100~240V,50/60Hz

额定功率: 260W

光源: 19颗12W RGBW 四合一 LED

控制通道: 16

水平扫描: 540° (16 bit精度扫描)

垂直扫描: 270° (16 bit精度扫描)

颜色: RGBW 全彩色

控制模式: 512信号控制, 自走模式, 主从,

功能: 超小, 速度快, 功能强大的LED

摇头光束, 带调焦功能

产品尺寸: 25X188X396 mm

净重: 9.2KG

调焦角度: 5-60度

N-BL012

LED infinite Beam light LED无限光束灯

Technical Parameters

Voltage: AC100-240V 50-60Hz

Power: 145w

Source: 12pcs 10W CREE 4-in-1 LEDs

Control Mode: DMX-512, music control, automatic, master & slave

Strobe: 1-25Hz

Dimming: 1-100% linear dimming

Gobo: 25 different gobos

Pan/Tilt: X axis 540° Y axis 200°, 16 bit precision scan

Function: 1.New seven color beam with flower effect and many

amazing effect.

2. Three lamps as a section controllable.

3. The Lens inside can rotate without limitation.

packing size (L x W x H) : 330 x 260 x 460 mm

G.W: 6.5 G

技术参数:

工作电压: AC100-240V 50-60Hz

耗电功率: 145w

光源: 12颗CREE 4合一, RGBW

控制模式: DMX512/自走/声控

调光: 线性调光

投射范围: 水平540°, 解析度16bit, 垂直200°, 解析度16bit

功能: 全新的无极光束、开花、多种梦幻效果功能。

无信号时灯具会慢自走

包装尺寸: 330*260*460mm (1台装)

毛重: 6.5KG

摇头灯系列

Moving head Light Series



N-Y030/ N-Y030A/ N-Y030B

Two-Sided LED Moving Light

双面无极摇头灯

Technical Parameters:

Power supply: AC100-240V,50/60Hz

Power Consumption: 70w

Light Source: 1pcs 10W (Cree RGBW 4 in 1)+4 pcs 10W (RGBW 4 in 1) LED

4 pcs 10W (Cree RGBW 4 in 1)+1 pcs 10W (Cree RGBW 4 in 1) LED

4 pcs 10W (RGBW 4 in 1) LED+4 pcs 10W (RGBW 4 in 1) LED

Stroboscopic: 1-25 times per second

Level Scanning: 540°

Vertical Scanning: Infinite rotation

color: RGBW full color

Control mode: DMX-512, music control, automatic, master & slave

Fouction: one face with beam effect and another face with wash effect, or Two-

Sided beam effect, or Two-Sided wash effect

技术参数:

输入电压: AC100-240V,50Hz-60Hz

最大功率: 60W

光源: 1颗RGBW (4in1) 10W 科瑞灯珠+4颗RGBW (4in1) 10W灯珠

1颗RGBW (4in1) 10W 科瑞灯珠+1颗RGBW (4in1) 10W 科瑞灯珠

4颗RGBW (4in1) 10W灯珠+4颗RGBW (4in1) 10W灯珠

频闪: 1-25次/秒

水平扫描: 540°

垂直扫描: 无极旋转

颜色: RGBW混色

控制: 自走、声控、主从、DMX512

功能: 一面光束一面染色或双面光束或双面染色

N-Y017

1 head RGBW /White LED Moving Beam Light

单头RGBW七彩 /白光LED 摇头光束

Technical Parameters:

Power supply: AC100-240V,50/60Hz

Power Consumption: 30 w

Light Source: 1 pcs 10W (cree RGBW

4 in 1 or white) LED

Channel: 13 or 11 channels /White 9/7 channels

Level Scanning: 540° (16 bit precision scan)

Vertical Scan: 270° (16 bit precision scan)

color: RGBW 7 color or White

Control mode: DMX-512, music control,

automatic, master & slave

技术参数:

输入电压: AC100-240V,50Hz-60Hz

最大功率: 30W

光源: 1颗10W高亮度白光/科瑞四合一全彩

通道: 13或11通道/白色9或7通道

水平扫描: 540°+微调

垂直扫描: 270°+微调

颜色: 七彩色或白色

控制: 自走、声控、主从机、DMX512

N-Y018

4 head RGBW LED Scanning Beam Light

4头RGBW七彩LED扫描光束灯

Technical Parameters:

Power supply: AC100-240V,50/60Hz

Power Consumption: 80 w

Light Source: 4 pcs 10W (cree RGBW 4 in 1) LED

Level Scanning: 120°

Vertical Scan: 120°

color: RGBW 7 color

Control mode: DMX-512, music control,

automatic, master & slave

技术参数:

输入电压: AC100-240V,50Hz-60Hz

最大功率: 80W

光源: 4颗 科瑞 四合一全彩

水平扫描: 120°

垂直扫描: 120°

颜色: 七彩色

控制: 自走、声控、主从机、DMX512

N-Y006/N-Y005

8 head RGBW/White LED Moving Beam Light
8头RGBW/白光 LED 摇头光束

Technical Parameters:

技术参数:

Power supply: AC100-240V, 50/60Hz

Power Consumption: 120W

Light Source: 8 pcs 10W (USA cree RGBW4 in 1)
8 pcs 10W White LED

Control mode: DMX-512, music control,
automatic, master & slave

Vertical Scan: 270°

Color: RGBW 4 color/white

Control Channel: 10 or 38/5 or 14

Packing size(L x W x H): 1150x160x250mm /PCS

Gross Weight: 8 kg

电源供应: AC100-240V, 50/60Hz

额定功率: 120W

光源: 8颗10W (科瑞 RGBW 4 in 1)
8颗10W 白光LED

控制模式: 512信号控制, 自走, 声控模式, 主从

垂直扫描: 270°

颜色: 红绿蓝白四色/白色

控制通道: 10或38/5或14通道控制模式

两种通道控制模式

包装尺寸: 1150x160x250mm

毛重: 8KG

N-Y026/N-Y026B

Spider Beam RGBW (White) LED Moving Light

全彩/白光LED 蜘蛛灯

Technical Parameters:

Power supply: AC100-240V, 50/60Hz

Power Consumption: 110 w

Light Source: 8 pcs 10W (cree RGBW 4 in 1 or
white) LED

Channel: 11 or 37 channels/White 7 or 13
channels

Stroboscopic: 1-25 times per second

Level Scanning: 540° (16 bit precision scan)

Vertical Scan: 185° (16 bit precision scan)

Smooth linear dimming: 0-100% dimmer

color: RGBW 7 color or White

Control mode: DMX-512, music control, automatic,
master & slave

技术参数:

输入电压: AC100-240V, 50Hz-60Hz

最大功率: 110W

光源: 8颗10W科瑞四合一全彩/白光LED灯珠

通道: 11通道或37通道/白色7通道或13通道

频闪: 1-25次/秒

水平扫描: 540° +微调

垂直扫描: 185° +微调

调光: 0-100%平滑线性调光

颜色: 七彩色或白色

控制: 自走、声控、主从、DMX512

功能: 本产品光束效果很好, 每个灯珠可单独控制, 具有光束跑马、跳频、频闪、旋转等多种效果, 投射范围极大。

N-Y025/N-Y025B

Spider Beam RGBW (White) LED Light

全彩/白光LED 蜘蛛灯

Technical Parameters:

Power supply: AC100-240V, 50/60Hz

Power Consumption: 110 w

Light Source: 8 pcs 10W (cree RGBW 4 in 1 or
white) LED

Channel: 10 or 36 channels/White 6 or 12
channels

Stroboscopic: 1-25 times per second

Vertical Scan: 185° (16 bit precision scan)

Smooth linear dimming: 0-100% dimmer

color: RGBW 7 color or White

Control mode: DMX-512, music control, automatic,
master & slave

技术参数:

输入电压: AC100-240V, 50Hz-60Hz

最大功率: 110W

光源: 8颗10W科瑞四合一全彩/白光LED灯珠

通道: 10通道或36通道/白色6通道或12通道

频闪: 1-25次/秒

垂直扫描: 185° +微调

调光: 0-100%平滑线性调光

颜色: 七彩色或白色

控制: 自走、声控、主从、DMX512

功能: 本产品光束效果很好, 每个灯珠可单独控制, 具有光束跑马、跳频、频闪、旋转等多种效果, 投射范围极大。

N-Y028/N-Y028B

40W/60W LED Patten Moving head Light
Technical Parameters:

power supply: AC 100-240V 50/60Hz

Power Consumption: 90W

Light Source: 40W/60W LED

Color: 11 colors + white color

Gobo: 10 design + white + rainbow effect

Prism: rotation 3-face prism, Bilateral rotation

Focus: linear adjustment

Dimmer: 0-100% linear adjustment

Pan/Tilt: X axis 540°, Y axis 270°

Strobe: 0-20HZ

Control mode: DMX512, Automatic and Master/

slave mode

40W/60W LED摇头图案灯
技术参数:

电源供应: AC100-240V/50-60Hz,

功率: 90W

光源: 40W/60W LED

颜色: 11种颜色+白光

图案盘: 10图案+白光+彩虹效果

棱镜: 旋转三棱镜, 可双向旋转

调焦: 线性调焦

调光: 0-100%线性调节

投射光范围: 水平540°, 垂直270°

频闪: 0-20HZ

控制模式: DMX512/自走/声控

N-Y021

10W LED MINI Patten Moving head Light
Technical Parameters:

Power supply: AC 100-240 V 50/60Hz

Power Consumption: 40W

Light Source: 10W LED

Color: 7 colors + white color

Gobo: 7 design + white + rainbow effect

Focus: Manual focusing

Dimmer: 0-100% linear adjustment

Pan/Tilt: X axis 540°, Y axis 270°

Strobe: 0-20HZ

Control mode: DMX512

Automatic and Master/ slave mode

Channel: 7/12 CHS

LED MINI摇头图案灯 10W
技术参数:

电源供应: AC100-240V/50-60Hz,

功率: 40W

光源: 10W LED

颜色: 7种颜色+白光

图案盘: 7图案+白光+彩虹效果

调焦: 手动调焦

调光: 0-100%线性调节

投射光范围: 水平540°, 垂直270°

频闪: 0-20HZ

控制模式: DMX512/自走/声控

通道数量: 7和12 通道两种模式

N-Y027

7 pcs RGBW(4 in 1) LED Moving Light Technical Parameters:

Technical Parameters:

Power supply: AC100-240V,50/60Hz

Power Consumption: 100W

Light Source: 7 pcs 10W (RGBW 4 in 1) LED

Channel: 9 or 14 channels

Stroboscopic: 1-25 times per second

Level Scanning: 540° (16 bit precision scan)

Vertical Scan: 180° (16 bit precision scan)

Smooth linear dimming: 0-100% dimmer

color: RGBW full color

Control mode: DMX-512, music control,
automatic, master & slave

7颗RGBW四合一LED摇头染色灯 技术参数:

输入电压: AC100-240V,50Hz-60Hz

最大功率: 100W

光源: 7颗10W RGBW四合一全彩LED灯珠

通道: 9通道或14通道

频闪: 1-25次/秒

水平扫描: 540°+微调

垂直扫描: 180°+微调

调光: 0-100%平滑线性调光

颜色: RGBW混色

控制: 自走、声控、主从、DMX512

N-Y029

4 pcs RGBW(4in1) LED Moving Light Technical Parameters:

Technical Parameters:

Power supply: AC100-240V,50/60Hz

Power Consumption: 60W

Light Source: 4 pcs 10W (RGBW 4 in 1) LED

Stroboscopic: 1-25 times per second

Level Scanning: 540° (16 bit precision scan)

Smooth linear dimming: 0-100% dimmer

color: RGBW full color

Control mode: DMX-512, music control,
automatic, master & slave

4颗RGBW全彩泡泡摇头灯 技术参数:

输入电压: AC100-240V,50Hz-60Hz

最大功率: 60W

光源: 4颗10W RGBW四合一全彩LED

灯珠频闪: 1-25次/秒

水平扫描: 540°+微调

调光: 0-100%平滑线性调光

颜色: RGBW混色

控制: 自走、声控、主从、DMX512

摇头灯系列 Moving head Light Series

N-Y015/N-Y007

150W/120W LED Pattern Moving head Light Technical Parameters:

power supply: AC 100-240 V 50/60Hz

Power Consumption: 240W

Light Source: German BUTTERFLY 1" 150 w white LED
120W (USA Luminus) LED

Color: 7 colors + white color + rainbow effect

Rotating Gobo: 7 Gobo (interchangeable), Gobo-flow effect, Gobo shake

Static gobo: 9 Gobo, Gobo-flow effect, Gobo shake

Prism: rotation 3-face prism, Bilateral rotation

Focus: linear adjustment

Dimmer: 0-100% linear adjustment

Pan/Tilt: X axis 540° Y axis 270°, 16 bit precision scan

Strobe: 0-20Hz

Control mode: Standard DMX512, Automatic and Master/ slave mode

Channel: 16/17 CHS

packing size (L x W x H): 490x370x375mm

G.W: 15KG

150W/120W LED 摇头图案灯 技术参数:

电源供应: AC100V-240V/50-60Hz,

功率: 240W

光源: 150W(德国BUTTERFLY)
120W(美国Luminus) LED

颜色: 7种颜色+白光+彩虹效果

旋转图案盘: 7个图案, 图案流水效果, 抖动效果

静态图案盘: 9个图案, 图案流水效果, 抖动效果

棱镜: 旋转三棱镜, 可双向旋转

调焦: 线性调焦

调光: 0-100%线性调光

投射光范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit

频闪: 0-20Hz

控制模式: DMX512/自走/主从

通道数量: 16/17通道

包装尺寸: 490x370x375mm

毛重: 15KG

N-Y010

90W LED pattern Moving head Light Technical Parameters:

power supply: AC 100-240 V 50/60Hz

Power Consumption: 150W

Light Source: 90W LED

Color: 7 colors + white color + rainbow effect

Rotating Gobo: rotation pattern 2 glass + 5 metal pattern

Static gobo: 9 Gobo, Gobo-flow effect, Gobo shake

Prism: rotation 3-face prism, Bilateral rotation

Digital zoom 15°, 28°

Dimmer: 0-100% linear adjustment

Pan/Tilt: X axis 540° Y axis 270°, 16 bit precision scan

Strobe: 0-20Hz

Control mode: Standard DMX512, Automatic and Master/ slave mode

Channel: 11/14 CHS

packing size (L x W x H): 295 x 290 x 515 mm

G.W: 14.8KG

90W LED 摇头图案灯 技术参数:

电源供应: AC100V-240V/50-60Hz,

功率: 150W

光源: 90W LED

颜色: 7种颜色+白光+彩虹效果

旋转图案盘: 2个玻璃图案+5个金属图案(可互换)

静态图案盘: 9个图案, 图案流水效果, 抖动效果

棱镜: 旋转三棱镜, 可双向旋转

电子变焦: 15°, 28°

调光: 0-100%线性调光

投射范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit

频闪: 0-20Hz

控制模式: DMX512/自走/声控

通道数量: 11通道/14通道 两种通道模式选择

尺寸: 295 x 290 x 515mm

毛重: 14.8KG

N-Y008

60W LED pattern Moving head Light Technical Parameters:

power supply: AC 100-240 V 50/60Hz

Power Consumption: 150W

Light Source: 60W (USA Luminus) LED

Color: 7 colors + white color + rainbow effect

Rotating Gobo: 7 Gobo (interchangeable), Gobo-flow effect, Gobo shake

Static gobo: 9 Gobo, Gobo-flow effect, Gobo shake

Prism: rotation 3-face prism, Bilateral rotation

Focus: linear adjustment

Dimmer: 0-100% linear adjustment

Pan/Tilt: X axis 540° Y axis 270°, 16 bit precision scan

Strobe: 0-20Hz

Control mode: Standard DMX512, Automatic and Master/ slave mode

Channel: 11/14 CHS

packing dimensions (L x W x H): 520x380x350mm

G.W: 16KG

60W LED 摇头图案灯 技术参数:

电源供应: AC100V-240V/50-60Hz,

功率: 150W

光源: 60W(美国Luminus) LED

颜色: 7种颜色+白光+彩虹效果

旋转图案盘: 7个图案, 图案流水效果, 抖动效果

静态图案盘: 9个图案, 图案流水效果, 抖动效果

棱镜: 旋转三棱镜, 可双向旋转

调焦: 线性调焦

调光: 0-100%线性调光

投射光范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit

频闪: 0-20Hz

控制模式: DMX512/自走/主从

通道数量: 11通道/14通道 两种通道模式选择

包装尺寸: 520x380x350mm

毛重: 16KG



N-Y011/N-Y009

60W/30W LED pattern Moving head Light

Technical Parameters:

power supply: AC 100-240 V 50/60Hz
Power Consumption: 80W
Light Source: 60W/30W LED
Color: 7 colors + white color
Rotating Gobo: 7 Gobo (interchangeable),
Focus: Manual focusing
Dimmer: 0-100% linear adjustment
Pan/Tilt: X axis 540°, Y axis 270°, 16 bit precision scan
Strobe: 0-20Hz
Control mode: DMX512, Automatic and Master/slave mode
Channel: 10CHS
packing dimensions(L x W x H): 350×350×440mm
G.W: 11KG

60W/30W LED 摇头图案灯

技术参数:

电源供应: AC100V~240V/50~60Hz,
功率: 80W
光源: 60W/30W LED
颜色: 7种颜色+白光
旋转图案盘: 7个图案, 图案轮可双向旋转
调焦: 手动调焦
调光: 0-100%线性调节
投射范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit
频闪: 0-20Hz
控制模式: DMX512/自走/主从
通道数量: 10通道
包装尺寸: 350×350×440mm
毛重: 11KG



N-Y012

30W LED MINI Patten Moving head Light

Technical Parameters:

power supply: AC 100-240 V 50/60Hz
Power Consumption: 60W
Light Source: 30W LED
Color: 9 colors + white color
Rotating Gobo: 7 kinds of replacing rotating design + white light
Focus: Manual focusing
Dimmer: 0-100% linear adjustment
Pan/Tilt: X axis 540°, Y axis 270°, 16 bit precision scan
Strobe: 0-20Hz
Prism: prism function
Control mode: DMX512, Automatic and Master/slave mode
Channel: 11/12CHS
packing size(L x W x H): 420×340×280mm
G.W: 7.5 KG

30W LED MINI 摇头图案灯

技术参数:

电源供应: AC100V~240V/50~60Hz,
功率: 60W
光源: 30W LED
颜色: 9种颜色+白光
旋转图案盘: 7种可更换旋转图案片+白光, 图案轮可双向旋转
调焦: 手动调焦
调光: 0-100%线性调节
投射范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit
频闪: 0-20Hz
棱镜: 3棱镜
控制模式: DMX512/自走/声控
通道数量: 11/12通道
包装尺寸: 420×340×280mm
毛重: 7.5KG



N-Y013

15W LED Mini Pattern Moving head Light

Technical Parameters:

power supply: AC 100-240 V 50/60Hz
Power Consumption: 30W
Light Source: 15W LED
Color: 7 colors + white color
Gobo: 9 design + white + rainbow effect
Focus: Manual focusing
Dimmer: 0-100% linear adjustment
Pan/Tilt: X axis 540°, Y axis 270°, 16 bit precision scan
Control mode: DMX512, Automatic and Master/slave mode
Channel: 13CHS
Special features: built-in a variety of lighting applications, but acoustic synchronous running out of control

15W LED 迷你摇头图案灯

技术参数:

电源供应: AC100V~240V/50~60Hz,
功率: 30W
光源: 15W LED
颜色: 7种颜色+白光
图案: 9个图案 + 白光 + 彩虹效果
调焦: 手动调焦
调光: 0-100%线性调节
投射范围: 水平540°, 解析度16Bit, 垂直270°, 解析度16Bit
控制模式: DMX512/自走/声控
通道数量: 13通道
功能: 内置多种灯光效果程序, 可脱离控台声控同步运行



FY-666/ FY-632

Spider Laser Beam RGB (Single Green) Moving Light

RGB/单绿激光摇头蜘蛛灯

Technical Parameters:

Power supply: AC100~240V, 50/60Hz
Power Consumption: 110 W
Laser Power: Green 60mw*4 + Red 300mw*2 + Blue 500mw*2 / Green 60mw*8
Channel: 13/16 / 20channels
Level Scanning: 540° (16 bit precision scan)
Vertical Scan: 185° (16 bit precision scan)
color: RGB or Green
Control mode: DMX-512, music control, automatic, master & slave



技术参数:

输入电压: AC100-240V, 50Hz-60Hz
最大功率: 110W
激光功率: 绿: 60mw*4+红: 300mw*2+蓝: 500mw*2
或: 绿 60mw*8
通道: 13通道/16通道/20通道
水平扫描: 540°+微调
垂直扫描: 185°+微调
颜色: 红绿蓝或绿色
控制: 自走、声控、主从、DMX512



FY-7005/7010/7020/7025/7050 FY-1605/1610/1620/1650/FY-1320

RGB/Single Color Moving head animation laser

摇头全彩/单色动画激光

Technical Parameters:

Power Supply: AC110V / AC230V, 50Hz~60Hz
Power Consumption: 150W max
Laser Power: RGB 500mw~5000mw
G 500mw~5000mw, B 2000mw
Laser Color: RGB/Green (532nm), Blue(450nm)
Scan System: 20-40kpps vibratory mirror system,
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control(optional)
Control Channel: 18 or 23/16 or 21
Flight case Size: 560×440×840mm
Total weight: <45KG
Operating Environment: 10~35° indoor

技术参数:

电源供应: AC110V / AC230V, 50Hz~60Hz
额定功率: <150W
激光功率: RGB 500mw~5000mw
绿 500mw~5000mw, 蓝2000mw
激光颜色: 全彩/绿色(532nm)或蓝色(450nm)
扫描系统: 20-40kpps振镜扫描,
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控、自走、主从、SD卡控制(可选)
控制通道: 18个或23个/16个或21个
航空箱尺寸: 560×440×840mm
总重: <45KG
工作环境: 室内(10~35°)





F5000-908/910/915/920/930

RGB Animation laser 8W~30W

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 350W max
Laser Power: RGB 8W~30W
Wavelength: Green: 532nm or 520nm/Red: 635nm or 640nm/Blue: 450nm or 457nm
Laser Modulation: analog modulation
Laser Color: RGB full colors
Scan System: high speed scanner 30-60kpps
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control(optional)
Cool System: fan
Operating Environment: 10~35°indoor

全彩动画激光灯8W~30W

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <350W
激光功率: 8W~30W
激光波长: 绿光: 532nm或520nm, 红光: 635nm或640nm, 蓝光: 450nm或457nm
调制信号: 模拟调制
激光颜色: 全彩色
扫描系统: 30-60kpps高速振镜扫描系统,
控制方式: ILDA, DMX-512, 声控、自走、主从、SD卡控制(可选)
冷却系统: 风机强制冷却系统
工作环境: 室内(10~35°)



F2000-901/9015/902/903/904/905/906/908

RGB Animation laser 1W~8W

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 200W max
Laser Power: RGB 1W~8W
Wavelength: Green 532nm or 520nm, Red 655nm/635nm/638nm/640nm, Blue 450nm
Laser Modulation: analog modulation or TTL
Laser Color: RGB
Scan System: high speed scanner 30-60kpps
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control(optional)
Cool System: fan
Operating Environment: 10~35°indoor

全彩动画激光灯1W~8W

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <200W
激光功率: 1W~8W
激光波长: 绿光: 532nm或520nm, 红光: 655nm或635nm或638nm或640nm, 蓝光: 450nm
调制信号: 模拟调制或TTL调制
激光颜色: 全彩
扫描系统: 30-60kpps高速振镜扫描系统,
控制方式: ILDA, DMX-512, 声控、自走、主从、SD卡控制(可选)
冷却系统: 风机强制冷却系统
工作环境: 室内(10~35°)



F4-RGB901/RGB9015/RGB902/RGB903/RGB904

RGB Animation laser 1W~4W

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 100W max
Laser Power: RGB 1W~4W
Wavelength: Green 532nm or 520nm, Red 650nm/635nm or 638nm, Blue 450nm
Laser Modulation: analog modulation or TTL
Laser Color: RGB
Scan System: 15-30kpps vibratory mirror system,
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control(optional)
Cool System: fan
Operating Environment: 10~35°indoor
Packing Size: 530×390×280mm
Gross Weight: 16KG max

全彩动画激光灯1W~4W

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <100W
激光功率: 1W~4W
激光波长: 绿光: 532nm或520nm, 红光: 650nm或635nm或638nm, 蓝光: 450nm
调制信号: 模拟调制或TTL调制
激光颜色: 全彩色
扫描系统: 15-30kpps振镜扫描,
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控、自走、主从、SD卡控制(可选)
冷却系统: 风机强制冷却系统
工作环境: 室内(10~35°)
纸箱包装尺寸: 530×390×280mm
毛重: <16KG



F1000-818/820/901/9015/902/903

RGB Animation laser 1W~3W

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 100W max
Laser Power: RGB 1~3W
Wavelength: Green 532nm or 520, Red 655nm/638nm, Blue 450nm
Laser Modulation: analog modulation or TTL
Laser Color: RGB seven colors
Scan System: 15~25kpps vibratory mirror system, scan angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave
Control Channel: 12
Cool System: fan
Operating Environment: 10~35°indoor

全彩动画激光灯1W~3W

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <100W
激光功率: RGB 1~3W
激光波长: 绿光: 532nm或520nm, 红光: 655nm或638nm, 蓝光: 450nm
激光调制信号: 模拟调制或TTL调制
激光颜色: 全彩色
扫描系统: 15~25kpps振镜扫描,
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控、自走、主从。
控制通道: 12
冷却系统: 风机强制冷却系统
工作环境: 室内(10~35°)



NF-815/-820/-828

RGB Animation laser 830mw~2.3W

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 100W max
Laser Power: RGB 830mw~2.3W
Wavelength: Green 532nm or 520nm, Red 650nm/638nm, Blue 450nm
Laser Modulation: analog modulation or TTL
Laser Color: RGB
Scan System: 30kpps vibratory mirror system,
Control Mode: ILDA, DMX-512, music control, automatic, master & slave
Control Channel: 12
Cool System: fan
Operating Environment: 10~35°indoor
Flightcase Size: 415×335×340mm
Gross Weight: 15KG max

全彩动画激光灯830mw~2.3W

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <100W
激光功率: RGB 830mw~2.3W
激光波长: 绿光: 532nm或520nm, 蓝光: 450nm, 红光: 650nm或638nm
激光调制信号: 模拟调制或TTL调制
激光颜色: 全彩
扫描系统: 30kpps振镜扫描,
控制方式: ILDA, DMX-512, 声控、自走、主从。
控制通道: 12
冷却系统: 风机强制冷却系统
工作环境: 室内(10~35°)
航空箱包装尺寸: 415×335×340mm
毛重: <15KG



F600-705/-710/-718/-720

RGB Animation laser 500mw~2.3W

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 100W max
Laser Power: RGB 500mw~2.3W
Wavelength: Green 532nm or 520nm, Red 650nm/638nm, Blue 450nm
Laser Modulation: analog modulation or TTL
Laser Color: RGB
Scan System: 15~25kpps vibratory mirror system,
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control(optional)
Control Channel: 17 or 22
Cool System: fan
Operating Environment: 10~35°indoor
Packing Size: 410×310×190mm
Gross Weight: 8KG max

全彩动画激光灯500mw~2.3W

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <100W
激光功率: RGB 500mw~2.3W
激光波长: 绿光: 532nm或520nm, 红光: 650nm或638nm, 蓝光: 450nm
激光调制信号: 模拟调制或TTL调制
激光颜色: 全彩
扫描系统: 15~25kpps振镜扫描,
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控、自走、主从、SD卡控制(可选)
控制通道: 17或22
冷却系统: 风机强制冷却系统
工作环境: 室内(10~35°)
纸箱包装尺寸: 410×310×190mm
毛重: <8KG



F1003-750/F1003-723/F1101-750

RGB Animation laser 230mw~500mw Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 60W max
Laser Power: RGB 500mw/230mw
Wavelength: Green:532nm or 520nm, Red:650nm, Blue:450nm or 405nm
Laser Color: RGB seven colors
Scan System: 15~25kpps vibratory mirror system
Scan Angle: ± 20 degrees
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control (optional)
Control Channel: 22 or 12
Operating Environment: 10~35 $^{\circ}$ indoor
Inner Packing Size: 345 $\times$ 290 $\times$ 165mm
Gross Weight: 3KG max
Packing Size: 910 $\times$ 370 $\times$ 320mm (5 pcs), Total weight: 17KG max

全彩动画激光灯230mw~500mw 技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <60W
激光功率: 500mw/230mw
激光波长: 绿光: 532nm或520nm, 红光: 650nm, 蓝光: 450nm/紫光405nm
激光颜色: 全彩色
扫描系统: 15~25kpps振镜扫描,
扫描角度: ± 20 度
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控, 自走, 主从, SD卡控制(可选)
控制通道: 22/12个
工作环境: 室内(10~35 $^{\circ}$)
内包尺寸: 345 $\times$ 290 $\times$ 165mm
毛重: <3KG
外包装尺寸: 910 $\times$ 370 $\times$ 320mm (5支/箱), 总重量: <17KG



F3-503/F3-506/F3-513/F600-503

Three Color Animation Laser 250mw~1300mw Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 80W max
Laser Power: RGY/RBM 500mw~1300mw
Wavelength: Green:532nm or 520nm, Red:650nm or 638nm, Blue:450nm
Laser Modulation: TTL
Laser Color: RGY or RBM three color
Scan System: 15~25kpps vibratory mirror system,
Scan Angle: ± 20 degrees
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave, ILDA(optional)
Control Channel: 12 or 22
Cool System: fan
Operating Environment: 10~35 $^{\circ}$ indoor

三色动画激光250mw~1300mw 技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <80W
激光功率: RGY/RBM500mw~1300mw
激光波长: 绿光: 532nm/520nm, 红光: 650nm/638nm, 蓝光: 450nm
激光调制信号: TTL
激光颜色: 红、绿、黄三色或红、蓝、粉三色
扫描系统: 15~25kpps振镜扫描,
扫描角度: ± 20 度
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控, 自走, 主从, ILDA(可选)
控制通道: 12或22个
冷却系统: 风机强制冷却系统
工作环境: 室内(10~35 $^{\circ}$)

F3-520/F3-501

Three Color Animation Laser 200mw~480mw Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 30W max
Laser Power: RGY 200mw~480mw
Wavelength: green:532nm or 520nm, red:650nm, blue:450nm
Laser Color: RGY or RBM three color
Scan System: 15kpps vibratory mirror system,
Scan Angle: ± 20 degrees
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave, ILDA(optional)
Control Channel: 12
Cool System: fan
Operating Environment: 10~35 $^{\circ}$ indoor

三色动画激光200mw~480mw 技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <30W
激光功率: RGY 200mw~480mw
激光波长: 绿光: 532nm/520nm, 红光: 650nm, 蓝光: 450nm
激光颜色: 红、绿、黄或红、蓝、粉红三色
扫描系统: 15kpps振镜扫描,
扫描角度: ± 20 度
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控, 自走, 主从, ILDA(可选)
控制通道: 12
冷却系统: 风机强制冷却系统
工作环境: 室内(10~35 $^{\circ}$)




F5000-681/682/685/690/695/698/699

Green Animation Laser 1W~30W Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 1000W max
Laser Power: 1W~30W
Laser Source: solid semiconductor laser generator
Wavelength: Green:532nm or 520nm
Laser Modulation: analogue modulation or 0~20K TTL modulation
Scan System: 20KPPS scanning(Large lens)or 40kpps high speed scanner
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control(optional)
Cool System: fan
Operating Environment: 10~35 $^{\circ}$ indoor

单绿动画激光1W~30W 技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <1000W
激光功率: 1W~30W
激光光源: 半导体激光发生器
激光波长: 绿光: 532nm或520nm
激光调制信号: 模拟调制或TTL调制0~20K
扫描系统: 20k大镜片振镜片或者40kpps高速振镜扫描系统,
控制方式: ILDA, DMX-512, 声控, 自走, 主从, SD卡控制(可选)
冷却系统: 风机强制冷却系统
工作环境: 室内(10~35 $^{\circ}$)



F4-675/681/682/683/685

Green Animation Laser 500mw~5W Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 200W max
Laser Power: 500mw~5W
Wavelength: 532nm or 520nm
Laser Color: Green
Scan System: 15~40kpps vibratory mirror system,
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave, SD Card control(optional)
Control Channel: 10 or 17
Cool System: fan
Operating Environment: 10~35 $^{\circ}$ indoor
Packing Size: 530 $\times$ 390 $\times$ 280mm
Gross Weight: <13KG

单绿动画激光500mw~5W 技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <200W
激光功率: 500mw~5W
激光波长: 绿光: 532nm或520nm
激光颜色: 翠绿色
扫描系统: 15~40kpps振镜扫描,
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控, 自走, 主从, SD卡控制(可选)
控制通道: 10或17个
冷却系统: 风机强制冷却系统
工作环境: 室内(10~35 $^{\circ}$)
包装尺寸: 530 $\times$ 390 $\times$ 280mm
毛重: <13KG

NF-653/655/660/662/665

Green Animation Laser 300mw~5W Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 200W max
Laser Power: 300mw~5W
Laser Color: Green(532nm) or 520nm
Scan System: 30kpps vibratory mirror system,
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control, automatic, master & slave
Control Channel: 10 or 23
Operating Environment: 10~35 $^{\circ}$ indoor
Flight case Size: 415 $\times$ 335 $\times$ 340mm
Gross Weight: 16KG max

单绿动画激光300mw~5W 技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <200W
激光功率: 300mw~5W
激光颜色: 翠绿色(532nm)/520nm
扫描系统: 30kpps振镜扫描
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控, 自走, 主从
控制通道: 10或23个
工作环境: 室内(10~35 $^{\circ}$)
航空箱尺寸: 415 $\times$ 335 $\times$ 340mm
毛重: <16KG





F1000-653/655/681/682/683/685

Green Animation laser 200mw-5W
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 100W max
Laser Power: 200~5000mw
Laser Color: Green(532nm) or 520nm
Scan System: 15-30kpps vibratory mirror system,
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control,
automatic, master & slave
Control Channel: 10
Operating Environment: 10~35°indoor

绿色动画激光灯200mw-5W
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <100W
激光功率: 200~5000mw
激光颜色: 翠绿色(532nm)或520nm
扫描系统: 15-30kpps振镜扫描
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控, 自走,
主从
控制通道: 10个
工作环境: 室内(10~35°)



F1101-650/651/652/653

Green Animation Laser 100~300mw
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 60W max
Laser Power: 100mw/150mw/200mw/300mw
Laser Color: Green(532nm) or 520nm
Scan System: 15kpps vibratory mirror system,
Scan Angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control,
automatic, master & slave
Control Channel: 10 or 22
Operating Environment: 10~35°indoor
Inner Packing Size: 345×290×165mm
Gross Weight: 2.6~3.2KG
Packing Size: 910×370×320mm(5 pcs)
Total weight: 15~18KG

单绿动画激光100mw~300mw
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <60W
激光功率: 100mw/150mw/200mw/300mw
激光颜色: 翠绿色(532nm)或520nm
扫描系统: 15kpps振镜扫描
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控, 自走, 主从
控制通道: 10或22个
工作环境: 室内(10~35°)
内包尺寸: 345×290×165
毛重: 2.6~3.2KG
外包尺寸: 910×370×320mm(5支/箱)
总重量: 15~18KG



F1002-606/610/615

Green Animation Laser 60mw~150mw
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 50W max
Laser Power: 60mw/100mw/150mw
Laser Color: Green(532nm) or 520nm
Scan System: 15kpps vibratory mirror system,
Scan Angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic,
master & slave, ILDA(optional)
Control Channel: 10
Operating Environment: 10~35°indoor
Inner Packing Size: 270×230×165mm
Gross Weight: 2~2.4KG
Packing Size: 905×300×260mm(5 pcs)
Total weight: 12~14KG

单绿动画激光60mw~150mw
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <50W
激光功率: 60mw/100mw/150mw
激光颜色: 翠绿色(532nm)或520nm
扫描系统: 15kpps振镜扫描
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控, 自走, 主从, ILDA(可选)
控制通道: 10个DMX-512信号通道
工作环境: 室内(10~35°)
内包尺寸: 270×230×165
毛重: 2~2.4KG
外包尺寸: 905×300×260mm(5支/箱)
总重量: 12~14KG



F6-606/610/615/ F6-302/305/310 / F6-13

Single Color Animation SD card Laser
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 60W max
Laser Power: Green:60-150mw
Blue:200-1000mw Red:300mw
Laser Color: Green or Blue or Red
Scan System: 20kpps vibratory mirror system,
scan angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: ILDA, DMX-512, music control,
automatic, master & slave, SD
Card control(optional)
Operating Environment: 10~35°indoor

单色动画SD卡激光
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <60W
激光功率: 绿:60-150mw,
蓝:200-1000mw,红:300mw
激光颜色: 绿或蓝或红
扫描系统: 20kpps振镜扫描
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: ILDA, DMX-512, 声控, 自走, 主从, SD卡控制(可选)
工作环境: 室内(10~35°)



F1101-305/310/510

Blue/Pink Animation Laser 500~1000mw
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 60W max
Laser Power: 500mw~1000mw
Laser Color: Blue(450nm)/Pink
Scan System: 15-30kpps vibratory mirror system,
Scan Angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: DMX-512, music control,
automatic, master & slave,
ILDA(optional)
Control Channel: 10 or 22
Operating Environment: 10~35°indoor
Inner Packing Size: 345×290×165mm
Gross Weight: 2.2~3KG
Packing Size: 910×370×320mm(5pcs)
Total weight: 12~16KG

单蓝/粉色动画激光500~1000mw
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <60W
激光功率: 500mw~1000mw
激光颜色: 蓝色(450nm)/粉红色
扫描系统: 15-30kpps振镜扫描
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控, 自走, 主从, ILDA(可选)
控制通道: 10或22个
工作环境: 室内(10~35°)
内包尺寸: 345×290×165
毛重: 2.2~3KG
外包尺寸: 910×370×320mm(5支/箱)
总重量: 12~16KG



F1002-302/ 303/ 305/308/310

Blue Animation Laser 200~1000mw
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 50W max
Laser Power: 200mw~1000mw
Laser Color: Blue(450nm)
Scan System: 15kpps vibratory mirror system,
Scan Angle: ±20degrees
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic,
master & slave, ILDA(optional)
Control Channel: 10
Operating Environment: 10~35°indoor
Inner Packing Size: 270×230×165mm
Gross Weight: 2~2.2KG
Packing Size: 905×300×260mm(5pcs)
Total weight: 11~12.5KG

单蓝动画激光200~1000mw
技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: <50W
激光功率: 200mw~1000mw
激光颜色: 蓝色(450nm)
扫描系统: 15kpps振镜扫描
扫描角度: ±20度
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控, 自走, 主从, ILDA(可选)
控制通道: 10个
工作环境: 室内(10~35°)
内包尺寸: 270×230×165mm
毛重: 2~2.2KG
外包尺寸: 905×300×260mm(5支/箱)
总重量: 11~12.5KG



F1668 / F1688/F6228 / F6268

RGB/RG Dazzling laser RGB/RG 步步炫 激光灯

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz

Power Consumption: 30W

Laser Power: Green(532nm) 60/100mw,

Red (650nm) 150mw/(638nm)

300mw, Blue200/1000mw (450nm)

Laser Color: RGB seven color/RGB 3 color

Scan System: 15kpps vibratory mirror system

Laser Patterns: 128pcs, including 3D, grating

and other 13 group effect

Control Mode: DMX-512, music control,

automatic, master & slave

Control Channel: 23

Operating Environment: 10~35°indoor

技术参数:

电源供应: AC90~240V, 50Hz~60Hz

额定功率: 30W

激光功率: 532nm绿光60/100mw, 650nm

红光150mw或638nm 红光300mw,

450nm蓝光200/1000mw

激光颜色: RGB七彩/红绿黄三色

扫描系统: 15kpps振镜扫描

激光图案: 128幅, 包括3D、光栅等15组效果

控制方式: DMX-512、声控、自走、主从

控制通道: 23

工作环境: 室内(10~35°)

F1645/F1645A/F1645B

RGB/RG/RB 5D Twin Effects RGB/RG/RB五维流花台

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz

Power Consumption: 30W

Laser Power: Green(532nm)60~150mw / Red(650nm/638nm)

100~300mw / Blue200~1000mw(450nm)

Laser Color: RGB/RG/RB

Scan System: 15kpps vibratory mirror system

Laser Patterns: 128pcs, including 3D, grating

and other 5 group effect

Control Mode: DMX-512, music control, automatic,

master & slave. Wireless remote(Optional)

Control Channel: 23

Operating Environment: 10~35°indoor

电源供应: AC90~240V, 50Hz~60Hz

额定功率: 30W

激光功率: 532nm绿光60~150mw, 650/638nm红光

100~300mw, 450nm蓝光200~1000mw

激光颜色: RGB七彩/RGB/RB

扫描系统: 15kpps振镜扫描

激光图案: 128幅, 包括3D、光栅等5组效果

控制方式: DMX-512、声控、自走、主从、

遥控(可选)

控制通道: 23

工作环境: 室内(10~35°)



F1643A / F1643

RGB 5D Twin Effects RGB

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz

Power Consumption: 30W

Laser Power: Green(532nm)60mw / Red(650nm)

150mw / Blue200~300mw(450nm)

Laser Color: RGB seven color

Scan System: 15kpps vibratory mirror system

Laser Patterns: 128pcs, including 3D, grating

and other 5 group effect

Control Mode: DMX-512, music control, automatic,

master & slave. Wireless remote(Optional)

Control Channel: 23

Operating Environment: 10~35°indoor

RGB五维流花台

技术参数:

电源供应: AC90~240V, 50Hz~60Hz

额定功率: 30W

激光功率: 532nm绿光60mw, 650nm红光

150mw, 450nm蓝光200~300mw

激光颜色: RGB七彩

扫描系统: 15kpps振镜扫描

激光图案: 128幅, 包括3D、光栅等5组效果

控制方式: DMX-512、声控、自走、主从、

遥控(可选)

控制通道: 23

工作环境: 室内(10~35°)

F6295A/F6223A / F6295/F6223

RB/RG 5D Twin Effects RB/RG

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz

Power Consumption: 30W

Laser Power: Green(532nm)60mw / Red(650nm)

150mw / Blue200~300mw(450nm)

Laser Color: RBM /RGY three color

Scan System: 15kpps vibratory mirror system

Laser Patterns: 128pcs, including 3D, grating

and other 5 group effect

Control Mode: DMX-512, music control, automatic,

master & slave. Wireless remote(Optional)

Control Channel: 23

Operating Environment: 10~35°indoor

RB/RG五维流花台

技术参数:

电源供应: AC90~240V, 50Hz~60Hz

额定功率: 30W

激光功率: 532nm绿光60mw, 650nm红光

150mw, 450nm蓝光200~300mw

激光颜色: 红蓝粉/红绿黄三色

扫描系统: 15kpps振镜扫描

激光图案: 128幅, 包括3D、光栅等5组效果

控制方式: DMX-512、声控、自走、主从、

遥控(可选)

控制通道: 23

工作环境: 室内(10~35°)



F1508 / F1508A

RGB rotating Twin Effects RGB

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz

Power Consumption: 30W

Laser Power: Green(532nm) 60mw / Red (650nm)

150mw / Blue200~300mw(450nm)

Laser Color: red & green & blue

Scan System: 15kpps vibratory mirror system

Laser Patterns: 128pcs

Control Mode: DMX-512, music control, automatic,

master & slave. Wireless remote(Optional)

Control Channel: 23

Operating Environment: 10~35°indoor

RGB旋转流花台

技术参数:

电源供应: AC90~240V, 50Hz~60Hz

额定功率: 30W

激光功率: 532nm绿光60mw, 650nm红光

150mw, 450nm蓝光200~300mw

激光颜色: 红色、绿色、蓝色

扫描系统: 15kpps振镜扫描

激光图案: 128幅,


控制方式: DMX-512、声控、自走、主从、

遥控(可选)

控制通道: 23

工作环境: 室内(10~35°)





F1045A/F5830A/F1045/F5830

RB/RG rotating Twin Effects

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 30W
Laser Power: Green(532nm)60mw / Red(650nm) 150mw / Blue200~300mw(450nm)
Laser Color: red & blue or red & green
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave, Wireless remote (Optional)
Control Channel: 23
Operating Environment: 10~35° indoor

RB/RG 旋转流花台

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: 30W
激光功率: 532nm绿光60mw, 650nm红光 150mw, 450nm蓝光200~300mw
激光颜色: 红色、蓝色或、红色、绿色
扫描系统: 15kpps振镜扫描
激光图案: 128幅
控制方式: DMX-512, 声控、自走、主从、遥控(可选)
控制通道: 23
工作环境: 室内(10~35°)

F1003-250/F1101-250

RGB Twin Effects

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 30W
Laser Power: Green(532nm)60mw
Red(650nm) 150mw
Blue200~300mw(450nm)
Laser Color: red & green & blue
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave
Control Channel: 22
Operating Environment: 10~35° indoor
Inner Packing Size: 345×290×165mm
Gross Weight: 2.4KG
Packing Size: 910×370×320mm(5 pcs)
Total weight: 13.5KG

RGB 流花台

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: 30W
激光功率: 532nm绿光60mw
650nm红光150mw
450nm蓝光200~300mw
激光颜色: 红色、绿色、蓝色
扫描系统: 15kpps振镜扫描
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控、自走、主从
控制通道: 22
工作环境: 室内(10~35°)
内包尺寸: 345×290×165mm
毛重: 2.4KG
外包装尺寸: 910×370×320mm(5支/箱)
总重量: 13.5KG

F1003-220/245/F1101-220/245

RB/RG Twin Effects


Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 20W
Laser Power: Green(532nm) 60mw
Red(650nm) 150mw
Blue(450nm) 200~300mw
Laser Color: red & blue or green & red
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave
Control Channel: 22
Operating Environment: 10~35° indoor
Inner Packing Size: 345×290×165mm
Gross weight: 2.2KG
Packing Size: 910×370×320mm(5 pcs)
Gross weight: 12KG

RB/RG 流花台

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: 20W
激光功率: 532nm绿光60mw
650nm红光150mw
450nm蓝光200~300mw
激光颜色: 红蓝或红绿
扫描系统: 15kpps振镜扫描
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控、自走、主从
控制通道: 22个
工作环境: 室内(10~35°)
内包尺寸: 345×290×165mm
毛重: 2.2KG
外包装尺寸: 910×370×320mm(5支/箱)
总重量: 12KG



F1002-210/ 230

RG/RB Twin Effects

Technical Parameters:

Power Supply: AC90~240V, 50Hz~60Hz
Power Consumption: 20W
Laser Power: Green(532nm) 50mw
Red(650nm) 100mw
Blue(450nm)200~300mw
Laser Color: red & green or red & blue
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs
Control Mode: DMX-512, music control, automatic, master & slave
Control Channel: 22
Operating Environment: 10~35° indoor
Inner Packing Size: 260×290×185mm
Gross weight: 2.1KG
Packing Size: 905×300×260mm(5 pcs)
Total weight: 11KG

RG/RB 流花台

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
额定功率: 20W
激光功率: 532nm绿光50mw
650nm红光100mw
450nm蓝光200~300mw
激光颜色: 红绿或红蓝
扫描系统: 15kpps振镜扫描
激光图案: 128幅激光效果图案
控制方式: DMX-512, 声控、自走、主从
控制通道: 22个
工作环境: 室内(10~35°)
内包尺寸: 260×290×185mm
毛重: 2.1KG
外包装尺寸: 905×300×260mm(5支/箱)
总重量: 11KG

F1001/F1001A/F1001B

RG/RB Cat eye

Technical Parameters:

Power Supply: AC90~240V
Power Consumption: 20W
Laser Power: Green(532nm) 50mw
Red(650nm) 100mw
Blue(450nm)200~1000mw
Laser Color: green & red or red & blue
Scan System: 15kpps vibratory mirror system
Laser Patterns: 128pcs, There are 8 festival patterns, New Year's Day, Easter, Valentine's Day, Christmas Day, Wedding and Birthday.
Control Mode: music control, automatic Wireless remote(optional)
Operating Environment: 10~35° indoor

红绿/红蓝节日猫眼

技术参数:

电压供应: AC90~240V
额定功率: 20W
激光功率: 绿光50mw/532nm
红光100mw/650nm
蓝光 200~1000mw/450nm
激光颜色: 红色、绿色或红色和蓝色
扫描系统: 15kpps振镜扫描
激光图案: 128幅图案, 内置新年、元宵节、情人节、万圣节、圣诞节、婚礼、生日以及平日等八套节目
控制方式: 声控、自走、遥控(可选)
工作环境: 室内(10~35°)

F092A/F092B/F092C

4 in 1 grating laser

Technical Parameters:

Power Supply: AC110V/AC230V, 50Hz~60Hz
Power Consumption: 20W
Laser Power: Green(532nm)50mw
Red(650nm)100mw
Blue(450nm)200~300mw
Laser Color: green & red or blue & red or green & blue
Control Mode: music control, automatic
Operating Environment: 10~35° indoor
Inner Packing Size: 265×180×100mm
Gross Weight: 1.25 KG
Packing Size: 530×280×390mm(10 pcs)
Total weight: 13 KG

四合一光栅激光灯

技术参数:

电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: 20W
激光功率: 532nm绿光 50mw
650nm红光100mw
450nm蓝光200~300mw
激光颜色: 红色、绿色、红色、蓝色、绿色、蓝色
控制方式: 声控、自走
工作环境: 室内(10~35°)
内包尺寸: 265×180×100mm
毛重: 1.25KG
外包装尺寸: 530×280×390mm(10个/箱)
总重量: 13KG



F1340/F1340B

RG/RB 40 in 1 grating laser
Technical Parameters:

Power Supply: AC110V /AC230V , 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Green(532nm)50~100mw

Blue(450nm) 200~1000mw

Laser Color: red & green or red & blue

Laser Patterns: 40pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红绿/红蓝40合一
技术参数:

电源供应: AC110V /AC230V , 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,

532nm绿色50~100mw,


450nm 蓝色200~1000mw

激光颜色: 红色和绿色 或 红色和蓝色

激光图案: 40个

控制方式: 声控, 自走

工作环境: 室内(10~35°)



F1332/F1332B

RG/RB 32 in 1 grating laser
Technical Parameters:

Power Supply: AC110V /AC230V , 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Green(532nm)50~100mw

Blue(450nm) 200~1000mw

Laser Color: red & green or red & blue

Laser Patterns: 32pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红绿/红蓝32合一
技术参数:

电源供应: AC110V /AC230V , 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,

532nm绿色50~100mw,

450nm 蓝色200~1000mw

激光颜色: 红色和绿色 或 红色和蓝色

激光图案: 32个

控制方式: 声控, 自走

工作环境: 室内(10~35°)



F1320/F1320B/F1320W

RG/RB/RGB 20 in 1 grating laser
Technical Parameters:

Power Supply: AC110V /AC230V , 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Green(532nm)50~100mw

Blue(450nm) 200~1000mw

Laser Color: red & green or red & blue or RGB

Laser Patterns: 20pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红绿/红蓝/红绿蓝20合一
技术参数:

电源供应: AC110V /AC230V , 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,

532nm绿色50~100mw,

450nm 蓝色200~1000mw

激光颜色: 红和绿 或 红和蓝 或 红绿蓝

激光图案: 20个

控制方式: 声控, 自走

工作环境: 室内(10~35°)



F1316/F1316B/F1312/F1312B

RG/RB16 in1/12 in 1 grating laser
Technical Parameters:

Power Supply: AC110V /AC230V , 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Green(532nm)50~100mw

Blue(450nm) 200~1000mw

Laser Color: red & green or red & blue

Laser Patterns: 16/12pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红绿/红蓝16合一/12合一
技术参数:

电源供应: AC110V /AC230V , 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,

532nm绿色50~100mw,

450nm 蓝色200~1000mw

激光颜色: 红色和绿色 或 红色和蓝色

激光图案: 16/12个

控制方式: 声控, 自走

工作环境: 室内(10~35°)



FX316/FX316B/FX312/FX312B

RG/RB 16 in 1/12 in 1 grating Ceiling laser
Technical Parameters:

Power Supply: AC110V /AC230V , 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Green(532nm)50~100mw

Blue(450nm) 200~1000mw

Laser Color: red & green or red & blue

Laser Patterns: 16/12pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红绿/红蓝吸顶16合一/12合一
技术参数:

电源供应: AC110V /AC230V , 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,

532nm绿色50~100mw,

450nm 蓝色200~1000mw

激光颜色: 红色和绿色 或 红色和蓝色

激光图案: 16/12个

控制方式: 声控, 自走

工作环境: 室内(10~35°)



F1208/F1208A

RB 12 in 1/8 in 1 grating laser
Technical Parameters:

Power Supply: AC110V /AC230V , 50HZ~60HZ

Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw

Blue(450nm) 200~1000mw

Laser Color: red & blue

Laser Patterns: 12/8pcs

Control Mode: music control, automatic

Operating Environment: 10~35°indoor

红蓝12合一/8合一
技术参数:

电源供应: AC110V /AC230V , 50Hz~60Hz

额定功率: 20W

激光功率: 650nm红光100~150mw,


450nm 蓝色200~1000mw

激光颜色: 红色和蓝色

激光图案: 12/8个

控制方式: 声控, 自走

工作环境: 室内(10~35°)



F1209/F1209A

RG 12 in 1 / 8 in 1 grating laser Technical Parameters:

Power Supply: AC110V / AC230V, 50HZ~60HZ
Power Consumption: 20W

Laser Power: Red (650nm) 100~150mw / Green (532nm) 50mw

Laser Color: red & green

Laser Patterns: 12 / 8 pcs

Control Mode: music control, automatic

Operating Environment: 10~35° indoor

红绿12/8合一 技术参数:

电源供应: AC110V / AC230V, 50Hz~60Hz
额定功率: 20W


激光功率: 650nm红光100~150mw, 532nm
绿色50mw

激光颜色: 红色和绿色

激光图案: 12/8个

控制方式: 声控、自走

工作环境: 室内(10~35°)



F088/F088B

F088 / F088B RG/RB Firefly Technical Parameters:

Power Supply: AC110V / AC230V, 50HZ~60HZ
Power Consumption: 20W

Laser Power: Green (532nm) 50mw, Red (650nm) 100mw, Blue(450nm) 300mw

Laser Color: red & green or red & blue

Control Mode: DMX-512, music control, automatic
Control Channel: 5

Inner Packing Size: 270*245*105mm

Gross Weight: 2.35 KG

Packing Size: 565*295*275mm(5 pcs)

Total weight: 12.8 KG

红绿/红蓝萤火虫 技术参数:

电源供应: AC110V / AC230V, 50Hz~60Hz
额定功率: 20W

激光功率: 532nm绿光 50mw, 650nm红光 100mw, 450nm蓝光300mw

激光颜色: 红绿或红蓝

控制方式: DMX-512, 自走、声控


控制通道: 5个

内包尺寸: 270*245*105mm

毛重: 2.35KG

外包尺寸: 565*295*275mm (5个/箱)

总重量: 12.8KG



F099

MINI RG laser

Technical Parameters:

Power Supply: AC110V / AC230V, 50HZ~60HZ
Power Consumption: 20W

Laser Power: Green (532nm) 50mw
Red (650nm) 100mw

Laser Color: green & red

Control Mode: music control, automatic

迷你红绿激光

技术参数:

电源供应: AC110V / AC230V, 50Hz~60Hz
额定功率: 20W

激光功率: 532nm绿光 50mw
650nm红光 100mw

激光颜色: 红色、绿色

控制方式: 自走、声控

F099A/F099B/F099C/F099D/F099E/F099F/F099G

MINI RG Firefly 2 in 1/4 in 1/8 in 1/12 in 1/20 in 1/40 in 1/80 in 1/160 in 1/320 in 1/640 in 1/1280 in 1/2560 in 1/5120 in 1/10240 in 1/20480 in 1/40960 in 1/81920 in 1/163840 in 1/327680 in 1/655360 in 1/1310720 in 1/2621440 in 1/5242880 in 1/10485760 in 1/20971520 in 1/41943040 in 1/83886080 in 1/167772160 in 1/335544320 in 1/671088640 in 1/1342177280 in 1/2684354560 in 1/5368709120 in 1/10737418240 in 1/21474836480 in 1/42949672960 in 1/85899345920 in 1/171798691840 in 1/343597383680 in 1/687194767360 in 1/1374389534720 in 1/2748779069440 in 1/5497558138880 in 1/10995116277760 in 1/21990232555520 in 1/43980465111040 in 1/87960930222080 in 1/175921860444160 in 1/351843720888320 in 1/703687441776640 in 1/1407374883553280 in 1/2814749767106560 in 1/5629499534213120 in 1/11258999068426240 in 1/22517998136852480 in 1/45035996273704960 in 1/90071992547409920 in 1/180143985094819840 in 1/360287970189639680 in 1/720575940379279360 in 1/1441151880758558720 in 1/2882303761517117440 in 1/5764607523034234880 in 1/11529215046068469760 in 1/23058430092136939520 in 1/46116860184273879040 in 1/92233720368547758080 in 1/184467440737095516160 in 1/368934881474191032320 in 1/737869762948382064640 in 1/1475739525896764129280 in 1/2951479051793528258560 in 1/5902958103587056517120 in 1/11805916207174113034240 in 1/23611832414348226068480 in 1/47223664828696452136960 in 1/94447329657392904273920 in 1/188894659314785808547840 in 1/377789318629571617095680 in 1/755578637259143234191360 in 1/1511157274518286468382720 in 1/3022314549036572936765440 in 1/6044629098073145873530880 in 1/12089258196146291747061760 in 1/24178516392292583494123520 in 1/48357032784585166988247040 in 1/96714065569170333976494080 in 1/193428131138340667952988160 in 1/386856262276681335905976320 in 1/773712524553362671811952640 in 1/1547425049106725343623905280 in 1/3094850098213450687247810560 in 1/6189700196426901374495621120 in 1/12379400392853802748991242240 in 1/24758800785707605497982484480 in 1/49517601571415210995964968960 in 1/99035203142830421991929937920 in 1/198070406285660843983859875840 in 1/396140812571321687967719751680 in 1/792281625142643375935439503360 in 1/1584563250285286751870879006720 in 1/3169126500570573503741758013440 in 1/6338253001141147007483516026880 in 1/12676506002282294014967032053760 in 1/25353012004564588029934064107520 in 1/50706024009129176059868128215040 in 1/101412048018258352119736256430080 in 1/202824096036516704239472512860160 in 1/405648192073033408478945025720320 in 1/811296384146066816957890051440640 in 1/1622592768292133633915780102881280 in 1/3245185536584267267831560205762560 in 1/6490371073168534535663120411525120 in 1/12980742146337069071326240823050240 in 1/25961484292674138142652481646100480 in 1/51922968585348276285304963292200960 in 1/103845937170696552570609926584401920 in 1/207691874341393105141219853168803840 in 1/415383748682786210282439706337607680 in 1/830767497365572420564879412675215360 in 1/1661534994731144841129758825350430720 in 1/3323069989462289682259517650700861440 in 1/6646139978924579364519035301401722880 in 1/13292279957849158729038070602803445760 in 1/26584559915698317458076141205606891520 in 1/53169119831396634916152282411213783040 in 1/106338239662793269832304564822427566080 in 1/212676479325586539664609129644855132160 in 1/425352958651173079329218259289710264320 in 1/850705917302346158658436518579420528640 in 1/1701411834604692317316873037158841057280 in 1/3402823669209384634633746074317682114560 in 1/6805647338418769269267492148635364229120 in 1/13611294676837538538534984297270728458240 in 1/2722258935367507707706996859454145691520 in 1/5444517870735015415413993718908291383040 in 1/10889035741470030830827987437816582766080 in 1/21778071482940061661655974875633165532160 in 1/43556142965880123323311949751266331064320 in 1/87112285931760246646623899502532662128640 in 1/174224571863520493293247799005065324257280 in 1/348449143727040986586495598010130648514560 in 1/696898287454081973172991196020261297029120 in 1/1393796574908163946345982392040522594058240 in 1/2787593149816327892691964784081045188116480 in 1/5575186299632655785383929568162090376232960 in 1/11150372599265311570767859136324180752465920 in 1/22300745198530623141535718272648361504931840 in 1/44601490397061246283071436545296723009863680 in 1/89202980794122492566142873090593446019727360 in 1/178405961588244985132285746181186892039454720 in 1/356811923176489970264571492362373784078909440 in 1/713623846352979940529142984724747568157818880 in 1/1427247692705959881058285969449495136315637760 in 1/2854495385411919762116571938898990272631275520 in 1/5708990770823839524233143877797980545262551040 in 1/11417981541647679048466287755595961090525102080 in 1/22835963083295358096932575511191922181050204160 in 1/45671926166590716193865151022383844362100408320 in 1/91343852333181432387730302044767688724200816640 in 1/182687704666362864775460604089535377448401633280 in 1/365375409332725729550921208179070754896803266560 in 1/730750818665451459101842416358141509793606533120 in 1/1461501637330902918203684832716283019587213066240 in 1/2923003274661805836407369665432566039174426132480 in 1/5846006549323611672814739330865132078348852264960 in 1/11692013098647223345629478661730264156697704529920 in 1/23384026197294446691258957323460528313395409059840 in 1/46768052394588893382517914646921056626790818119680 in 1/93536104789177786765035829293842113253581636239360 in 1/187072209578355573530071658587684226507163272478720 in 1/374144419156711147060143317175368453014326544957440 in 1/748288838313422294120286634350736906028653089914880 in 1/1496577676626844588240573268701473812057306179829760 in 1/2993155353253689176481146537402947624114612359659520 in 1/5986310706507378352962293074805895248229224719319040 in 1/11972621413014756705924586149611790496458449438638080 in 1/23945242826029513411849172299223580992916898877276160 in 1/47890485652059026823698344598447161985833797754552320 in 1/95780971304118053647396689196894323971667595509104640 in 1/191561942608236107294793378393788647943335191018209280 in 1/383123885216472214589586756787577295886670382036418560 in 1/766247770432944429179173513575154591773340764072837120 in 1/1532495540865888858358347027150309183546681528145674240 in 1/3064991081731777716716694054300618367093363056291348480 in 1/6129982163463555433433388108601236734186726112582696960 in 1/12259964326927110866866776217202473468373452225165393920 in 1/24519928653854221733733552434404946936746904450330787840 in 1/49039857307708443467467104868809893873493808900661575680 in 1/98079714615416886934934209737619787746987617801323151360 in 1/196159429230833773869868419475239575493975235602646302720 in 1/392318858461667547739736838950479150987950471205292605440 in 1/784637716923335095479473677900958301975900942410585210880 in 1/1569275433846670190958947355801916603951801884821170421760 in 1/3138550867693340381917894711603833207903603769642340843520 in 1/6277101735386680763835789423207666415807207539284681687040 in 1/12554203470773361527671578846415332831614415078569363374080 in 1/25108406941546723055343157692830665663228830157138726748160 in 1/50216813883093446110686315385661331326457660314277453496320 in 1/100433627766186892221372630771322662652915320628554906992640 in 1/200867255532373784442745261542645325305830641257109813985280 in 1/401734511064747568885490523085290650611661282514219627970560 in 1/803469022129495137770981046170581301223322565028439255941120 in 1/1606938044258990275541962092341162602446645130056878511882240 in 1/3213876088517980551083924184682325204893290260113757023764480 in 1/6427752177035961102167848369364650409786580520227514047528960 in 1/12855504354071922204335696738729300819573161040455028095057920 in 1/25711008708143844408671393477458601639146322080910056190115840 in 1/51422017416287688817342786954917203278292644161820112380231680 in 1/102844034832575377634685573909834406556585288323640224760463360 in 1/205688069665150755269371147819668813113170576647280449520926720 in 1/411376139330301510538742295639337626226341153294560899041853440 in 1/822752278660603021077484591278675252452682306589121798083706880 in 1/1645504557321206042154969182557350504905364613178243596167413760 in 1/3291009114642412084309938365114701009810729226356487192334827520 in 1/6582018229284824168619876730229402019621458452712974384669655040 in 1/13164036458569648337239753460458804039242916905425948769339310080 in 1/26328072917139296674479506920917608078485833810851897538678620160 in 1/52656145834278593348959013841835216156971667621703795077357240320 in 1/105312291668557186697918027683670432313943335243407590154714480640 in 1/210624583337114373395836055367340864627886670486815180309428961280 in 1/421249166674228746791672110734681729255773340973630360618857922560 in 1/842498333348457493583344221469363458511546681947260721237715845120 in 1/1684996666896914987166688442938726917023093363894521442475431690240 in 1/3369993333793829974333376885877453834046186727789042884950863380480 in 1/6739986667587659948666753771754907668092373455578085769901726760960 in 1/13479973335175319897333507543509815336184746911156171539803453521920 in 1/26959946670350639794667015087019630672369493822312343079606907043840 in 1/53919893340701279589334030174039261344738987644624686159213814087680 in 1/107839786681402559178668060348078522689477975289249372318427628175360 in 1/215679573362805118357336120696157045378955950578498744636855256350720 in 1/431359146725610236714672241392314090757911901156997489273710512701440 in 1/862718293451220473429344482784628181515823802313994978547421025402880 in 1/1725436586902440946858688965569256363031647604627989957094842050805760 in 1/3450873173804881893717377931138512726063295209255979914189684101611520 in 1/6901746347609763787434755862277025452126590418511959828379368203223040 in 1/13



F020-06/03/12

Green / Blue / Red Ceiling Laser Curtain Technical Parameters:

Power Supply: AC110V/AC230V, 50Hz~60Hz
Power Consumption: 10W max
Laser Power: G:60mw/B:300-1000mw/R:100-300mw
Laser Color: green (532nm), Blue (450nm),
R (638/650nm)
Control Mode: TTL modulation
Operating Environment: 10~35°indoor

单绿/单蓝/单红吸顶激光雨帘 技术参数:

电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: <10W
激光功率: 绿60mw, 蓝300-1000mw,
红100-300mw
激光颜色: 绿色(532nm), 蓝(450nm),
红(638/650nm)
控制方式: TTL调制
工作环境: 室内(10~35°)



F010-06/03/12

Green / Blue / Red Laser Curtain Technical Parameters:

Power Supply: AC110V/AC230V, 50Hz~60Hz
Power Consumption: 10W max
Laser Power: G:60mw/B:300-1000mw/R:100-300mw
Laser Color: green (532nm), Blue (450nm),
R (638/650nm)
Control Mode: TTL modulation
Operating Environment: 10~35°indoor

单绿/单蓝/单红激光雨帘 技术参数:

电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: <10W
激光功率: 绿60mw, 蓝300-1000mw,
红100-300mw
激光颜色: 绿色(532nm), 蓝(450nm),
红(638/650nm)
控制方式: TTL调制
工作环境: 室内(10~35°)

F0971-53/56/58/59

Green/Red/Blue Laser Technical Parameters:

Power Supply: AC110V/AC230V, 50Hz~60Hz
Power Consumption: 50W max
Laser Power: Green(532nm)60mw/100mw,
Red(650nm)100mw,
Blue(450nm)200-1000mw
Laser Color: Green or Red or Blue
Scan System: Micro-step motor scanner,
big angle scanning
Control Mode: DMX-512, music control, automatic
Control Channel: 8
Operating Environment: 10~35°indoor
Inner Packing Size: 320×230×110mm
Gross Weight: 2.6KG max
Packing Size: 655×340×265mm (5 pcs)
Total weight: 14KG max

绿色/红色/蓝色激光灯 技术参数:

电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: <50W
激光功率: 532nm绿: 60mw/100mw,
650nm红: 100mw,
450nm蓝: 200-1000mw
激光颜色: 绿色或红色或蓝色
扫描系统: 高精度步进电机扫描系统,
大角度扫描
控制方式: DMX-512、自走、声控
控制通道: 8个DMX-512信号通道
工作环境: 室内(10~35°)
内包尺寸: 320×230×110mm
毛重: <2.6KG
外包尺寸: 655×340×265mm (5个/箱)
总重量: <14KG



F0973

RGY Tri Colour Laser Technical Parameters:

Power Supply: AC110V/AC230V, 50Hz~60Hz
Power Consumption: 30W
Laser Power: Green (532nm) 40mw
Red (650nm) 150mw
Laser Color: green & red & yellow
Scan System: Micro-step motor scanner,
big angle scanning
Control Mode: DMX-512, music control, automatic
Control Channel: 5
Operating Environment: 10~35°indoor
Inner Packing Size: 320×230×110mm
Gross Weight: 2.9KG
Packing Size: 655×340×265mm (5 pcs)
Total weight: 15.8KG

红绿黄三色激光 技术参数:

电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: 30W
激光功率: 绿光 (532nm) 40mw
红光 (650nm) 150mw
激光颜色: 绿色、红色、黄色
扫描系统: 高精度步进电机扫描系统,
大角度扫描
控制方式: DMX-512、自走、声控
控制通道: 5个
工作环境: 室内(10~35°)
内包尺寸: 320×230×110mm
毛重: 2.9KG
外包尺寸: 655×340×265mm (5个/箱)
总重量: 15.8KG



F1066

Red & Green Four Head Laser Light Technical Parameters:

Power Supply: AC110V/AC230V, 50Hz~60Hz
Power Consumption: 30W
Laser Power: Green(532nm)60mw
Red(650nm) 100mw*2
Laser Color: green & red
Scan System: Micro-step motor scanner,
Control Mode: DMX-512, music control, automatic
Control Channel: 5
Operating Environment: 10~35°indoor
Inner Packing Size: 700×250×180mm
Gross Weight: 4.7KG
Packing Size: 720×530×410mm (4 pcs)
Total weight: 20.5KG

红绿四头激光 技术参数:

电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: 30W
激光功率: 532nm绿60mw,
650nm红100mw*2
激光颜色: 绿色、红色
扫描系统: 高精度步进电机扫描系统,
控制方式: DMX-512、自走、声控
控制通道: 5个
工作环境: 室内(10~35°)
内包尺寸: 700×250×180mm
内包毛重: 4.7KG
外包尺寸: 720×530×410mm (4个/箱)
外包毛重: 20.5KG

F1066B/F1066C

5/4 Color Four Head Laser Light Technical Parameters:

Laser Power: Green(532nm)60mw, Red(650nm)
150mw*1+100mw*2, Purple(405nm)
100mw, Green(532nm)60mw, Red(650nm)
100mw*2, Blue(450nm)200-300mw
Laser Color: green & red & purple & yellow & fuchsia
green & red & blue & yellow
Scan System: Micro-step motor scanner,
Control Mode: DMX-512, music control, automatic
Control Channel: 5
Operating Environment: 10~35°indoor
Inner Packing Size: 700×250×180mm
Gross Weight: 5.3KG
Packing Size: 720×530×410mm (4 pcs)
Total weight: 23.5KG

五彩/四色缤纷激光灯 技术参数:

激光功率: 532nm绿60mw, 650nm红光
(150mw*1+100mw*2),
405nm紫光100mw
532nm绿60mw, 650nm红光
100mw*2, 450nm蓝光200-300mw
激光颜色: 绿色、红色、紫色、黄、品红
或者绿色、红色、蓝色、黄色
扫描系统: 高精度步进电机扫描系统
控制方式: DMX-512、自走、声控
控制通道: 5个
工作环境: 室内(10~35°)
内包尺寸: 700×250×180mm
内包毛重: 5.3KG
外包尺寸: 720×530×410mm (4个/箱)
外包毛重: 23.5KG




F1022/F1022G/F1022B/F1022Y/F1022M/F1022D

Double Head Laser Light Technical Parameters:

Power Consumption: 60W max
Laser Power: F1022: Green(532nm)40mw & Red
(650nm) 100mw
F1022G: Green(532nm) 60mw
F1022B: Blue(450nm)500-1000mw
F1022Y: Green(532nm)80mw & Red
(650nm) 150mw
F1022M: Blue(450nm)500mw & Red
(650nm) 150mw
F1022D: Green(532nm)40mw & Blue
(450nm)300mw
Laser Color: F1022: Green & Red, F1022G: Green
F1022B: Blue, F1022Y: Green & Red
& Yellow, F1022M: Blue & Red & fuchsia
F1022D: Green & Blue
Inner Packing Size: 345×290×165mm
Gross Weight: 3.3KG
Packing Size: 910×370×320mm (5 pcs)
Total weight: 18.5KG

双头激光 技术参数:

额定功率: <60W
激光功率: F1022: 绿(532nm)40mw, 红
(650nm) 100mw
F1022G: 绿(532nm) 60mw
F1022B: 蓝(450nm)500-1000mw
F1022Y: 绿(532nm)80mw 和
红(650nm) 150mw
F1022M: 蓝(450nm)500mw,
红(650nm) 150mw
F1022D: 绿(532nm)40mw &
蓝(450nm)300mw
激光颜色: F1022: 绿和红, F1022G: 绿
F1022B: 蓝, F1022Y:
绿、红、黄, F1022M:
蓝、红、品红
F1022D: 绿、蓝
内包尺寸: 345×290×165mm
内包毛重: 3.3KG
外包尺寸: 910×370×320mm, (5个/箱)
外包毛重: 18.5KG





F1238

RGB 8 Head Laser Light 红绿蓝8头激光灯

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ
Power Consumption: 80W
Laser Power: Green(532nm)60mw*3, Red(650nm)
150mw*3, Blue(450nm)200mw*2

Laser Color: green & red & blue
Scan System: Micro-step motor scanner, big angle scanning
Control Mode: DMX-512, music control, automatic
Control Channel: 26

Operating Environment: 10~35°indoor

技术参数:

电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: 80W
激光功率: 532nm绿60mw*3, 650nm红光150mw*3,
450nm蓝光200mw*2
激光颜色: 绿色、红色、蓝色
扫描系统: 高精度步进电机扫描系统, 大角度扫描
控制方式: DMX-512、自走、声控
控制通道: 26个
工作环境: 室内(10~35°)

F1237

7 color 7 Head Laser Light 七头七色激光灯

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ
Power Consumption: 80W
Laser Power: Green(532nm)60mw*3, Red(650nm)
100mw*1+150mw*3, Blue(450nm)200mw*2

Laser Color: RGB 7 color
Scan System: Micro-step motor scanner, big angle scanning
Control Mode: DMX-512, music control, automatic
Control Channel: 12

Operating Environment: 10~35°indoor

技术参数:

电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: 80W
激光功率: 532nm绿60mw*3, 650nm红光100mw*1,
650nm红光150mw*3, 450nm蓝光200mw*2
激光颜色: 红、绿、蓝、白、黄、粉红、青
扫描系统: 高精度步进电机扫描系统, 大角度扫描
控制方式: DMX-512、自走、声控
控制通道: 12个
工作环境: 室内(10~35°)

F100-06/03/12

10 Head Green / Blue / Red Laser Curtain 技术参数:

Power Supply: AC110V/AC230V, 50HZ~60HZ
Power Consumption: 30W max
Laser Power: G:60mw/B:300-1000mw/R:100-300mw
Laser Color: green (532nm), Blue (450nm),
R (638/650nm)
Control Mode: TTL modulation
Operating Environment: 10~35°indoor

10孔单绿/单蓝/单红激光雨帘 技术参数:

电源供应: AC110V/AC230V, 50Hz~60Hz
额定功率: <30W
激光功率: 绿60mw, 蓝300-1000mw,
红100-300mw
激光颜色: 绿色(532nm)、蓝(450nm)、
红(638/650nm)
控制方式: TTL调制
工作环境: 室内(10~35°)



High power green laser landmark can be installed in the top buildings, such as tourist attractions and other outdoor place, is a laser application technology, computer image processing technology and speed scanner control of high-tech products. This products used high power green laser, can deduce dynamic short line, surface, rotating and geometric patterns, also can play text editor. Laser patterns can scan 360-degree, can enjoy its unique laser effects in a far place, wonderful effects, robust, shock, is the city landmark, the famous scenic, can become a shining landmark in the city and the unique urban landscape, urban lighting project a symbol of high quality.

高功率绿激光地标可安装在城市高层大厦顶端, 旅游景点等户外场所, 是集激光应用技术、计算机图像处理技术和超高速振镜控制技术于一体的高科技产品。该产品使用高功率的绿激光, 可在空中演绎出各种动态的线、面、旋转体等几何图案, 也可演绎编辑的各种图形文字。纯粹绚丽的激光图案可360度全方位扫描, 方圆数公里均能观赏到其独特的激光夜景, 视觉效果强劲、震撼, 具有王者风范, 是都市标志性建筑、著名景区的点睛之“笔”, 能使该建筑物活景区成为城市中耀眼的地标及独特的城市夜景, 是城市亮化工程中高品质的象征。



HW-910/920/930/940

Laser Landmarks 10W-40W

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power Consumption: 1500W max
Laser Power: 10W-40W
Laser Color: Green(532nm)
Scan System: high speed scanner
≥20kpps vibratory mirror system
Single line range: 1KM-10KM
Range Scanning: 1KM-5KM
Pan: 360 degree
Control Software: Pangolin or Phoneix
Cool System: fan

10W~40W风冷地标激光灯

技术参数:

电源供应: AC100~240V, 50Hz~60Hz
额定功率: <1500W
激光功率: 10W-40W
激光颜色: 翠绿色(532nm)
扫描系统: 高速振镜扫描 ≥20Kkpps, 具有完善的过压、过流、过热等监控和保护功能
单线射程距离: 1KM-10KM
扫描距离: 1KM-5KM
旋转角度: 水平360度
控制软件: 美国Pangolin(穿山甲), 德国Phoenix(火凤凰)
冷却方式: 风冷

Laser man is the laser programming, creative dance, music to combine a new laser performers, along with the rhythm of the music, laser dancer seems to have been given life, form time to time with the shadow moving. The beam of light is the best, gorgeous and surprise, applicable for Disco, Clubs, KTV station, pub, bar where the special dancing effect required.

激光人是融合了激光编程、舞蹈创意、音乐制作三位一体的全新激光舞蹈表演形式, 伴随着动感的音乐节奏, 舞者就像光影界的魔术师, 激光仿佛被赋予了生命的灵性, 时而光随影动, 时而人舞交融。每一束光线都是最好的道具, 或绚烂或惊奇。

激光人表演系统一般由激光器、控制软件及表演程序、激光扫描组件、舞台、激光笔等组成。适用于Disco, 演艺吧、夜总会、电视台、歌剧院等要求较高的场所使用。



F5000-820/830/850/950

Laser Man

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power Consumption: 200W max
Laser Power: Green2W/3W/5W or RGB 5W
Laser Color: Green(532nm) or RGB
Scan System: high speed scanner 40kpps
vibratory mirror system
Control Mode: ILDA
Control Software: Pangolin or Phoneix
Operating Environment: 10~35°indoor

激光人

技术参数:

电源供应: AC100~240V, 50Hz~60Hz
额定功率: <200W
激光功率: 绿2W/3W/5W或RGB 5W
激光颜色: 翠绿色(532nm)或RGB
扫描系统: 40kpps振镜扫描
控制方式: ILDA
控制软件: 美国Pangolin(穿山甲), 德国Phoenix(火凤凰)
工作环境: 室内(10~35°)

NK-1102X/NK-802X

产品名称：智能控制箱

功能简介：智能控制箱是智能灯光控制系统的核心组件：常照照明灯、娱乐效果灯、门牌服务灯、具DMX512功能的娱乐效果灯、摇头灯、RGB/全彩灯带、排风、空调、点歌系统的切换选择、音量调整功能和播控等包房几乎全部设施均可集中此设备统一控制。

基本参数：

- ◆ 工作电压：AC220V 50Hz
- ◆ 开关路数及功率：2*3KW+8*1KW/2*3KW+6*1KW
- ◆ 2路调光通道：AC220V 1KW*2
- ◆ 总负载：≤6KW（不含空调，不含DMX灯具电源）
- ◆ 灯光场景模式：16个（1-8场景具有DMX512学习功能，9-14场景具有开关和调光功能，场景15为全关，场景16为全开）。
- ◆ 场景叠加、切换、开关：继电器通道单独切换
- ◆ 面板直连：支持
- ◆ 风机盘管式中央空调控制：高中低风+闸开/关
- ◆ 风机空调控制（多联机、风管机）：红外控制
- ◆ DMX512通道数：256CH（V0.9版本的256CH）
- ◆ DMX512学习时间：1-8场景DMX512总学习时间21分钟，每个场景学习时间由20秒至5分钟，时间可调。
- ◆ 灯光与歌曲类型同步：支持
- ◆ 灯光与音乐节奏同步：外接音频检测器
- ◆ RS232接口：3.5耳机插座*1
- ◆ RS485接口：RJ45*2
- ◆ 摇麦接口：5.0的2P插座*1
- ◆ 集成中控功能
- ◆ 外形尺寸（长X宽X高 mm）：345*185*75



NK-800

产品名称：DMX灯光控制器

功能简介：DMX灯光控制器可控制具DMX512功能的娱乐效果灯、摇头灯、RGB/全彩灯带以及红外控制风机空调（多联机、风管机）和播控

基本参数：

- ◆ 工作电压：AC220V 50Hz
- ◆ 灯光场景模式：8个具有DMX512学习功能的场景
- ◆ 面板直连：支持
- ◆ 风机空调控制（多联机、风管机）：红外控制
- ◆ DMX512通道数：256CH
- ◆ 灯光与歌曲类型同步：支持（需外接中控器）
- ◆ 灯光与音乐节奏同步：外接音频检测器
- ◆ RS232接口：3.5耳机插座*1
- ◆ RS485接口：RJ45*2
- ◆ 摇麦接口：5.0的2P插座*1
- ◆ 外形尺寸（长X宽X高 mm）：225*85*49



NK-810

产品名称：带中控灯光控制箱

功能简介：内置中控功能，8路开关可通过控制回路来控制照明灯具和娱乐效果灯，其中有三路可设置为空调高低风控制

基本参数：

- ◆ 工作电压：AC220V 50Hz
- ◆ 开关路数及功率：8*1KW
- ◆ 灯光场景：8个+开机场景
- ◆ 面板直连：支持
- ◆ 风机盘管式中央空调控制：高中低三档风速
- ◆ 灯光与点歌系统联动：支持
- ◆ 数据对接：支持
- ◆ 外形尺寸（长X宽X高 mm）：225*85*49



NK-D05/D08

产品名称：灯光控制器

功能简介：通过控制回路来控制照明灯具和娱乐效果灯

基本参数：

- ◆ 工作电压：AC220V 50Hz
- ◆ 开关路数及功率：5*1KW/8*1KW
- ◆ 总负载：≤6KW
- ◆ 灯光场景：8个+开机场景
- ◆ 面板直连：支持
- ◆ 数据对接：支持
- ◆ 灯光与点歌系统联动：支持，需要连接中控
- ◆ 外形尺寸（长X宽X高 mm）：225*85*49



NK-100

产品名称：中控器

功能简介：实现各类控制面板、控制器、门牌灯等与上位机之间的通讯中继，传输指令

产品特点：模块化设计，小巧、紧凑，可壁挂或固定于其它控制上；能力而散，门牌灯提供工作电源，系统有模块化主要接口：LINK接口4个，USB接口1个，3.5插孔接口1个

外形尺寸（长X宽X高 mm）：143*56*24



BPM-01

产品名称：音频检测器

功能简介：对音频信号的信号进行采集，并将音乐节奏BPM转换成数字信号输出至控制器，实现灯光同步的效果，更好的表现灯光的艺术效果

产品特点：内置拾音器，可以选择使用线路输入音频信号或拾音器采集两种方式

主要接口：立体声音频输入RCA1组，RJ45接口1个



NK-808

产品名称：LED解码器

功能简介：接受DMX512控制指令，用于对LED灯条实现RGB三色调光

产品特点：驱动能力强，3路每路20A（灯条长度可达20米），共阳方式，直流5~36V电压设计

主要接口：DMX控制线4PIN插头2组，驱动6PIN插头1组

外形尺寸（长X宽X高 mm）：125*57*25



NK-F03

产品名称：LED多色服务灯控制箱

功能简介：安装到用户自制的门牌服务灯内，通过按键可以设定颜色及亮度，双色闪烁指示状态

产品特点：可用按键调节，支持RGB无限混色，三色交替闪烁时间颜色可调，显示开房状态

主要接口：LINK接口2个



302D/303D/302HD/303HD

名称：30系列控制面板（灯光、空调、服务综合面板）

边框材质：铝合金电镀

触摸屏材质及类型：钢化玻璃，电容触摸

按键数量：15~18个

外形尺寸（高X宽X深mm）：115*185*12或185*115*12



302/301/303

名称：3系列控制面板

边框材质：铝合金电镀

触摸屏材质及类型：钢化玻璃，电容触摸

按键数量：12~18个

外形尺寸（高X宽X深mm）：115*185*12或185*115*12



701/705

名称：7系列控制面板

触摸屏材质及类型：钢化玻璃，电容触摸

按键数量：15/21个

外形尺寸（高X宽X深mm）：190*120*10

边框材质：ABS高光

按键数量：15/21个



202/202H/201/204/206

名称：2系列控制面板

触摸屏材质及类型：钢化玻璃，电容触摸

按键数量：12~18个

外形尺寸（高X宽X深mm）：240*110*9

边框材质：ABS高光

按键数量：15/21/16/19/16个



501

名称：5系列液晶触摸面板

液晶屏尺寸：10.1寸

液晶屏分辨率：1024*600

边框材质：ABS

触摸屏材质及类型：TOP cover，电容触摸

外形尺寸（高X宽X深mm）：262*165*15



M15/M02/M04/M07/M10/M12/M01/M03

门牌服务灯

基础材质和工艺：铝合金压铸框架，电镀或金框框架，电镀或亚克力材料或欧式铁艺件，烤漆

号牌材质及工艺：镜面亚克力印刷或黑色钛金板，激光雕刻或钢板激光雕刻，电镀

供电方式：LINK接口供电，无须另配电源





N-J025

LED Matrix Light

Technical Parameters:

Power Supply: AC90-240V, 50/60Hz

Power Consumption: 750W

Light Source: 25pcs RGB 30W (3 in 1 or white) LED

Control mode: DMX-512, music control,
automatic, master & slave

Channel: 8CH/20CH/80CH

Beam Angle: 45°, 25°, 15° (optional)

Operating Environment: indoor

25头LED 矩阵灯

技术参数:

输入电压: AC90-240V, 50/60Hz

额定功率: 750W

灯珠数量: 25颗30W 3-in-1 LED 或者单
色白光LED

控制模式: DMX512模式、主从机模式、
自走模式、声控模式

通道模式: (8CH/20CH/80CH)

3种DMX模式

光束角度: 45度/25度/15度选择

颜色范围: 1670万种颜色(0~100%饱和度可调)

工作环境: 室内使用

N-P026

100w RGB (3 in 1) COB LED PAR Light

Technical Parameters:

Power Supply: AC90-240V, 50Hz~60Hz

Power Consumption: 120W

Light Source: 1 pcs 100W RGB (3 in 1) COB LED

Beam angle: 40°

Color: 16.7 million for RGB

Control mode: DMX-512, music control,
automatic, master & slave

Strobe: 0-20Hz

Outer cover material: Aluminum body

100w RGB 3合1 COB LED PAR灯

技术参数:

电源供应: AC90-240V, 50Hz~60Hz

功率: 120W

光源: 1颗100w RGB (3合1) COB LED

发光角度: 40°

颜色: 1670万颜色变化

控制方式: DMX-512信号控制、声控、
自走、主从

频闪: 0-20Hz

机壳材料: 铸铝

N-P027

100W 2 in 1 COB LED PAR Light

Technical Parameters:

Power Supply: AC90-240V, 50Hz~60Hz

Power Consumption: 120W

Light Source: 1 pcs 100W White and Yellow 2 in 1

Function: Each color can be controlled alone,
8CTs inside (2800, 3200, 500, 4200,
4900, 5600, 5900, 6500K) Also you
can choose the CT in the DMX channels

Beam angle: 40°

Control mode: DMX-512, music control,
automatic, master & slave

Strobe: 0-20Hz

Outer cover material: Aluminum body

100w 2合1 COB LED PAR灯

技术参数:

电源供应: AC90-240V, 50Hz~60Hz

功率: 120W

光源: 1颗100w 正白和黄色(2合1)COB LED

功能: 每种颜色可单独控制, 内置了8种

色温可选 (2800, 3200, 3500,

4200, 4900, 5600, 5900, 6500K),

也可以通过控台来混色。

发光角度: 40°

控制方式: DMX-512信号控制、声控、
自走、主从

频闪: 0-20Hz

机壳材料: 铸铝



N-P022

18 pcs RGBW 5 in 1 LED Waterproof PAR Light

Technical Parameters:

Power Supply: AC90-240V, 50Hz~60Hz

Power Consumption: 300W

Light Source: 18 pcs 12W RGBW 5 in 1 LED

Beam angle: 25°, 40° (optional)

Color: 16.7 million for RGB

grade of waterproof: IP65

Control mode: DMX-512, music control,
automatic, master & slave

Outer cover material: Aluminum body

18颗RGBW 5合1防水PAR灯

技术参数:

电源供应: AC90-240V, 50Hz~60Hz

功率: 300W

光源: 18颗12W RGBW 5合1 LED

灯珠发光角度: 25°、40°可选

颜色: 1670万颜色变化

防水等级: IP65

控制方式: DMX-512信号控制、声控、
自走、主从

机壳材料: 铸铝

N-P015

24 pcs RGBW 4 in 1 LED Waterproof PAR Light

Technical Parameters:

Power Supply: AC90-240V, 50Hz~60Hz

Power Consumption: 300W

Light Source: 24 pcs 10W RGBW 4 in 1 LED

Beam angle: 25°, 40° (optional)

Color: 16.7 million for RGB

grade of waterproof: IP65

Control mode: DMX-512, music control,
automatic, master & slave

Outer cover material: Aluminum body

24颗 RGBW 4合1 LED 防水 PAR灯

技术参数:

电源供应: AC90-240V, 50Hz~60Hz

功率: 300W

光源: 24颗10W RGBW 4合1 LED灯珠

发光角度: 25°、40°可选

颜色: 1670万颜色变化

防水等级: IP65

控制方式: DMX-512信号控制、声控、
自走、主从

机壳材料: 铸铝

N-P016

18 pcs RGBW 4 in 1 LED Waterproof PAR Light

Technical Parameters:

Power Supply: AC90-240V, 50Hz~60Hz

Power Consumption: 200W

Light Source: 18 pcs 10W RGBW 4 in 1 LED

Beam angle: 25°, 40° (optional)

Color: 16.7 million for RGB

grade of waterproof: IP65

Control mode: DMX-512, music control,
automatic, master & slave

Outer cover material: Aluminum body

18颗 RGBW 4合1 LED 防水 PAR灯

技术参数:

电源供应: AC90-240V, 50Hz~60Hz

功率: 200W

光源: 18颗10W RGBW 4合1 LED灯珠


发光角度: 25°、40°可选

颜色: 1670万颜色变化

防水等级: IP65

控制方式: DMX-512信号控制、声控、
自走、主从

机壳材料: 铸铝



N-P017

12pcs RGBW 4 in 1 LED Waterproof PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 150W
Light Source: 12 pcs 10W RGBW 4 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
grade of waterproof: IP65
Control mode: DMX-512, music control,
automatic, master & slave
Outer cover material: Aluminum body

12颗 RGBW 4合1 LED 防水 PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 150W
光源: 12颗10W RGBW 4合1 LED灯珠
发光角度: 25°, 40°可选
颜色: 1670万颜色变化
防水等级: IP65
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P007/ N-P008

36 pcs LED Waterproof PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 120W
Light Source: High power 1W or 3W LED,
36 pcs of leds: 12 Red, 12 Green, 12Blue
Beam angle: 15°, 25°, 45°(optional)
Color: 16.7 million for RGB
grade of waterproof: IP65
Control mode: DMX-512, music control,
automatic, master & slave
Outer cover material: Aluminum body

36颗 LED 防水 PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 120W
光源: 36颗1W/3W高功率LED(红色12颗,
绿色12颗, 蓝色12颗)
发光角度: 15°, 25°, 45°可选
颜色: 1670万颜色变化
防水等级: IP65
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P009/ N-P010

54 pcs LED Waterproof PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 120W/200W
Light Source: High power 1W or 3W LED,
54 pcs of leds: 12Red, 18Green, 18Blue,
6White
Beam angle: 15°, 25°, 45°(optional)
Color: 16.7 million for RGB
grade of waterproof: IP65
Control mode: DMX-512, music control,
automatic, master & slave
Outer cover material: Aluminum body

54颗LED防水 PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 120W/200W
光源: 54颗1W/3W高功率LED(红色12颗,
绿色18颗, 蓝色18颗, 白光6颗)
发光角度: 15°, 25°, 45°可选
颜色: 1670万颜色变化
防水等级: IP65
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P021

18 pcs RGBW 5 in 1 LED PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 300W
Light Source: 18 pcs 12W RGBW 5 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control,
automatic, master & slave
Outer cover material: Aluminum body

18颗RGBW 5合1 PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 300W
光源: 18颗12W RGBW 5合1 LED
灯珠发光角度: 25°, 40°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P018

24 pcs RGBW 4 in 1 LED PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 300W
Light Source: 24 pcs 10W RGBW 4 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic,
master & slave
Outer cover material: Aluminum body

24颗 RGBW 4合1 LED PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 300W
光源: 24颗10W RGBW 4合1 LED灯珠
发光角度: 25°, 40°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P019

18 pcs RGBW 4 in 1 LED PAR Light
Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 200W
Light Source: 18 pcs 10W RGBW 4 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic,
master & slave
Outer cover material: Aluminum body

18颗 RGBW 4合1 LED PAR灯
技术参数:
电源供应: AC90~240V, 50Hz~60Hz
功率: 200W
光源: 18颗10W RGBW 4合1 LED灯珠
发光角度: 25°, 40°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制、声控、
自走、主从
机壳材料: 铸铝



N-P020

12 pcs RGBW 4 in 1 LED PAR Light
12颗 RGBW 4合1 LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 200W
Light Source: 12 pcs 10W RGBW 4 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave

Outer cover material: Aluminum body

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 200W
光源: 12颗10W RGBW 4合1 LED灯珠
发光角度: 25°、40°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制、声控、自走、主从

机壳材料: 铸铝



N-P012

54 pcs RGB 3 in 1 LED PAR Light
54颗RGB 3合1 LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 200W
Light Source: 54 pcs 3W RGB 3 in 1 LED
Beam angle: 25°, 40°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave

Outer cover material: Aluminum body

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 200W
光源: 54颗3W RGB 3合1 LED
发光角度: 25°、40°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制、声控、自走、主从

机壳材料: 铸铝



N-P001

18 pcs 1W LED PAR Light
18颗1W LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 20W
Light Source: 18 pcs 1W LED
Beam angle: 15°, 25°, 45°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 20W
光源: 18颗1W LED
发光角度: 15°、25°、45°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制、声控、自走、主从

N P0023/ N P0024

7 pcs RGBW 4in1 LED PAR Light 7颗RGBW 4合1 LED PAR灯
6 pcs RGB 3in1 LED PAR Light 6颗RGB 3合1 LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 20W
Light Source: 7 pcs RGBW 4 in 1 4W LED / 6 pcs RGB 3 in 1 3W LED
Beam angle: 25°, 45°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 20W
光源: 7颗RGBW 四合一 4W LED / 6颗RGB 三合一 3W LED
发光角度: 15°、25°、45°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制、声控、自走、主从



N-P003 / N-P004

36 pcs LED PAR Light 36颗 LED PAR灯

Technical Parameters:

Power Supply: AC90~240V 50HZ~60HZ
Power Consumption: 120W max
Light Source: High power 1W or 3W LED, 36 pcs of leds: 12 Red, 12 Green, 12Blue
Beam angle: 15°, 25°, 45°(optional)
Color: RGB color mixing
Function: Color Changing, Strobe, Speed, Luminance adjustable, etc.
Control mode: DMX-512, music control, automatic, master & slave
Channel: 6 channels
Outer cover material: Aluminium, black and white
Operating Environment: indoor

技术参数:

额定电压: AC90~240V 50Hz~60Hz
功率: <120W
光源: 36颗1W/3W高功率LED (红色12颗, 绿色12颗, 蓝色12颗)
发光角度: 15°、25°、45°可选
颜色: RGB混色
功能: 颜色变化、频闪、渐变、速度、亮度调节
控制方式: DMX-512、声控、自走、主从
控制通道: 6通道
机壳材料: 铝, 有黑色和白色
工作环境: 室内



N-P005 / N-P006

36 pcs LED PAR Light 36颗 LED PAR灯

Technical Parameters:

Power Supply: AC90~240V 50HZ~60HZ
Power Consumption: 60W/120W
Light Source: High power 1W or 3W LED, 36 pcs of leds: 12 Red, 12 Green, 12Blue
Beam angle: 15°, 25°, 45°(optional)
Color: RGB color mixing
Function: Color Changing, Strobe, Speed / Luminance adjustable, etc.
Control mode: DMX-512, music control, automatic, master & slave
Channel: 6 channels
Outer cover material: Aluminium
Operating Environment: indoor

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 60W/120W
光源: 36颗1W/3W高功率LED (红色12颗, 绿色12颗, 蓝色12颗)
发光角度: 15°、25°、45°可选
颜色: RGB混色
功能: 颜色变化、频闪、渐变、速度/亮度调节
控制方式: DMX-512、声控、自走、主从
控制通道: 6通道
机壳材料: 铸铝
工作环境: 室内



N-P013/ N-P014

54 pcs LED PAR Light 54颗LED PAR灯

Technical Parameters:

Power Supply: AC90~240V 50HZ~60HZ
Power Consumption: 120W/200W
Light Source: High power 1W or 3W LED, 54 pcs of leds: 12Red, 14Green, 14Blue, 14White
Beam angle: 15°, 25°, 45°(optional)
Color: 16.7 million for RGB
Control mode: DMX-512, music control, automatic, master & slave
Outer cover material: Aluminum body, black

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 120W/200W
光源: 54颗1W/3W高功率LED (红色12颗, 绿色14颗, 蓝色14颗, 白光14颗)
发光角度: 15°、25°、45°可选
颜色: 1670万颜色变化
控制方式: DMX-512信号控制、声控、自走、主从
机壳材料: 铸铝

N P025

54 3W Warm white LED PAR Light 54颗3W 暖白LED PAR灯

Technical Parameters:

Power Supply: AC90~240V, 50HZ~60HZ
Power Consumption: 200W
Light Source: High power 3W Warm white LED
Beam angle: 15°, 25°, 45°(optional)
Color Temperature: 2800K~3200K
Control mode: DMX-512, music control, automatic, master & slave
Channel: 4/8 channels
Outer cover material: Aluminum body, black

技术参数:

电源供应: AC90~240V, 50Hz~60Hz
功率: 200W
光源: 54颗3W高功率暖白LED
发光角度: 15°、25°、45°可选
色温: 2800~3200K
控制方式: DMX-512信号控制、声控、自走、主从
控制通道: 4/8通道 (可选)
机壳材料: 铸铝, 颜色为: 黑色





2014/2014A

Mini LED Super Rocket

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 25W
Light Source: 4 pcs 3W or 6 pcs 1W led
Color: 4 or 6 color
Control mode: DMX-512, music control, automatic
Channel: 8 channels
Operating Environment: indoor

LED迷你无级灯

技术参数:
额定电压: AC100~240V, 50Hz~60Hz
功率: 25W
光源: 4颗3W或6颗1W灯珠
颜色: 四色或六色
控制方式: DMX-512, 声控, 自走
控制通道: 8通道
工作环境: 室内



N-X013A

Mini LED Butterfly

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 30W
Light Source: 2 pos 10W (USA cree RGBW 4in1) LED
Color: seven color
Control mode: DMX-512, music control, automatic
Channel: 8 channels
Lens: 8*2 PCS
Operating Environment: indoor

迷你LED蝴蝶灯

技术参数:
额定电压: AC100~240V, 50Hz~60Hz
功率: 30W
光源: 2颗10W (美国科瑞RGBW四合一) 灯珠
颜色: 七彩色
控制方式: DMX-512, 声控, 自走
控制通道: 8通道
镜片: 8*2片
工作环境: 室内



N-X015/X015A

Mini LED Butterfly

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 25W
Light Source: 2 pcs 10W (USA cree RGBW 4in1)
Color: seven color
Control mode: DMX-512, music control, automatic
Channel: 8 channels
Lens: 6*2 PCS or 5*2 pcs
Operating Environment: indoor

迷你LED蝴蝶灯

技术参数:
额定电压: AC100~240V, 50Hz~60Hz
功率: 25W
光源: 2颗10W (美国科瑞RGBW四合一) 灯珠
颜色: 七彩色
控制方式: DMX-512, 声控, 自走
控制通道: 8通道
镜片: 6*2片或5*2片
工作环境: 室内



N-X016

Mini LED Super Rocket

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 25W
Light Source: 4 pcs 3W (USA CREE)
Color: Red and Green and Blue and White
Control mode: DMX-512, music control, automatic
Channel: 8 channels
Operating Environment: indoor

LED无级灯

技术参数:
额定电压: AC100~240V, 50Hz~60Hz
功率: 25W
光源: 4颗3W (美国科瑞) LED灯珠
颜色: 红绿蓝白
控制方式: DMX-512, 声控, 自走
控制通道: 8通道
工作环境: 室内



N-X013

LED Butterfly

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 40W
Light Source: 2 pcs 10W (USA cree RGBW 4in1)
Color: seven color
Control mode: DMX-512, music control, automatic
Channel: 8 channels
Operating Environment: indoor

LED蝴蝶灯

技术参数:
额定电压: AC100~240V, 50Hz~60Hz
功率: 40W
光源: 2颗10W (美国科瑞RGBW四合一) 灯珠
颜色: 七彩色
控制方式: DMX-512, 声控, 自走
控制通道: 8通道
工作环境: 室内



N-X013B


Mini LED Super Rocket

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 25W
Light Source: 4 pcs 3W
Color: Red and Green and Blue and White
Control mode: DMX-512, music control, automatic
Channel: 8 channels
Lens: 8*8 PCS
Operating Environment: indoor

Mini LED无级箭

技术参数:
额定电压: AC100~240V, 50Hz~60Hz
功率: 25W
光源: 4颗3W LED灯珠
颜色: 红绿蓝白
控制方式: DMX-512, 声控, 自走
控制通道: 8通道
镜片: 8*8片
工作环境: 室内



N-X024/N-X024A

LED ZOOM Magic Crystal Ball

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ
Power consumption: 20W
Light Source: 4 pcs 3W (CREE) / 2 pcs 10W (USA CREE) RGBW 4in1
Color: RGB or RGBW
Control mode: DMX-512, music, automatic
Channel: 6 channels
Operating Environment: indoor

LED调焦水晶魔球

技术参数:

额定电压: AC110V/AC230V, 50Hz~60Hz
功率: 20W
光源: 4颗3W (科瑞) 或2颗10W 四合一 (科瑞)
颜色: 红、绿、蓝或红、绿、蓝、白
控制方式: DMX-512信号控制, 声控, 自走
控制通道: 6通道
工作环境: 室内



N-X014

LED Magic Crystal Ball

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ
Power consumption: 25W
Light Source: 6 pcs 3W LED
Color: Red and Green and Blue
Control mode: DMX-512, music, automatic
Channel: 6 channels
Operating Environment: indoor

LED水晶魔球

技术参数:

额定电压: AC100~240V, 50Hz~60Hz
功率: 25W
光源: 6颗3W LED
颜色: 红、绿、蓝
控制方式: DMX-512信号控制, 声控, 自走
控制通道: 6通道
工作环境: 室内



N-X014A/N-X014B

LED Magic Crystal Ball

LED MP3 Magic Crystal Ball

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ
Power consumption: 20W
Light Source: 6 pcs 1W or 3 pcs 1W
Color: 6 color: Red and Green and Blue and white and yellow and pink
Or 3 color: Red and Green and Blue
Control mode: automatic, remote control
Operating Environment: indoor

LED水晶魔球

LED MP3水晶魔球

技术参数:

额定电压: AC110V/AC230V, 50Hz~60Hz
功率: 20W
光源: 6颗1W 或3颗1W 灯珠
颜色: 6色: 红、绿、蓝、白、黄、粉
或3色: 红绿蓝
控制方式: 仅自走或自走、声控、遥控
工作环境: 室内



N-X004

KTV MINI Matrix Light Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ

Power consumption: 30W

Light Source: 64 pcs Φ5 LEDs

Color: Red and Green and Blue and white

Control mode: music control, automatic

Outer cover material: Iron

Operating Environment: indoor

KTV 迷你小矩阵灯 技术参数:

额定电压: AC110V/AC230V, 50Hz~60Hz

功率: 30W

光源: 64 颗高亮度 Φ5 LED

颜色: 红、绿、蓝、白

控制方式: 声控、自走

机壳材料: 铁

工作环境: 室内



N-X001

LED Seven Heads Magic Light Technical Parameters:

Power Supply: AC110V/AC230V 50HZ~60HZ

Power consumption: 60W max

Light Source: 469 pcs Φ5 LEDs

Color: Red and Green and Blue

Function: 7 gobo teams dynamic change, Zoom out or Zoom in for each team is available, gobo speed change adjustable, gobo with flash function, etc.

Control mode: DMX-512, music control, automatic, master & slave

Channel: 9 or 11 channels

Outer cover material: Iron and Aluminium

Operating Environment: indoor

LED七头魔幻灯 技术参数:

额定电压: AC110V/AC230V 50Hz~60Hz

功率: <60W

光源: 469颗高亮度 Φ5 LED

颜色: 红、绿、蓝

功能: 7组图案动态变换, 每组图案均可放大缩小, 图案变换速度可调节, 并设有频闪功能

控制方式: DMX-512, 声控、自走、主从

控制通道: 9通道/11通道

机壳材料: 铁和铝

工作环境: 室内



N-X017

LED Crystal Mushroom Technical Parameters:

Power Supply: AC100-240V, 50HZ~60HZ

Power consumption: 35W

Light Source: 1 pcs 9W LED

Color: Red and Green and Blue

Control mode: DMX-512, music, automatic

Operating Environment: indoor

LED蘑菇灯 技术参数:

额定电压: AC110V/AC230V, 50Hz~60Hz

功率: 35W

光源: 1颗9W LED

颜色: 红、绿、蓝

控制方式: DMX-512信号控制, 声控、自走

工作环境: 室内



N-X003

LED Four Head Laser Light Technical Parameters:

Power Supply: AC110V/AC230V 50HZ~60HZ

Power consumption: 20W

Light Source: 256 pcs Φ5 LEDs

Color: Red and Green and Blue

Function: 85 Gobos Dynamic change, simulate the laser beam effect, the gobos can move by level and vertical, rotate, enlarge and narrow changeable, flashes frequency and the brightness is adjustable.

Control mode: DMX-512, music control, automatic, master & slave

Channel: 10 channels

Outer cover material: Iron

Operating Environment: indoor

LED四头线条灯 技术参数:

额定电压: AC110V/AC230V 50Hz~60Hz

功率: 20W

光源: 256颗高亮度 Φ5 LED

颜色: 红、绿、蓝

功能: 85种图案动态变换, 图案可移动翻转变, 放大缩小, 变换速度可调节, 并具有渐隐、频闪、亮度调节等功能

控制方式: DMX-512, 声控、自走、主从

控制通道: 10通道

机壳材料: 铁

工作环境: 室内



N-X036

LED 4 eyes infinite Beam Light Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ

Power consumption: 60W

Light Source: 4 pcs 10w RGBW(4 in 1) LEDs

Color: RGBW

Control mode: DMX-512, music, automatic

Operating Environment: indoor

LED四眼无限光束灯 技术参数:

额定电压: AC110V/AC230V, 50Hz~60Hz


功率: 60W

光源: 4颗RGBW 4合一灯珠

颜色: 红、绿、蓝、白

控制方式: DMX-512信号控制, 声控、自走

工作环境: 室内



N-X007

LED small airship Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 20W

Light Source: 64 pcs Φ10 LEDs

Color: Red and Green and Blue and white

Control mode: music control, automatic

Operating Environment: indoor

LED小飞艇 技术参数:

额定电压: AC100~240V, 50Hz~60Hz

功率: 20W

光源: 64颗高亮度 Φ10 LED

颜色: 红、绿、蓝、白

控制方式: 声控、自走

工作环境: 室内



N-X023

LED PYRAMID LIGHT Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 60W

Light Source: 4 pcs 10W (USA cree RGBW 4 in 1)

Color: RGBW

Control mode: DMX-512, music control, automatic

Channel: 8 channels

Operating Environment: indoor

LED魅力四射 技术参数:

额定电压: AC100~240V, 50Hz~60Hz

功率: 60W

光源: 4颗10W(美国科瑞RGBW四合一)灯珠

颜色: 红绿蓝白

控制方式: DMX-512, 声控、自走

控制通道: 8通道

工作环境: 室内



N-X012

LED Magic Crystal Ball Technical Parameters:

Power Supply: AC110V/AC230V 50HZ~60HZ

Power consumption: 20W

Light Source: 9W LED diodes

Color: Red and Green and Blue

Control mode: DMX-512, music, automatic, master & slave

Channel: 7 channels

Outer cover material: Iron

Operating Environment: indoor

LED水晶魔球 技术参数:

额定电压: AC110V/AC230V 50Hz~60Hz

功率: 20W

光源: LED 大功率 9W

颜色: 红、绿、蓝

控制方式: DMX-512信号控制, 声控、自走、主从

控制通道: 7通道

机壳材料: 铁

工作环境: 室内



N-X021

LED new small sun light

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 10W

Light Source: 48 pcs Φ10 LEDs

Color: Red and Green and Blue

Control mode: automatic

Operating Environment: indoor

LED 小太阳灯

技术参数:

额定电压: AC100~240V, 50HZ~60HZ

功率: 10W

光源: 48颗高亮度 Φ10 LED

颜色: 红、绿、蓝

控制方式: 自走

工作环境: 室内



N-X020

LED 6 EYES FLOWER

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 25W

Light Source: 1 pcs 15W RGB LED

Color: RGB

Control mode: DMX-512, music control, automatic, master & slave

Operating Environment: indoor

LED六眼灯泡灯

技术参数:

额定电压: AC100~240V, 50HZ~60HZ

功率: 20W

光源: 1颗15w RGB LED

颜色: 红、绿、蓝

控制方式: DMX512, 自走、声控、主从

工作环境: 室内



N-X025

LED CRYSTAL MAGIC & SUNFLOWER LIGHT

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ

Power consumption: 20W

Light Source: 3 pcs 1W + 48 pcs 5mm led

Color: RGB

Control mode: automatic, music control, rotary effect + Sunshine effect

Operating Environment: indoor

LED水晶魔球太阳灯

技术参数:

额定电压: AC110V/AC230V, 50Hz~60Hz

功率: 20W

光源: 3颗1W+ 48颗5mm高亮度灯珠
(16颗红色, 16颗蓝色, 16颗绿色)

颜色: 红、绿、蓝

控制方式: 自走、声控

效果: 水晶魔球效果+太阳灯效果

工作环境: 室内



N-X026

Ceiling LED EFFECT LIGHT

Technical Parameters:

Power consumption: 30W

Light Source: 4 or 6 pcs 3W led

Color: RGBW OR RGBWYP

吸顶LED水晶魔球

技术参数:

功率: 30W

光源: 4颗/6颗3W灯珠

颜色: 红、绿、蓝、白或红、绿、

蓝、白、黄、紫



N-X019

LED white spotlight

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ

Power consumption: 10W

Light Source: 1 pcs 3W/5W (USA CREE) LED

Color: White

Control mode: automatic

Operating Environment: indoor

LED白色射灯

技术参数:

额定电压: AC110V/AC230V, 50Hz~60Hz

功率: 10W

光源: 1颗3W/5W (美国科瑞) LED

颜色: 白色

控制方式: 自走

工作环境: 室内



N-X018

LED 7 colors spotlight

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 15W

Light Source: 1 pcs 10W (RGBW 4 IN 1) LEDs

Color: 7 colors

Control mode: DMX-512, music control, automatic

Channel: 6 channels

Operating Environment: indoor

LED七彩射灯

技术参数:

额定电压: AC100~240V, 50HZ~60HZ

功率: 15W

光源: 1颗10w (RGBW 4 in 1) LED

颜色: 七彩

控制方式: DMX512, 自走、声控

控制通道: 6通道

工作环境: 室内



N-X027

LED 7 colors spotlight

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 15W

Light Source: 1 pcs 10W (RGBW 4 IN 1) LEDs

Color: 7 colors

Control mode: music control, automatic

Operating Environment: indoor

LED自走七彩射灯

技术参数:

额定电压: AC100~240V, 50HZ~60HZ

功率: 15W

光源: 1颗10w (RGBW 4 in 1) LED

颜色: 七彩

控制方式: 自走、声控

工作环境: 室内



N-X028/N-X029

LED 7 colors/White Ceiling spotlight

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 15W

Light Source: 1 pcs 10W (RGBW 4 IN 1)/1pcs

3-10W White LED

Color: 7 colors or white

Control mode: music control, automatic,

Induction control (optional)

Operating Environment: indoor

LED吸顶七彩/白光射灯

技术参数:

额定电压: AC100~240V, 50HZ~60HZ

功率: 15W

光源: 1颗10w (RGBW 4 in 1) 或

1颗3-10W 白色LED

颜色: 七彩或白色

控制方式: 自走、声控、感应控制 (可选)

工作环境: 室内



N-X030

LED 7 colors Ceiling washing light

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 20W

Light Source: 1 pcs 15W (RGB 3 IN 1) LED

Color: RGB mixing color

Control mode: music control, automatic,

DMX512 control (optional),

Induction control (optional)

Operating Environment: indoor

吸顶LED七彩染色灯

技术参数:

额定电压: AC100~240V, 50HZ~60HZ

功率: 20W

光源: 1颗15W (RGB 3 in 1) LED

颜色: RGB混色

控制方式: 自走、声控、DMX512(可选)、

感应控制 (可选)

工作环境: 室内



N-X031

LED 7 colors Ceiling washing light

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 20W

Light Source: 2 pcs 15W (RGB 3 IN 1) LED

Color: RGB mixing color

Control mode: music control, automatic,

DMX512 control (optional),

Induction control (optional)

Operating Environment: indoor

吸顶LED七彩染色灯

技术参数:

额定电压: AC100~240V, 50HZ~60HZ

功率: 20W

光源: 2颗15W (RGB 3 in 1) LED

颜色: RGB混色

控制方式: 自走、声控、DMX512(可选)、

感应控制 (可选)

工作环境: 室内

N-X035

LED Full Color Kaleidoscope Light

Technical Parameters:

Power supply: AC 100-240 V 50/60Hz

Power Consumption: 90W

Light Source: 60W LED

Color: RGBW full color

Control mode: DMX-512, Music control,

Automatic

LED七彩万花筒

技术参数:


电源供应: AC 100-240V/50~60Hz,

功率: 90W

光源: 60W LED灯珠

颜色: RGBW全彩

控制模式: DMX-512/声控/自走



N-S022

MINI Strobe

Technical Parameters:

Power Supply: AC100~230V, 50HZ~60HZ

Power consumption: 25W

Light Source: 1 pcs 20W LED

Function: flash pace adjustable

Control mode: automatic, music control

Operating Environment: indoor

迷你20W频闪

技术参数:

额定电压: AC100~230V, 50HZ~60HZ

功率: 25W

光源: 1颗20W LED

功能: 频闪速度可调

控制模式: 自走、声控

工作环境: 室内



N-S007

LED White Strobe

Technical Parameters:

Power Supply: AC100~230V, 50HZ~60HZ

Power consumption: 20W

Light Source: 216pcs 5050 LED

Function: flash pace adjustable

Control mode: automatic, music control

Operating Environment: indoor

颗粒片频闪

技术参数:

额定电压: AC100~230V, 50HZ~60HZ

功率: 20W

光源: 216颗5050 LED

功能: 频闪速度可调

控制模式: 自走、声控

工作环境: 室内



N-S010/S011/S012/S020/S021

LED White Strobe

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 60W

Light Source: 20W/30W/50W/100W/150W
white LED

Function: flash pace adjustable

Control mode: music control, automatic

Outer cover material: Iron

Operating Environment: indoor

LED白光频闪

技术参数:

电源供应: AC100~240V, 50HZ~60HZ

功率: 60W max

光源: 20W/30W/50W/100W/150W
高功率白色LED

功能: 频闪速度可调

控制模式: 自走、声控

机壳材料: 铁

工作环境: 室内

N-S013/S014/S015

20w/30W/50W ceiling LED strobe light

Technical Parameters:

Power Supply: AC100~240V, 50HZ~60HZ

Power consumption: 60W

Light Source: 1 pcs 20W/30W/50W white LED

Function: flash pace adjustable

Control mode: music control, automatic

Outer cover material: Iron

Operating Environment: indoor

20w/30W/50W 吸顶LED频闪

技术参数:

电源供应: AC100~240V, 50HZ~60HZ

功率: 60W max

光源: 1颗20W/30W/50W 高功率白色LED

功能: 频闪速度可调

控制模式: 自走、声控

机壳材料: 铁

工作环境: 室内





N-S017

1000W Strobe

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ

Power consumption: 1200W

Lamp type : 1000W pulse tube

Function: flash pace adjustable

Control mode: automatic, controller control

Outer cover material: Iron

Operating Environment : indoor

1000W频闪

技术参数:

电源供应: AC110V/AC230V, 50HZ~60HZ

功率: 1200W

光源: 1000W脉冲管

功能: 频闪速度可调

控制模式: 自走、控制器控制

机壳材料: 铁

工作环境: 室内



N-S018

1500W Strobe

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ

Power consumption: 1800W

Lamp type : 1500W pulse tube

Function: flash pace/luminance adjustable

Control mode: automatic, controller control

Outer cover material: Iron

Operating Environment : indoor

1500W频闪

技术参数:

电源供应: AC110V/AC230V, 50HZ~60HZ

功率: 1800W

光源: 1500W脉冲管

功能: 频闪速度/亮度可调

控制模式: 自走、控制器控制

机壳材料: 铁

工作环境: 室内

N-S019

3000W DMX Strobe

Technical Parameters:

Power Supply: AC110V/AC230V, 50HZ~60HZ

Power consumption: 3500W

Lamp type : 3000W pulse tube

Function: 0-25 times / sec can be adjusted

continuously dazzling effects, and special effects can be edited. Intelligent thermal control, reducing the time required for cooling, with fan cooling. flash pace/luminance adjustable

Control mode: automatic, DMX512

Control Channel : 1/3/4

Outer cover material: Iron

Operating Environment : indoor

3000W 炫目超强化DMX频闪

技术参数:

电源供应: AC110V/AC230V, 50HZ~60HZ

功率: 3500W

光源: 使用长效氙气灯管

功能: 频闪频率: 0-25次/秒可调节, 连续的炫目效果, 及可编辑的特殊效果。智能化热能控制, 减低冷却所需时间, 有风扇冷却功能。

控制模式: 自走、DMX512

控制通道: 1CH/3CH/4CH可选, 最大控制

通道4CH

机壳材料: 铁

工作环境: 室内



N-C1308

Controller 1308

Technical Parameters:

Power input: DC 9-12V 1000mA min

Dimensions: 250mmX150mmX100mm

Net Weight: 1.5kg

Also it have following functions except the parameter of download program-mes can not be changed. Choose 1 among the 7 different programmes Change the speed of the sequence of the programme

Run the programme normally or automatically

Stop the programme

Storage up to a maximum of 7 different programmes up to a maximum of 127 cues for each programme

It accepts up to a maximum of 512 DMX channels

The programmes are stored in a flash memory 4Mb

The advantage of Easy control is not only price but also convenient use method -- it is really very easy to operate even you not know anything about DMX 512 console before.

控制台1308

技术参数:

电源输入: DC9V 1000mA

外形尺寸: 250mmX150mmX100mm

重量: 1.5 kg

易控台除了不能直接更改下载的程序外还有如下功能:

- * 备有7个可录制编程空间
 - * 场景转换速度可调
 - * 可由手动或自动驱动场景转换
 - * 暂停场景转换功能
 - * 最多可以存储7个不同的程序, 每个程序可以有127个不同的步
 - * 它最多可以控制512个通道
 - * 程序是储存在一个4MB的闪存里
- 易控台的优点不仅在于价格而且操作方法非常方便 -- 是真正的易于操控的, 哪怕你从来没有用过DMX512控制台。

N-C1323

Controller 1323

Technical Parameters:

* 3Pin female DMX connector

* Dimension: 482X133X75 mm

* Net weight: about 2.2KG.

* Controls up to 12 intelligent lights of up to 16 channels each

* 23 banks of 8 scenes, 184 scenes max

* 192 DMX channels of control

* 6 sets of chases containing 240 scenes

* Sequential linking of chases

* Grab any fixture on the fly

* 3 space 19" rack mount

* MIDI compatible

* Beat activation, tap-sync and auto run

控制台1323

技术参数:

* 3芯母 DMX 输入座

* 尺寸: 482X133X75 mm

* 净重: 约 2.2KG.

* 可控每台有16通道的灯12台

* 可编程23个记忆储存 (bank), 每个可储存8个场景 (scene) 共计192通道

* 6个可编程程序 (chase), 每个程序可编184步 (即23个bank8个 scene)

* 步序 (chase) 可循环运行

* 可随意提灯操作

* 可拉声, 同步或是自动运行

* 标准19"机柜安装长度

* MIDI输入

* 断电、重启自动播放功能



N-C1312

Controller 1312

Technical Parameters:

* Frequency: 2.45GHz

* Transmit distance: 300m (Visible distance)

* Limitless receivers

* DMX channel: 512 CHL (each receiver)

* Antenna: Helical SMA antenna

* Electric: AC100-240V, 50/60Hz

* Dimension: 153 x 147 x 41mm

* Net Weight: 0.5kg (with AC power supply)

Specification:

* Maximum 16 transmitters at same place without any disturb.

Each transmitter has 512 channels and total 8192 channels.

* Professional and un-replaceable W-LAN product for convenient use to control as much as maximum lighting units you need especially for architectural building.

* Easy learn and operate

* One transmitter to one receiver, One transmitter to multiple receiver or Multiple transmitter to multiple receiver.

* Free set frequency and transmit password with transmitter and receiver via buttons on operation panel

控制台1312

技术参数:

* 频率: 2.45GHz

* 接收器数量不受限制

* 最近距离: 250米(无阻碍情况下)

* 尺寸: 153X147X41

* 电压: 100-240V, 50/50HZ

* 重量: 0.5KG (含电源)

* DMX通道数: 512通道(每一个接收器)

特征:

- * 同一个地点最多安装16个发送器, 准确快速互不干扰, 每一个发送器都有512通道, 最多可控制8192通道
- * 此产品非常专业, 是不可替代的简单实用的产品, 多台同时使用时可以最大限度的实现你想要控制的灯特别是在建筑上
- * 简单易学, 操作方便
- * 可以一发送一接收, 可以一发送多个接收, 也可以多个发送多个接收
- * 发送器和接收器可以通过按健切换频率和通讯密码可以自己设定





N-C512A

Controller 512A 控制台 512A

Technical Parameters:

Power supply: DC9V 1000mA
DMX512/1990 Standard, 512 channels
Up to 32 scanners may be connected with a maximum of 16 channels each assignable joystick for easy of movement, four keys fine adjustment
8 chases and 32 scenes can be run at the same time
32 chases (at most 120 steps for each chase)
3840 chase steps
The music trigger source can be selected between audio line input or in-build microphone
The Data auto-saves
DMX signal output connector: XLR-D3F X4
Size: 482mm×300mm×100mm
Net Weight: 6.0kg

技术参数:

电源输入: DC9V 1000mA
DMX512/1990信号输出, 512个控制通道
可同时控制32台16通道电脑灯
16个通道的控制推子
一个可设置的摇杆装置
可同时运行8个走灯程序和32个场景
32个走灯程序, 每个程序最大120步
共3840个电脑灯走灯程序步
走灯音乐同步, 线路电平-10dB--+10dB
自适应/机内话筒
关机数据保存
DMX信号输出连接器: XLR-D3F×4
外形尺寸: 482mm×300mm×110mm
重量: 6.0KG

N-CS512

Controller S512 控制台 S512

Technical Parameters:

Power input: DC9V 1000mA
DMX512/1990 standard, 512 DMX control channels, 4 output with optical isolated, withstand 2000Vrms.
Up to 32 scanners may be connected with a maximum of 16 channels each.
A large backlight LCD to display operation parameters.
16 sliders for channel, 1 slider for speed control.
1600 chase steps, 48 chases, up to 100 steps each. Each step contains its speed and cross time, can be set respectively. Trigger mode selectable: Music synchronously and manual speed.
Cooperating with the chase speed slider, the time of the program step can be changed from 0.03s to 180s.
48 scanner scenes can be used directly.
8 chases, 48 scenes operated at the same time.
At most 32 scanners can be selected
15 environment programs to output the combination, which are composed of different scenes, chases and manual output quickly.
Dimension: 498 x 420 x 115mm
Net Weight: 6.5kg

技术参数:

电源输入: DC9V 1000mA
DMX512/1990标准, 512个DMX控制通道
2路带光隔离的独立输出驱动端口, 具有抗2000VDC电气冲击能力
可控制32台16通道电脑灯
带背光的大屏幕LCD显示各种运行参数
1600个走灯程序步容量, 48个走灯程序, 每程序最多100步, 每步速度、渐变参数独立设置, 可随音乐同步或手动速度控制
在走灯速率推杆的配合下, 程序步的时间范围可从0.03S-180S
48个可直接调用的电脑灯场景
可同时运行8个走灯程序, 48个场景, 并可同时对32台电脑灯进行手动运行(提灯)
15个环境键, 快速调用不同的场景、走灯、手动运行组合
尺寸: 498mm×420mm×115mm
重量: 6.5KG

N-C200

Controller 200 控制台 200

Technical Parameters:

Power input: DC 9-12V 1000mA min
DMX512/1990 Standard
Total of 192 output channels
30 banks have 8 programmable scenes each
16 slider for manual control of channels
Midi control over banks, chases and Blackout
Record up to 6 programmable chases with fade time and speeds
LED function and program display
Built in microphone for music triggering
Auto mode program controlled by fade time sliders
Dimensions: 520mm×183mm×73mm
Net Weight: 3.0kg

技术参数:

电源输入: DC9V 1000mA
DMX512/1990信号输出, 192控制通道
有30个BANKS, 每个BANKS有8个可编程的SCENES
有16个可调位器调节输出大小, 内置MIC头, 提供声音触发, 在自动触发状态, 通过TAP SYNC键或SPEED电位器确定自动触发时间在MIDI接口, 可随时间MIDI信号控制, 4位数码显示屏, BLACK OUT功能可用于手动或MIDI做能控制, CHASES编程和CHASES运动功能, 可用手动或MIDI做能控制输出延时功能, 用FADE TIME电位器调节延时时间
外形尺寸: 520mm×183mm×73mm
重量: 3.0KG



N-C2024

Controller 2024 控制台 2024

Technical Parameters:

Power supply: DC9V 10 00mA
DMX512/1990 Standard, 504 channels
Up to 20 scanners may be connected with a maximum of 24 channels each 24 channels for dimmers
8 slider for manual control of channels assignable joystick for ease of movement
24 chases (at most 40 steps for each chase)
960 chase steps
Each chase speed and cross time can be saved automatic
128 K high capacity memory card
The Data auto-saves
DMX signal output connector: XLR-D3F
Size: 485mm×250mm×91mm
Net Weight: 5Kg

技术参数:

电源输入: DC9V 10 00mA
DMX512/1990信号输出, 504个控制通道
可同时控制20台24通道电脑灯 + 24调光通道
8个通道的控制推子
一个可设置的摇杆装置
24个走灯程序, 每个程序最大40步
共960个电脑灯走灯程序步
各程序速度、渐变值自动记忆
128K 大容量记忆
关机数据保存
DMX信号输出连接器: XLR-D3F
外形尺寸: 485mm×250mm×91mm
重量: 5kg

N-C1216

Controller 1216 控制台 1216

Technical Parameters:

Power supply: DC9V 10 00mA
DMX512/1990 Standard, 240 channels
Up to 12 scanners may be connected with a maximum of 16 channels each 24 channels for dimmers, 24 channels for switch of lamp
8 slider for manual control of channels assignable joystick for ease of movement
12 chases (at most 40 steps for each chase)
480 chase steps
Each chase speed and cross time can be saved automatic
128 K high capacity memory card
The Data auto-saves
DMX signal output connector: XLR-D3F
Size: 485mm×250mm×91mm
Net Weight: 5Kg

技术参数:

电源输入: DC9V 10 00mA
DMX512/1990信号输出, 408个控制通道
可同时控制12台16通道电脑灯 + 24调光通道 + 24开关通道
8个通道的控制推子
一个可设置的摇杆装置
12个走灯程序, 每个程序最大40步
共480个电脑灯走灯程序步
各程序速度、渐变值自动记忆
128K 大容量记忆
关机数据保存
DMX信号输出连接器: XLR-D3F
外形尺寸: 485mm×250mm×91mm
重量: 5kg

N-C240A

Controller 240A 控制台 240A

Technical Parameters:

Power input: DC 9-12V 300mA min
12 scanners of 16 channels each
30 banks have 8 programmable scenes each
6 programmable chase have 240 scenes each
8 slider for manual control of channels
2 assignable wheels for ease of movement
auto mode program controlled by speed and fade time sliders
fade time/assign fade time
reversible DMX channels fixture to react in opposition to others in a chase
8 channel or 16 channel mode
fine adjustment for Wheel pan and tilt
blackout master button
manual override button allow you to grab any fixture on the fly
built in microphone for music triggering
midi control over banks, chases and blackout
power failure memory
Dimensions(mm): 482 x 190 x 90
Net Weight: 3.0kg

技术参数:

电源输入: DC9-12V 300mA
最多可控制12台电脑灯, 每台电脑灯最多16个通道
可编程30个记忆储存(Bank), 每个可存储8个场景(Scene)
6个可编程程序(Chase), 每个程序可编240步(即30个Bank Scene)
8个通道控制推子
两个手控轮
在自动运行模式中, FADE可选择全部具有ALL或X/Y, 具有FADE, 都具有SPEED调节, 8通道或16通道工作模式
数码轮装置可对灯具的水平/垂直运动进行微调
具Blackout输出
内置麦克风, MIDI控制
掉电记忆保护
尺寸: 482mm×190mm×90mm
重量: 3.0KG



AB-1500



Power: 1500W
Voltage: AC110V,220-250V 50/60Hz
Heat-up Time: 12 minutes
Tank capacity: 2L
Approx. Fog Projection: 12 M
Output: 20000cu.ft/min
Control mode: Circuitry Control,
Remote Control
Weight: 7.4KG
Size: 46.5*22.5*19.5(cm)
功率: 1500W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 12分钟
油箱容量: 2L
喷油距离: 12米
喷油量: 20000cu.ft/min
控制模式: 线控、遥控
重量: 7.44KG
尺寸: 46.5*22.5*19.5(cm)

F-3000R



Power: 3000W
Voltage: AC110V,220-250V 50/60Hz
Heat-up Time: 12 minutes
Tank capacity: 10L
Output: 40000cu.ft/min
Control mode: DMX512 Manual
Controler,
Remote Control
Weight: 20KG
Size: 72*31*18(cm)
功率: 3000W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 12分钟
油箱容量: 10L
喷油量: 40000cu.ft/min
控制模式: DMX512、线控、遥控
重量: 20KG
尺寸: 72*31*18(cm)

S-1200



Power: 1200W
Voltage: AC110V,220-250V 50/60Hz
Tank capacity: 5L
Output: 60 Cubic Meters
Control mode: DMX512,Circuitry Control,
Remote Control
Weight: 11KG
Size: 51.5*31*23(cm)
功率: 1200W
工作电压: AC110V,220-250V 50/60Hz
油箱容量: 5L
喷油量: 60 Cubic Meters
控制模式: DMX512、线控、遥控
重量: 11KG
尺寸: 51.5*31*23(cm)

Z-800



Power: 900W
Voltage: AC110V,220-250V 50/60Hz
Heat-up Time: 7 minutes
Tank capacity: 1L
Output: 5000cu.ft/min
Control mode: Circuitry Control
Weight: 4KG
Size: 33*17*14(cm)
功率: 900W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 7分钟
油箱容量: 1L
喷油量: 5000cu.ft/min
控制模式: 线控
重量: 4KG
尺寸: 33*17*14(cm)

AB-1200



Power: 1200W
Voltage: AC110V, 220-250V 50/60Hz
Heat-up Time: 8 minutes
Tank capacity: 2L
Approx. Fog Projection: 10 M
Output: 18000cu.ft/min
Control mode: Circuitry Control,
Remote Control
Weight: 6.8KG
Size: 49.5*23*14(cm)
功率: 1200W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 8分钟
油箱容量: 2L
喷油距离: 10米
喷油量: 18000cu.ft/min
控制模式: 线控、遥控
重量: 6.8KG
尺寸: 49.5*23*14(cm)

AB-900



Power: 900W
Voltage: AC110V,220-250V 50/60Hz
Heat-up Time: 8 minutes
Tank capacity: 1L
Approx. Fog Projection: 8 M
Output: 5000cu.ft/min
Control mode: Circuitry Control,
Remote Control
Weight: 4.6KG
Size: 33.5*19*14(cm)
功率: 900W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 8分钟
油箱容量: 1L
喷油距离: 8米
喷油量: 5000cu.ft/min
控制模式: 线控、遥控
重量: 4.6KG
尺寸: 33.5*19*14(cm)

T-400



Power: 400W
Voltage: AC110V,220-250V 50/60Hz
Heat up Time: 8 minutes
Tank capacity: 0.3L
Output: 2000cu.ft/min
Control mode: Circuitry Control
Weight: 2.5 KG
Size: 23*11*11(cm)
功率: 400W
工作电压: AC110V,220-250V 50/60Hz
预热时间: 8分钟
油箱容量: 0.3L
喷油距离: 8米
喷油量: 2000cu.ft/min
控制模式: 线控
重量: 2.5KG
尺寸: 23*11*11(cm)

B-300



Power: 300W
Voltage: AC110V,220-250V 50/60Hz
Bubble Oil Container: 2.5L
Blowing Height: 10 M
Output: 600 cubic meters
Control mode: Remote Control
Weight: 14KG
Size: 45*39*41(cm)
功率: 300W
工作电压: AC110V,220-250V 50/60Hz
油箱容量: 2.5L
喷油距离: 10米
喷油量: 600 cubic meters
控制模式: 线控
重量: 14KG
尺寸: 45*39*41(cm)

新感觉灯光

——酒吧、KTV全线灯光供应商



广州新感觉灯光音响设备有限公司是一家集科研、生产、销售、工程服务为一体的科技型专业灯光民营企业。本公司聚集了一批光电科技研发精英和经验丰富、技术精湛的专业生产施工人员，精雕细琢后推出了品种繁多、质量上乘的智能化舞台灯光系列产品。目前主要产品包括了摇头灯系列、激光灯系列、LED PAR灯系列、LED效果灯系列、频闪灯系列等等，涵盖了酒吧、KTV使用的全线灯光产品。

卓越的品质和优良的服务为我们赢得了广阔的市场空间，也使我们的产品倍受国内外用户的青睐；目前我们已经和欧亚、南北美洲等多个国家和地区建立了代理、经销等多种形式的合作关系，而在国内各地的舞台灯光工程、市政工程、地标建筑、主题公园、舞厅、俱乐部、电视台、歌剧院及大型演出等场所，我们的产品也得到了广泛的应用。

以精品缔造行业传奇，以品质树立诚信品牌，以服务感动所有客户，新感觉愿与您携手并进，共同打造灯光世界的绚丽辉煌！

Guangzhou New Feel Lighting & Audio Equipment CO. LTD is a researching, producing, selling and professional privately-owned manufacturer. We gathered a group of experienced photoelectric R & D elites and skilled producing technicians. We are professional supplier specializing in all range of lighting for bars and KTV, now our main products including moving head series, laser series, LED PAR light series, LED effect series and strobe light etc.

With superior quality and excellent service has made us owned a board marketing space and enabled our products highly appreciated both at home and abroad. At present we established agents, distributions and many other kinds of cooperating relationship with Europe and Asia, North and South Americas and so on. Our products have widely used in our own country, such as stage lighting engineering, municipal works, land mark building, theme park, dance hall, club, opera house, big show and other entertainment venues.

Well-made goods make industrial legend, quality entrusted brand, superior service inspire customer. In order to be remarkable in lighting field, New Feel is looking forward to working with you.



封二

配件系列 Accessories Series

保险绳 / Safety rope



灯架 / Stand



重烟油
Heavy Fog Oil



DJ烟油
DJ Fog Oil



烟油
Fog Oil



德国油
Germany Fog Oil



雪花油
Snow Oil



泡泡油
Bubble Oil



喷火油
Fire Machine Oil

灯钩 / Lighthook



玻璃球 / Glass Ball Light



色片 / Color Filter (1x40m)



航空箱 / Fly Box



光源

Lamp With Different Measurement



封三



KTV、酒吧全线灯光优质供应商
Professional supplier specializing in
all range of lighting for bars and KTV



KTV、酒吧全线灯光优质供应商
Professional supplier specializing in
all range of lighting for bars and KTV

KTV智能灯光领跑者.....

新感觉实业发展有限公司
NEW FEEL INDUSTRIAL DEVELOPMENT LIMITED

广州新感觉灯光音响设备有限公司
GUANGZHOU NEW FEEL LIGHTING AND AUDIO EQUIPMENTS CO.,LTD.

地址：广州白云区石井镇榕溪榕荫路35号榕荫工业园B栋2楼

Add: 2/F, Rongxi Industry Zone, No.35, Rongyin Road, Shijing Town,

Baiyun District, Guangzhou, China.

Tel: +86 20-36393166 36396409

Http://www.newfeellight.com

E-mail: info@newfeellight.com

2015-2016 Catalogue

工程案例 Project case



2014-2015宝乐迪全国连锁KTV

2013年恩平88BAR



2014-2015福建欢唱连锁KTV

2013年西塘潘多拉酒吧



2013年西塘水调歌头酒吧



2010年上海展




2011年广州展



2011年上海展



2012年北京展



2013年北京展



2012年广州展



2013年广州展



2014年广州展



2015年广州展

工程案例
Project case



2009年上海五月天演唱会



2010年成都中国会所



2012年增城,你好!新年晚会



2012年邵武元宵焰火晚会



2012年台北灯会