NS-1 NOISE GENERATOR (1-2150 MHZ)

OVERVIEW

The NS-1 is a handheld broadband noise generator. It generates a wide, even, RF noise signal. The NS-1 is popular for testing network components and aligning a building's coaxial cable network.

The NS-1's signal is injected into the network at point A. Using a signal receiver, such as a spectrum analyzer or a signal level meter (i.e. Applied Instruments Super Buddy or XR-3), the NS-1's signal is received at point B.

The frequency response of the network, between points A and B, is obtained. This measurement allows the user to verify the RF integrity of cabling and its associated connections at all frequencies between 5 and 2150 MHz.

NS-1 RF Noise Generator for Testing and Aligning



BENEFITS

- Cost effective
- Compact and convenient handheld design
- Field replaceable "F" connector
- Signal drops out with low battery (no sagging)

STANDARD ACCESSORIES

- Padded carrying case with belt clip
- Spare 9V battery

NS-1 NOISE GENERATOR (1-2150 MHZ)

SPECIFICATIONS

- RF Signal Type
 - White Noise energy, Constant Spectral Density
- Frequency Range
 1 to 2150 MHz

Maximum Output Level (at least)

- Total
 - -101.572 dBm/Hz, -8.3 dBm, +40.5 dBmV, +100.5 dBµV
- 280 kHz bandwidth

 -47 dBm, -2 dBmV, +58 dBµV
- 24 MHz bandwidth

 -28 dBm, +21 dBmV, +81 dBµV
- 6 MHz bandwidth

 -34 dBm, +15 dBmV, +75 dBµV

Amplitude Output Flatness

- 5 to 46 MHz
 +0.5 dB
- 46 to 860 MHz
 ±1.0 dB
- 950 to 1450 MHz
 ±1.0 dB
- 1550 to 2000 MHz
 ±2.0 dB
- 5 to 2150 MHz
 ±2.5 dB
- Output Impedance
 75Ω
- Operating Temperature
 0° to 120°F (-18°C to +50°C)
- DC Power
 9V Alkaline battery
- Operation Time Per Battery

 15 hours continuous
- Low Battery Indicator

 LED flashes during last 10% of battery life
- Low Battery Cutoff

 Turns off signal when battery is insufficient

- Enclosure Type/Size/Weigh
 ABS Plastic, 2.4"W x 4.7"H x 0.9"D
 - / 4 oz. / 6.1 cm x 11.9 cm x 2.3 cm / 113 g

• Warranty

- 12 month limited
 - Specifications subject to change without notice.



2431 Directors Row STE F Indianapolis, IN 46241



737-800-1982 support@appliedin.com <u>appliedinstruments.com</u>