

Mitutoyo

Mitutoyo Quality

SURFTEST SJ-500/SV-2100 SURFACE ROUGHNESS MEASURING SYSTEM

Surface roughness testers offer benchtop or portable operation and the choice of data analysis by PC or an easy-to-use dedicated processor

FORM MEASUREMENT



Dedicated data processor type Surftest SJ-500/SV-2100

Improved operability

7.5 Color TFT LCD

The dedicated data processor has a high-visibility 7.5" color TFT LCD. Icon display and touch panel operation provide user-friendly display and easy operation.

Positioning by joystick and manual control knobs on the processor

Easy-to-operate joystick. Fine positioning of stylus required for small-hole measurements can be easily performed using the manual fine-adjustment knobs.

Multiple trace function

A machine can be programmed to take up to three traces, one after the other.

Auto leveling table (optional)

Automatically levels the surface to be tested for easy, strain-free setup.

Various types of analysis

Capable of fine-contour analysis

Supports 43 types of analysis parameters, complying with surface roughness standards such as ISO 1997 and JIS 2001. Also capable of various fine-contour analysis.

* Contour analyses: Area, circle, angle, coordinate difference, step, inclination

High-durability

Ceramic guideway

A ceramic guideway, inherently free from wear and deterioration with age, is employed to maintain the traversing straightness of the drive unit (X-axis) indefinitely. Maintenance-free design, since anti-corrosion treatment is not required for ceramic.

SJ-500

Traverse: 1.97" (50mm)
Compact, high-performance type

SV-2100M4

Traverse: 3.94" (100mm)
Manual column type

SV-2100S4/H4/W4

Traverse: 3.94" (100mm)
Power column type



Dedicated data processor

Advanced processing and easy operation

Easy operation, high-accuracy analysis of surface roughness and fine contours!

High-visibility color display panel

A high-visibility 7.5" color TFT LCD, color icon display and touch-operated panel provide user-friendly, easy operation. Built-in thermal printer. Fine contour analysis provided as standard.



Supports 16 languages


Japanese, English, German, French, Italian, Spanish, Portuguese, Korean, Simplified Chinese, Traditional Chinese, Czech, Polish, Hungarian, Turkish, Swedish, Dutch

Multiple trace programming function

A machine can be programmed to take up to three consecutive traces by one-key operation, as shown in the figure below.


•SJ-500/SV-2100M4

Consecutive tracing in X-axis direction only



•SV-2100S4/H4/W4

X-axis tracing with programmed Z-axis shifts possible



Measurement

Traverse


Example: SV-2100S4 input screen




Efficient positioning by joystick and adjustment knobs

Both a fast-traverse joystick (X-axis: .78"/s (20mm/s) for **SJ-500**, 1.98"/s (40mm/s) for **SV-2100**, Z2-axis: .78"/s (20mm/s) for **SV-2100S4/H4/W4**) and manual fine-adjustment knobs, essential for positioning in small hole measurement, are standard features.

Positioning in small hole measurement



Positioning in Y/Z-directions with column fine-adjustment knob (or detector elevation knob) and optional cross-travel table.




Positioning at the trace start point with X-axis fine-adjustment knob.

Navigation function aids leveling

Powerful support for leveling adjustments

When using an optional 3-axis adjustment table or leveling table, a navigation screen is available to help the operator level the surface to be tested.

Example of 3-axis adjustable table




The user is guided through the leveling procedure to determine the amount of adjustment needed.

A portable tester also boasting high performance in desktop applications

Surftest SJ-500

High accuracy, high performance, user-friendly display and easy operation



Class-leading traverse straightness:

$8\mu\text{in}/2"$ ($0.2\mu\text{m}/50\text{mm}$)

High-speed traverse at up to $0.78"/\text{s}$ (20mm/s) under joystick control

Smooth positioning using the vertical adjustment knob

Vertical adjustment knob

Essential for positioning the stylus close to the workpiece!




Support for testing problematic features

Supports measurement in the axial direction for shrouded features, such as found on crankshafts, by simply swiveling the detector through 90 degrees.

Normal tracing



Tracing a shrouded feature




Drive unit inclination adjustment mechanism

Digital Adjustment Tilting (DAT) function is supplied as standard for efficient leveling of workpieces: $\pm 1.5^\circ$

DAT function: Patent pending (Japan, U.S., Germany)




DAT function



A desktop tester that's easy to use for portable applications

Surftest SV-2100

By setting the origin point at start-up, the Absolute scale system allows accurate positioning for repeated or multiple measurements.




SV-2100M4



SV-2100S4

*High-speed traverse at up to 1.98"/s (40mm/s) (X-axis) under joystick control
Smooth positioning, using the Z-axis fine-adjustment knobs
Stable, high-accuracy measurement with a traverse straightness of
 $6\mu\text{in}/4"$ ($0.15\mu\text{m}/100\text{mm}$)*

1. Capable of a series of automatic measurements, plus auto leveling (optional) and stylus retraction. Accurate positioning for repeated or multiple measurements possible.



Measurement setup screen

2. **SV-2100S4/H4/W4** models are equipped with an emergency stop button.




3. Base sizes and vertical travel range on column

Model No.	Vertical travel range	Vertical traverse method	Base size	
SV-2100S4	13.8" (350mm)	Power and manual	23.6" x 17.72" (600x450mm)	
SV-2100H4	21.6" (550mm)		39.4" x17.72" (1000x450mm)	
SV-2100W4				
SV-2100M4	13.8" (350mm)	Manual only	23.6" x 17.72" (600x450mm)	

Dedicated data processor

the standard in world
metrology software
FORM



Statistical data processing possible (up to 300 data samples)
Statistical processing items: MAX, MIN, average, standard deviation, histogram, probability of acceptance.




Statistical data input

Statistical results




Up to 10 measurement setups can be saved to and recalled from internal memory.



Analysis to international standards

Evaluates surface roughness using up to 43 parameters complying with international standards such as ISO 1997 and JIS 2001.

Bearing Area Curve (BAC), Amplitude Distribution Curve (ADC), and power spectrum (wavelength display) are readily available in graph form.




A large variety of optional accessories

Options supporting measurement including an auto leveling table, a 3-axis adjustment table, and a leveling table. Furthermore, these can be easily operated via a navigation function. (Supported accessories differ depending on the model.)



Fine-contour analysis

Various contour analyses (area, circle, angle, coordinate difference, step, inclination) are supplied as standard.




Select desired analysis icon and then specify the range.

Easy, icon-based input of setup conditions

* Patent pending


Setups are aided by icons representing ISO/JIS roughness standard parameters with appropriate values selected from recommended lists.

Typical surface roughness symbol on drawing



Typical result of icon-based setup

U"X"0.08—0.8/Rz8max 3.3



Clicking a parameter icon displays the recommended cut-off value, etc.

Built-in thermal printer

Measurement data is printed by the high-definition, high-speed thermal printer.

In addition to calculation results and evaluation results, BAC, ADC and other curves can also be printed.



PC data processing type **Surftest SJ-500P**

A superior data processing tester with PC data analysis for higher efficiency.


* If a power column type with PC data-processing is desired, consider the SV-3100 series




SJ-500P

FORMTRACEPAK: Best-seller for surface roughness analysis


A best-seller dedicated software especially for surface roughness measurement and analysis capable of free print format settings for original inspection certificates.



Measurement and results display screen



Setup definition screen



Printing screen

Specifications


Specifications

Type of data processing	Dedicated data processor					PC system					
Model No.	SJ-500	SV-2100M4	SV-2100S4	SV-2100H4	SV-2100W4	SJ-500P					
Order No.*	with 0.75 mN detector	178-533-01A	178-637-01A	178-681-01A	178-683-01A	178-685-01A					
	with 4 mN detector	178-533-02A	—	—	—	—					
Travel range (operation)	X axis Z2 axis (column)	2" (50mm) —	3.94" (100mm) (power drive / manual)			2" (50mm) —					
Measuring range	X axis Z1 axis (detector unit)	2" (50mm)	3.94" (100mm) 3200µin / 3200µin / 320µin (800µm / 80µm / 8µm)			2" (50mm)					
Resolution	X axis Z1 axis (detector unit) Z2 axis (column)	1.97µin (0.05µm) 0.4µin / 3200µin range, 0.4µin / 3200µin range, 0.004µin / 320µin range (0.01µm / 800µm range, 0.001µm / 80µm range, 0.0001µm / 8µm range) (1µm)			—	—					
Power drive speed	X axis Z2 axis (column)	0 - 0.78"/s 0 - 20mm/s (via joystick)	0 - 1.98"/s (0 - 40mm/s) (via joystick) 0 - 0.78"/s (0 - 20mm/s) (via joystick)			0 - 20mm/s (via PC) —					
Measuring speed	0.00078" - 0.2" / s (0.02 - 5mm/s)										
Traverse guideway straightness	8 µin / 2" (0.2µm / 50mm)	6µin / 4" (0.15µm / 100mm)			8µin / 2" (0.2µm / 50mm)						
Stylus up/down operation	Arc movement										
Point of stylus	Downward										
Detector	Measuring force Stylus tip	0.75 mN or 4 mN 0.75mN detector: 60°, R2 µm or 4mN detector: 90°, R5µm									
Applicable standards	JIS'82 / JIS'94 / JIS'01 / ISO'97 / ANSI / VDA										
Assessed profiles	Dedicated data processor type: P (primary profile), R (roughness profile), WC, envelope residual profile, roughness motif, waviness motif PC system type: P (primary profile), R (roughness profile), WC, WCA, WE, WEA, DIN4776 profile, E (envelope residual profile), roughness motif, waviness motif										
Evaluation parameters	Dedicated data processor type: Ra, Rc, Ry, Rz, Rq, Rt, Rmax, Rp, Rv, R3z, Sm, S, Pc, mr (c), δc, mr, tp, Htp, Lo, lr, Ppi, HSC, Δa, Δq, Ku, Sk, Rpk, Rvk, Rk, Mr1, Mr2, A1, A2, Vo, λa, λq, R, AR, Rx, W, AW, Wx, Wte, (43 parameters), Customization PC system type: Pa, Pq, Psk, Pku, Pp, Pv, Pz, Pt, Pc, PSm, PΔq, Pmr (c), Pmr, Pδc, Ra, Rq, Rsk, Rku, Rp, Rv, Rz, Rt, Rc, RSm, RΔq, Rmr (c), Rmr, Rδc, Wa, Wq, Wsk, Wku, Wp, Wv, Wz, Wt, Wc, WSm, WΔq, Wmr (c), Wmr, Wδc, Rk, Rpk, Rvk, Mr1, Mr2, A1, A2, Rx, AR, R, Wx, AW, W, Wte, Ry, RyDIN, RzDIN, R3y, R3z, S, HSC, Lo, lr, Δa, λa, λq, Vo, Htp, NR, NCRX, CPM, SR, SAR, NW, SW, SAW										
Analysis graphs	Dedicated data processor type: ADC, BAC, power spectrum graph PC system type: ADC, BAC Graph, power spectrum graph, auto-correlation graph, Walsh power spectrum graph, Walsh auto-correlation graph, slope distribution graph, local peak distribution graph, parameter distribution graph										
Curved surface compensation	Dedicated data processor type: Parabolic compensation, Hyperbolic compensation, Elliptical compensation, Circular compensation Conic compensation, Inclination (Entire, Arbitrary) PC system type: Parabolic compensation, Hyperbolic compensation, Elliptical compensation, Circular compensation, Conic compensation, Inclination (Entire, Arbitrary), Polynomial compensation										
Contour analysis	Dedicated data processor type: Area, Circle, Angle, Coordinate difference, Step, Inclination PC system type (SURFPAK-EZ): Area, Circle, Angle, Coordinate difference, Step, Inclination										
Filters	Dedicated data processor type: 2CR-75%, 2CRPC-75%, Gaussian, Robust-spline PC system type: 2CR-75%, 2CR-50%, 2CRPC-75%, 2CRPC-50%, Gaussian, Robust-spline										
Base size (width x depth)	—	23.6" x 17.7" (600x450mm)			39.4" x 17.7" (1000x450mm)	—					
Base material	—	Granite									
External dimensions (W x D x H)	Main unit	16.7" x 3.7" x 6.3" (425x94x160mm)	28.2" x 17.7" x 34" (716x450x863mm)	30.16" x 17.7" x 38" (766x450x966mm)	30.16" x 17.7" x 45.9" (766x450x1166mm)	45.9" x 17.7" x 46.3" (1166x450x1176mm)					
	Display unit	12.9" x 10.63" x 4.38 (330x270x124mm)									
	Electronic unit	—	—	14.6" x 9.65" x 2.83" (372x245x71.8mm)							
Mass	PC I/F unit	—	—	—	—	13.7" x 10.4" x 3.4" 350x263x86mm					
	Main unit	5.9 lbs (2.7kg)	308.6 lbs (140kg)	308.6 lbs (140kg)	330.7 lbs (150kg)	485 lbs (220kg)					
	Display unit	8.8 lbs (4.0kg)				—					
	Electronic unit	—	—	6.6 lbs (3.0kg)							


Dimensions

Unit: mm


SJ-500



Dedicated data processor




Electronic unit




Only for SV-2100S4 / H4 / W4

SV-2100M4




SV-2100S4 / SV-2100H4



(): SV-2100H4



SV-2100W4



T-groove dimensions
(common to all types)



Measuring range



Optional Accessories


Manual column stand: 178-085 (for SJ-500)

Suitable for desktop use in inspection rooms and such.

No.178-085 * Except measuring unit
 Vertical adjustment range: 11.8" (300mm)
 Dimension (W x D x H): 23.6" x 17.7" x 28"
 (600 x 450 x 710mm)
 Weight: 242 lbs (110kg)



Dimensions of SJ-500 with manual column stand Unit: mm



Auto-leveling table: 178-081 (for SJ-500 / SV-2100M4), 178-083 (for SV-2100S4 / H4 / W4)

This is a stage that performs fully automatic leveling as measurement starts, freeing the user from this tedious operation. Fully automatic leveling can be done quickly by anyone. In addition, the operation is easy and reliable.



Inclination adjustment angle	$\pm 2^\circ$
Maximum load	15.4 lbs (7kg)
Table dimensions	5.12" x 3.94" (130x100mm)
Mass	7.7lbs (3.5kg)



DAT leveling table: 178-048



Inclination adjustment angle	$\pm 1.5^\circ$
Maximum load	15.4 lbs (7kg)
Table dimensions	5.12" x 3.94" (130x100mm)

This table can be used by itself or in conjunction with other leveling tables.

Leveling table: 178-043-1 (with analog heads) 178-042-1 (with digital heads)



No.178-043-1

No.178-042-1

Order No.	178-043-1	178-042-1
Table dimensions	5.12" x 3.94" (130x100mm)	
Maximum load	33 lbs (15kg)	
Inclination adjustmnt. angle	$\pm 1.5^\circ$	
Swiveling angle	$\pm 3^\circ$	
X/Y-axis travel range	$\pm 0.49"$ ($\pm 12.5\text{mm}$)	
Resolution	0.01mm	0.001mm
Dimensions	8.66" x 7.4" x 3.27" (220x189x83mm)	10.3" x 9.17 x 3.27" (262x233x83mm)
Mass	13.2 lbs (6Kg)	13.9 lbs (6.3Kg)

Quick chuck: 211-032

This chuck is useful when measuring small workpieces. The knurled ring makes clamping very easy.



Retention range	Inner latch OD: $\phi 0.039"$ - 1.42" (1 - 36mm)
	Inner latch ID: $\phi 0.55"$ - 2.76" (14 - $\phi 70\text{mm}$)
	Outer latch OD: $\phi 0.039$ - 2.95" (1 - $\phi 75\text{mm}$)
Dimensions	$\phi 4.64 \times 1.61"$ (118x41mm)
Mass	2.65 lbs (1.2kg)

Micro-chuck: 211-031

This chuck is suitable for clamping extra-small diameter workpieces ($\phi 1\text{mm}$ or less), which cannot be clamped with the centering chuck.



Clamping range	OD: $\phi 0$ - 0.06" (0 - 1.5mm)
Dimensions	$\phi 4.64$ - 1.91" (118x48.5mm)
Mass	1.32 lbs (0.6kg)


Optional Accessories

3-axis adjustment table: 178-047


This table helps make the alignment adjustments required when measuring cylindrical surfaces. The corrections for the pitch angle and the swivel angle are determined from a preliminary measurement and the Digimatic micrometers are adjusted accordingly. A flat-surfaced workpiece can also be leveled with this table.



Inclination adjustment angle	$\pm 1.5^\circ$
Swiveling angle	$\pm 2^\circ$
Y-axis range	0.49" ($\pm 12.5\text{mm}$)
Resolution of heads	0.001mm
Table dimensions	5.12" x 3.94" (130x100mm)
Maximum load	33 lbs (15kg)




System configuration including optional accessories (for SV-2100M4 / S4 / H4 / W4)



Optional Accessories

System configuration including optional accessories (for SJ-500 with optional manual column stand)



*1: 2.76" (70mm) stage to be mounted onto the base required for calibration of roughness specimen. Not required when using cross-travel table, plain stage, cross-travel stage, or 3-axis adjustment table.

*3: PC for managing the analysis result externally output from the dedicated data processor.

*3: Only SJ-500P can be connected. Use a USB cable when connecting the SJ-500P main unit and a PC. A USB cable is a standard accessory of the SJ-500P.

Roughness specimen (standard accessory): 178-601

Display	Ra = about 3 µm
Material	Ni (TiN surface coating)

Reference step specimen: 178-611 (mm), 178-612 (inch)

For sensitivity calibration of detector

Nominal value of step	2µm 10µm, 79µin 394µin
-----------------------	------------------------

Roughness specimen: 178-604


For checking stylus tip

Display	Ra = about 3 µm, about 0.4 µm
---------	-------------------------------



Optional Styli

Detectors



Detector (0.75mN): **178-396-2**
Detector (4mN): **178-397-2**


Extension rods



Extension rods
12AAG202: 1.97" (50mm), **12AAG203:** 3.94" (100mm)


Styli

Standard stylus




12AAE882 (1µm)*
12AAE924 (1µm)**
12AAC731 (2µm)*
12AAB403 (5µm)**
12AAB415 (10µm)**
12AAE883 (250µm)
(): Tip radius
*Tip angle: 60° **Tip angle: 90°

For small hole




12AAC732 (2µm)*
12AAB404 (5µm)**
12AAB416 (10µm)**
(): Tip radius
*Tip angle: 60° **Tip angle: 90°

For very small hole




12AAC733 (2µm)*
12AAB405 (5µm)**
12AAB417 (10µm)**
(): Tip radius
*Tip angle: 60° **Tip angle: 90°

For extra small hole




12AAC734 (2µm)*
12AAB406 (5µm)**
12AAB418 (10µm)**
(): Tip radius
*Tip angle: 60° **Tip angle: 90°

For deep hole (double-length and triple-length)




12AAC740 (2µm)*
12AAB413 (5µm)**
12AAB425 (10µm)**
(): Tip radius
*Tip angle: 60° **Tip angle: 90°




12AAC741 (2µm)*
12AAB414 (5µm)**
12AAB426 (10µm)**
(): Tip radius
*Tip angle: 60° **Tip angle: 90°

Double-length for deep hole




12AAE898 (2µm)*
12AAE914 (5µm)**
(): Tip radius
*Tip angle: 60° **Tip angle: 90°

For small hole/Double-length for deep hole




12AAE892 (2µm)*
12AAE908 (5µm)**
(): Tip radius
*Tip angle: 60° **Tip angle: 90°

For very small hole




12AAE884 (0.8mm)
(): Tip radius

For ultra small hole



12AAJ662 (0.25mm)
(): Tip radius

For small slotted hole
















12AAE938 (2µm)*
12AAE940 (5µm)**
(): Tip radius
*Tip angle: 60° **Tip angle: 90°

Customized special interchangeable styli are available on request,
Please contact any Mitutoyo office for more information.

Tip radius	1µm	2µm	5µm	10µm	250µm
Color coding	White	Black	No color	Yellow	No notch or color

Styli

<p>For deep groove (10mm)</p>  <p>Detail-A</p> <p>12AAC735 (2µm)* 12AAB409 (5µm)** 12AAB421 (10µm)** (): Tip radius *Tip angle: 60° **Tip angle: 90°</p>	<p>For deep groove (20mm)/Double-length for deep hole</p>  <p>12AAE893 (2µm)* 12AAE909 (5µm)** (): Tip radius *Tip angle: 60° **Tip angle: 90°</p>
<p>For deep groove (20mm)</p>  <p>Detail-A</p> <p>12AAC736 (2µm)* 12AAB408 (5µm)** 12AAB420 (10µm)** (): Tip radius *Tip angle: 60° **Tip angle: 90°</p>	<p>For deep groove (40mm)</p> <p>12AAE895 (2µm)* 12AAE911 (5µm)** (): Tip radius *Tip angle: 60° **Tip angle: 90°</p>
<p>For deep groove (30mm)</p>  <p>Detail-A</p> <p>12AAC737 (2µm)* 12AAB407 (5µm)** 12AAB419 (10µm)** (): Tip radius *Tip angle: 60° **Tip angle: 90°</p>	<p>For deep groove (30mm)/Double-length for deep hole</p>  <p>12AAE894 (2µm)* 12AAE910 (5µm)** (): Tip radius *Tip angle: 60° **Tip angle: 90°</p>
<p>For gear tooth</p>  <p>Detail-A</p> <p>12AAB737 (2µm)* 12AAB410 (5µm)** 12AAB422 (10µm)** (): Tip radius *Tip angle: 60° **Tip angle: 90°</p>	<p>For gear tooth/Double-length for deep hole</p>  <p>12AAE896 (2µm)* 12AAE912 (5µm)** (): Tip radius</p>
<p>For rolling circle waviness surface</p>  <p>12AAB338 (ø1.588)</p> <p>(): Tip radius</p>	<p>For rolling circle waviness/Double-length for deep hole</p>  <p>12AAE886 (250µm) (): Tip radius</p>
<p>For knife-edge detector</p>  <p>Detail-A</p> <p>12AAC738 (2µm)* 12AAB411 (5µm)** 12AAB423 (10µm)** (): Tip radius *Tip angle: 60° **Tip angle: 90°</p>	<p>For corner hole/Double-length for deep hole</p>  <p>12AAE897 (2µm)* 12AAE913 (5µm)** (): Tip radius *Tip angle: 60° **Tip angle: 90°</p>
<p>For eccentric arm</p>  <p>Detail-A</p> <p>12AAC739 (2µm)* 12AAB412 (5µm)** 12AAB424 (10µm)** (): Tip radius *Tip angle: 60° **Tip angle: 90°</p>	<p>For bottom surface</p>  <p>12AAE899 (2µm)* 12AAE915 (5µm)** (): Tip radius *Tip angle: 60° **Tip angle: 90°</p>

Customized special interchangeable styli are available on request,
Please contact any Mitutoyo office for more information.

Tip radius	2µm	5µm	10µm
Color coding	Black	No color	Yellow



**Whatever your challenges are,
Mitutoyo supports you from start to finish.**

Mitutoyo is not only a manufacturer of top-quality measuring products but one that also offers qualified support for the lifetime of the equipment, backed by comprehensive services that ensure your staff can make the very best use of the investment.

Apart from the basics of calibration and repair, Mitutoyo offers product and metrology training, as well as IT support for the sophisticated software used in modern measuring technology. We can also design, build, test and deliver measuring solutions and even, if deemed cost-effective, take your critical measurement challenges in-house on a sub-contract basis.



**Find additional product literature
and our product catalog**

www.mitutoyo.com

Note: All information regarding our products, and in particular the illustrations, drawings, dimensional and performance data contained in this printed matter as well as other technical data are to be regarded as approximate average values. We therefore reserve the right to make changes to the corresponding designs. The stated standards, similar technical regulations, descriptions and illustrations of the products were valid at the time of printing. In addition, the latest applicable version of our General Trading Conditions will apply. Only quotations submitted by ourselves may be regarded as definitive. Specifications are subject to change without notice.

Mitutoyo products are subject to US Export Administration Regulations (EAR). Re-export or relocation of our products may require prior approval by an appropriate governing authority.

Trademarks and Registrations

Designations used by companies to distinguish their products are often claimed as trademarks. In all instances where Mitutoyo America Corporation is aware of a claim, the product names appear in initial capital or all capital letters. The appropriate companies should be contacted for more complete trademark and registration information.

Mitutoyo

Mitutoyo America Corporation

www.mitutoyo.com

One Number to Serve You Better

1-888-MITUTOYO (1-888-648-8869)

M³ Solution Centers:

Aurora, Illinois (Headquarters)

Boston, Massachusetts

Charlotte, North Carolina

Cincinnati, Ohio

Detroit, Michigan

Los Angeles, California

Birmingham, Alabama

Seattle, Washington

Houston, Texas