



# Professional, Rechargeable Color Match Light



The **NextLED Professional, Rechargeable Color Match Light** is a CRI 96+ handheld rechargeable LED work light that is perfect for accurate color matching and identifying imperfections before and after paint repairs. By replicating natural sunlight, you can perfectly match paint colors, clearly evaluate damaged areas, and identify paint defects such as swirl marks and sanding scratches. It features 3 different color temperatures: 2700K, 4000K, and 6500K at a maximum 500 lumen brightness. The head lamp tilts up to 180 degrees and includes a fold-out swivel hanging hook, a built-in magnet, an LED battery status indicator and a charging station base that can be wall-mounted.

**WARNING:** To avoid serious injury or death from electrical shock or fire:

1. This fixture **MUST ALWAYS BE USED IN ACCORDANCE WITH ALL ELECTRICAL AND SAFETY CODES AND ORDINANCES**, including the most recent National Electric Code (NEC) and with the Occupational Safety and Health Act (OSHA) Volume 1 on General Industry Standards and interpretations.
2. **ALWAYS** make certain that the power source conforms to the requirements on the product.
3. **CAUTION:** Keep dry. Do not open, drop, short-circuit, incinerate, expose to temperatures higher than 140°F, or use if damaged.
4. People with pacemakers should consult their physician(s) before use. Electromagnetic fields in close proximity to heart pacemaker could cause pacemaker interference or pacemaker failure.
5. This fixture is not explosive-proof, **DO NOT** use in potentially dangerous locations, such as in flammable or explosive atmospheres.
6. **NEVER** operate the light with the clear protective glass broken or removed.
7. **NEVER LOOK DIRECTLY INTO LIGHT SOURCE** LED's are extremely bright and can damage eyes with prolonged exposure.
8. **KEEP AWAY** from heating vents, radiators, or other sources of heat.
9. **KEEP OUT OF REACH OF CHILDREN**
10. **INTENDED FOR INDOOR AND OUTDOOR USE**

### OPERATING INSTRUCTIONS

**WARNING:** READ ENTIRE IMPORTANT SAFETY INFORMATION SECTION at the beginning of this document including all text under subheadings before set up or use of this product.

1. Charge light fully before first use. Light should not be on during charging
2. Green LED light flashes while charging. When charging is complete the Green LED light will stop flashing
3. Use only the charger adapter and cable that came with this product.
4. Avoid charging product in the rain or other damp environments.
5. Press the button once for the 6500K temperature.
6. Press the button again for the 4000K temperature.
7. Press the button a third time for the 2700K temperature.
8. Press the button a fourth time to turn light off.

### ONE YEAR LIMITED WARRANTY

If this NextLED® product fails due to a defect in materials or workmanship, NextLED® will at its option, repair it or replace it with the same or comparable model, free of charge.

To make claim under warranty, contact customer service. This warranty gives you specific legal rights and you may have other rights that vary from state to state.

This warranty is void if damage or defect has resulted from accident, abuse, misuse or faulty repair. In no event will NextLED® be liable for any consequential, special, incidental, or indirect damages of any kind arising out of the use or misuse of this product.

Maximum liability shall not in any case exceed the purchase price of the product including shipping. Some states do not allow the exclusion or limitation of incidental or consequential damages so the above exclusions or limitations may not apply to you.



Your product, accessories and packaging should be discarded in an environmentally responsible way.

Illustrations, figures and photos may vary slightly due to our program of continuous product improvements.

**WARNING!** LED's are extremely bright and direct exposure to eyes may cause injury. Avoid shining LED's in eyes.

### WARNING:

Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### SPECIFICATIONS:

Rating .....	CRI96+
Run Time .....	Up to 2.5 hrs.
Color Temperature .....	6500K, 4000K, 2700K
Maximum Brightness.....	500 lumens
Power.....	3.7V, 2200 mAh Rechargeable Lithium-Ion
Charger .....	5V/1A
Cable.....	USB (Included)
Charge Time .....	4 hrs.
Water Resistance .....	IP-65
Switch Sequence .....	6500K, 4000K, 2700K, Off