

OWNER'S INSTRUCTIONS



Rechargeable 2 in 1 LED and UV Work Light. 500 and 1000 Lumens



Model 370-5525 (EF-2061A-10UV)

The NextLED 1000 Lumen Rechargeable LED Work Light is designed for automotive maintenance or mechanical shop application. Full and half power settings produce 1000 lumens on high power and 500 lumens on low. It features a comfortable rubber grip and 2 convenient hooks for multiple lighting positions. Lithium ion rechargeable battery and USB charging cable are included. Keep this manual and the receipt in a safe and dry place for future reference. This LED light also comes with a UV lighting to conveniently be used to check for leakage.

CAUTION: Read all instructions and warnings before operating!
SAVE THESE INSTRUCTIONS!

WARNING: To avoid serious injury or death from electrical shock or fire:

1. This fixture **MUST ALWAYS BE USED IN ACCORDANCE WITH ALL ELECTRICAL AND SAFETY CODES AND ORDINANCES**, including the most recent National Electric Code (NEC) and with the Occupational Safety and Health Act (OSHA) Volume 1 on General Industry Standards and interpretations.
2. **ALWAYS** make certain that the power source conforms to the requirements on the fixture.
3. **DO NOT** inspect or service the fixture while charging.
4. **CAUTION:** This fixture is for indoor use. Keep dry. Do not open, drop, short-circuit, incinerate, expose to temperatures higher than 140°F, or charge/use if damaged.
5. People with pacemakers should consult their physician(s) before use. Electromagnetic fields in close proximity to heart pacemaker could cause pacemaker interference or pacemaker failure
6. This fixture is not explosive-proof, **DO NOT** use in potentially dangerous locations, such as in flammable or explosive atmospheres.
7. **NEVER** operate the light with the clear protective glass broken or removed.
8. **NEVER LOOK DIRECTLY INTO LIGHT SOURCE.** LED's are extremely bright and can damage eyes with prolonged exposure.
9. **KEEP AWAY** from heating vents, radiators, or other sources of heat.
10. **KEEP OUT OF REACH OF CHILDREN.**

LITHIUM BATTERY SAFETY WARNINGS

LITHIUM BATTERIES STORE A LARGE AMOUNT OF ENERGY AND WILL VENT FIRE OR EXPLODE IF MISTREATED:

1. Keep work light dry.
2. **DO NOT DO ANY OF THE FOLLOWING TO BATTERY PACK:**
 - a. Drop
 - b. Open
 - c. Short-circuit
 - d. Puncture
 - e. Incinerate, or
 - f. Expose to temperatures greater than 140°F.
3. Charge work light only according to these instructions

MAINTENANCE

Only qualified service personnel must perform repairs. Opening or visible attempts to open or repair work light will void any warranty and/or cause damage to the product or personal injury.

CAUTION! Do not use solvents such as gasoline, turpentine, etc. to clean the unit. Aerosols and other chemical will fog the clear polycarbonate lens.


BATTERY CHARGING

NOTE: Each individual light must be charged separately

1. Connect micro end of USB cable to worklight.
2. Connect the regular end of USB cable to 5V AC adaptor with rated amperage under 2A (not included).
3. Connect the adapter to an electric outlet.

Battery Charging Indicating:

Light Red In process of charging
Light Green Fully charged, please unplug the adaptor.



WARNING! Charge while indoors only.

WARNING! Always use only a 5V charging adaptor rated under 2A. Using a non-compatible charger could cause damage to the work light or personal injury.

ONE YEAR LIMITED WARRANTY

If this NextLED® product fails due to a defect in materials or workmanship, NextLED® will at its option, repair it or replace it with the same or comparable model, free of charge.

For repair or replacement under warranty, return to the retail establishment where the product was purchased. This warranty give you specific legal rights and you may have other rights that vary from state to state.

This warranty is void if damage or defect has resulted from accident, abuse, misuse or faulty repair. In no event will NextLED® be liable for any consequential, special, incidental, or indirect damages of any kind arising out of the use or misuse of this product. Maximum liability shall not in any case exceed the purchase price of the product including shipping. Some states do not allow the exclusion or limitation of incidental or consequential damages so the above exclusions or limitations may not apply to you.

SPECIFICATIONS

LED's	15W COB
Max Brightness	1000 lm (high)/500 lm (low)
Run Time	2.5 hrs. (high), 5 hrs. (low)
Battery Size	3.7V 4000 MAH
Operating Temperature.....	23 to 118°F
Input Rating.....	5V DC (Charger not included, sold separately)
Charging Time	Approx. 4 hrs. (based on 1A)
Net Weight.....	0.9 lbs. (0.4kg)
Overall Length	17.7" (448mm)
UV Switch for UVA lighting to check for leakage	



Your product, accessories and packaging should be discarded in an environmentally responsible way.

Illustrations, figures and photos may vary slightly due to our program of continuous product improvements.

Cancer and Reproductive Harm
www.P65Warnings.ca.gov

© 2021 Distributed by SunZi Products Inc.
Schaumburg, IL
Visit www.mynextled.com
Customer Service: (877) 886-6822

v.2

MADE IN CHINA



**Scan to register
your product**

Simply scan and register
your product for warranty
or visit www.mynextled.com