

HDMI IP Extender

Model:DT-7043R



Description:

This extender consists of a transmitter and a receiver. Transmitter is for the completion of signal acquisition and compression, the receiver for the completion of signal decoding and port allocation, the middle of the transmission medium for high-quality CAT5e/6 cable, support 120 meters point to point transmission, support multiple receivers with a switch, Max. 253 receivers. Widely used in computer teaching system, high-quality multimedia display, video conferencing, computer, LCD plasma high-definition display venue, digital home theater, exhibition, education, finance, research, meteorology and other fields.

Features:

- 1- Using broadcast bandwidth balanced transmission, anti-interference, support point to point 120 meters transmission.
- 2- Supports Cat5 / Cat6 / single shield / unshielded twisted pair real-time point-to-point, point-to-multipoint transmission of images and audio signals.
- 3- VGA signal support 1920 X1080 @ 60Hz resolution, backward compatible with a variety of resolutions.
- 4- HDMI signal support 1080P @ 60Hz resolution, backward compatible with a variety of resolutions.
- 5- KVM products support keyboard, mouse remote operation.
- 6- POE-enabled products that can be connected to POE-enabled switches without adapter power supply.
- 7- Support IR return function.
- 8- With signal 3dB gain or pre-compensation to ensure that the signal high-definition true reduction.
- 9- Lightning protection, dust, anti-static, to extend the service life.
- 10- Can be through the switch / router and other relay equipment to achieve cascade and zoom. transmission, to achieve an extension of 240 meters.

More Detailed Photos:



Made in China