



2 FINISHING

3 PROTECTION

NW 1 PLUS

SUPREME





PRODUCT DESCRIPTION

Super cutting polishing compound used either to remove marks and P600-P800 sand scratches (according to the hardness of treated resins) or to restore high-oxidized gelcoats very fast and well, without overheating the surface. It assures a high quality finish without marks and haze as well as with low particles' over-splatting. This newest version of Pai Boat bestseller allows an even easier application, thanks to its specific viscosity. Further, its new revolutionary formula has been designed to remain wet for longer time, thus avoiding drying-up.

PHYSICAL PROPERTIES

Colour: White

Physical form: Creamy Odour: Light and pleasant Density: 1,610 g/ml

Flammability: Not flammable

Type of surface: Standard gelcoat,

epoxy, lacquer, carbon

HOW TO USE

Mix well, then apply by variable speed polisher, selecting either an anti-scratch wool pad SL3 for a balanced cutting-polishing action or ST1 for a more aggressive one. Apply a small quantity of compound on the polisher-pad. Let the polisher turn at low revolutions, speeding them up (800-1500 RPM) while spreading the paste with crossed movements. Pay attention at not overheating the surface. If necessary, please repeat the application more times. Eventually, wipe it off with a clean cloth.

PRODUCT INFORMATION

Packaging	Code	Pcs/Box
1 kg	600587	16
3 kg	600588	4

INSTRUCTIONS FOR USE









CROSSED MOVEMENTS

RECOMMENDATIONS









MIX BEFORE USE

SMALL QUANTITY

CLOSE THE CAP

EASY GLOSS

STORAGE

FOLLOWING STEPS



TOPFINISH 2

