

1715L 17-inch LCD

Touchscreen Monitor





Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo 1715L 17-inch standard format touchscreen monitor is designed, developed and built to provide a space-saving and cost-effective touch solution. The 17-inch touchscreen monitor can function as a desktop or wall-mounted unit and includes a VESA mounting option. The touchscreen is factory-sealed against dirt, dust, and liquids and with controls on the side rather than the front, the touchscreen can be locked-out for public use.

Available with AccuTouch five-wire resistive and IntelliTouch surface acoustic wave (SAW) with an antiglare display and Dual/Serial USB

Touchscreen sealed from dirt, dust and liquid

Removable base and VESA mounting option

1715L 17-inch LCD Desktop Touchmonitor

Specifications			
Model	1715L		
Color	Dark gray		
Active Display Area	13.3" x 10.6" / 338 mm x 270 mm		
LCD Technology	Active Matrix TFT LCD with LED backlighting		
Diagonal Size	17" / 431.8 mm		
Aspect Ratio	5:4		
Native Resolution	1280 x 1024		
Other Supported Resolutions	1280 x 1024 60, 75 Hz; 1280 x 960 60 Hz; 1152 x 864 75 Hz; 1024 x 768 60, 70, 75 Hz; 1024 x 768 65 Hz; 832 x 624 75 Hz; 800 x 600 56, 60, 72, 75 Hz; 720 x 400 70 Hz; 720 x 350 70 Hz; 640 x 480 60, 72, 75 Hz; 640 x 480 66 Hz		
Number of Colors	16.7 million		
Number of Touches	Single-touch		
Brightness (typical)	LCD panel: 250 nits; IntelliTouch: 225 nits; AccuTouch: 200 nits		
Response Time - Total (typical)	20 msec		
Viewing Angle	Horizontal: ±85° or 170° total; Vertical: ±80° or 160° total		
Contrast Ratio (typical)	1000:1		
On-Screen Display	Accessible through switches along the bottom.		
	Controls: Menu, Power, Up, Down, Select		
	Settings: Auto Adjust, Brightness, Contrast, H-position, V-position, Clock, Phase, Color Temperature, OSD Timeout, OSD Language, Sharpness, Recall Defaults, Information		
	Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese		
	Lockouts: OSD, Power		
	VGA		
	DC jack		
1/0	AC jack		
	USB Type B		
	RS232 (DB-9)		
	VGA (VGA DE-15 (DB-15) Male connecter cable included)		
Video	Input Video Horizontal Sync frequency range: 31.5 – 80 KHz		
	Input Video Vertical Sync (frame rate) frequency range: 56.3 - 75Hz		
Power	Internal AC, power cable-C6 type		
	Input voltage range: 100-240VAC, 50/60Hz		
	Monitor input power connector: Coaxial power jack (2.0mm pin outer diameter, 6.4mm barrel inner diameter, 8.8mm Barrel depth)		
	Monitor input power signal specifications: 12VDC +/- 5%		
Power Consumption (typical)	Monitor only: ON: 10.52 W; SLEEP: 1.34 W; OFF: 0.30 W		
Monitor Dimension	With Stand: 14.4" x 15.4" x 8.0" / 366 mm x 391 mm x 203 mm		
	Without Stand: 13.0" x 15.4" x 2.44" / 331 mm x 391 mm x 62 mm		
Shipping Dimensions	With Stand: 10.2" x 19.4" x 17.6" / 260 mm x 494 mm x 448 mm		
Weight	Unpackaged: 15.2 lbs / 6.9 kg; Packaged: 21.2 lbs / 9.6 kg		
Temperature	Operating: 32°F to 104°F / 0°C to 40°C; Storage: -4°F to 122°F / -20°C to 60°C		
Humidity (non-condensing)	Operating 20%-80%; Storage 10%-95% (38.7° maximum wet bulb temperature)		
Regulatory Approvals and Declarations	Canada CUL, IC; China CCC; Europe CE; United Kingdom UKCA; Korea KCC; Taiwan BSMI; United States FCC, UL; Japan VCCI; International CB; Australia RCM; Russia EAC; Mexico NoM; RoHS, China RoHS, WEEE, REACH		
Mounting Options	VESA 4-hole 100mm mounting interface on rear of unit		
Warranty	3 years		
Extended Warranty	4 year warranty coverage - Elo P/N: E898247		
	5 year warranty coverage - Elo P/N: E898449		
	3 year warranty coverage + AUR - Elo P/N: E898648		
	4 year warranty coverage + AUR - Elo P/N: E894921		
	5 year warranty coverage + AUR - Elo P/N: E895125		
MTBF	50,000 hours demonstrated		
What's in the Box	Touch monitor, Quick Install Guide, 3x Tie wraps, VGA cable, Touch USB cable, NA Power cable, EU Power cable, EEI Label		
THIS CONTINUE DOX	Todas Timos Tallact Timodia Guide, of the wraps, 40/1 cable, Todas Obb cable, 14/1 Owel cable, E0 1 Owel cable, E1 Label		

Ordering Information

Part Number	Technology	Interface	Surface Treatment
E603162	AccuTouch	Serial/USB	Antiglare
E719160	IntelliTouch	Serial/USB	Antiglare

Learn more about Elo at **EloTouch.com**.

Americas Europe (EMEA)

Tel +1 408 597 8000 Tel +32 16 930 136 elosales.na@elotouch.com EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385 EloAsia@elotouch.com

