

Material Safety Data Sheet

Section 1: Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: Soak Off Gel Polish

Chemical Name: Gel Polish

Family: Soak Off Gel Polish

Product Use: cosmetics

MSDS Prepared By/Date: 11/14/2013

Updated 11/14/2013

Manufacture: Hand & Nail Harmony Inc

1545 Moonstone Brea, CA 92821

Emergency Phone Number: (800) 535-5053

Information Contacts: (714) 773-9758

Product #s :

01852 / 01856 /01857 / 01858

Description: Various Shades

Section 2: Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- Flammable Liquid
- May be slightly toxic.
- May cause moderate skin injury (reddening & swelling).
- May cause eye irritation



Potential Health Effects, Signs and Symptoms of Exposure:

| | |
|------------|---|
| Eye | Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering |
| Skin | May be irritating to skin in some individuals, especially after prolonged and/or repeated contact |
| Ingestion | If product is swallowed, may cause nausea, vomiting, and/or diarrhea |
| Inhalation | Vapors of this product may be slightly irritating to the nose, throat and other tissue of the respiratory system. Systems of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. |

NOTE: Refer to Section II, Toxicological Information for Details

Section 3: Composition/Information on Ingredients

| INCI NAME | CAS# | EINECS# | Exposure OSHA TWA/STEL | Limits ACGIH TWA/STEL | Carcinogen IARC/NTP/OSHA | % |
|--|------------------------|-----------|------------------------|-----------------------|--------------------------|-------------|
| Di-HEMA Trimethylhexyl Dicarbamate | 41137-60-4 /72869-86-4 | 276-957-5 | N/E | N/E | Not Listed | 30.0 - 55.0 |
| Hydroxypropyl Methacrylate | 27813-02-1 | 248-666-3 | N/E | N/E | Not Listed | 30.0 - 55.0 |
| Isobornyl Methacrylate | 7534-94-3 | 231-403-1 | N/E | N/E | Not Listed | 5.0-20.0 |
| Ethyl Acetate | 141-78-6 | 205-500-4 | 400ppm | 400ppm | Not Listed | 5.0-20.0 |
| Butyl Acetate | 123-86-4 | 204-658-1 | 150ppm | 150ppm | Not Listed | 5.0-20.0 |
| HEMA | 868-77-9 | 212-782-2 | N/E | N/E | Not Listed | 1.0-5.0 |
| Trimethylolpropane Trimethacrylate | 3290-92-4 | 221-950-4 | N/E | N/E | Not Listed | 1.0-5.0 |
| Nitrocellulose | 9004-70-0 | N/A | N/E | N/E | Not Listed | 1.0-5.0 |
| Adipic Acid/Neopentyl Glycol/Trimellitic Anhydride Copolymer | 28407-73-0 | N/A | N/E | N/E | Not Listed | 1.0-5.0 |
| Isopropyl Alcohol | 67-63-0 | 200-661-7 | 400 ppm | 200 ppm | Not Listed | 1.0-5.0 |
| Trimethyl Pentanyl Diisobutyrate | 6846-50-0 | 229-934-9 | N/E | N/E | Not Listed | 1.0-5.0 |
| Triphenyl Phosphate | 115-86-6 | 204-112-2 | N/E | N/E | Not Listed | 1.0-5.0 |
| Propyl Acetate | 109-60-4 | 203-686-1 | N/E | N/E | Not Listed | 1.0-5.0 |
| n-Butyl Alcohol | 71-36-3 | 200-751-6 | N/E | N/E | Not Listed | 1.0-5.0 |
| Ethyl Trimethylbenzoyl Phenylphosphinate | 84434-11-7 | 282-810-6 | N/E | N/E | Not Listed | 1.0-5.0 |
| Clay | N/A | N/A | N/E | N/E | Not Listed | 1.0-5.0 |
| Stearalkonium Hectorite | 12691-60-0 | 305-633-9 | N/E | N/E | Not Listed | 1.0-5.0 |
| Stearalkonium Bentonite | 130501-87-0 | N/A | N/E | N/E | Not Listed | 1.0-5.0 |
| Diacetone Alcohol | 123-42-2 | 204-626-7 | N/E | N/E | Not Listed | 1.0-5.0 |
| Hydroxycyclohexyl Phenyl Ketone | 947-19-3 | 213-426-9 | N/E | N/E | Not Listed | 1.0-5.0 |
| Acrylates Copolymer | 9010-88-2 | N/A | N/E | N/E | Not Listed | 1.0-5.0 |
| Ethylene /VA Copolymer | 24937-78-8 | N/A | N/E | N/E | Not Listed | 1.0-5.0 |
| PEG/PPG 27/27 Dimethicone | N/A | N/A | N/E | N/E | Not Listed | <1.0 |
| Benzophenone-1 | 131-56-6 | 205-029-4 | N/E | N/E | Not Listed | <1.0 |
| Dimethicone | 9006-65-9 | N/A | N/E | N/E | Not Listed | <1.0 |
| Citric Acid | 77-92-9 | 201-069-1 | N/E | N/E | Not Listed | <1.0 |
| Sucrose Acetate Isobutyrate | 126-13-6 | 204-771-6 | N/E | N/E | Not Listed | <1.0 |
| p-Hydroxyanisole | 150-76-5 | 205-769-8 | N/E | N/E | Not Listed | ≤0.02 |
| May Contain | | | | | | |
| Titanium Dioxide (CI 77891) | 13463-67-7 | 236-675-5 | 15 mg/m3 | 10 mg/m3 | Not Listed | |

N/E - None Established
N/R - Not Reviewed

N/DA - No Data Available
N/A - Not Applicable

* See section 16

Di-Hema Trimethylhexyl Dicarbamate
Butyl Acetate
Ethyl Acetate
Hydroxypropyl Methacrylate:

Hazard Symbol: Xi
Hazard Symbol: Xi
Hazard Symbol: Xi
Hazard Symbol: Xi

Risk Phrases: R36/37/38
Risk Phrases: R36/38, R43
Risk Phrases: R36/38, R43
Risk Phrases: R36//37/38, R43

Safety Phrases: S14, S3/7, S62
Safety Phrases: S2, S26
Safety Phrases: S2, S26
Safety Phrases: S26, S36/37

| | | | |
|------------------------|-----------------------|-----------------------------|---|
| Isobomyl Methacrylate: | Hazard Symbol: Xi | Risk Phrases: R36/37/38 | Safety Phrases: S26,S27,S28,S29,S30,S33,S35,S36 |
| Triphenyl Phosphate | Hazard Symbol: N | Risk Phrases: R50/53 | Safety Phrases: S16/23/25/29/33 |
| TPO-L: | Hazard Symbol: | Risk Phrases: R99 | Safety Phrases: |
| Isopropyl Alcohol: | Hazard Symbols: Xi, F | Risk Phrases: R11, R36, R67 | Safety Phrases: S2, S7, S16, S24/25, S26 |

See Section 16 for Risk and Safety Phrase Key

Section 4: First Aid Measures

| | |
|--------------------------|---|
| First Aid for Eye | Splashes are not likely, however, if product gets into the eyes, flush with plenty of water for at least 15 minutes. If irritation occurs, seek medical attention immediately. |
| First Aid for Skin | Remove contaminated clothing and wash contact area with soap and water for 15 minutes. |
| First Aid for Inhalation | In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention. |
| First Aid for Ingestion | If appreciable quantities are swallowed, seek medical attention. |

Section 5: Fire Fighting Measures

| Flash Point (°F/ °C) | Flammable Limit (vol%) | Auto-ignition Temperature (vol%) |
|--------------------------|------------------------|----------------------------------|
| > 35°F / 1.6°C estimated | No Data | No Data |

| | |
|---|---|
| Method: | |
| WARNING: Flammable. Keep away from heat, lit cigarettes, sparks & open flame .Keep containers closed | |
| Extinguishing Media: | Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires. |
| Fire Fighting Instructions: | Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists. |

Section 6: Accidental Release Measures

| | |
|--------|---|
| Spill: | Before cleaning any spills or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. Dike and contain spill with inert material (e.g. sand or earth). Use ONLY non sparking tools for recovery and clean-up. Transfer liquid to containers for recovery or disposal and solid diking material to separated containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways. |
|--------|---|

Section 7: Handling and Storage

| | |
|---------------------|--|
| Handling: | Keep container closed when not in use. Avoid prolong contact with the product. Avoid breathing vapors of this product. Use in a well ventilated location. |
| Storage: | Product is extremely light sensitive. If exposed to natural light, LED, UVA, UVB or UV any light, material will cure very quickly. Store in a cool, dry place, away from heat and all types of light. Store away from incompatible materials |
| Special precautions | Keep this materials away from heat, sparks, and open flame. Keep containers tightly closed when not in use. |

Section 8: Exposure Controls / Personal Protection

| | |
|--------------------------------------|--|
| Engineering Controls | When working with large quantities of product, provide adequate ventilation. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. |
| Personal Protective Equipment | |
| General: | To identify additional Personal protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron boots, or whole body suits. Nitrile rubber is better than PVC. |
| Eye / Face Protection: | Wear chemical splash goggles |
| Skin Protection: | Wear impervious gloves (Neoprene) |
| Respiratory Protection: | A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. |

Section 9: Physical and Chemical Properties

| Appearance | Odor & Odor Threshold | pH | Specific Gravity | Viscosity | %Volatile |
|----------------|------------------------------|----|------------------|-----------|-----------------|
| viscous liquid | characteristic acrylate odor | NA | (H20=1): 1.15 | N/DA | By Volume: <7.0 |

| Boiling Point/Freezing Point | Decomposition Temperature | Octanol/Water Partitioning Coefficient Log Po/w | Vapor Pressure: | Vapor Density | Evaporation Rate | Ignition | Solubility In Water (20°C) |
|------------------------------|---------------------------|---|----------------------|---------------|------------------|----------|----------------------------|
| N/A | N/A | N/A | (mm Hg) @ 20 C:<0.01 | No Data | No Data | No Data | Insoluble |

| Flash Point (°F/ °C) | Flammable Limit (vol%) | Auto-ignition Temperature (vol%) |
|--------------------------|------------------------|----------------------------------|
| > 35°F / 1.6°C estimated | No Data | No Data |

Section 10: Stability and Reactivity

| | |
|---|--|
| Stability Normally Stable | Incapability (Material to Avoid): Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases. |
| Hazardous Decomposition Products: Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide | Hazardous Polymerization: May occur --- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers. |
| Conditions to Avoid: Storage > 100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization, contamination with incompatible materials. | |

Section 11: Toxicological Information

| Acute Oral Toxicity | Acute Dermal Toxicity | Acute Inhalation Toxicity | Irritation - skin | Irritation - Eye |
|---------------------|-----------------------|---------------------------|-------------------|-------------------|
| No info available | No info available | No info available | No info available | No info available |

Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

| Sensitization | Mutagenicity | Sub-chronic Toxicity |
|---------------|--------------|----------------------|
| N/DA | N/DA | N/DA |

Section 12: Ecological Information

Ecotoxicological Information

| Acute Toxicity to Fish | Acute Toxicity to Invertebrates | Acute Toxicity to Algae | Bioconcentration | Toxicity to Sewage Bacteria |
|--------------------------|---------------------------------|--------------------------|--------------------------|-----------------------------|
| No Information Available | No Information Available | No Information Available | No Information Available | No Information Available |

Environmental Stability:

| | |
|----------------------------------|--|
| Ethyl Acetate: | removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. |
| Butyl Acetate: | compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. |
| Isopropyl Alcohol: | or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days, Isopropyl alcohol is not expected to bioconcentrate. |
| Chemical Fate Information | |
| Biodegradability | No Information Available |
| Chemical Oxygen Demand | No Information Available |

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated.

Do not allow to enter drinking water supplies, wastewater, or soil.

Section 13: Disposal Considerations

Waste disposal must be in accordance with appropriate Federal, State and local regulations. US. EPA Waste #: D001

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member State, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

Section 14: Transport Information

DOT (49 CFR 172)

Proper Shipping Name: UN 1263, Paint Related Material, 3, II
Identification Number: UN1263
Marine Pollutant: Yes, Triphenyl Phosphate
Consumer Commodity ORM-D (≤ 1.0 L)

Emergency Response Guidebook (ERG) #:

IATA (DGR):

Proper Shipping Name: UN 1263, Paint Related Material, 3, II
Class or Division: 3
UN or ID Number: UN 1263
Consumer Commodity, 9, ID8000 (≤ 0.5 L)

Emergency Response Guidance (ICAO) #:

IMO (IMDG):

Proper Shipping Name: UN 1263, Paint Related Material, 3, II
Class or Division: 3
UN or ID Number: UN1263
Special Provisions & Stowage/Segregation:

Emergency Schedule (Ems) #:

TDGR (Canadian GND): Mark Package "Limited Quantity" or "Quantite Limitee" or "LTD QTY" or "Quant Ltee" (≤ 1.0 L)
UN1263, Paint, 3, II, (>1.0 L)

ADR/RID (EU): UN 1263, Paint Related Material, 3, II, ADR

Other Information:

MEXICO (SCT): UN1263, Pintura, 3, II, Cantidad Limitada (≤ 1.0L)

ADGR (AUS): UN1263, Paint, 3, II LTD QTY (≤ 1.0L)

Section 15: Regulatory Information

US Federal Regulations

| | |
|-------------------------------------|---|
| Clean Air Act: HAP/ODS | This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act: <ul style="list-style-type: none"> • NONE This product does not contain any Class I or Class 2 ODS |
| Clean Water Act: Priority Pollutant | This product contains the following Hazardous Substances as defined by the CWA: <ul style="list-style-type: none"> • NONE This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA |
| FDA: Food Packaging Status | This product has not been cleared by the FDA for use in food packaging and /or other applications as an indirect food additive. |
| Occupational Safety and Health Act | This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are: <ul style="list-style-type: none"> • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard |
| RCRA | This product is not considered to be a hazardous waste under RCRA (40 CFR 261) |
| SARA Reporting Requirements: | SARA 304 (40 CFR Table 302.4)- Butyl Acetate, Ethyl Acetate |
| SARA Threshold Planning Quantity: | There are no specific Threshold Planning Quantities for the components of this product. |
| TSCA Section 8(b) Inventory: | This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA pre-manufacture notification requirements. |
| CERCLA Reportable Quantity (RQ): | Butyl Acetate: 2270 kg; 5000 lbs.; Ethyl Acetate: 2270 kg; 5000 lbs. |


State Regulations

| | |
|--------------------------------------|--|
| CA Right-to-Know Law: | Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4, |
| California No Significant Risk Rule: | NONE |
| MA Right-to-Know Law: | Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4, Nitrocellulose CAS# 9004-70-0, Triphenyl Phosphate CAS# 115-86-6 |
| NJ Right-to-Know Law: | Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4 |
| PA Right-to-Know Law: | Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4, Triphenyl Phosphate CAS# 115-86-6 |
| FL Right-to-Know Law: | Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4 |
| MN Right-to-Know Law: | Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4, Triphenyl Phosphate CAS# 115-86-6 |

International Regulations

| | |
|---|--|
| CDSL: Canadian Inventory (on Canadian Transitional List) | Hydroxypropyl methacrylate CAS #27813-02-1 is on the DSL List. WHMIS = D2B Hydroxycyclohexyl phenyl ketone CAS# 947-19-3 is on the DSL list. WHMIS - n/da 2-Hydroxyethyl methacrylate CASE# 868-77-9 is on the DSL List. WHMIS - n/da Isobornyl Methacrylate CAS# 7534-94-3 is on the DSL list. WHMIS - n/da Titanium Dioxide CAS# 13463-67-7 WHMIS- not controlled D&C Violet 2/CI60725 CAS # 81-48 is not on the DSL List. WHMIS = N/DA Ethyl Acetate CAS# 141-78-6 is on the DSL list. WHMIS= B2,D2B Butyl Acetate CAS # 123-86-4 is on the list. WHMIS + B2, D1B, D2B Acrylates Copolymer CAS # 25035-69-2 is on the DSL list. WHMIS= N/DA |
|---|--|

Labeling according to EC Directives - 1999/45/EC

| | |
|---|--|
| European Community:  | HNH Base Gel: <ul style="list-style-type: none"> • HAZARD SYMBOLS: Xi irritant, F: Flammable, Xn: Harmful • RISK PHRASES: R22: Harmful if swallowed, R36/38/37: Irritating to eyes, respiratory system, and skin, R43: May cause sensitization by skin contact. R10 Flammable, R11 Highly Flammable, R20 Harmful by inhalation R21 Harmful in contact with the skin, R41 Risk of serious damage to eyes, R50 Very toxic to aquatic organisms R53 May cause long term adverse effect in the aquatic environment, R65 Harmful, may cause lung damage R66 Repeated exposure may cause skin dryness or cracking, R67 Vapors may cause drowsiness and dizziness • SAFETY PHRASES: S18: Handle and open container with care, S24/25: avoid contact with skin and eyes, S36/37: Wear suitable protective clothing and gloves, S38: in case of insufficient ventilation, wear suitable respiratory equipment. S16: Keep away from sources of ignition-No Smoking, S23: Do not breathe vapor, S29: Do not empty into drains, S33: Take precautionary measures against. |
|---|--|

EU Classes and Risk / Safety Phrases :

Hazard Symbols:

Xi - Irritants

F - Flammable substances or preparations

Xn: Harmful

• **RISK PHRASES:** **R22:** Harmful if swallowed, **R36/38/37:** Irritating to eyes, respiratory system, and skin, **R43:** May cause sensitization by skin contact. **R10** Flammable, **R11** Highly Flammable, **R20** Harmful by inhalation **R21** Harmful in contact with the skin, **R41** Risk of serious damage to eyes, **R50** Very toxic to aquatic organisms **R53** May cause long term adverse effect in the aquatic environment, **R65** Harmful, may cause lung damage

R66 Repeated exposure may cause skin dryness or cracking, **R67** Vapors may cause drowsiness and dizziness

• **SAFETY PHRASES:** **S18:** Handle and open container with care, **S24/25:** avoid contact with skin and eyes, **S36/37:**


Wear suitable protective clothing and gloves, **S38:** in case of insufficient ventilation, wear suitable respiratory equipment. **S16:** Keep away from sources of ignition-No Smoking, **S23:** Do not breathe vapor,

S2 Keep out of reach of children; **S3/7** Keep container tightly closed in a cool place; **S26** In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; **S27** Take off immediately all contaminated clothing; **S28** After contact with skin, wash immediately with plenty of water; **S29** Do not empty into drains;

S30 Never add water to this product; **S33** Take precautionary measures against static discharges; **S35** This material and its container must be disposed of in a safe way;

S62 If swallowed, do not induce vomiting; seek medical advice immediately and show the container or label

Hazard Rating System (Pictograms)



This information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).