

1.1 1.2

1.3

1.4

1.5

1.6 1.7

1.8

1.9

SAFETY DATA SHEET

Page 1 of 7

1703A-060

SDS Revision: 1.0 SDS Revision Date: 05/24/2018

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

Business Phone / Fax: +1 (770) 534-0300 / +1 (770) 534-8954

1. PRODUCT & COMPANY IDENTIFICATION						
Product Name:	John Paul Mitchell Systems – Awapuhi Wild Ginger Anti-Frizz Hairspray					
Chemical Name:	Aerosol Hair Spray					
Synonyms:	Awapuhi Wild Ginger Anti-Frizz Hairspray					
Trade Names:	JPMS – Awapuhi Wild Ginger Anti-Frizz Hairspray 55% VOC - 1703A-060					
Product Uses/ Restrictions	Professional and Cosmetic Use					
Distributor's Name:	KIK Custom Products					
Distributor's Address:	2030 Old Candler Road, Gainesville, GA 30507 USA					
Emergency Phone:	CHEMTREC: +1 (800) 424- 9300 / + 1 703- 527 - 3887 CCN810912					

2. HAZARDS IDENTIFICATION

Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the 2.1 classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia) DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED.

> HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION. Classification: Level 3 Aerosol; Category 1 Extremely Flammable Aerosol. Eye irrit. 2B

Hazard Statements (H): H-222- Extremely Flammable Aerosol. H229-Pressurized container: may burst if heated. H320 - Causes eye irritation. H280 - Contents under pressure; may explode if heated. Precautionary Statement (P):

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.

P211 – Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 – avoid breathing vapors/spray.

P271 – Use only in well-ventilated area.

P304+P340 – IF INHALED; Remove person to fresh air and keep comfortable for breathing.

P305+P351+338 – IF INEYES; Rinse cautiously with water for several minutes. Remove contact lenses, if present, continue rinsing.

P337+P313 – If eye irritation persists: Get medical advice/attention.

P410+P412 - Protect from sunlight. Do no expose to temperature exceeding 48°C (120 °F).

P501 – Dispose of contents/container to licensed and permitted disposal or recycling facility.

3. COMPOSITION & INGREDIENT INFORMATION

Substance / Chemical Name(s)	CAS No.	EINECS No.	%	Other
DIFLUOROETHANE (R-152a)	75-37-6	200-866-1	20 - 45	Flam. Gas 1; H220
Ethanol (SD Alcohol 40B)	64-17-5	200-578-6	30 - 55	Flam. Liq. 2; H225
Isobutane	75-28-5	200-857-2	3 - 20	Flam. Gas 1; H220

4. FIRST AID MEASURES

		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals upon prolonged or repeated exposure.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.
		Inhalation:	Remove victim to fresh air and keep comfortable for breathing.
		Eyes:	If product get in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.
		Skin:	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before ruse. If irritation, redness or swelling persists, consult a physician immediately.
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.



1703A-060

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 05/24/2018

Extinguishing Methods: Firefighting Procedures: Spills:	uninvolved cobursting. If a and release fl containers co Water Fog, Fo As in any fire, demand_ and water spray trunoff from f natural water pressure self-or decompose. Before cleani Equipment (F Small spills W combustible not use wate (e.g., plastic because Large spills: K release. Isola done with mi	5. FIREFIGHTING MEASURES Fool (NFPA 30B). Aerosols may burst at temperatures about a containers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is completed ammable liquids and/or exposed gases if exposed to the fool by spraying them with water until the fire has been exposed, CO2, Dry Chemical water MSHA/NIOSH approved self-contained breathing of full protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, dring the fire control or dilution from entering sewers, drains, dring the fire contained breathing apparatus to protect against potentiation products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURING and spill or leak, individuals involved in spill cleanup repropriate personal protective equipment including material such as vermiculite or sand to soak up the product or or a material such as "speedy dry" to soak up material. Procoms, shovels, dustpans) and place into a plastic contained incompatible materials (e.g., organics such as oil) and the immediate hazard area and keep unauthorized personal risk. Wear appropriate protective equipment including this product. Contents un	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent lking water supply, or any IOSH-approved positive intial hazardous combustion ES must wear appropriate Personal Pressure duct and place into a container for la sweep up material using non-spaniner or plastic liner within another way from spill. Stay upwind and aw bonnel out of area. Stop spill or releated luding respiratory protection as cor	Use a non- ater disposal. Do rking materials container. yay from spill or ase if it can be ditions warrant.					
Extinguishing Methods: Firefighting Procedures:	uninvolved cobursting. If a and release fl containers co Water Fog, Fo As in any fire, demand_ and water spray trunoff from f natural water pressure self-or decompos Before cleani Equipment (F Small spills W combustible not use wate (e.g., plastic k Large spills: K release. Isola done with mi	col (NFPA 30B). Aerosols may burst at temperatures about a containers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is completed and busting and/or exposed gases if exposed to the color by spraying them with water until the fire has been exposed, or Dry Chemical and MSHA/NIOSH approved self-contained breathing at full protective gear. Keep containers cool until well after the cool fire-exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, dring and full burker gear including NI-contained breathing apparatus to protect against potentiation products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURI and any spill or leak, individuals involved in spill cleanup representations are appropriate personal protective equipment including material such as vermiculite or sand to soak up the product or or a material such as "speedy dry" to soak up material. For own, shovels, dustpans) and place into a plastic contained incompatible materials (e.g., organics such as oil) and the immediate hazard area and keep unauthorized person inimal risk. Wear appropriate protective equipment including materials.	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive ntial hazardous combustion ES must wear appropriate Personal Pro fuct and place into a container for la cut and place into a	Use a non- ater disposal. Do rking materials container. vay from spill or ase if it can be					
Extinguishing Methods: Firefighting Procedures:	uninvolved co bursting. If a and release fl containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water pressure self- or decompos Before cleani Equipment (F Small spills W combustible not use wate (e.g., plastic b Large spills: K release. Isola	col (NFPA 30B). Aerosols may burst at temperatures about a containers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete a comparison to the proof of the proo	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent lking water supply, or any IOSH-approved positive ntial hazardous combustion ES must wear appropriate Personal Pre fluct and place into a container for la c. Sweep up material using non-spa ainer or plastic liner within another way from spill. Stay upwind and aw onnel out of area. Stop spill or relea	Use a non- ater disposal. Do rking materials container. vay from spill or ase if it can be					
Extinguishing Methods: Firefighting Procedures:	uninvolved co bursting. If a and release fl containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water pressure self- or decompos Before cleani Equipment (F Small spills W combustible not use wate (e.g., plastic b Large spills: K release. Isola	col (NFPA 30B). Aerosols may burst at temperatures about a containers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete a comparison to the proof of the proo	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent lking water supply, or any IOSH-approved positive ntial hazardous combustion ES must wear appropriate Personal Pre fluct and place into a container for la c. Sweep up material using non-spa ainer or plastic liner within another way from spill. Stay upwind and aw onnel out of area. Stop spill or relea	Use a non- ater disposal. Do rking materials container. vay from spill or ase if it can be					
Extinguishing Methods: Firefighting Procedures:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water pressure self- or decompos Before cleani Equipment (F Small spills W combustible not use wate (e.g., plastic b Large spills: K	col (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete alammable liquids and/or exposed gases if exposed to the col by spraying them with water until the fire has been exposed, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing diffull protective gear. Keep containers cool until well after cool fire-exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, drining apparatus to protect against potentiation products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURI or any spill or leak, individuals involved in spill cleanup repel. Vear appropriate personal protective equipment including material such as vermiculite or sand to soak up the product or or a material such as "speedy dry" to soak up material. Procoms, shovels, dustpans) and place into a plastic contained incompatible materials (e.g., organics such as oil) and service of the compatible materials (e.g., organics such as oil) and compatible materials (e.g., organics such as oil) and contained to the contained such as oil and compatible materials (e.g., organics such as oil) and contained to the contained such as oil and compatible materials (e.g., organics such as oil) and contained to the contained such as oil and contained to the contained such as of the conta	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent lking water supply, or any IOSH-approved positive intial hazardous combustion ES must wear appropriate Personal Pro ing gloves and protective eyewear. Iduct and place into a container for la is. Sweep up material using non-spa ainer or plastic liner within another way from spill. Stay upwind and aw	Use a non- ater disposal. Do rking materials container. vay from spill or					
Extinguishing Methods: Firefighting Procedures:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water pressure self- or decompos Before cleani Equipment (F Small spills W combustible not use wate	col (NFPA 30B). Aerosols may burst at temperatures about a containers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is completed ammable liquids and/or exposed gases if exposed to the col by spraying them with water until the fire has been exposed, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing diffull protective gear. Keep containers cool until well aftor cool fire-exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, dring raway. Firefighters must use full bunker gear including NI-contained breathing apparatus to protect against potentiation products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURING any spill or leak, individuals involved in spill cleanup repeb. Wear appropriate personal protective equipment including material such as vermiculite or sand to soak up the product or a material such as "speedy dry" to soak up material.	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent liking water supply, or any IOSH-approved positive ntial hazardous combustion ES must wear appropriate Personal Pro ang gloves and protective eyewear. duct and place into a container for is . Sweep up material using non-spa	Use a non- ater disposal. Do rking materials					
Extinguishing Methods: Firefighting Procedures:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water pressure self- or decompos	col (NFPA 30B). Aerosols may burst at temperatures about a containers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete a lammable liquids and/or exposed gases if exposed to the col by spraying them with water until the fire has been exposed, Dry Chemical wear MSHA/NIOSH approved self-contained breathing a full protective gear. Keep containers cool until well after the cool fire-exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, dring rway. Firefighters must use full bunker gear including NI recontained breathing apparatus to protect against potentiation products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURING any spill or leak, individuals involved in spill cleanup representations.	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive ntial hazardous combustion ES must wear appropriate Personal Pro- ting gloves and protective eyewear. duct and place into a container for la	Use a non- ater disposal. Do					
Extinguishing Methods: Firefighting Procedures:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water pressure self- or decompos	col (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the old by spraying them with water until the fire has been exposed, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing diffull protective gear. Keep containers cool until well aft to cool fire-exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, dring rway. Firefighters must use full bunker gear including NI e-contained breathing apparatus to protect against potentition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURI and any spill or leak, individuals involved in spill cleanup repel.	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent liking water supply, or any IOSH-approved positive ntial hazardous combustion ES must wear appropriate Personal Pro- ng gloves and protective eyewear.	Use a non-					
Extinguishing Methods: Firefighting Procedures:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water pressure self- or decompos	col (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the old by spraying them with water until the fire has been exposed, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing difull protective gear. Keep containers cool until well after the cool of fire-exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, drink the contained breathing apparatus to protect against potential products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURING any spill or leak, individuals involved in spill cleanup repel.	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent iking water supply, or any IOSH-approved positive ntial hazardous combustion ES must wear appropriate Personal Pre						
Extinguishing Methods: Firefighting Procedures:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water pressure self- or decompos	col (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the old by spraying them with water until the fire has been exposed, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing difull protective gear. Keep containers cool until well after the cool of fire-exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, drink the contained breathing apparatus to protect against potentiation products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURIng any spill or leak, individuals involved in spill cleanup responses to the container of the	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive ntial hazardous combustion	otective					
Extinguishing Methods:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water pressure self-	tol (NFPA 30B). Aerosols may burst at temperatures about a containers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the old by spraying them with water until the fire has been enough, CO ₂ , Dry Chemical, wear MSHA/NIOSH approved self-contained breathing diffull protective gear. Keep containers cool until well after cool fire-exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, drining the contained breathing apparatus to protect against potential products and oxygen deficiencies.	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive ntial hazardous combustion	30					
Extinguishing Methods:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water pressure self-	col (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the book by spraying them with water until the fire has been exposed, CO ₂ , Dry Chemical, wear MSHA/NIOSH approved self-contained breathing of full protective gear. Keep containers cool until well after the cool of the exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, drink the contained breathing apparatus to protect against potential.	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive	30					
Extinguishing Methods:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water pressure self-	col (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the book by spraying them with water until the fire has been exposed, CO ₂ , Dry Chemical, wear MSHA/NIOSH approved self-contained breathing of full protective gear. Keep containers cool until well after the cool of the exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, drink the contained breathing apparatus to protect against potential.	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive	30					
Extinguishing Methods:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f natural water	col (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the bool by spraying them with water until the fire has been exposed, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing of full protective gear. Keep containers cool until well after the cool fire-exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, drinkrway. Firefighters must use full bunker gear including NI	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive	30					
Extinguishing Methods:	uninvolved co bursting. If a and release fl containers co Water Fog, Fo As in any fire, demand_ and water spray t runoff from f	ool (NFPA 30B). Aerosols may burst at temperatures about a containers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the ool by spraying them with water until the fire has been enoun, CO ₂ , Dry Chemical, wear MSHA/NIOSH approved self-contained breathing of full protective gear. Keep containers cool until well after o cool fire-exposed surfaces and to protect personnel. Fire control or dilution from entering sewers, drains, drink	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent king water supply, or any	30					
Extinguishing Methods:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and water spray t	ool (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the ool by spraying them with water until the fire has been enough, CO ₂ , Dry Chemical, wear MSHA/NIOSH approved self-contained breathing of full protective gear. Keep containers cool until well after o cool fire-exposed surfaces and to protect personnel.	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent	30					
Extinguishing Methods:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire, demand_ and	ol (NFPA 30B). Aerosols may burst at temperatures about a containers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the old by spraying them with water until the fire has been end and, CO ₂ , Dry Chemical, wear MSHA/NIOSH approved self-contained breathing a full protective gear. Keep containers cool until well after	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ter the fire is out. Use	30					
Extinguishing Methods:	uninvolved co bursting. If a and release fi containers co Water Fog, Fo As in any fire	ool (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the ool by spraying them with water until the fire has been exposed, CO ₂ , Dry Chemical, wear MSHA/NIOSH approved self-contained breathing	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure-	30					
Extinguishing Methods:	uninvolved co bursting. If a and release fl containers co Water Fog, Fo	ool (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the ool by spraying them with water until the fire has been exposed, CO ₂ , Dry Chemical	e projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished.	3					
•	uninvolved co bursting. If a and release f	ol (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete lammable liquids and/or exposed gases if exposed to the	e projectile hazards when e. Containers may rupture e heat of fire. Keep						
Fire and Explosion Hazards:	uninvolved co bursting. If a	ool (NFPA 30B). Aerosols may burst at temperatures abountainers to prevent possible bursting. Aerosols may be erosols are bursting, stay clear until bursting is complete	e projectile hazards when e. Containers may rupture	_					
Fire and Explosion Hazards:	uninvolved co	ool (NFPA 30B). Aerosols may burst at temperatures aboontainers to prevent possible bursting. Aerosols may be	projectile hazards when						
Fire and Explosion Hazards:		ol (NFPA 30B). Aerosols may burst at temperatures abo							
Fire and Explosion Hazards	Level 3 Aeros		ove 120° F (48°C) Cool						
		5. FIREFIGHTING MEASURES							
	1		LILS JANIA						
	exacerbated.		PROTECTIVE EQUIPMENT EYES SKIN	В					
	_	natological conditions (such as eczema) and respiratory uch as bronchial asthma and/or bronchitis) may be	PHYSICAL HAZARDS	0					
Aggravated by Exposure		-		3					
Medical Conditions			HEALTH	1					
Target Organs:									
Chronic Health Effects:	symptoms in	some sensitive individuals. May also induce skin sensiti	zation and respiratory hypersensiti	vity. Possible					
Character Health Effects			-						
			ngle accidental ingestion. These ing	redients may be					
Acute Health Effects:									
	Evec:	Overexposure in eyes, may cause redness, itching and watering (risk of serious damage to eyes) Contact							
	<u> </u>	overexposure may include redness, itching, and irritation of affected areas.							
	Skin:								
Symptoms of Overexposure	<u>Ingestion:</u>								
	<u>innalation:</u>	difficulty breathing. Inhalation of concentrated vapors can cause nervous system depression (e.g.,							
	respiratory system. Symptoms of overexposure can include coughing, wheezing, pasal congestion, and								
	<u>Eyes.</u>		derately irritating to the nose, throat and other tissues of the						
	Chronic Health Effects: Target Organs:	Skin: Eyes: Inhalation: Moderate irr drowsiness, of No harmful of irritating to s symptoms in allergic derm Target Organs: Medical Conditions Aggravated by Exposure Skin: Eyes: Inhalation: Moderate irridrowsiness, of No harmful of irritating to s symptoms in allergic derm Acute health include irritating to s symptoms in allergic derm include irritating to s	Vapors of this product may be moderately irritating to respiratory system. Symptoms of overexposure can in difficulty breathing. Inhalation of concentrated vapors drowsiness, dizziness, headaches, nausea). Symptoms of Overexposure Ingestion: May cause nausea, vomiting and/or diarrhea and cent Prolonged contact with skin may result in bleaching are skin reactions (e.g., rashes, welts, dermatitis) in some overexposure may include redness, itching, and irritat Overexposure may include redness, itching, and irritat may cause mild eye irritation including stinging, water Inhalation: Symptoms of overexposure can include coughing, when Moderate irritation to eyes and skin near affected areas. Additionall drowsiness, dizziness, headaches and nausea. No harmful or chronic health effects are expected to occur from a sir irritating to skin and mucous membrane of the eye and respiratory symptoms in some sensitive individuals. May also induce skin sensitiallergic dermatitis. Target Organs: Eyes, skin, respiratory system. Medical Conditions Acute health hazards may be delayed. Most common symptoms	Vapors of this product may be moderately irritating to the nose, throat and other tissues respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal co difficulty breathing. Inhalation of concentrated vapors can cause nervous system depress drowsiness, dizziness, headaches, nausea). Ingestion: May cause nausea, vomiting and/or diarrhea and central nervous system depression. Prolonged contact with skin may result in bleaching and irritation of skin. The product cat skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Symptoms of overexposure may include redness, itching, and irritation of affected areas. Eyes: Overexposure in eyes, may cause redness, itching and watering (risk of serious damage to may cause mild eye irritation including stinging, watering and redness. Inhalation: Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult of the stimulation of complete irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can drowsiness, dizziness, headaches and nausea.					



1703A-060

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 05/24/2018

	Storage and Handling:	Use and store in a cool, dry, we sunlight. Avoid temperatures a									
		physical damage. To avoid unintentional spraying, keep cap in place when not in use. Storage level 3.									
7.3	Special Precautions:	Spilled material may present a	slipping l	nazard if	left unatte	ended. Clea	an all spills	promptly	/.		
		8. EXPOSURE CON	TROL	S & P	ERSON	IAL PRO	OTECTIO	NC			
8.1	Exposure Limits:			GIH		NOHSC	712011		OSHA		OTHER
0.1	Ppm (mg/m³)	Chemical Name(s)							STEL	IDLH	OTTIER
	r (6/ /	Ethanol (SD Alcohol 40B)	1000	3000	1000	1800	NF	1000	1900	3300	
		DIFLUOROETHANE (R-152a)	1000	NA	1000	NA	NA	NE	NA	NA	
		Isobutane	600	750	NF	NF	NA	NA	NA	NA	
8.2	Ventilation & Engineering	General mechanical (e.g., fans)	or natur	al ventila	tion is suf	ficient whe	n this prod	uct is in i	use. Use	local or	general
	Controls	exhaust ventilation to effective	ly remov	e and pr	event buil	dup of vapo	ors or mist {	generate	d from t	he handl	ing of this
		product.									
8.3	Respiratory Protection:	No special respiratory protection	n is requ	ired und	der typical	circumstan	ices of use o	or			
		handling. In instances where d		•	-		•	•			
		protection is needed, use only I							S.		
		State regulations, or the Canad				and applica	ıble standar	ds of			
		Canadian Provinces, EC member									
8.4	Eye Protection:	None required under normal co									
		be used when handling or using	g large qu	uantities	of this pro	duct (e.g.,	<u>></u> 1 gallon (3.8 L)).		Ě	
0.5	Hand Duckers	Nieus as actual 1	lini	- C	I I		alitie to the st				
8.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation is some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber,									m
			_	ge quan	tities (e.g.,	, <u>></u> 1 gallon	(3.8 L)), we	ar rubbe	er,	<u> </u>	(1)
		nitrile or impervious plastic glo	ves.								
8.6	Pady Protection:	No apron required when handling small quantities. When handling large quantities (e.g., >									
8.0	Body Protection:								-		
5 lbs.), eye wash station and deluge showers should be available. Upon completion of											
	work activities involving large quantities of this product, wash any exposed areas										
				or tills p	product, w	ash any exp	posed areas	•			
		thoroughly with soap and wate			product, w	ash any exp	posed areas				
		thoroughly with soap and wate	r.								
Q 1	Annearance	9. PHYSICA	r.								
	Appearance:	9. PHYSICA Aerosol, misty spray	r.					•			
9.2	Odor:	9. PHYSICA Aerosol, misty spray Fresh odor	r.								
9.2 9.3	Odor: Odor Threshold	9. PHYSICA Aerosol, misty spray Fresh odor NA	r.								
9.2 9.3 9.4	Odor: Odor Threshold pH:	9. PHYSICA Aerosol, misty spray Fresh odor NA NA	r.								
9.2 9.3 9.4 9.5	Odor: Odor Threshold pH: Melting/Freezing Point	9. PHYSICA Aerosol, misty spray Fresh odor NA NA	r.								
9.2 9.3 9.4 9.5	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling	9. PHYSICA Aerosol, misty spray Fresh odor NA NA	r.								
9.2 9.3 9.4 9.5 9.6	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range:	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA	r. L & CI	HEMI	CAL PR	OPERT	IES				
9.2 9.3 9.4 9.5 9.6	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint:	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA NA -30 °F (-34 °C) TCC for propellar	r. L & CI	HEMI	CAL PR	OPERT	IES				
9.2 9.3 9.4 9.5 9.6	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range:	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA NA -30 °F (-34 °C) TCC for propellar	r. L & CI	HEMI	CAL PR	OPERT	IES				
9.2 9.3 9.4 9.5 9.6 9.7	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint: Upper/Lower Flammability limits	9. PHYSICA Aerosol, misty spray Fresh odor NA	r. L & CI	HEMI ()	CAL PR	ethod 1010	TES Concentra				
9.2 9.3 9.4 9.5 9.6 9.7 9.8	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint: Upper/Lower Flammability limits Vapor Pressure:	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA NA -30 °F (-34 °C) TCC for propellar	r. L & CI	HEMI ()	CAL PR	ethod 1010	TES Concentra				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint: Upper/Lower Flammability limits Vapor Pressure: Vapor Density	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA NA NA NA -30 °F (-34 °C) TCC for propellar NA @ 20 °C (68° F) – Can pressure	r. L & CI	HEMI ()	CAL PR	ethod 1010	TES Concentra				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint: Upper/Lower Flammability limits Vapor Pressure: Vapor Density Relative Density:	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA NA NA O -30 °F (-34 °C) TCC for propellar NA @ 20 °C (68° F) – Can pressure >1	r. L & CI	HEMI ()	CAL PR	ethod 1010	TES Concentra				
9.2 9.3 9.4 9.5 9.6 9.7 9.9 9.9 9.11 9.11	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint: Upper/Lower Flammability limits Vapor Pressure: Vapor Density Relative Density:	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA NA -30 °F (-34 °C) TCC for propellar NA @ 20 °C (68° F) – Can pressure >1 0.85 – 0.95	r. L & CI	HEMI ()	CAL PR	ethod 1010	TES Concentra				
9.2 9.3 9.4 9.5 9.6 9.7 9.9 9.9 9.11 9.11	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint: Upper/Lower Flammability limits Vapor Pressure: Vapor Density Relative Density: Solubility:	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA NA -30 °F (-34 °C) TCC for propellar NA @ 20 °C (68° F) – Can pressure >1 0.85 – 0.95 Soluble	r. L & CI	HEMI ()	CAL PR	ethod 1010	TES Concentra				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint: Upper/Lower Flammability limits Vapor Pressure: Vapor Density Relative Density: Solubility: Partition Coefficient (log Pow):	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA NA -30 °F (-34 °C) TCC for propellar NA @ 20 °C (68° F) – Can pressure >1 0.85 – 0.95 Soluble NA	r. L & CI	HEMI ()	CAL PR	ethod 1010	TES Concentra				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.10 9.11 9.12 9.13	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint: Upper/Lower Flammability limits Vapor Pressure: Vapor Density Relative Density: Solubility: Partition Coefficient (log Pow):	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA NA -30 °F (-34 °C) TCC for propellar NA @ 20 °C (68° F) – Can pressure >1 0.85 – 0.95 Soluble NA	r. L & CI	HEMI ()	CAL PR	ethod 1010	TES Concentra				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12 9.13	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint: Upper/Lower Flammability limits Vapor Pressure: Vapor Density Relative Density: Solubility: Partition Coefficient (log Pow): Auto ignition Temperature:	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA NA -30 °F (-34 °C) TCC for propellar NA @ 20 °C (68° F) – Can pressure >1 0.85 – 0.95 Soluble NA NA	r. L & CI	HEMI ()	CAL PR	ethod 1010	TES Concentra				
9.11 9.12 9.13 9.14 9.15	Odor: Odor Threshold pH: Melting/Freezing Point Initial Boiling Point/ Boiling Range: Flashpoint: Upper/Lower Flammability limits Vapor Pressure: Vapor Density Relative Density: Solubility: Partition Coefficient (log Pow): Auto ignition Temperature: Decomposition	9. PHYSICA Aerosol, misty spray Fresh odor NA NA NA NA -30 °F (-34 °C) TCC for propellar NA @ 20 °C (68° F) – Can pressure >1 0.85 – 0.95 Soluble NA NA	r. L & CI	HEMI ()	CAL PR	ethod 1010	TES Concentra				



SDS Revision: 1.0

1703A-060

SDS Revision Date: 05/24/2018

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

		1	0. STABI	LITY & REACTIVIT	Υ			
10.1	Stability:	Stable at normal tempe	eratures.					
10.2	Hazardous Decomposition Products:	Oxides of carbon (CO, CO ₂) and sulfur (SO ₂)						
10.3	Hazardous Polymerization:	Will not occur.						
10.4	Conditions to Avoid	Excessive heat, direct s	unlight, flame	es, heat sources and incomp	atible substances.			
10.5	Incompatible Substances	Mixture with strong ac	ds, alkalis or	oxidizers.				
		11. T	OXICOLO	OGICAL INFORMA	TION			
11.1	Routes of Entry:	Inhalation:	YES	Absorption:	YES	Ingestion: YES		
11.2	·	NA	123	7.0501 pt. 011.	123	ingestion.		
	Acute Toxicity:	See Section 4.4						
11.4	·	See Section 4.5						
11.5	'	NA						
	Reproductive Toxicity:		orted to cause	reproductive toxicity in hu	mans			
11.0	Mutagenicity:			uce mutagenic effects in hu				
	Embryo toxicity:			uce embryo toxic effects in I				
	Teratogenicity:			eratogenic effects in human				
	Reproductive Toxicity:	· · · · · · · · · · · · · · · · · · ·		eproductive effects in human				
11 7	Irritancy of Product:	See Section 4.3	ort to cause re	eproductive effects in fluina	115.			
		3ee 3ection 4.5						
	Biological Exposure Indices:	NA .						
11.9	Physician Recommendations:	Treat symptomatically.						
				GICAL INFORMATI	ON			
12.1	,	There is no specific dat	a available fo	r this product.				
12.2	Effects on Plants & Animals	There is no specific dat	a available fo	r this product.				
12.3	Effects on Aquatic Life:	The product itself has r	ot been teste	ed as a whole. There is no sp	pecific data available for this	s product.		
		13.	DISPOSA	AL CONSIDERATION	NS			
13.1	Waste Disposal:	appropriate disposal m local, state and federal	ethod for the laws and reg	ral laws, codes, statutes and ingredients listed in Sectior ulations. Contact the appro nent, transport, storage and	n 2. Any disposal practice m priate agency for specific in	nust be in compliance wit formation. A licensed fa		
13.2	Special Considerations:	U.S. EPA Hazardous Wa	iste – Charact	eristic				
		14. TR	ANSPOR	RTATION INFORMA	ATION			
14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.	1 (LTD QTY, IF			_		
14.2	IATA (AIR)	UN1950, AEROSOLS, FL	AMMABLE, 2	.1 (LTD QTY, IP VOL <u><</u> 0.5 L)				
1/1 2	IMDG (OCN):	UN1950, AEROSOLS, 2.		ORM-D (IP VOL <u>< 0.5 l=L)</u>				
	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.				W./		
14.4	TOOK (Callaulali GND):			y", "LTD QTY", OR "QUANT I	TÉE" OR "OLIANITITÉ LINAITE	ée"		
1/1 5	ADR/RID (EU):	UN1950, AEROSOLS, 2.			THE ON QUANTITE LIMITE	<u> </u>		
	SCT (MEXICO): ADGR (AUS):	UNIBOU, AERUSULES, A	ı (CANTIDAL	D LIMITADA, IP VOL <u><</u> 1.0 L)		——— 〈Y		
	ו הטעוז והעטו.	UN1950, AEROSOLS, 2.				_		



1703A-060

SDS Revision Date: 05/24/2018

SDS Revision: 1.0

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

		15. REGULATORY INFOR	MATION				
15.1	SARA Reporting Requirements:	This product does not contain any substance subject to SATA Title III, section 313 reporting requirements.					
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.					
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.					
15.4	CERCLA Reportable Quantity (RQ):	Ethanol: 2270 kg; 5000 lbs.					
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G (Cosmetics)					
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of the product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substance List. WHMIS Class B5 (Flammable Aerosol)					
15.7	State Regulatory Information:	Ethanol: is found on the following state criteria lists FL, MA, MN, NJ, PA, and WA Isobutane can be found on the following state criteria lists: MA, NJ, and PA. Difluoroethane can be found on the following state criteria lists: MA and NJ No other ingredients of this product, present in a concentration of 1.0% or greater, are listed on any of the follow state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substite (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazard Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).					
15.8	Other Requirements:	The primary components of this product are listed in Ann Isobutane: Flammable (F+). Risk Phrases (R): 12 – Highl out of reach of children. Keep container in a well-ventil No smoking. Ethanol: Flammable (F). Risk Phrases (R): 11 – Flammabl children. Keep container tightly closed. Keep away from	y Flammable. Safety Phrases (S): 2-9-16 – Keep lated place. Keep away from sources of ignition – le. Safety Phrase (S): 2-7-16 – Keep out of reach of				
		16. OTHER INFORMA	TION				
16.1	Other Information:	DANGER! FLAMMABLE AEROSOL. PRESSURIZED CONTAIND VAPORS. CAUSES EYE IRRITATION. Keep away from sources. No Smoking. Do not spray on an open flame or Avoid breathing vapor/spray. Wash thoroughly with soan Wear eye protection. Protect from sunlight. Do not exp Remove person to fresh air and keep comfortable for breathing vapor.	AINER: MAY BURST IF HEATED, HIGHLY FLAMMABLE LIQUID m heat, hot surfaces, sparks open flames and other ignition other ignition source. Do not pierce or burn, even after use. In and water after handling. Use only in a well ventilated area. Ose to temperature exceeding 48°C (120°F). IF INHALED: eathing. IF IN EYES: Rinse cautiously with water for several do. Continue rinsing. If eye irritation persists: Get medical				
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.					
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Haz government regulations must be reviewed for applicabili knowledge, the information contained herein is reliable completeness are not guaranteed and no warranties of a information contained herein relates only to the specific	and accurate as of this date; however, accuracy, suitability or				
16.4	Prepared By:	KIK Custom Products 2030 Old Candler Road Gainesville, GA 30507 USA http://www.kikcorp.com	KIK CUSTOM PRODUCTS				




1703A-060

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 05/24/2018





Full Face Respirator

Biohazard

Infectious

Toxic

SAFETY DATA SHEET

Irritation

1703A-060

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

O01/58 & 1272/2008/EC Standards

SDS Revision: 1.0 SDS Revision Date: 05/24/2018

Reactive

Irritant / Harmful

Oxidizing

Flammable

Corrosive

Compressed