Product Name:

Chemical Name:

Synonyms:

Trade Names:

Distributor's Name:

Emergency Phone:

Distributor's Address:

Business Phone / Fax:

Product Uses & Restrictions:

1.2

1.3

1.4

1.5

1.6

1.7 1.8

19

SAFETY DATA SHEET

Page 1 of 6 PM-033

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.3

SDS Revision Date: 7/1/2016

1. PRODUCT & COMPANY IDENTIFICATION					
PAUL MITCHELL – FLASH BACK DEMI-PERMANENT COLOR 3WN DARK					
WARM NEUTRAL					
NA NA					
JPMS – Flash Back Demi-permanent Color 3WN Dark Warm Neutral					
Paul Mitchell – Flash Back Demi-permanent Color 3WN Dark Warm Neutral					
Professional Use Only					
JPMS Manufacturing, LLC					
237 Buttonwood Street, Reading, PA 19601 USA					

2. HAZARDS IDENTIFICATION

CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 11977)

This product is classified as a HAZARDOUS SUBSTANCE but NOT as DANGEROUS GOODS Hazard Identification: according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia).

> WARNING! MAY CAUSES AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

Classification: Skin Sens.1; Eye Irrit. 2A

+1 (610) 374-4845 / +1(610) 373-7101

Hazard Statements (H): H317 - May cause an allergic skin reaction. H319 - Causes serious eye

Precautionary Statements (P): P271 - Use only in well-ventilated area. P280 - Wear protective gloves and eye/face protection. P305+P351+P338 - IF IN EYES: Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P312 - Call a POISON CENTER/doctor if you feel unwell. P332+P313 - If skin irritation occurs: get medical advice/attention. P405 - Store locked up. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).

NOTICE: This product is designed and intended for use by a licensed cosmetologist/professional hairdresser only, and carries no warranty, expressed or implied, if used by others. CAN CAUSE AN ALLERGIC REACTION. Preliminary patch testing is recommended. Tattoos, including black and temporary henna, may increase the risk of allergy. If a severe allergic reaction should occur, seek immediate medical attention. This product must not be used for dyeing the eyelashes or eyebrows - to do so may cause blindness.



3. COMPOSITION & INGREDIENT INFORMATION

					EXPOSURE LIMITS IN AIR (mg/m³)								
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
JPMS PROPRIETARY BLEND	NA	NA	NA	60-100	NA	NA	NF	NF	NF	NA	NA	NA	
JPMS PROPRIETARY BLEND													
- DUENN ENEDIAMINE	106-50-3	SS8050000	203-404-7	1-5	NA	NA	NF	0.1	NF	NA	NA	25	
p-PHENYLENEDIAMINE	Acute Tox. 3 *; Acute Tox. 3 *; Acute Tox. 3 *; Eye Irrit. 2; Skin Sens. 1; H331, H311, H301, H319, H317												
O METUNA DECODORNO	608-25-3	VH2009500	210-155-8	0.5-1.0	NA	NA	NF	NF	NF	NA	NA	NA	
2-METHYLRESORCINOL													
4-CHLORORESORCINOL	95-88-5	VH0450000	202-462-1	< 1.0	NA	NA	NF	NF	NA	NF	NF	NF	
4-CHLORORESORCINOL	Acute Tox. 4;	Skin Irrit. 2; Eye Ir	rrit. 2A; STOT SE	3; H302,	H312, F	1332, H	1331, H	319, H3	35				
AMINORUENIOI	591-27-5	NA	209-711-2	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
m-AMINOPHENOL													
2-AMINO-4-HYDROXYETHYL-	83763-48-8	NA	280-734-8	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
AMINOANISOLE SULFATE													

4. FIRST AID MEASURES

4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk
			IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an
			unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an
			estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm
		<u>=,00</u> .	water for at least 15 minutes. If irritation occurs, contact a physician.
		Skin:	If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough
			washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.
		Inhalation:	Remove victim to fresh air at once.
		innalation:	Remove victim to fresh air at once.

SAFETY DATA SHEET

Page 2 of 6 **PM-033**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.3 SDS Revision Date: 7/1/2016 4. FIRST AID MEASURES - cont'd 42 Effects of Exposure: Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and Eyes: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: 4.3 Symptoms of Overexposure: Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. 4.4 Acute Health Effects: Moderate irritation to eyes. Symptoms of overexposure may include redness, itching, stinging, irritation and watering. Moderate irritation to skin near affected areas. 4.5 Chronic Health Effects: No harmful or chronic health effects are expected to occur from a single accidental ingestion. 4.6 Target Organs: Eyes, Skin 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the 1 HEALTH Aggravated by Exposure: target organs (eyes and skin). **FLAMMABILITY** 0 PHYSICAL HAZARDS 1 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO₂, and NOx). 5.2 Extinguishing Methods: Water, Foam, CO2, Dry Chemical 5.3 Firefighting Procedures: Fight fires as for surrounding materials. Hazardous decomposition products may be released. Thermal degradation may produce oxides of carbon and/or nitrogen, hydrocarbons and/or derivatives. Firefighters should wear a MSHA/NIOSH approved or equivalent self-contained breathing apparatus (SCBA) and protective clothing. Fire should be fought from a safe distance. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Do not expose to heat and flame. Use only in ventilated areas. Keep out of the reach of children. Wash unintentional residues with soap and warm water. Storage & Handling: 7.2 Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120°F. Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying keep cap in place when not in use. Keep away from children at all times! 7.3 Special Precautions Spilled material may present a slipping hazard. Clean up all spills promptly. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION NOHSC Exposure Limits: ACGIH OSHA OTHER 8 1 ppm (mg/m³) STEL ES-TWA ES-STEL PEL STEL TLV ES-PEAK IDLH CHEMICAL NAME(S) NA NF P-PHENYLENEDIAMINE NA 0.1 NF NA NA General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general 8.2 Ventilation & Engineering Controls: exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).



Physician Recommendations:

Treat symptomatically.

11.9

SAFETY DATA SHEET

Page 3 of 6

PM-033 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 7/1/2016 8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. 8 4 Eve Protection: Avoid eye contact. None required under normal conditions of use. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)) safety glasses with side shields should be used. 8.5 Hand Protection: Required under normal conditions of use to prevent staining and keep exposure level to a minimum. Use latex or PVC gloves. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber or impervious plastic gloves must be worn. Body Protection: 8.6 No apron required when handling small quantities. Lab coat or apron should be worn to protect skin and clothing. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water. 9. PHYSICAL & CHEMICAL PROPERTIES 9 1 Appearance: Clear liquid 9.2 Odor Perfumery 9.3 Odor Threshold: NA 94 pH: NA 9.5 Melting Point/Freezing Point: NA 9.6 Initial Boiling Point/Boiling NA 97 Flashpoint NA Upper/Lower Flammability 9.8 NA Limits: Vapor Pressure: 9.9 NA Vapor Density: 9 10 1.12 g/mL 9 11 Relative Density NA 9.12 Solubility Slightly soluble Partition Coefficient (log Pow): 9.13 NA 9 14 Autoignition Temperature NA 9.15 Decomposition Temperature: NA Viscosity: 9.16 NA Other Information: 9.17 NA 10. STABILITY & REACTIVITY 10.1 Stability: Ths product is stable. Hazardous Decomposition 10.2 Oxides of carbon (CO, CO₂), nitrogen (NO_x) and sulfur (SO₂). Products 10.3 Hazardous Polymerization: 10.4 Conditions to Avoid Open flames, sparks, high heat, incompatible substances and direct sunlight. Incompatible Substances: 10.5 Avoid extreme heat and ignition sources. Store away from oxidizers 11. TOXICOLOGICAL INFORMATION Absorption: YES Ingestion: YES 11.1 Routes of Entry: Inhalation: NO 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product but is not presented in this document. 11.3 Acute Toxicity: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea Chronic Toxicity 11.4 This material may aggravate any pre-existing skin condition (e.g., dermatitis). This product contains p-Phenylenediamine and Resorcinol, which are not carcinogenic to humans, but are listed as 11.5 Suspected Carcinogen: Group 3 carcinogens by the IARC. This product contains p-Phenylenediamine listed by ACGIH in group A4 116 Reproductive Toxicity This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices NE

SAFETY DATA SHEET

Page 4 of 6 **PM-033**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.3 SDS Revision Date: 7/1/2016 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There is no specific data available for this product. 12 2 Effects on Plants & Animals There are no specific data available for this product. Effects on Aquatic Life: 12.3 There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS Waste Disposal: Products covered by this MSDS, in their original form, when disposed as waste, are considered non hazardous waste 13.1 according to Federal RCRA regulations (40 CFR 261). Disposal should be in accordance with local, state and federal regulations. Dispose of in accordance with federal, state and local regulations. 13 2 Special Considerations: California Waste Code: 331 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): 14 1 **NOT REGULATED** IATA (AIR): 14 2 **NOT REGULATED** IMDG (OCN): 14.3 **NOT REGULATED** 14.4 TDGR (Canadian GND): **NOT REGULATED** ADR/RID (EU): 14.5 **NOT REGULATED** 14.6 SCT (MEXICO): **NOT REGULATED** ADGR (AUS): NOT REGULATED 14.7 15. REGULATORY INFORMATION SARA Reporting 15.1 This product contains p-Phenylenediamine a substance subject to SARA Title III, section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning This product is not subject to the reporting requirements of SARA Title III, Section 302. Quantity: 15.3 TSCA Inventory Status: All components of this product are listed in the TSCA Inventory or are exempt. **CERCLA Reportable Quantity** 15.4 p-Phenylenediamine: 2,270 kg (5,000 lbs). (RQ): 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G. (Cosmetics). 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects). p-Phenylenediamine is found on the following state criteria list: Florida Toxic Substances List (FL), Massachusetts 15.7 State Regulatory Information: Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List (WA). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). Other Requirements: NA 15.8

SAFETY DATA SHEET

Page 5 of 6 **PM-033**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.3

SDS Revision Date: 7/1/2016

		16. OTHER INFORMATION			
16.1	Other Information:	WARNING! CAUSES MILD SKIN IRRITATION. CAUSES EYE IRRITATION. For external use only. Use only as directed. Discontinue use immediately if irritation develops Keep away from children. Keep container tightly closed in a cool place. When using do not eat or drink. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves and eye/face protection. If case of accident or if you feel unwell seek medical advice immediately (show the label where possible). KEEP LOCKED UP AND OUT OF REACH OF CHILDREN. This product is designed and intended for use by a licensed cosmetologist/professional hairdresser only, and carries no warranty expressed or implied if used by others. CAN CAUSE AN ALLERGIC REACTION. Preliminary patch testing is recommended. Tattoos, including black and temporary henna, may increase the risk of allergy, If a severe allergic reaction should occur, immediately seek medical attention. This product must not be used for dyeing the eyelashes or eyebrows; to do so may cause blindness.			
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.			
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & JPMS Manufacturing, LLC's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.			
16.4	Prepared for:	JPMS Manufacturing, LLC 237 Buttonwood Street Reading, PA 19601 USA Tel: +1 (610) 374-4845 Fax: +1 (610) 373-7101 PAUL MITCHELL			
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com			

SAFETY DATA SHEET

Page 6 of 6 PM-033

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 7/1/2016

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. | Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists			
C Ceiling Limit				
ES Exposure Standard (Australia)				
IDLH Immediately Dangerous to Life and Health				
OSHA U.S. Occupational Safety and Health Administration				
PEL Permissible Exposure Limit				
STEL Short-Term Exposure Limit				
TLV	TLV Threshold Limit Value			
TWA	TWA Time Weighted Average			

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE PERSON NAMED IN COLUMN TO PERSON NAMED I	
D		TH.	
E			
F		THE PERSON NAMED IN COLUMN TO PERSON NAMED I	











Full Face Respirator









Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA Not Available	
ND Not Determined	
NE	Not Established
NF	Not Found
NR	No Results
ppm parts per million	
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition	Autoignition Minimum temperature required to initiate combustion in air with no other				
Temperature	Temperature source of ignition				
LEL	LEL Lower Explosive Limit - lowest percent of vapor in air, by volume, that will				
	explode or ignite in the presence of an ignition source				
UEL	UEL Upper Explosive Limit - highest percent of vapor in air, by volume, that will				
	explode or ignite in the presence of an ignition source				

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	DOT U.S. Department of Transportation					
TC	Transport Canada					
EPA U.S. Environmental Protection Agency						
DSL	Canadian Domestic Substance List					
NOHSC National Occupational Health and Safety Commission (Australia)						
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(*)	(2)	(3)	\odot	(4)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

•	,						
17.4		No.	*		® X	X	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment