

		<h1 style="margin: 0;">SAFETY DATA SHEET</h1>										Page 1 of 6 KIK-009		
Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards					SDS Revision: 1.5			SDS Revision Date: 5/1/2018						
1. PRODUCT & COMPANY IDENTIFICATION														
1.1	Product Name:	JOHN PAUL MITCHELL SYSTEMS - SUPER CLEAN EXTRA 55%VOC												
1.2	Chemical Name:	Aerosol												
1.3	Synonyms:	John Paul Mitchell Systems - Super Clean Extra 55%VOC - B-9120												
1.4	Trade Names:	John Paul Mitchell Systems - Super Clean Extra												
1.5	Product Uses & Restrictions:	Professional and Cosmetic Use												
1.6	Distributor's Name:	KIK Custom Products.												
1.7	Distributor's Address:	2030 Old Candler Road, Gainesville, GA 30507 USA												
1.8	Emergency Phone:	CHEMTEL: +1 (813) 248-0585 / +1 (800) 255-3924 (CN – MIS0002907)												
1.9	Business Phone / Fax:	+1 (770) 534-0300 / +1 (770) 534-8954												
2. HAZARDS IDENTIFICATION														
2.1	Hazard Identification:	<p>This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC:1008 (2004) and ADG Code (Australia).</p> <p>WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.</p> <p><u>Classification</u>: Aerosol Level 2, Category 1 Aerosol; Extremely Flammable Aerosol</p> <p><u>Hazard Statements</u> (H): H223 – Flammable aerosol. H229 – Pressurized container: may burst if heated. H320 – Causes eye irritation.</p> <p><u>Precautionary Statements</u> (P): P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking. P211 – Do not spray on an open flame or other ignition source. P251 – Do not pierce or burn, even after use. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persists: Get medical advice/attention. P101 If medical advice is needed, have product container or label at hand. P102 – Keep out of reach of children. P410+P412 – Protect from sunlight. Do not expose to temperature exceeding 50 °C (122 °F). P501 – Dispose of contents/container to licensed and permitted disposal or recycling facility.</p>												
3. COMPOSITION & INGREDIENT INFORMATION														
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH			NOHSC			OSHA			
					ppm			ppm			ppm			
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
ETHANOL (SD ALCOHOL 40B)	64-17-5	KQ6300000	200-578-6	30-60	1000	3000	1000	1800	NF	1000	1900	3300		
		Flam. Liq. 2; H225												
DIFLUOROETHANE (R-152a)	75-37-6	KJ4100000	200-866-1	30-45	1000	NA	1000	NA	NA	NE	NA	NA		
		Flam. Gas 1; H220												
4. FIRST AID MEASURES														
4.1	First Aid:	<p><u>Ingestion</u>: If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p><u>Skin</u>: If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately.</p> <p><u>Eyes</u>: If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.</p> <p><u>Inhalation</u>: Remove victim to fresh air and keep comfortable for breathing. If breathing is difficult, administer supplemental oxygen and seek immediate medical attention. If breathing stops, perform artificial respiration</p>												
4.2	Effects of Exposure:	<p><u>Ingestion</u>: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.</p> <p><u>Eyes</u>: Moderately irritating to the eyes.</p> <p><u>Skin</u>: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals upon prolonged or repeated exposure.</p> <p><u>Inhalation</u>: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of concentrated vapors can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).</p>												

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.5

SDS Revision Date: 5/1/2018

4. FIRST AID MEASURES – cont'd

4.3	Symptoms of Overexposure:	<p>Ingestion: May cause nausea, vomiting and/or diarrhea and central nervous system depression.</p> <p>Eyes: Overexposure in eyes may cause redness, itching and watering (risk of serious damage to eyes). Contact may cause mild eye irritation including stinging, watering and redness.</p> <p>Skin: Prolonged contact with skin may result in bleaching and irritation of skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas.</p> <p>Inhalation: Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing.</p>											
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.											
4.5	Chronic Health Effects:	No harmful or chronic health effects are expected to occur from a single accidental ingestion. These ingredients may be irritating to skin and mucous membrane of the eye and respiratory system. Overexposure may trigger asthma-like symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible allergic dermatitis.											
4.6	Target Organs:	Eyes, skin, respiratory system.											
4.7	Medical Conditions Aggravated by Exposure:	Acute health hazards may be delayed. Most common symptoms include irritating properties to eyes, respiratory system and skin. Existing dermatological conditions (such as eczema) and respiratory conditions (such as bronchial asthma and/or bronchitis) may be exacerbated.	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #0056b3; color: white;">HEALTH</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: #ff0000; color: white;">FLAMMABILITY</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="background-color: #ff8c00; color: white;">PHYSICAL HAZARDS</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: #000000; color: white;">PROTECTIVE EQUIPMENT</td> <td style="text-align: center;">B</td> </tr> <tr> <td style="background-color: #000000; color: white;">EYES</td> <td style="text-align: center;">SKIN</td> </tr> </table>	HEALTH	1	FLAMMABILITY	3	PHYSICAL HAZARDS	0	PROTECTIVE EQUIPMENT	B	EYES	SKIN
HEALTH	1												
FLAMMABILITY	3												
PHYSICAL HAZARDS	0												
PROTECTIVE EQUIPMENT	B												
EYES	SKIN												

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	Level 2 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Containers may rupture and release flammable liquids or/and exposed gasses if exposed to the heat of fire. Keep containers cool by spraying them with water until the fire has been extinguished.	
5.2	Extinguishing Methods:	Water Fog, Foam, Dry Chemical, CO ₂	
5.3	Firefighting Procedures:	As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.	

6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. Plastic or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills.</p> <p>Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Do not use water or a material such as "speedy dry" to soak up material. Sweep up material using non-sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within another container.</p> <p>Large Spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant.</p>
-----	---------	---

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Do not eat, drink or smoke when handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying keep cap in place when not in use. Storage level 2.
7.3	Special Precautions:	Spilled material may present a slipping hazard if left unattended. Clean all spills promptly.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.5

SDS Revision Date: 5/1/2018

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)	CHEMICAL NAME(S)	ACGIH		NOHSC			OSHA			OTHER
			TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		ETHANOL(SD ALCOHOL 40B)	1000	3000	1000	1800	NF	1000	1900	3300	
		DIFLUOROETHANE (R-152a)	1000	NA	1000	NA	NA	NE	NA	NA	
8.2	Ventilation & Engineering Controls:	General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product.									
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.									
8.4	Eye Protection:	Avoid eye contact. None required under normal conditions of use. Safety glasses could be used when handling or using large quantities of this product.									
8.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves.									
8.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 5 lbs), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.									

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Aerosol, clear misty spray of liquid
9.2	Odor:	Fresh floral
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	NA
9.7	Flashpoint:	-30 °F (-34 °C)TCC for propellant only: 35.6 °F (2 °C) EPA method 1010 (concentrate only)
9.8	Upper/Lower Flammability Limits:	NA
9.9	Vapor Pressure:	@ 20 °C (68 °F) - Can pressure not to exceed 180 psig @ 55 °C (131 °F) 12.4 bar
9.10	Vapor Density:	> 1
9.11	Relative Density:	0.81-0.85
9.12	Solubility:	Soluble
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	Aerosol at ambient temperature
9.17	Other Information:	Evaporation Rate > 1: Percent Volatile 55%

10. STABILITY & REACTIVITY

10.1	Stability:	Stable at normal temperatures.
10.2	Hazardous Decomposition Products:	Oxides of carbon (CO, CO ₂) and sulfur (SO ₂).
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Excessive heat, direct sunlight, flames, heat sources and incompatible substances.
10.5	Incompatible Substances:	Mixture with strong acids, alkalis or oxidizers.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards | SDS Revision: 1.5 | SDS Revision Date: 5/1/2018

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product was not tested on animals.		
11.3	Acute Toxicity:	See Section 4.4		
11.4	Chronic Toxicity:	See Section 4.5		
11.5	Suspected Carcinogen:	No		
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 4.3		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	There is no specific data available for this product.
12.2	Effects on Plants & Animals:	There is no specific data available for this product.
12.3	Effects on Aquatic Life:	The product itself has not been tested as a whole. There is no specific data available for this product.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. A licensed facility or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.
13.2	Special Considerations:	U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001)

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020	
14.2	IATA (AIR):	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L)	
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE"	
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1950, AEROSOLS, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	Ethanol: 2270 kg; 5000 lbs.	
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, (Cosmetics).	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class B5 (Flammable Aerosol)	

15. REGULATORY INFORMATION – cont'd

15.7	State Regulatory Information:	<p><u>Ethanol</u> is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Pennsylvania Right-to-Know List (PA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ).</p> <p><u>Difluoroethane</u> can be found on the following state criteria lists: MA and NJ.</p> <p>No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p>
15.8	Other Requirements:	<p>The primary components of this product are listed in Annex I of EU Directive 67/548/EEC.</p> <p><u>Ethanol</u>: Flammable (F). <u>Risk Phrases</u> (R): 11 – Flammable. <u>Safety Phrases</u> (S): 2-7-16 – Keep out of reach of children. Keep container tightly closed. Keep away from sources of ignition – No smoking.</p>



16. OTHER INFORMATION

16.1	Other Information:	<p>WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapor/spray. Wash thoroughly with soap and water after handling. Use only in a well-ventilated area. Wear eye protection. Protect from sunlight. Do not expose to temperature exceeding 50 °C (122 °F). IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.</p>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	<p>This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & KIK Custom Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.</p>	
16.4	Prepared for:	<p>KIK Custom Products 2030 Old Candler Road Gainesville, GA 30507 USA Tel: +1 (770) 534-0300 Fax: +1 (770) 534-8954 http://www.kikcorp.com</p>	
16.5	Prepared by:	<p>ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com</p>	

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.5

SDS Revision Date: 5/1/2018

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
EXPOSURE LIMITS IN AIR:	
ACGIH	American Conference on Governmental Industrial Hygienists
C	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
mg/m3	milligrams per cubic meter
NA	Not Available
ND	Not Determined
NE	Not Established
NF	Not Found
NR	No Results
ppm	parts per million
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:	
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) w s
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₀₁	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₀₁, LD₀₁, & LD₅₀ or TC, TC₀₁, LC₀₁, & LC₅₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{OW} or log K_{OC}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NOHSC	National Occupational Health and Safety Commission (Australia)
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährungsklassen (German Water Hazard Class)
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment