	KIK CUSTOM	PRODUCTS

First Aid:

SAFETY DATA SHEET

Page 1 of 6

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

Ingestion:

SDS Revision: 1.3

SDS Revision Date: 1/1/2018

1. PRODUCT & COMPANY IDENTIFICATION				
1.1 Product N	lame:	JOHN PAUL MITCHELL SYSTEMS - SUPER CLEAN SPRAY 55%VOC		
1.2 Chemical	Name:	Aerosol		
1.3 Synonyms	s:	John Paul Mitchell Systems - Super Clean Spray 55%VOC - B-9122		
1.4 Trade Nar	mes:	John Paul Mitchell Systems - Super Clean Spray		
1.5 Product U	Ises & Restrictions:	Professional and Cosmetic Use		
1.6 Distributor	r's Name:	KIK Custom Products.		
1.7 Distributor	r's Address:	2030 Old Candler Road, Gainesville, GA 30507 USA	•	
1.8 Emergend	cy Phone:	CHEMTEL: +1 (813) 248-0585 / +1 (888) 255-3924 (CN – MIS0002907)		
1.9 Business I	Phone / Fax:	+1 (770) 534-0300 / +1 (770) 534-8954		

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC:1008 (2004) and ADG Code (Australia).

WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.

Classification: Aerosol Level 2, Category 1 Aerosol; Extremely Flammable Aerosol Hazard Statements (H): H223 – Flammable aerosol. H229 – Pressurized container: may burst if heated. H320 – Causes eye irritation.

Precautionary Statements (P): P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking. P211 – Do not spray on an open flame or other ignition



and other ignition sources. No Smoking. P211 – Do not spray on an open flame or other ignition source. P251 – Do not pierce or burn, even after use. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P337+P313 – If eye Irritation persists: Get medical advice/attention. P101 If medical advice is needed, have product container or label at hand. P102 – Keep out of reach of children. P410+P412 – Protect from sunlight. Do not expose to temperature exceeding 50 °C (122 °F). P501 – Dispose of contents/container to licensed and permitted disposal or recycling facility.

3. COMPOSITION & INGREDIENT INFORMATION

								EXPO	SURE LI	MITS IN	AIR (mg	g/m³)	
					AC	GIH		NOHSC			OSHA		
					pp	m		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
ETHANOL (SD ALCOHOL 40B)	64-17-5	KQ6300000	200-578-6	30-60	1000	3000	1000	1800	NF	1000	1900	3300	
ETHANOL (3D ALCOHOL 40B)	Flam. Liq. 2; H2	225											
DIFLUOROETHANE (R-152a)	75-37-6	KI4100000	200-866-1	30-45	1000	NA	1000	NA	NA	NE	NA	NA	
DIFLOORGETHANE (R-152a)	Flam. Gas 1; H	220	·		-	-			-	-	-		

4. FIRST AID MEASURES

If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk

			IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Skin:	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately.
		Eyes:	If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.
		Inhalation:	Remove victim to fresh air and keep comfortable for breathing.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.
		Eyes:	Moderately irritating to the eyes.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals upon prolonged or repeated exposure.
		Inhalation:	Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of concentrated vapors can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).



7.3

Special Precautions:

SAFETY DATA SHEET

Page 2 of 6

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.3 SDS Revision Date: 1/1/2018 4. FIRST AID MEASURES - cont'd 4.3 Symptoms of Overexposure: May cause nausea, vomiting and/or diarrhea and central nervous system depression. Ingestion: Overexposure in eyes may cause redness, itching and watering (risk of serious damage to eyes). Eyes: Contact may cause mild eye irritation including stinging, watering and redness. Prolonged contact with skin may result in bleaching and irritation of skin. The product can cause allergic Skin: skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Acute Health Effects: 4.4 Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Chronic Health Effects: 4.5 No harmful or chronic health effects are expected to occur from a single accidental ingestion. These ingredients may be irritating to skin and mucous membrane of the eye and respiratory system. Overexposure may trigger asthma-like symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible allergic dermatitis. Target Organs: 4.6 Eyes, skin, respiratory system. Acute health hazards may be delayed. Most common symptoms 4.7 Medical Conditions **HEALTH** 1 Aggravated by Exposure: include irritating properties to eyes, respiratory system and skin. **FLAMMABILITY** 3 Existing dermatological conditions (such as eczema) and respiratory **PHYSICAL HAZARDS** 0 conditions (such as bronchial asthma and/or bronchitis) may be PROTECTIVE EQUIPMENT В exacerbated. **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: Level 2 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120 °F. Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Containers may rupture and release flammable liquids or/or exposed gasses if exposed to the heat of fire. Keep containers cool by spraying them with water until the fire has been extinguished. Extinguishing Methods: Water Fog, Foam, Dry Chemical, CO₂ As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-5.3 Firefighting Procedures demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. Plastic or rubber gloves, respirator, eye protection and apron may be required for clean-up of large spills. Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Do not use water or a material such as "speedy dry" to soak up material. Sweep up material using non-sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within another container. Large Spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink or smoke when handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical

damage. To avoid unintentional spraying keep cap in place when not in use. Storage level 2.

Spilled material may present a slipping hazard if left unattended. Clean all spills promptly



10.3

10.4

10.5

Hazardous Polymerization:

Conditions to Avoid:
Incompatible Substances:

Will not occur.

Mixture with strong acids, alkalis or oxidizers.

SAFETY DATA SHEET

Page 3 of 6

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 1/1/2018 SDS Revision: 1.3 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: ACGIH OTHER ppm (mg/m³) TLV STEL ES-TWA ES-STEL ES-PEAK IDLH CHEMICAL NAME(S) PEL STEL ETHANOL(SD ALCOHOL 40B) 1000 3000 1000 1800 1000 1900 3300 DIFLUOROETHANE (R-152a) 1000 NA 1000 NA NA NE NA 8.2 Ventilation & Engineering General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general Controls: exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. Eye Protection: Avoid eye contact. None required under normal conditions of use. Safety glasses could be used when handling or using large quantities of this product. 8.5 Hand Protection: None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves. No apron required when handling small quantities. When handling large quantities (e.g., ≥ 5 lbs), 8.6 Body Protection: eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Aerosol, clear misty spray of liquid 9.2 Odor: Fresh floral Odor Threshold: 9.3 NA 9.4 pH: NA 9.5 Melting Point/Freezing Point: NΑ 9.6 Initial Boiling Point/Boiling NΑ Range: 9.7 Flashpoint: -30 °F (-34 °C)TCC for propellant only: 35.6 °F (2 °C) EPA method 1010 (concentrate only) Upper/Lower Flammability 9.8 9.9 Vapor Pressure: @ 20 °C (68 °F) - Can pressure not to exceed 180 psig @ 55 °C (131 °F) 12.4 bar 9.10 Vapor Density: > 1 Relative Density: 9 11 0.81-0.85 Solubility: 9 12 Soluble Partition Coefficient (log Pow): 9.13 NA 9.14 Autoignition Temperature: NA Decomposition Temperature: 9.15 NA 9.16 Viscosity Aerosol at ambient temperature Evaporation Rate > 1: Percent Volatile 55% 9.17 Other Information 10. STABILITY & REACTIVITY 10.1 Stability Stable at normal temperatures. 10.2 Hazardous Decomposition Oxides of carbon (CO, CO₂) and sulfur (SO₂). Products:

Excessive heat, direct sunlight, flames, heat sources and incompatible substances.



SAFETY DATA SHEET

Page 4 of 6

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 1/1/2018 11. TOXICOLOGICAL INFORMATION Routes of Entry: Inhalation: YES Ingestion: YES 11.1 Absorption: YES Toxicity Data: This product was not tested on animals. Toxicology data, found in scientific literature, is available and not presented in this document. 11.3 Acute Toxicity: See Section 4.4 Chronic Toxicity: 11.4 See Section 4.5 Suspected Carcinogen: 11.5 No 11.6 Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. Irritancy of Product: 11.7 See Section 4.3 Biological Exposure Indices: 11.8 ΝE 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There is no specific data available for this product. Effects on Plants & Animals There is no specific data available for this product. The product itself has not been tested as a whole. There is no specific data available for this product. 12.3 Effects on Aquatic Life: 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. A licensed facility or waste hauler must provide treatment, transport, storage and disposal of hazardous waste. 13.2 Special Considerations U.S. EPA Hazardous Waste - Characteristic - Ignitable (D001) 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or 49 CFR (GND): CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020 IATA (AIR): UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or 14.2 ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) IMDG (OCN): 14.3 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 14 4 TDGR (Canadian GND): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE" ADR/RID (EU): 14.5 UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 14.6 SCT (MEXICO): UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L) 14.7 ADGR (AUS): UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L) 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements SARA Threshold Planning 15.2 There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory, CERCLA Reportable Quantity 15.4 Ethanol: 2270 kg; 5000 lbs. (RQ): 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class B5 (Flammable Aerosol)



SAFETY DATA SHEET

Page 5 of 6

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.3 SDS Revision Date: 1/1/2018

		15. REGULATORY INF	ORMATION - cont'd			
15.7	State Regulatory Information:	Ethanol is found on the following state criter Substances List (MA), Pennsylvania Right-to-K Right-to-Know List (NJ). Difluoroethane can be found on the following st. No other ingredients in this product, present in criteria lists: California Proposition 65 (CA65) List (FL), Massachusetts Hazardous Substance Substances List (MN), New Jersey Right-to-Kr Right-to-Know List (PA), Washington Permissib	a lists: Florida Toxic Substances List (FL), Massachusetts Hazardous now List (PA), Minnesota Hazardous Substances List (MN), New Jersey ate criteria lists: MA and NJ. a concentration of 1.0% or greater, are listed on any of the following state Delaware Air Quality Management List (DE), Florida Toxic Substances s List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous low List (NJ), New York Hazardous Substances List (NY), Pennsylvania Exposures List (WA), Wisconsin Hazardous Substances List (WI).			
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC. <u>Ethanol</u> : Flammable (F). <u>Risk Phrases</u> (R): 11 – Flammable. <u>Safety Phrases</u> (S): 2-7-16 – Keep out of reach of children. Keep container tightly closed. Keep away from sources of ignition – No smoking.				
		16. OTHER INF	ORMATION			
16.1	Other Information:	WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapor/spray. Wash thoroughly with soap and water after handling. Use only in a well-ventilated area. Wear eye protection. Protect from sunlight. Do not expose to temperature exceeding 50 °C (122 °F). IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye Irritation persists: Get medical advice/attention. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.				
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.				
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to government regulations must be reviewed for Products' knowledge, the information contains suitability or completeness is not guaranteed at the information contained herein relates only	OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other applicability to this product. To the best of ShipMate's & KIK Customed herein is reliable and accurate as of this date; however, accuracy, nd no warranties of any type, either expressed or implied, are provided. It to the specific product(s). If this product(s) is combined with other insidered. Data may be changed from time to time. Be sure to consult the			
16.4	Prepared for:	KIK Custom Products 2030 Old Candler Road Gainesville, GA 30507 USA Tel: +1 (770) 534-0300 Fax: +1 (770) 534-8954 http://www.kikcorp.com	KIK CUSTOM PRODUCTS			
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	ShipMate Dangerous Goods Training & Consulting			

SAFETY DATA SHEET

Page 6 of 6

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 1/1/2018

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists			
С	C Ceiling Limit			
ES	Exposure Standard (Australia)			
IDLH	Immediately Dangerous to Life and Health			
OSHA	OSHA U.S. Occupational Safety and Health Administration			
PEL Permissible Exposure Limit				
STEL Short-Term Exposure Limit				
TLV	Threshold Limit Value			
TWA Time Weighted Average				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.


HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard			
1 Slight Hazard				
2	Moderate Hazard			
3 Severe Hazard				
4	Extreme Hazard			

HEALTH FLAMMABILITY **PHYSICAL HAZARDS** PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

Α			
В			
С			
D	B B		
Ε			
F		The state of the s	







Face Shield & Protective Eyewear













Dust & Vapor Half-Mask Respirator

Full Face Respirator

To the Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit			
mg/m3	mg/m3 milligrams per cubic meter			
NA	Not Available			
ND	Not Determined			
NE	Not Established			
NF	Not Found			
NR	No Results			
ppm	parts per million			
SCBA	Self-Contained Breathing Apparatus			

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition	Autoignition Minimum temperature required to initiate combustion in air with no other					
Temperature	nperature source of ignition					
LEL	LEL Lower Explosive Limit - lowest percent of vapor in air, by volume, that will					
	explode or ignite in the presence of an ignition source					
UEL	UEL Upper Explosive Limit - highest percent of vapor in air, by volume, that will					
	explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard				
1	Slight Hazard				
2	Moderate Hazard				
3	Severe Hazard				
4	4 Extreme Hazard				
ACD	Acidic				
ALK	Alkaline				
COR	Corrosive				
₩	Use No Water				
ОХ	Oxidizer				
TREFOIL	Radioactive				



TOXICOLOGICAI	L INFORMATION:
---------------	----------------

		SPECIAL		
LD ₅₀	Lethal Dose (solids & liquids) w	PRECAUTIONS		
	s	THEORETICAL		
LC ₅₀	Lethal concentration (gases) which kills 5	0% of the exposed animal		
ppm	Concentration expressed in parts of mate	rial per million parts		
TD _{lo}	Lowest dose to cause a symptom			
TCLo	Lowest concentration to cause a sympton	n		
TD _{lo} , LD _{lo} , & LD _o or	Lowest dose (or concentration) to cause	ethal or toxic effects		
TC, TC _o , LC _{Io} , & LC _o	,			
IARC	International Agency for Research on Car	ncer		
NTP	National Toxicology Program			
RTECS	Registry of Toxic Effects of Chemical Sub	stances		
BCF	Bioconcentration Factor			
TL _m	Median threshold limit			
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution			

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System	
DOT	U.S. Department of Transportation	
TC	Transport Canada	
EPA	U.S. Environmental Protection Agency	
DSL	Canadian Domestic Substance List	
NOHSC National Occupational Health and Safety Commission (Australia)		
NDSL	Canadian Non-Domestic Substance List	
PSL	Canadian Priority Substances List	
TSCA	U.S. Toxic Substance Control Act	
EU	EU European Union (European Union Directive 67/548/EEC)	
WGK	Wassergefährdungsklassen (German Water Hazard Class)	
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System	

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

					, ,			
	0	●	((((%)		Ŕ
	Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
	Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

			* *		*		X
С	Е	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

		(%)		\Diamond	(ph)		\		*
	GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Ī	Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Hea l th Hazard	Environment