



1. Shock Mount (Front) - 8Nm



2. Shock Mount (Rear) - 8Nm



3. Rocker (Upper) - 8-10Nm



4. Rocker (Lower) - 10-12Nm



5. Main Pivot - 10-12 Nm



6. Chainstay Pivot (2x) - 5-7Nm



| | |
|----------------------|---------------------|
| Frame: | La Sal Peak |
| Year: | 2019 |
| Wheel Size: | 29"/27.5+ |
| Material: | Carbon |
| Front Travel: | 160-170mm |
| Rear Travel: | 150mm |
| Tire Compatibility: | 29x2.6, 27.5x2.8 |
| Rear Dropout: | 148mm (boost) |
| Rear Axle: | 174x12x1.75mm |
| Rear Brake Mount: | 180 Post Mount |
| Bottom Bracket: | 73mm English Thread |
| Seatpost Diameter: | 31.6mm |
| Clamp Diameter: | 34.9mm |
| Dropper Routing: | Internal |
| Headset Standard: | ZS44/ZS56 |
| Shock Length: | 210mm |
| Shock Stroke: | 55mm |
| Front Hardware: | M8x25 |
| Rear Hardware: | M8x25 |
| Seatstay Bearings: | 4x 6900 (10x22x6mm) |
| Rocker Bearings: | 2x 6901 (12x24x6mm) |
| Main Bearings: | 2x 6902 (15x28x7mm) |
| Max Chaining: | 34 round |
| Bashguard Mount: | ISCG-05 |
| Derailleur Hanger #: | 14 |
| Chaining Offset: | 3 mm |