Description

This stereo audio cable has a 3.5mm male on one end and two 1/4 inch TS male connectors on the other. It is typically used to connect audio devices such as PCs and stereo systems to the input of unbalanced pro audio equipment.

- Hi-flex balanced cable is used to capture all highs & lows for optimum audio performance
- Braided shield surrounds center conductors for maximum EMI/RFI noise rejection therefore maintaining the cleanest signal possible
- Multi-stranded copper center conductors and a durable cable jacket is ultra Flexible to maximize mobility
- High quality, gold plated shielded connectors allows for optimum connectivity and maintains a clean signal integrity
- FT4 riser fire rated jacket for in-wall use
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

Physical Characteristics

Color	Black
Connector Plating	Gold
Cable Diameter	5.0mm x 10.0mm
Wire Gauge	22AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	95% Bare Copper Braid
Strain Relief	Metal Shell

Connectors

Connector A	3.5mm Stereo Male
Connector B	1/4 Inch TS Male - Black
Connector C	1/4 Inch TS Male - Red

Approvals

cUL	Yes - Cable

Environmental

RoHS	Yes

Package Information

Package Quantity	1

Warranty Information

Warranty	Limited Lifetime

Cable Weights

1.5ft	3ft	6ft	10ft	15ft	25ft	35ft	50ft
0.45 lbs	0.55 lbs	0.80 lbs	1.00 lbs	1.35 lbs	2.00 lbs	2.65 lbs	3.65 lbs