

1000ft 4 Pair Cat6a Stranded (SSTP) FT4/CMR Bulk Cable

BK-C6AST-4xxS - Specifications

Description

This bulk riser rated Cat6a cable is 1000 feet in length and consists of 4 pairs of 26AWG stranded wires with individually foil shielded pairs plus an overall braid. It is typically used to manufacture shielded Cat6a patch cables and terminated with shielded RJ45 plugs.



Physical Characteristics

Lengths Available	1000 foot [305m] Pull Box	Temperature Rating	75 deg C
Color	Black / Blue / Green / Grey / Red / White / Yellow		
Cable Diameter	6.80 mm	Electrical Characteristics	
Number of Pairs	4 Pairs	Before Aging	Insulation Tensile Strength: >1.68 Kgf/mm2
Wire Gauge	26 AWG Stranded		Elongation (%): >300
Conductor Material	100% Bare Copper	Aging Condition (°C x hrs)	100x168
Construction	7/0.16±0.008 mm	After Aging	Jacket Tensile Strength: >1.41 Kgf/mm2
Stranded Diameter	0.6 mm		Elongation (%): >=100
Insulation	PE		
Insulation Nominal Thickness (mm)	0.22mm	Approvals/Environmental	
Insulation Diameter (±0.005)	1-1.05	ETL, c(UL)us, RoHS	Yes
Jacket Material	PVC - Polyvinyl Chloride		
Jacket Rating	CMR/FT4 [Riser Rated]	Packaging Information	
Jacket Outer Diameter (±0.2mm)	6.0	Package Quantity	1
Jacket Nominal Thickness (mm)	0.5 - 0.6	Product Weight	25.96 lbs [11.77 kg]