


OM3 Multimode 50 Micron Indoor/Outdoor AFL (Corning ClearCurve) - OFNR Riser Fiber Bulk Cable (per meter)

This bulk 24-strand OM3 fiber cable is indoor/outdoor riser rated and has a tight buffer construction. It is OFNR rated for riser and general inside plant environments. It also has a UV stabilizer for protection against exposure to the sun plus an anti-fungus protection for use in underground applications.

Features include: Exceeds ICEA S-104-696 and GR-20-CORE water penetration requirements, moisture-resistant, fungus-resistant, UV resistant for outdoor use, suitable for installations in most spaces requiring UL flame ratings (Plenum, Riser, General Purpose and outside plants), RoHS/Reach compliant.

Physical Characteristics

Color	Aqua
Fiber Optic Type	OM3 50 micron Multimode Riser Indoor/Outdoor Tight Buffered Cable
Fiber Count / Glass Fiber	24-Strand / Corning ClearCurve
Sub Unit Diameter	900 Micron
Nominal Diameter	8.7mm
Tension(Installation)	300 lbs
Tension(Long Term)	90 lbs
Bending Radius(Installation)	13.1cm
Bending Radius(Long Term)	8.7cm
Operating/Storage Temperature	-40 deg C ~ +75 deg C
Installation Temperature	-20 deg C ~ +75 deg C
Attenuation Range	@850nm 3.0dB/km @1300nm 1.2dB/km
Bandwidth Range	@850nm > 1500MHz/km @1300nm > 500 MHz/km
Gigabit Ethernet Min. Link Distance	850nm = 1000 1300nm = 500
10 Gigabit Ethernet Min. Link Distance	300
Fire Rating	OFNR
UV Stabilizer, Anti-Fungus Protection	Yes



Certification(s)

ETL	Yes
c(ETL)	Yes

Environmental

RoHS	Yes
------	-----

Packaging Information

24-strand
0.19 lbs

Name	OM3 Multimode 50 Micron Indoor/Outdoor AFL (Corning ClearCurve) - OFNR Riser Fiber Bulk Cable (per meter)
P/N	BK-F24D-OM3-R