



# 2-fiber 9 Micron Singlemode (SM) Mini-Armored (ClearCurve LBL) Plenum (per meter) - Yellow

## BK-F2MA-SM-P - Specifications

### Description

This bulk 2-strand OS2 mini-armored fiber cable is plenum rated and has a tight buffer construction. It is constructed of plenum rated material for inside plant environments. It's interlocking armor provides the best balance of ruggedness, flexibility, and low weight. Ideal for harsh environments such as manufacturing plants, data centers and inside of buildings where additional ruggedness is required. The cable is also rodent resistant.

### Physical Characteristics

Color	Yellow
Fiber Optic Type	OS2 9 $\mu$ Singlemode Plenum Armored Tight Buffered Cable
Fiber Count	2-Strand
Glass Fiber	ClearCurve LBL
Sub Unit Diameter	600Micron
Nominal Diameter	3.3mm
Tension(Installation)	400N
Tension(Long Term)	200N
Bending Radius(Installation)	20D(mm)
Bending Radius(Long Term)	10D(mm)
Storage/Operating Temperature	-20deg C ~ +60 deg C
Crush Resistance	5000N/100mm (Short-term) 3000N/100mm (Long-term)
Attenuation Range	@1310nm0.4dB/km @1550nm0.3dB/km
Fire Rating	Plenum



### Environmental

RoHS Yes

### Packaging Information

Package Quantity 1  
Product Weight 0.05 lbs [0.02 kg]