



OM2 Multimode 62.5 Micron AFL (Plus Corning) Duplex Zip Cord - 3mm Jacket - LSZH/OFNR Riser Fiber Bulk Cable (per meter)

BK-F2Z-OM2C-L- Specifications

Description

This cable is primarily used in the assembly of duplex fiber patch cords used in server rooms, data centers and other point to point indoor applications.

Physical Characteristics

Color	Orange
Fiber Optic Type	Zipcord 3.0 Multimode 62.5/125 micron
Fiber Core Diameter	62.5 micron \pm 3.0 micron
Bandwidth Range	@850 > 160 MHz/km @1310 > 500 MHz/km
Attenuation Range	@850nm 3.0dB/km @1310nm 1.0dB/km
Maximum Tensile Load	Short Term, N 500 Long Term, N 300
Minimum Bending Radius	Load 50mm Unload 30mm
Fiber Count	2C
Tight Buffer Diameter	0.9 micron \pm 0.05
Cable Diameter	3mm
Fire Rating	LSZH jacket meet IEC 60332-3C and OFNR
Uniformly Distributed	Kevlar
Operating Temperature	-20 °C ~ +60 °C

Environmental

RoHS Yes

Packaging Information

Package Quantity	1
Product Weight	0.03 lbs [0.01 kg]

