


1000ft 26AWG Stranded Flat Cable - 4 Conductors - Black

BK-PH04C26-BK - Specifications

Description

This bulk modular flat phone cable consists 4 conductors and is 26 gauge. It is typically used to manufacture modular phone/data cables.



Physical Characteristics

Cable Length 1000 foot [305m]

Color Black/ Silver Satin

No. of Conductors 4 Conductor

Conductor Diameter 0.48 7/0.16AS±0.005mm S=11~13mm

Cable Diameter 5mm x 2.5mm ±0.15mm

Wire Gauge 26AWG CCA

Insulation Material PP

Insulation Diameter 0.95 ± 0.05 mm

Jacket Material PVC - Polyvinyl Chloride

Jacket Rating VW-1 / FT1

Temperature Rating Cable -10°C to +60°C

Electrical Characteristics

Conductor Resistance at 20°C 139.76Ω/Km max 150V

Voltage Rating

Mechanical Characteristics

Before Tensile Strenath Insulation 20.7MPa

Jacket 10.3MPa Before Aging Elongation Insulation 150%

Jacket 100%

Aging Condition (0C) Insulation 100 ± 10C*168hrs Jacket 113± 10C*168hrs

After Tensile Strength Insulation 70%

Jacket 70% After Aging Elongation Insulation 70%

Jacket 65% Cold Bend (-200C±2x4hrs) Insulation No Crack

Jacket No Crack

Heat Shock (1210C±1x1hrs) Insulation No Crack Jacket No Crack

Approvals

c(UL)us Yes (AWM 20251)

CSA Yes (204790 I/II A)

Environmental

RoHS Yes

Yes Reach

Conflict Minerals Yes

Packaging Information

Package Quantity

Product Weight 9.35 lbs [4.21 kg]