



# 500ft 2C 14AWG Direct Burial Bulk Speaker Cable - Black


BK-SPE223-xx - Specifications

## Description

This bulk in-wall speaker cable is made from oxygen free multi-stranded copper cable to capture all highs & lows for optimum audio performance. It is typically run in walls and used to connect speakers to amplifiers.

## Physical Characteristics

Cable Length	500 foot [152.4m]
Color	Black
Temperature Rating	-40°C ~ 75°C
Cable Diameter	7.00±0.10mm
Number of Conductors	2 Conductor
Wire Gauge	14AWG
Conductor Material	100% Bare Copper
Stranding Count & Diameter	105/0.16mm ± 0.004
Assembly Diameter	5.80±0.20
Jacket Material	PVC - Polyvinyl Chloride
Jacket Rating	Outdoor
Jacket Average Thickness	0.60mm
Jacket Minimum Thickness	0.54mm
Insulation Average Thickness	0.355mm
Insulation Minimum Thickness	0.330mm
Insulation Diameter	2.60±0.05
Ripcord	Nylon
Cable Shielding	None
Core wrap 1	PET Tape
Core wrap 2	Water Block Tape
Max Voltage Rating	300V
Flammability Test	CMX
Capacitance	< 11.2nF/100M
Resistance	70+/-10 OHM
Conductor Resistance	Max 9.2ohm/km at 20°C
Insulator Resistance	Min 50MΩ km at 20°C



**Printing:** PHANTOM CABLES - SPEAKER WIRE - 2C/14AWG DIRECT BURIAL STRANDED OFC LLDPE (-40C to +75C) RoHS xxxxFT

## Mechanical Characteristics

Before Aging		
Tensile Strength (Mpa):		>=10.6
Elongation (%):		>=300
Aging Condition (deg C x hrs)		100x168
After Aging		
Tensile Strength (Mpa):		>=85% of unaged
Elongation (%):		>=50% of unaged

## Packaging Information

Package Quantity	1
Product Weight	19.9 lbs

## Approvals

CE Yes

## Environmental

RoHS Yes