



Premium Phantom Cables RG6 Composite BNC Cable Male to Male FT4

BNC1-xx - Specifications

Description

This premium double shielded RG6 cable consists of BNC male connectors on both ends. It is typically used to connect a video cameras BNC composite output to a monitors BNC composite input.

- Constructed of low-loss, High Definition 75 ohm RG6 solid 18 awg cable
- FPE dielectric insulation allows for a stable velocity of propagation therefore minimizing possible timing delays
- Dual shielding includes a 100% aluminum/mylar foil, plus a 95% tinned copper braid
- Cables nominal capacitance is an exceptional 17.3 pf/ft and has a nominal attenuation of 3.10 dB/100ft @ 200Mhz
- High quality, gold plated, heavy duty shielded connectors optimizes connectivity and maintains a clear signal integrity
- The connector backshells are made of a durable, zinc plated metal alloy
- FT4 riser fire rated jacket for in-wall use
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

Physical Characteristics

Color	Black
Connector Plating	Gold
Cable Type	RG6
Cable Diameter	6.86mm
Wire Gauge	18AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	Dual Shielding 100% aluminum/mylar foil, plus a 95% tinned copper braid

Environmental

RoHS	Yes
------	-----

Package Information

Package Quantity	1
------------------	---

Warranty Information

Warranty	Limited Lifetime
----------	------------------



Connectors

Connector A	BNC Male
Connector B	BNC Male

Cable Weights

3ft	6ft	10ft	15ft	25ft	35ft
0.40 lbs	0.55 lbs	0.75 lbs	1.00 lbs	1.50 lbs	2.00 lbs
50ft	75ft	100ft	125ft	150ft	
2.75 lbs	4.00 lbs	5.25 lbs	6.50 lbs	7.75 lbs	

Approvals

c(UL)us	Yes - Cable
---------	-------------