



RJ45 Male with IP68 Shroud to Blunt Cat6 Solid FTP Outdoor UV / Direct Burial Pigtail Cable (568x) - Black

CAT6SOIPT-xxBK - Specifications

Description

This Cat6 FTP outdoor UV direct burial Ethernet cable consists of RJ45 male with IP68 rated shroud on one end and has no termination on the other. The un-terminated end is typically used for punching down onto a jack or panel and the IP68 shroud is intended to mate with our IP68 rated couplers for a weather tight seal. It is typically used outdoors either above or below ground as premise wiring to connect network devices.

Physical Characteristics

Color	Black
Connector Plating	Gold Plated 50 Micron
Conductor Material	100% Bare Copper
Cable Diameter	8.00mm
Wire Gauge	23AWG Solid
Color Code	568A / 568B
Shielding	FTP (100% Aluminium Foil Shield)
Pairs	4
Temperature Rating	-40°C to +75°C
Strain Relief	Tab Style Strain Relief Boot
Jacket Rating	Direct Burial / UV
Jacket Material	LLDPE
UV	Yes

Connectors

Connector A	RJ45 Long Body Male
Connector B	Un-terminated

Environmental

RoHS	Yes
------	-----

Packaging Information

Package Quantity	1
------------------	---

Warranty Information

Warranty	Limited Lifetime
----------	------------------

