

## Cat6 RJ45 Female to RJ45 Female Shielded Coupler - Waterproof IP68 Rated - Black

CN-C6-FFSB-IP68 - Specifications

## **Description**

This Cat6 shielded coupler consists of a RJ45 female on both ends. It is typically used to connect two RJ45 male outdoor network cables where protection from dust, water and the elements are required. This IP68 rated coupler is suitable for outdoor applications and can be installed on terminated cable assemblies.

## **Physical Characteristics**

Color Black

Body Material PA66

Insert Material Fame Retardancy PBT

PCB Material FR-4 T=1.6mm

Connector Plating Phosphor Bronze with Nickel Plating Gold Plated (3U/6U/15U/30U/50U)

Shielded Case Nickel Plated

RJ45 Jack Life 750 Times Min.

Operating Temperature  $0^{\circ}$ C to  $70^{\circ}$ C

Storage Temperature  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ 

**Performance** 

Voltage Rating 120 VAC RMS

Current Rating 1.5A

Contact Resistance 1000 MΩ Min. @500 VDC

Dielectric Strength 750 VAC RMS 60Hz, 1Min

Connector(s)

RJ45 - 8P8C Female to Female

**Environmental** 

IP Rating IP68Rated

RoHS Yes

**Packaging Information** 

Product Weight 0.10 lbs [0.04 kg]

Package Quantity 2 - End Covers 2 - Long Tubes 1 - RJ45 Coupler 2 - O-shape sealing rings

2 - Waterproof Sealing Plugs 1 - Installation Instructions



## Cat6 RJ45 Female to RJ45 Female Shielded Coupler - Waterproof IP68 Rated - Black

CN-C6-FFSB-IP68 - Line Drawing

