



Premium Phantom Cables 5-Pin XLR DMX Male To Male Cable

DMX-5MM-xx - Specifications

Description

This premium 5-pin DMX lighting cable has a 5-pin XLR male on one end and a 5-pin XLR male on the other. It is typically used to control stage lighting and effects.

- Constructed true 110 ohm cable for quick response time movement
- Dual shielding includes a 100% aluminum/mylar foil, plus a 95% tinned copper braid
- 100% aluminum/mylar foil shield for superior EMI and RFI rejection
- High quality, heavy duty premium strain relief connectors optimizes connectivity and maintains a clear signal integrity
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity
- Standard Color Kinetics Color Blast® pinout.

Physical Characteristics

Shielded	100% aluminum/mylar foil shield, 85% Braid
Color	Black Cable, Nickel Plated Connectors, Gold Plated Pins
Cable Diameter	7.1mm
Cable Temperature Rating	-30 deg C to 75 deg C

Performance

Impedance	110 Ohms
-----------	----------

Connectors

Connector A	5-pin XLR Male
Connector B	5-pin XLR Male

Packaging Information

Packaging Quantity	1 Cable
--------------------	---------

Warranty Information

Warranty	Lifetime Limited
----------	------------------

Cable Weights

1.5ft	3ft	6ft	10ft	15ft
0.30 lbs	0.35 lbs	0.45 lbs	0.55 lbs	0.70 lbs
25ft	35ft	50ft	75ft	100ft
1.00 lbs	1.30 lbs	1.75 lbs	2.75 lbs	3.52 lbs

